

FCC Sub6 REPORT

Certification

Applicant Name:

SAMSUNG Electronics Co., Ltd.

Date of Issue:

July 21, 2020

Address:

129, Samsung-ro, Yeongtong-gu,
 Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Location:

HCT CO., LTD.,
 74, Seoicheon-ro 578beon-gil, Majang-myeon,
 Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-RF-2007-FC036

FCC ID: A3LSMT878U

APPLICANT: SAMSUNG Electronics Co., Ltd.

Model(s): SM-T878U
 EUT Type: Tablet
 FCC Classification: PCS Licensed Transmitter (PCB)
 FCC Rule Part(s): §22, §2

| Mode (MHz) | Tx Frequency (MHz) | Emission Designator | Modulation | ERP | |
|--------------|--------------------|---------------------|------------|----------------|------------------|
| | | | | Max. Power (W) | Max. Power (dBm) |
| Sub6 n5 (5) | 826.5 – 846.5 | 4M51G7D | PI/2 BPSK | 0.157 | 21.96 |
| | | 4M50G7D | QPSK | 0.150 | 21.76 |
| | | 4M50W7D | 16QAM | 0.126 | 21.01 |
| | | 4M49W7D | 64QAM | 0.093 | 19.67 |
| | | 4M49W7D | 256QAM | 0.051 | 17.04 |
| Sub6 n5 (10) | 829.0 – 844.0 | 8M97G7D | PI/2 BPSK | 0.158 | 21.98 |
| | | 8M98G7D | QPSK | 0.149 | 21.74 |
| | | 8M98W7D | 16QAM | 0.126 | 20.99 |
| | | 8M98W7D | 64QAM | 0.091 | 19.58 |
| | | 8M97W7D | 256QAM | 0.049 | 16.88 |
| Sub6 n5 (15) | 831.5 – 841.5 | 13M5G7D | PI/2 BPSK | 0.154 | 21.87 |
| | | 13M5G7D | QPSK | 0.146 | 21.65 |
| | | 13M5W7D | 16QAM | 0.124 | 20.94 |
| | | 13M5W7D | 64QAM | 0.091 | 19.59 |
| | | 13M5W7D | 256QAM | 0.051 | 17.06 |
| Sub6 n5 (20) | 834.0 – 839.0 | 17M9G7D | PI/2 BPSK | 0.156 | 21.94 |
| | | 17M9G7D | QPSK | 0.147 | 21.68 |
| | | 17M9W7D | 16QAM | 0.127 | 21.03 |
| | | 17M9W7D | 64QAM | 0.094 | 19.71 |
| | | 17M9W7D | 256QAM | 0.050 | 16.99 |

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

Report No.: HCT-RF-2007-FC036

REVIEWED BY



Report prepared by : Kwon Jeong
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

Version

| TEST REPORT NO. | DATE | DESCRIPTION |
|-------------------|---------------|-------------------------|
| HCT-RF-2007-FC036 | July 21, 2020 | - First Approval Report |

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

Table of Contents

| | |
|--|----|
| REVIEWED BY | 2 |
| 1. GENERAL INFORMATION | 5 |
| 2. INTRODUCTION | 6 |
| 2.1. DESCRIPTION OF EUT | 6 |
| 2.2. MEASURING INSTRUMENT CALIBRATION | 6 |
| 2.3. TEST FACILITY | 6 |
| 3. DESCRIPTION OF TESTS..... | 7 |
| 3.1 TEST PROCEDURE | 7 |
| 3.2 RADIATED POWER..... | 8 |
| 3.3 RADIATED SPURIOUS EMISSIONS | 9 |
| 3.4 OCCUPIED BANDWIDTH. | 10 |
| 3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL | 11 |
| 3.6 BAND EDGE | 12 |
| 3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE | 13 |
| 3.8 WORST CASE(RADIATED TEST) | 14 |
| 3.9 WORST CASE(CONDUCTED TEST) | 15 |
| 4. LIST OF TEST EQUIPMENT | 16 |
| 5. MEASUREMENT UNCERTAINTY | 18 |
| 6. SUMMARY OF TEST RESULTS | 19 |
| 7. SAMPLE CALCULATION | 20 |
| 8. TEST DATA | 22 |
| 8.1 EFFECTIVE RADIATED POWER..... | 22 |
| 8.2 RADIATED SPURIOUS EMISSIONS | 26 |
| 8.3 OCCUPIED BANDWIDTH | 30 |
| 8.4 CONDUCTED SPURIOUS EMISSIONS | 31 |
| 8.5 BAND EDGE | 31 |
| 8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE | 32 |
| 9. TEST PLOTS..... | 36 |
| 10. ANNEX A_ TEST SETUP PHOTO..... | 93 |

MEASUREMENT REPORT

1. GENERAL INFORMATION

| | |
|----------------------------|---|
| Applicant Name: | SAMSUNG Electronics Co., Ltd. |
| Address: | 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea |
| FCC ID: | A3LSMT878U |
| Application Type: | Certification |
| FCC Classification: | PCS Licensed Transmitter (PCB) |
| FCC Rule Part(s): | §22, §2 |
| EUT Type: | Tablet |
| Model(s): | SM-T878U |
| SCS(kHz): | 15 |
| Bandwidth(MHz): | 5, 10, 15, 20 |
| Waveform: | CP-OFDM, DFT-S-OFDM |
| Modulation: | DFT-S-OFDM: PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM CP-OFDM: QPSK, 16QAM, 64QAM, 256QAM |
| Tx Frequency: | 826.5 MHz – 846.5 MHz (Sub6 n5(5 MHz)) 829.0 MHz – 844.0 MHz (Sub6 n5(10 MHz)) 831.5 MHz – 841.5 MHz (Sub6 n5(15 MHz)) 834.0 MHz – 839.0 MHz (Sub6 n5(20 MHz)) |
| Date(s) of Tests: | June 07, 2020 ~ July 17, 2020 |

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Tablet with UMTS and LTE, Sub6.

It also supports IEEE 802.11 a/b/g/n/ac/ax (HT20/40/80), Bluetooth, BT LE, WPT, mmWave(n260/261).

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

| Test Description | Test Procedure Used |
|---|---|
| Occupied Bandwidth | - KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4 |
| Band Edge | - KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7 |
| Spurious and Harmonic Emissions at Antenna Terminal | - KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7 |
| Conducted Output Power | - N/A (See SAR Report) |
| Frequency stability | - ANSI C63.26-2015 – Section 5.6 |
| Effective Radiated Power/ Effective Isotropic Radiated Power | - KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17 |
| Radiated Spurious and Harmonic Emissions | - KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12 |

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW ≥ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.
These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration
4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated. The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundalmatal frequency is below 1GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW \geq 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep \geq 2 x Span / RBW

3.6 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize


Test Notes

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels (low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.

- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.8 WORST CASE(RADIATED TEST)

- Waveform : All Waveform of operation were investigated and the worst case configuration results are reported.

(Worst case: DFT-S-OFDM)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.

- All modes of operation were investigated and the worst case configuration results are reported.

- Radiated Spurious emissions are measured while operating in EN-DC mode with Sub 6 NR carrier as well as an LTE carrier (anchor).

All EN-DC mode of operation were investigated and the worst case configuration results are reported.

(Worst case: 2A-n5A)

- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.

Please refer to the table below.

[Worst case]

| Test Description | Modulation | RB size | RB offset | Axis |
|------------------------------------|---|---------|-----------|------|
| Effective Isotropic Radiated Power | PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM | 1 | 1 | Z |
| Radiated Spurious Emissions | PI/2 BPSK | 1 | 1 | X |

3.9 WORST CASE(CONDUCTED TEST)

- Waveform : All Waveform of operation were investigated and the worst case configuration results are reported.
(Worst case: DFT-S-OFDM)
- Modulation : All Modulation of operation were investigated and the worst case configuration results are reported.
(Worst case: PI/2 BPSK)
- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.
Please refer to the table below.

[Worst case]

| Test Description | Modulation | Bandwidth (MHz) | Frequency | RB size | RB offset |
|--------------------|---|-----------------|---------------|----------------------|-----------|
| Occupied Bandwidth | PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM | 5, 10, 15, 20 | Mid | Full RB | 0 |
| Band Edge | PI/2 BPSK | 5 | Low | 1 | 0 |
| | | | High | 1 | 24 |
| | | 10 | Low | 1 | 0 |
| | | | High | 1 | 51 |
| | | 15 | Low | 1 | 0 |
| | | | High | 1 | 78 |
| | | 20 | Low | 1 | 0 |
| | | | High | 1 | 105 |
| 5, 10, 15, 20 | Low, High | Full RB | 0 | | |
| | Spurious and Harmonic Emissions at Antenna Terminal | PI/2 BPSK | 5, 10, 15, 20 | Low, Mid, High | 1 |

4. LIST OF TEST EQUIPMENT

| Manufacture | Model/ Equipment | Serial Number | Calibration Date | Calibrati on Interval | Calibration Due |
|-----------------------|--|---------------|------------------|-----------------------|-----------------|
| T&M SYSTEM | FBSR-02B(WHK1.2/15G-10EF)/H.P.F | - | 03/09/2020 | Annual | 03/09/2021 |
| T&M SYSTEM | FBSR-02B(WHK3.3/18G-10EF)/H.P.F | - | 03/09/2020 | Annual | 03/09/2021 |
| WAINWRIGHT INSTRUMENT | WHNX6.0/26.5G-6SS/H.P.F | 1 | 03/19/2020 | Annual | 03/19/2021 |
| Hewlett Packard | 11667B / Power Splitter(DC~26.5 GHz) | 11275 | 04/27/2020 | Annual | 04/27/2021 |
| Hewlett Packard | E3632A/DC Power Supply | MY4004427 | 09/27/2019 | Annual | 09/27/2020 |
| Schwarzbeck | UHAP/ Dipole Antenna | 557 | 03/29/2019 | Biennial | 03/29/2021 |
| Schwarzbeck | UHAP/ Dipole Antenna | 558 | 03/29/2019 | Biennial | 03/29/2021 |
| ESPEC | SU-642 / Chamber | 93000717 | 08/14/2019 | Annual | 08/14/2020 |
| Schwarzbeck | BBHA 9120D/ Horn Antenna(1~18GHz) | 147 | 08/29/2019 | Biennial | 08/29/2021 |
| Schwarzbeck | BBHA 9120D/ Horn Antenna(1~18GHz) | 9120D-1298 | 09/25/2019 | Biennial | 09/25/2021 |
| Schwarzbeck | BBHA 9170/ Horn Antenna(15~40GHz) | BBHA9170342 | 04/29/2019 | Biennial | 04/29/2021 |
| Schwarzbeck | BBHA 9170/ Horn Antenna(15~40GHz) | BBHA9170124 | 02/11/2020 | Biennial | 02/11/2022 |
| Agilent | N9020A/Signal Analyzer(10Hz~26.5GHz) | MY51110063 | 04/27/2020 | Annual | 04/27/2021 |
| Hewlett Packard | 8493C/ATTENUATOR(20dB) | 17280 | 06/04/2020 | Annual | 06/04/2021 |
| REOHDE & SCHWARZ | FSV40/Spectrum Analyzer(10Hz~40GHz) | 100931 | 10/14/2019 | Annual | 10/14/2020 |
| Agilent | 8960 (E5515C)/ Base Station | MY48360800 | 08/27/2019 | Annual | 08/27/2020 |
| Schwarzbeck | FMZB1513/ Loop Antenna(9kHz~30MHz) | 1513-175 | 04/26/2019 | Biennial | 04/26/2021 |
| Schwarzbeck | VULB9160/ Bilog Antenna | 9160-3368 | 08/09/2018 | Biennial | 08/09/2020 |
| Schwarzbeck | VULB9160/ Hybrid Antenna | 760 | 03/22/2019 | Biennial | 03/22/2021 |
| Anritsu Corp. | MT8821C/Wideband Radio Communication Tester | 6201502997 | 08/09/2019 | Annual | 08/09/2020 |
| Anritsu Corp. | MT8820C/Wideband Radio Communication Tester | 6201026545 | 01/22/2020 | Annual | 01/22/2021 |
| REOHDE & SCHWARZ | SMB100A/ SIGNAL GENERATOR (100kHz~40GHz) | 177633 | 07/13/2020 | Annual | 07/13/2021 |
| KEYSIGHT | E7515B / 5G Wireless Tester | MY58300756 | 01/07/2020 | Annual | 01/07/2021 |
| KEYSIGHT | N9030B / Signal Analyzer(5Hz~40.0GHz) | MY55480167 | 06/04/2020 | Annual | 06/04/2021 |
| Mini-Circuits | ZC4PD-K1844+ / 4-Way Divider | 942907 | 09/05/2019 | Annual | 09/05/2020 |
| HCT CO., LTD., | FCC LTE Mobile Conducted RF Automation Test Software | - | - | - | - |

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).
3. Model : SMB100A (S/N: 177633)
 - Use date of Equipment : June 07, 2020 ~ July 12, 2020/ July 14, 2020 ~ July 17, 2020

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Parameter | Expanded Uncertainty (\pm dB) |
|--|----------------------------------|
| Conducted Disturbance (150 kHz ~ 30 MHz) | 1.82 |
| Radiated Disturbance (9 kHz ~ 30 MHz) | 3.40 |
| Radiated Disturbance (30 MHz ~ 1 GHz) | 4.80 |
| Radiated Disturbance (1 GHz ~ 18 GHz) | 5.70 |
| Radiated Disturbance (18 GHz ~ 40 GHz) | 5.05 |

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

| Test Description | FCC Part Section(s) | Test Limit | Test Result |
|--|------------------------|--|------------------|
| Occupied Bandwidth | §2.1049 | N/A | PASS |
| Band Edge / Spurious and Harmonic Emissions at Antenna Terminal. | §2.1051, §22.917(a) | < 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions | PASS |
| Conducted Output Power | §2.1046 | N/A | <u>See Note1</u> |
| Frequency stability / variation of ambient temperature | §2.1055, §22.355 | < 2.5 ppm | PASS |

Note:

1. See SAR Report
2. The same samples were used for SAR and EMC

6.2 Test Condition : Radiated Test

| Test Description | FCC Part Section(s) | Test Limit | Test Result |
|--|------------------------|---|-------------|
| Effective Radiated Power | §22.913(a)(5) | < 7 Watts max. ERP | PASS |
| Radiated Spurious and Harmonic Emissions | §2.1053, §22.917(a) | < 43 + 10log10 (P[Watts]) for all out-of band emissions | PASS |

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

| Ch./ Freq. | | Measured Level(dBm) | Substitute Level(dBm) | Ant. Gain (dBd) | C.L | Pol. | ERP | |
|------------|------------|---------------------|-----------------------|-----------------|------|------|-------|-------|
| channel | Freq.(MHz) | | | | | | W | dBm |
| 128 | 824.20 | -21.37 | 38.40 | -10.61 | 0.95 | H | 0.483 | 26.84 |

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

| Ch./ Freq. | | Measured Level(dBm) | Substitute Level(dBm) | Ant. Gain (dBi) | C.L | Pol. | EIRP | |
|------------|------------|---------------------|-----------------------|-----------------|------|------|-------|-------|
| channel | Freq.(MHz) | | | | | | W | dBm |
| 20175 | 1,732.50 | -15.75 | 18.45 | 9.90 | 1.76 | H | 0.456 | 26.59 |

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW
GSM BW = 249 kHz
G = Phase Modulation
X = Cases not otherwise covered
W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W
GSM BW = 249 kHz
G = Phase Modulation
7 = Quantized/Digital Info
W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W
WCDMA BW = 4.17 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)

PSK Modulation

Emission Designator = 4M48G7D
LTE BW = 4.48 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D
LTE BW = 4.48 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EFFECTIVE RADIATED POWER

| Freq (MHz) | Mod/ Bandwidth [SCS (kHz)] | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | ERP | |
|------------|-------------------------------|------------|----------------------|------------------------|----------------|------|-----|--------|-------|-------|
| | | | | | | | | | W | W dBm |
| 826.5 | Sub6 n5/ 5 MHz [15 kHz] | PI/2 BPSK | -30.77 | 32.94 | -10.24 | 1.28 | V | < 7.00 | 0.139 | 21.43 |
| | | QPSK | -30.89 | 32.82 | -10.24 | 1.28 | V | | 0.135 | 21.31 |
| | | 16-QAM | -31.57 | 32.14 | -10.24 | 1.28 | V | | 0.115 | 20.63 |
| | | 64-QAM | -33.05 | 30.66 | -10.24 | 1.28 | V | | 0.082 | 19.15 |
| | | 256-QAM | -35.57 | 28.14 | -10.24 | 1.28 | V | | 0.046 | 16.63 |
| 836.5 | | PI/2 BPSK | -30.74 | 33.44 | -10.19 | 1.29 | V | | 0.157 | 21.96 |
| | | QPSK | -30.94 | 33.24 | -10.19 | 1.29 | V | | 0.150 | 21.76 |
| | | 16-QAM | -31.69 | 32.49 | -10.19 | 1.29 | V | | 0.126 | 21.01 |
| | | 64-QAM | -33.03 | 31.15 | -10.19 | 1.29 | V | | 0.093 | 19.67 |
| | | 256-QAM | -35.66 | 28.52 | -10.19 | 1.29 | V | | 0.051 | 17.04 |
| 846.5 | | PI/2 BPSK | -31.14 | 33.09 | -10.15 | 1.30 | V | | 0.146 | 21.64 |
| | | QPSK | -31.35 | 32.88 | -10.15 | 1.30 | V | | 0.139 | 21.43 |
| | | 16-QAM | -32.01 | 32.22 | -10.15 | 1.30 | V | | 0.119 | 20.77 |
| | | 64-QAM | -33.48 | 30.75 | -10.15 | 1.30 | V | | 0.085 | 19.30 |
| | | 256-QAM | -36.08 | 28.15 | -10.15 | 1.30 | V | | 0.047 | 16.70 |

| Freq (MHz) | Mod/ Bandwidth [SCS (kHz)] | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | ERP | |
|------------|--------------------------------|------------|----------------------|------------------------|----------------|------|-------|--------|-------|-------|
| | | | | | | | | | W | W |
| 829.0 | Sub6 n5/ 10 MHz [15 kHz] | PI/2 BPSK | -30.86 | 32.95 | -10.22 | 1.28 | V | < 7.00 | 0.140 | 21.45 |
| | | QPSK | -31.03 | 32.78 | -10.22 | 1.28 | V | | 0.134 | 21.28 |
| | | 16-QAM | -31.72 | 32.09 | -10.22 | 1.28 | V | | 0.114 | 20.59 |
| | | 64-QAM | -33.22 | 30.59 | -10.22 | 1.28 | V | | 0.081 | 19.09 |
| | | 256-QAM | -35.80 | 28.01 | -10.22 | 1.28 | V | | 0.045 | 16.51 |
| 836.5 | | PI/2 BPSK | -30.72 | 33.46 | -10.19 | 1.29 | V | | 0.158 | 21.98 |
| | | QPSK | -30.96 | 33.22 | -10.19 | 1.29 | V | | 0.149 | 21.74 |
| | | 16-QAM | -31.71 | 32.47 | -10.19 | 1.29 | V | | 0.126 | 20.99 |
| | | 64-QAM | -33.12 | 31.06 | -10.19 | 1.29 | V | | 0.091 | 19.58 |
| | | 256-QAM | -35.82 | 28.36 | -10.19 | 1.29 | V | | 0.049 | 16.88 |
| 844.0 | PI/2 BPSK | -31.02 | 33.12 | -10.16 | 1.30 | V | 0.147 | 21.66 | | |
| | QPSK | -31.30 | 32.84 | -10.16 | 1.30 | V | 0.137 | 21.38 | | |
| | 16-QAM | -31.95 | 32.19 | -10.16 | 1.30 | V | 0.118 | 20.73 | | |
| | 64-QAM | -33.41 | 30.73 | -10.16 | 1.30 | V | 0.085 | 19.27 | | |
| | 256-QAM | -36.03 | 28.11 | -10.16 | 1.30 | V | 0.046 | 16.65 | | |

| Freq (MHz) | Mod/ Bandwidth [SCS (kHz)] | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | | ERP | |
|------------|--------------------------------|------------|----------------------|------------------------|----------------|------|-------|--------|-------|-------|-----|
| | | | | | | | | W | W | dBm | dBm |
| 831.5 | Sub6 n5/ 15 MHz [15 kHz] | PI/2 BPSK | -30.84 | 33.16 | -10.21 | 1.29 | V | < 7.00 | 0.147 | 21.66 | |
| | | QPSK | -30.99 | 33.01 | -10.21 | 1.29 | V | | 0.142 | 21.51 | |
| | | 16-QAM | -31.60 | 32.40 | -10.21 | 1.29 | V | | 0.123 | 20.90 | |
| | | 64-QAM | -33.15 | 30.85 | -10.21 | 1.29 | V | | 0.086 | 19.35 | |
| | | 256-QAM | -35.77 | 28.23 | -10.21 | 1.29 | V | | 0.047 | 16.73 | |
| 836.5 | | PI/2 BPSK | -30.83 | 33.35 | -10.19 | 1.29 | V | | 0.154 | 21.87 | |
| | | QPSK | -31.05 | 33.13 | -10.19 | 1.29 | V | | 0.146 | 21.65 | |
| | | 16-QAM | -31.76 | 32.42 | -10.19 | 1.29 | V | | 0.124 | 20.94 | |
| | | 64-QAM | -33.11 | 31.07 | -10.19 | 1.29 | V | | 0.091 | 19.59 | |
| | | 256-QAM | -35.64 | 28.54 | -10.19 | 1.29 | V | | 0.051 | 17.06 | |
| 841.5 | PI/2 BPSK | -30.86 | 33.30 | -10.17 | 1.30 | V | 0.153 | 21.83 | | | |
| | QPSK | -31.07 | 33.09 | -10.17 | 1.30 | V | 0.145 | 21.62 | | | |
| | 16-QAM | -31.75 | 32.41 | -10.17 | 1.30 | V | 0.124 | 20.94 | | | |
| | 64-QAM | -33.11 | 31.05 | -10.17 | 1.30 | V | 0.091 | 19.58 | | | |
| | 256-QAM | -35.80 | 28.36 | -10.17 | 1.30 | V | 0.049 | 16.89 | | | |

| Freq (MHz) | Mod/ Bandwidth [SCS (kHz)] | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | ERP | |
|------------|--------------------------------|------------|----------------------|------------------------|----------------|------|-------|--------|-------|-------|
| | | | | | | | | | W | W |
| 834.0 | Sub6 n5/ 20 MHz [15 kHz] | PI/2 BPSK | -31.09 | 33.09 | -10.19 | 1.29 | V | < 7.00 | 0.145 | 21.61 |
| | | QPSK | -31.24 | 32.94 | -10.19 | 1.29 | V | | 0.140 | 21.46 |
| | | 16-QAM | -31.94 | 32.24 | -10.19 | 1.29 | V | | 0.119 | 20.76 |
| | | 64-QAM | -33.39 | 30.79 | -10.19 | 1.29 | V | | 0.085 | 19.31 |
| | | 256-QAM | -35.77 | 28.41 | -10.19 | 1.29 | V | | 0.049 | 16.93 |
| 836.5 | | PI/2 BPSK | -30.98 | 33.20 | -10.19 | 1.29 | V | | 0.149 | 21.72 |
| | | QPSK | -31.23 | 32.95 | -10.19 | 1.29 | V | | 0.140 | 21.47 |
| | | 16-QAM | -31.81 | 32.37 | -10.19 | 1.29 | V | | 0.123 | 20.89 |
| | | 64-QAM | -33.19 | 30.99 | -10.19 | 1.29 | V | | 0.089 | 19.51 |
| | | 256-QAM | -35.91 | 28.27 | -10.19 | 1.29 | V | | 0.048 | 16.79 |
| 839.0 | PI/2 BPSK | -30.75 | 33.41 | -10.17 | 1.30 | V | 0.156 | 21.94 | | |
| | QPSK | -31.01 | 33.15 | -10.17 | 1.30 | V | 0.147 | 21.68 | | |
| | 16-QAM | -31.66 | 32.50 | -10.17 | 1.30 | V | 0.127 | 21.03 | | |
| | 64-QAM | -32.98 | 31.18 | -10.17 | 1.30 | V | 0.094 | 19.71 | | |
| | 256-QAM | -35.70 | 28.46 | -10.17 | 1.30 | V | 0.050 | 16.99 | | |

8.2 RADIATED SPURIOUS EMISSIONS

- NR Band: N5
- LTE Band(Anchor): B2
- Bandwidth: 5 MHz
- Modulation: PI/2 BPSK
- Distance: 3 meters
- SCS: 15 kHz

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | Limit (dBm) |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------------|
| 165300 (826.5) | 1,653.00 | -50.87 | 9.54 | -61.67 | 1.85 | H | -53.98 | -13.00 |
| | 2,479.50 | -52.87 | 10.60 | -57.68 | 2.30 | V | -49.38 | -13.00 |
| | 3,306.00 | -57.03 | 12.33 | -59.02 | 2.69 | V | -49.38 | -13.00 |
| 167300 (836.5) | 1,673.00 | -50.78 | 9.65 | -61.54 | 1.86 | H | -53.75 | -13.00 |
| | 2,509.50 | -55.86 | 10.75 | -60.97 | 2.32 | H | -52.54 | -13.00 |
| | 3,346.00 | -57.11 | 12.48 | -58.76 | 2.70 | H | -48.99 | -13.00 |
| 169300 (846.5) | 1,693.00 | -49.59 | 9.73 | -60.21 | 1.87 | V | -52.35 | -13.00 |
| | 2,539.50 | -53.47 | 10.85 | -57.33 | 2.32 | V | -48.80 | -13.00 |
| | 3,386.00 | -57.11 | 12.63 | -59.11 | 2.72 | V | -49.20 | -13.00 |

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | Limit (dBm) |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------------|
| 18650 (1855.0) | 3,710.00 | -50.38 | 12.43 | -55.37 | 2.86 | V | -45.80 | -13.00 |
| | 5,565.00 | -56.78 | 13.18 | -55.11 | 3.59 | V | -45.52 | -13.00 |
| | 7,420.00 | -57.17 | 11.15 | -47.41 | 4.24 | H | -40.50 | -13.00 |

- NR Band: N5
- LTE Band(Anchor): B2
- Bandwidth: 10 MHz
- Modulation: PI/2 BPSK
- Distance: 3 meters
- SCS: 15 kHz

| Ch | Freq (MHz) | Measured Level (dBi) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | Limit (dBm) |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------------|
| 165800 (829.0) | 1,658.00 | -51.97 | 9.58 | -62.81 | 1.85 | V | -55.08 | -13.00 |
| | 2,487.00 | -53.50 | 10.65 | -58.64 | 2.30 | V | -50.29 | -13.00 |
| | 3,316.00 | -56.12 | 12.38 | -57.97 | 2.68 | V | -48.27 | -13.00 |
| 167300 (836.5) | 1,673.00 | -51.10 | 9.65 | -61.86 | 1.86 | H | -54.07 | -13.00 |
| | 2,509.50 | -56.25 | 10.75 | -61.36 | 2.32 | V | -52.93 | -13.00 |
| | 3,346.00 | -57.06 | 12.48 | -58.71 | 2.70 | V | -48.94 | -13.00 |
| 168800 (844.0) | 1,688.00 | -52.00 | 9.73 | -62.62 | 1.87 | V | -54.76 | -13.00 |
| | 2,532.00 | -53.82 | 10.80 | -58.56 | 2.33 | V | -50.09 | -13.00 |
| | 3,376.00 | -57.84 | 12.60 | -59.85 | 2.72 | V | -49.97 | -13.00 |

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | Limit (dBm) |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------------|
| 18650 (1855.0) | 3,710.00 | -50.28 | 12.43 | -55.27 | 2.86 | V | -45.70 | -13.00 |
| | 5,565.00 | -57.15 | 13.18 | -55.48 | 3.59 | V | -45.89 | -13.00 |
| | 7,420.00 | -56.27 | 11.15 | -46.51 | 4.24 | H | -39.60 | -13.00 |

- NR Band: N5
- LTE Band(Anchor): B2
- Bandwidth: 15 MHz
- Modulation: PI/2 BPSK
- Distance: 3 meters
- SCS: 15 kHz

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | Limit (dBm) |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------------|
| 166300 (831.5) | 1,663.00 | -54.56 | 9.58 | -65.40 | 1.85 | V | -57.67 | -13.00 |
| | 2,494.50 | -56.49 | 10.68 | -61.60 | 2.31 | H | -53.23 | -13.00 |
| | 3,326.00 | -58.01 | 12.40 | -59.88 | 2.69 | V | -50.16 | -13.00 |
| 167300 (836.5) | 1,673.00 | -52.04 | 9.65 | -62.80 | 1.86 | H | -55.01 | -13.00 |
| | 2,509.50 | -55.71 | 10.75 | -60.82 | 2.32 | H | -52.39 | -13.00 |
| | 3,346.00 | -55.81 | 12.48 | -57.46 | 2.70 | H | -47.69 | -13.00 |
| 168300 (841.5) | 1,683.00 | -52.22 | 9.65 | -62.90 | 1.86 | H | -55.11 | -13.00 |
| | 2,524.50 | -55.79 | 10.80 | -60.46 | 2.33 | H | -51.98 | -13.00 |
| | 3,366.00 | -57.26 | 12.58 | -59.07 | 2.72 | H | -49.22 | -13.00 |

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | Limit (dBm) |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------------|
| 18650 (1855.0) | 3,710.00 | -50.38 | 12.43 | -55.37 | 2.86 | V | -45.80 | -13.00 |
| | 5,565.00 | -57.06 | 13.18 | -55.39 | 3.59 | V | -45.80 | -13.00 |
| | 7,420.00 | -56.25 | 11.15 | -46.49 | 4.24 | H | -39.58 | -13.00 |

- NR Band: N5
- LTE Band(Anchor): B2
- Bandwidth: 20 MHz
- Modulation: PI/2 BPSK
- Distance: 3 meters
- SCS: 15 kHz

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | Limit (dBm) |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------------|
| 166800 (834.0) | 1,668.00 | -52.85 | 9.73 | -63.47 | 1.87 | H | -55.61 | -13.00 |
| | 2,502.00 | -55.80 | 10.70 | -60.88 | 2.31 | H | -52.49 | -13.00 |
| | 3,336.00 | -58.41 | 12.43 | -60.14 | 2.70 | H | -50.41 | -13.00 |
| 167300 (836.5) | 1,673.00 | -53.04 | 9.65 | -63.80 | 1.86 | V | -56.01 | -13.00 |
| | 2,509.50 | -56.38 | 10.75 | -61.49 | 2.32 | V | -53.06 | -13.00 |
| | 3,346.00 | -58.02 | 12.48 | -59.67 | 2.70 | H | -49.90 | -13.00 |
| 167800 (839.0) | 1,678.00 | -53.13 | 9.65 | -63.81 | 1.86 | H | -56.02 | -13.00 |
| | 2,517.00 | -57.21 | 10.80 | -61.80 | 2.32 | V | -53.32 | -13.00 |
| | 3,356.00 | -57.36 | 12.53 | -59.15 | 2.71 | H | -49.33 | -13.00 |

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | Limit (dBm) |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------------|
| 18650 (1855.0) | 3,710.00 | -50.69 | 12.43 | -55.68 | 2.86 | V | -46.11 | -13.00 |
| | 5,565.00 | -56.54 | 13.18 | -54.87 | 3.59 | V | -45.28 | -13.00 |
| | 7,420.00 | -56.90 | 11.15 | -47.14 | 4.24 | H | -40.23 | -13.00 |

8.3 OCCUPIED BANDWIDTH

| Band | Band Width | Frequency (MHz) | Modulation | Resource Block Size | Resource Block Offset | Data (MHz) |
|---------|------------|-----------------|------------|---------------------|-----------------------|--------------|
| Sub6 n5 | 5 MHz | 836.5 | BPSK | 25 | 0 | 4.5048 |
| | | | QPSK | | | 4.5022 |
| | | | 16-QAM | | | 4.5041 |
| | | | 64-QAM | | | 4.4876 |
| | | | 256-QAM | | | 4.4932 |
| | 10 MHz | | BPSK | 50 | | 8.9705 |
| | | | QPSK | | | 8.9823 |
| | | | 16-QAM | | | 8.9764 |
| | | | 64-QAM | | | 8.9766 |
| | | | 256-QAM | | | 8.9731 |
| | 15 MHz | | BPSK | 75 | | 13.464 |
| | | | QPSK | | | 13.491 |
| | | | 16-QAM | | | 13.519 |
| | | | 64-QAM | | | 13.467 |
| | | | 256-QAM | | | 13.476 |
| | 20 MHz | | BPSK | 100 | | 17.861 |
| | | | QPSK | | | 17.901 |
| | | | 16-QAM | | | 17.913 |
| | | | 64-QAM | | | 17.872 |
| | | | 256-QAM | | | 17.904 |

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 37 ~ 56.

8.4 CONDUCTED SPURIOUS EMISSIONS

| Band | Band Width (MHz) | Frequency (MHz) | Frequency of Maximum Harmonic (GHz) | Factor (dB) | Measurement Maximum Data (dBm) | Result (dBm) | Limit (dBm) |
|---------|------------------|-----------------|-------------------------------------|-------------|--------------------------------|--------------|-------------|
| Sub6 n5 | 5 | 826.5 | 3.6880 | 30.278 | -66.879 | -36.601 | -13.00 |
| | | 836.5 | 3.7109 | 30.278 | -67.177 | -36.899 | |
| | | 846.5 | 3.6895 | 30.278 | -67.316 | -37.038 | |
| | 10 | 829.0 | 3.6955 | 30.278 | -67.143 | -36.865 | |
| | | 836.5 | 3.6950 | 30.278 | -67.269 | -36.991 | |
| | | 844.0 | 3.6840 | 30.278 | -67.325 | -37.047 | |
| | 15 | 831.5 | 3.6840 | 30.278 | -67.043 | -36.765 | |
| | | 836.5 | 3.7159 | 30.278 | -67.527 | -37.249 | |
| | | 841.5 | 3.6925 | 30.278 | -66.918 | -36.640 | |
| | 20 | 834.0 | 3.6810 | 30.278 | -66.532 | -36.254 | |
| | | 836.5 | 3.6920 | 30.278 | -66.820 | -36.542 | |
| | | 839.0 | 3.6920 | 30.278 | -66.925 | -36.647 | |

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 81 ~ 92.
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
3. Factor(dB) = Cable Loss + Attenuator + 4-Way Divider

| Frequency Range (GHz) | Factor [dB] |
|-----------------------|-------------|
| 0.03 – 1 | 28.691 |
| 1 – 5 | 30.278 |
| 5 – 10 | 31.391 |
| 10 – 15 | 31.716 |
| 15 – 20 | 32.553 |
| Above 20(26.5) | 33.984 |

8.5 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 57 ~ 80.

8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

- ▣ BandWidth: 5 MHz
- ▣ Voltage(100%): 3.880 VDC
- ▣ Batt. Endpoint: 3.400 VDC
- ▣ Deviation Limit: ± 0.000 25 % or 2.5 ppm

| Test. Frequency (MHz) | Voltage (%) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|-----------------------|----------------|------------|----------------|----------------------|---------------|-------|
| 836.5 | 100% | +20(Ref) | 836 500 013 | 0.0 | 0.000 000 | 0.000 |
| | 100% | -30 | 836 500 028 | 14.6 | 0.000 002 | 0.017 |
| | 100% | -20 | 836 500 019 | 5.5 | 0.000 001 | 0.007 |
| | 100% | -10 | 836 500 024 | 10.8 | 0.000 001 | 0.013 |
| | 100% | 0 | 836 500 025 | 11.8 | 0.000 001 | 0.014 |
| | 100% | +10 | 836 500 018 | 5.2 | 0.000 001 | 0.006 |
| | 100% | +30 | 836 500 028 | 15.1 | 0.000 002 | 0.018 |
| | 100% | +40 | 836 500 018 | 4.3 | 0.000 001 | 0.005 |
| | 100% | +50 | 836 500 023 | 10.0 | 0.000 001 | 0.012 |
| | Batt. Endpoint | +20 | 836 500 025 | 12.1 | 0.000 001 | 0.014 |

- ▣ BandWidth: 10 MHz
- ▣ Voltage(100%): 3.880 VDC
- ▣ Batt. Endpoint: 3.400 VDC
- ▣ Deviation Limit: ± 0.000 25 % or 2.5 ppm

| Test. Frequency (MHz) | Voltage (%) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|-----------------------|----------------|------------|----------------|----------------------|---------------|-------|
| 836.5 | 100% | +20(Ref) | 836 500 013 | 0.0 | 0.000 000 | 0.000 |
| | 100% | -30 | 836 500 028 | 14.9 | 0.000 002 | 0.018 |
| | 100% | -20 | 836 500 019 | 5.6 | 0.000 001 | 0.007 |
| | 100% | -10 | 836 500 021 | 8.3 | 0.000 001 | 0.010 |
| | 100% | 0 | 836 500 028 | 15.1 | 0.000 002 | 0.018 |
| | 100% | +10 | 836 500 024 | 10.6 | 0.000 001 | 0.013 |
| | 100% | +30 | 836 500 017 | 3.8 | 0.000 000 | 0.005 |
| | 100% | +40 | 836 500 022 | 8.3 | 0.000 001 | 0.010 |
| | 100% | +50 | 836 500 026 | 12.4 | 0.000 001 | 0.015 |
| | Batt. Endpoint | +20 | 836 500 021 | 8.2 | 0.000 001 | 0.010 |

- ▣ BandWidth: 15 MHz
- ▣ Voltage(100%): 3.880 VDC
- ▣ Batt. Endpoint: 3.400 VDC
- ▣ Deviation Limit: ± 0.000 25 % or 2.5 ppm


| Test. Frequency (MHz) | Voltage (%) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|-----------------------|----------------|------------|----------------|----------------------|---------------|-------|
| 836.5 | 100% | +20(Ref) | 836 500 007 | 0.0 | 0.000 000 | 0.000 |
| | 100% | -30 | 836 500 018 | 10.9 | 0.000 001 | 0.013 |
| | 100% | -20 | 836 500 012 | 5.4 | 0.000 001 | 0.006 |
| | 100% | -10 | 836 500 014 | 7.9 | 0.000 001 | 0.009 |
| | 100% | 0 | 836 500 018 | 11.2 | 0.000 001 | 0.013 |
| | 100% | +10 | 836 500 018 | 11.6 | 0.000 001 | 0.014 |
| | 100% | +30 | 836 500 014 | 7.3 | 0.000 001 | 0.009 |
| | 100% | +40 | 836 500 022 | 15.0 | 0.000 002 | 0.018 |
| | 100% | +50 | 836 500 020 | 13.1 | 0.000 002 | 0.016 |
| | Batt. Endpoint | +20 | 836 500 022 | 14.9 | 0.000 002 | 0.018 |

- ▣ BandWidth: 20 MHz
- ▣ Voltage(100%): 3.880 VDC
- ▣ Batt. Endpoint: 3.400 VDC
- ▣ Deviation Limit: ± 0.000 25 % or 2.5 ppm


| Test. Frequency (MHz) | Voltage (%) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|-----------------------|----------------|------------|----------------|----------------------|---------------|-------|
| 836.5 | 100% | +20(Ref) | 836 500 007 | 0.0 | 0.000 000 | 0.000 |
| | 100% | -30 | 836 500 019 | 12.2 | 0.000 001 | 0.015 |
| | 100% | -20 | 836 500 015 | 8.0 | 0.000 001 | 0.010 |
| | 100% | -10 | 836 500 022 | 15.3 | 0.000 002 | 0.018 |
| | 100% | 0 | 836 500 015 | 8.3 | 0.000 001 | 0.010 |
| | 100% | +10 | 836 500 020 | 13.5 | 0.000 002 | 0.016 |
| | 100% | +30 | 836 500 016 | 8.9 | 0.000 001 | 0.011 |
| | 100% | +40 | 836 500 014 | 6.7 | 0.000 001 | 0.008 |
| | 100% | +50 | 836 500 017 | 9.8 | 0.000 001 | 0.012 |
| | Batt. Endpoint | +20 | 836 500 011 | 3.7 | 0.000 000 | 0.004 |

9. TEST PLOTS


Sub6 n5. Occupied Bandwidth Plot (5M BW Ch.167300 BPSK_RB6_0)




Sub6 n5. Occupied Bandwidth Plot (5M BW Ch.167300 QPSK_RB6_0)




Sub6 n5. Occupied Bandwidth Plot (5M BW Ch.167300 16QAM_RB6_0)




Sub6 n5. Occupied Bandwidth Plot (5M BW Ch.167300 64QAM_RB6_0)




Sub6 n5. Occupied Bandwidth Plot (5M BW Ch.167300 256QAM_RB6_0)




Sub6 n5. Occupied Bandwidth Plot (10M BW Ch.167300 BPSK_RB15_0)




Sub6 n5. Occupied Bandwidth Plot (10M BW Ch.167300 QPSK_RB15_0)




Sub6 n5. Occupied Bandwidth Plot (10M BW Ch.167300 16QAM_RB15_0)




Sub6 n5. Occupied Bandwidth Plot (10M BW Ch.167300 64QAM_RB15_0)




Sub6 n5. Occupied Bandwidth Plot (10M BW Ch.167300 256QAM_RB15_0)




Sub6 n5. Occupied Bandwidth Plot (15M BW Ch.167300 BPSK_RB25_0)




Sub6 n5. Occupied Bandwidth Plot (15M BW Ch.167300 QPSK_RB25_0)




Sub6 n5. Occupied Bandwidth Plot (15M BW Ch.167300 16QAM_RB25_0)




Sub6 n5. Occupied Bandwidth Plot (15M BW Ch.167300 64QAM_RB25_0)




Sub6 n5. Occupied Bandwidth Plot (15M BW Ch.167300 256QAM_RB25_0)




Sub6 n5. Occupied Bandwidth Plot (20M BW Ch.167300 BPSK_RB50_0)




Sub6 n5. Occupied Bandwidth Plot (20M BW Ch.167300 QPSK_RB50_0)




Sub6 n5. Occupied Bandwidth Plot (20M BW Ch.167300 16QAM_RB50_0)




Sub6 n5. Occupied Bandwidth Plot (20M BW Ch.167300 64QAM_RB50_0)



Sub6 n5. Occupied Bandwidth Plot (20M BW Ch.167300 256QAM_RB50_0)



Sub6 n5. Lower Band Edge Plot (5M BW Ch.165300 BPSK_RB1_Offset 0)




Sub6 n5. Lower Band Edge Plot (5M BW Ch.165300 BPSK_RB25_Offset 0)



Sub6 n5. Lower Extended Band Edge Plot (5M BW Ch.165300 BPSK_RB25_0)



Sub6 n5. Lower Band Edge Plot (10M BW Ch.165800 BPSK_RB1_Offset 0)



Sub6 n5. Lower Band Edge Plot (10M BW Ch.165800 BPSK_RB50_Offset 0)



Sub6 n5. Lower Extended Band Edge Plot (10M BW Ch.165800 BPSK_RB50_0)



Sub6 n5. Lower Band Edge Plot (15M BW Ch.166300 BPSK_RB75_Offset 0)



Sub6 n5. Lower Extended Band Edge Plot (15M BW Ch.166300 BPSK_RB75_0)



Sub6 n5. Lower Band Edge Plot (20M BW Ch.166800 BPSK_RB1_Offset 0)



Sub6 n5. Lower Band Edge Plot (20M BW Ch.166800 BPSK_RB100_Offset 0)



Sub6 n5. Upper Band Edge Plot (5M BW Ch.169300 BPSK_RB1_Offset 24)



Sub6 n5. Upper Band Edge Plot (5M BW Ch.169300 BPSK_RB25_Offset 0)



Sub6 n5. Upper Extended Band Edge Plot (5M BW Ch.169300 BPSK_RB25_0)



Sub6 n5. Upper Band Edge Plot (10M BW Ch.168800 BPSK_RB1_Offset 49)




Sub6 n5. Upper Band Edge Plot (10M BW Ch.168800 BPSK_RB50_Offset 0)



Sub6 n5. Upper Extended Band Edge Plot (10M BW Ch.168800 BPSK_RB50_0)



Sub6 n5. Upper Band Edge Plot (15M BW Ch.168300 BPSK_RB1_Offset 74)




Sub6 n5. Upper Extended Band Edge Plot (15M BW Ch.168300 BPSK_RB75_0)




Sub6 n5. Upper Band Edge Plot (20M BW Ch.167800 BPSK_RB1_Offset 99)




Sub6 n5. Upper Extended Band Edge Plot (20M BW Ch.167800 BPSK_RB100_0)




Sub6 n5. Conducted Spurious Plot (165300ch_5MHz_BPSK_RB 1_0)




Sub6 n5. Conducted Spurious Plot (167300ch_5MHz_BPSK_RB 1_0)




Sub6 n5. Conducted Spurious Plot (169300ch_5MHz_BPSK_RB 1_0)




Sub6 n5. Conducted Spurious Plot (165800ch_10MHz_BPSK_RB 1_0)




Sub6 n5. Conducted Spurious Plot (167300ch_10MHz_BPSK_RB 1_0)




Sub6 n5. Conducted Spurious Plot (168800ch_10MHz_BPSK_RB 1_0)




Sub6 n5. Conducted Spurious Plot (166300ch_15MHz_BPSK_RB 1_0)




Sub6 n5. Conducted Spurious Plot (167300ch_15MHz_BPSK_RB 1_0)




Sub6 n5. Conducted Spurious Plot (168300ch_15MHz_BPSK_RB 1_0)




Sub6 n5. Conducted Spurious Plot (166800ch_20MHz_BPSK_RB 1_0)



Sub6 n5. Conducted Spurious Plot (167300ch_20MHz_BPSK_RB 1_0)



Sub6 n5. Conducted Spurious Plot (167800ch_20MHz_BPSK_RB 1_0)



10. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

| No. | Description |
|-----|---------------------|
| 1 | HCT-RF-2007-FC036-P |