

RF Test Report

Wireless Power Transmission

Report No. : RF200522K003-4 R3
Customer : Samsung Electronics Co., Ltd.
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do,
16677, Korea
Use of Report : Certification
Model Name : SM-T975
FCC ID / IC : A3LSMT975
Date of Test : 2020.06.01 to 2020.07.15
Test Method Used : FCC 47 CFR PART 15 Subpart C (Section §15.209) /
ISED RSS-216
Testing Environment : Refer to the Test Condition

Test Result : **Pass** **Fail**

ISSUED BY: BV CPS ADT Korea Ltd., EMC/RF Laboratory

ADDRESS: Innoplex No.2 106, Sinwon-ro 306, Yeongtong-gu,
Suwon-si, Gyeonggi-do, Korea 16675

TEST LOCATION: HeungAn-daero 49, DongAn-gu, Anyang-si,
Gyeonggi-do, Korea, 14119

Tested by

Name : Donghwa Shin



(Signature)

Technical Manager

Name : Jongha Choi



(Signature)

2020. 07. 16

BV CPS ADT Korea Ltd.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



RELEASE CONTROL RECORD

| REPORT NO. | REASON FOR CHANGE | DATE ISSUED |
|-------------------|---|-------------|
| RF200522K003-4 | Original release | 2020.07.01 |
| RF200522K003-4 R1 | Revised information about the test | 2020.07.08 |
| RF200522K003-4 R2 | Corrected the regarding distance extrapolation factor | 2020.07.15 |
| RF200522K003-4 R3 | Revised frequency range | 2020.07.16 |

Table of Contents

| | |
|---|-----------|
| RELEASE CONTROL RECORD | 2 |
| 1 SUMMARY OF TEST RESULTS..... | 4 |
| 1.1 MEASUREMENT UNCERTAINTY | 4 |
| 2 GENERAL INFORMATION..... | 5 |
| 2.1 GENERAL DESCRIPTION OF EUT | 5 |
| 2.2 DESCRIPTION OF TEST MODE | 6 |
| 2.2.1 <i>Description of EUT</i> | 6 |
| 2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS..... | 8 |
| 2.4 TEST EQUIPMENT | 8 |
| 3 TEST RESULTS | 9 |
| 3.1 ANTENNA REQUIREMENT..... | 9 |
| 3.2 RADIATED EMISSIONS..... | 10 |
| 3.2.1 <i>Regulation</i> | 10 |
| 3.2.2 <i>Test Procedure</i> | 11 |
| 3.2.3 <i>Deviation from Test Standard</i> | 12 |
| 3.2.4 <i>Test Setup</i> | 12 |
| 3.2.5 <i>Test Result</i> | 13 |
| 3.3 AC CONDUCTED EMISSIONS (150 KHZ TO 30 MHZ)..... | 15 |
| 3.3.1 <i>Regulation</i> | 15 |
| 3.3.2 <i>Test Procedure</i> | 15 |
| 3.3.3 <i>Deviation from Test Standard</i> | 15 |
| 3.3.4 <i>Test Setup</i> | 16 |
| 3.3.5 <i>Test Result</i> | 17 |
| APPENDIX – INFORMATION OF THE TESTING LABORATORIES | 18 |

1 Summary of Test Results

The EUT has been tested according to the following specifications

| Applied Standard : FCC Part 15, Subpart C 15.209, RSS-216 | | | | | |
|---|----------------|---|---|-------------|-------------|
| FCC Part Section(s) | RSS Section(s) | Test Description | Limit | Test Result | Reference |
| 15.209(a) | RSS-216 | Radiated emission | Emissions in Restricted bands must meet the radiated limits detailed in 15.209 (RSS-247 limits) | PASS | Section 3.2 |
| 15.207 | RSS-210 [8.8] | AC Conducted Emissions (150 kHz – 30 MHz) | < FCC 15.207 limits (RSS-Gen [8.8] limits) | PASS | Section 3.3 |

NOTES

- 1) The general test methods used to test on this devices are ANSI C63.10.
- 2) Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

1.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2

| Measurement Items | Frequency Range | Expanded Uncertainty $U = kU_c (k = 2)$ |
|-----------------------------------|------------------|--|
| Conducted Emissions at main ports | 150 kHz – 30 MHz | 2.62 |
| Radiated Spurious Emissions | 9 kHz – 30 MHz | 1.97 |
| | 30 MHz – 1 GHz | 4.04 |

This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of $k = 2$.

2 General Information

2.1 General Description of EUT

| | |
|----------------------------------|--|
| Product | Tablet |
| Brand | Samsung |
| Model | SM-T975 |
| Identification No. of EUT | - |
| Series Model | - |
| Model Difference | - |
| Power Supply | 3.86 V DC By Battery / DC 5/9 V By Adapter |
| Modulation Type | ASK |
| Operating Frequency | 530 kHz |
| Number of Channel | N/A |
| Output Power | 56.8 dBuV/m |
| Antenna Type | Coil Antenna |
| Antenna Connector | C-clip |
| H/W Version | REV0.4 |
| S/W Version | T975.001 |

NOTES

- 1) The above equipment has been tested by **Bureau Veritas Consumer Products Services ADT Korea**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.
- 2) List of Accessories

| Accessories | Brand | Model | Manufacturer | Specification |
|-------------|---------|-------------|--------------|---|
| Ear phone | Samsung | EHS64 | Samsung | 3.5 mm |
| S-pen | Samsung | EJ-PT870 | Samsung | Bluetooth |
| Keyboard | Samsung | EF-DT970 | Samsung | N/A |
| TA | Samsung | EP-TA200 | Samsung | Input : AC 100-240 V, 50 – 60 Hz, 0.5 A Output : DC 9.0 V, 1.67 A, DC5.0 V, 2.0 A |
| Cable | Samsung | EP-DG930M | Samsung | A to C type, Shielded, 1.m |
| Battery | Samsung | EB-BT975ABY | Samsung | Rating: 3.86Vdc, 9800mAh, 37.83Wh |

2.2 Description of Test Mode

[Test Channel of EUT]

| Mode 1 | Test Case | Description |
|--------------------|-----------|-------------------------------|
| Power Sharing mode | 1 | Charging from Tablet to S-Pen |

2.2.1 Description of EUT

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X axis for radiated emission. Following channel(s) was(were) selected for the final test as listed below :

| EUT Configure mode | Applicable to | | | | Description |
|--------------------|---------------|---------|-----|------|-------------|
| | RE < 1G | RE ≥ 1G | PLC | APCM | |
| - | √ | - | √ | - | - |

Where RE ≥ 1 G : Radiated Emission above 1 GHz & Bandedge Measurement
 RE < 1 G : Radiated Emission below 1 GHz
 PLC : Power Line Conducted Emission
 APCM : Antenna Port Conducted Measurement

Radiated Emission Test (Below 1 GHz)

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure mode | Available Frequency | Tested Frequency | Modulation Type |
|-------------------------------|---------------------|------------------|-----------------|
| Charging from Tablet to S-Pen | 530 kHz | 530 kHz | ASK |

Radiated Emission Test (Above 1 GHz)

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure mode | Available Frequency | Tested Frequency | Modulation Type |
|--------------------|---------------------|------------------|-----------------|
| N/A | N/A | N/A | N/A |

Power line Conducted Emission Test

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure mode | Available Frequency | Tested Frequency | Modulation Type |
|-------------------------------|---------------------|------------------|-----------------|
| Charging from Tablet to S-Pen | 530 kHz | 530 kHz | ASK |

Antenna Port Conducted Measurement

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure mode | Available Frequency | Tested Frequency | Modulation Type |
|--------------------|---------------------|------------------|-----------------|
| N/A | N/A | N/A | N/A |

Test Condition

| Applicable to | Environmental Conditions | Test Voltage | Tested by |
|---------------|--------------------------|---------------------|--------------|
| RE < 1G | 22 °C, 55 % RH | DC 5/9 V By Adaptor | Donghwa Shin |
| RE ≥ 1G | N/A | N/A | N/A |
| PLC | 23 °C, 49 % RH | DC 5/9 V By Adaptor | Donghwa Shin |
| APCM | N/A | | |

2.3 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards.

FCC CFR 47 Part 15, Subpart C
ANSI C63.10-2013

All test items in this test report have been performed and recorded as per the above standards.

2.4 Test Equipment

Test Equipment is traceable to the National Institute of Standards and Technology (NIST). Measurement antenna used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

| Manufacturer | Model | Description | Serial Number | Cal Date | Cal Due |
|--------------|-------------|---|---------------|------------|------------|
| R&S | HFH2-Z2E | Active Loop Antenna, 30 MHz | 349806 | 2019.03.27 | 2021.03.27 |
| Schwarzbeck | VULB 9163 | Trilog Antenna, 3 GHz (with 6 dB ATT.) | 01199 | 2019.04.03 | 2021.04.03 |
| R&S | SCU08F2 | Signal Conditioning Unit, 8 GHz | 08400016 | 2019.12.30 | 2020.12.30 |
| R&S | ESW44 | EMI Test Receiver, 44 GHz | 101812 | 2020.02.20 | 2021.02.20 |
| Aeroflex | 40AH2W-10 | Attenuator, 10 dB | 1 | 2019.12.31 | 2020.12.31 |
| Wt Microwave | WT-A1698-HS | High Pass Filter 3.5 GHz | WT190313-6-4 | 2020.01.03 | 2021.01.03 |
| R&S | ENV216 | LISN | 102437 | 2019.12.26 | 2020.12.26 |
| R&S | ESR | EMI Test Receiver, 3.6 GHz | 102529 | 2019.12.27 | 2020.12.27 |

3 Test Results

3.1 Antenna Requirement

Except from §15.203 of the FCC Rules/Regulations:

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of the section.

- The antenna(s) of the EUT are Permanently attached.
- There are no provisions for connection to an external antenna.

Result

The EUT complies with the requirement of §15.203

3.2 Radiated Emissions

3.2.1 Regulation

§15.247(d) : In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

§15.209(a) : Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100** | 3 |
| 88-216 | 150** | 3 |
| 216-960 | 200** | 3 |
| Above 960 | 500 | 3 |

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

3.2.2 Test Procedure

Spurious Radiated Emissions

1. The preliminary radiated measurement were performed to determine the frequency producing the maximum emissions in an semi-anechoic chamber at a distance of 3 meters.
2. The EUT was placed on the top of the 0.8-meter height, 1 x 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360°.
3. The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 9 kHz to 30 MHz using the loop antenna, and from 30 to 1000 MHz using the Bi-Log antenna, and from 1000 MHz to 26500 MHz using the horn antenna.
4. To obtain the final measurement data, the EUT was arranged on a turntable situated on a 4 x 4 meter in an semi-anechoic chamber. The EUT was tested at a distance 3 meters.
5. Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector fuction with specified bandwidth.
6. The 0.8 m height is for below 1 GHz testing, and 1.5 m is for above 1GHz testing.

- Procedure for unwanted emissions measurements below 1 000 MHz

The procedure for unwanted emissions measurements below 1 000 MHz is as follows:

- a) Follow the requirements in 12.7.4.
- b) Compliance shall be determined using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.


- Sample Calculation

- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m] + Duty Cycle Correction [dB]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable loss [dB]
- Margin [dB] = Field Strength Level [dB μ V/m] – Limit [dB μ V/m]


3.2.3 Deviation from Test Standard

No deviation.

3.2.4 Test Setup



[Radiated Emission Test Setup Below 30 MHz]




[Radiated Emission Test Setup Below 1 GHz]



3.2.5 Test Result

3.2.5.1 Radiated Emissions (Below 30 MHz)

RSE(Below 30 MHz)_Wireless Charging_Face on_Z_(530 kHz)




| Frequency [MHz] | Peak Reading Value [dBµV/m] | Peak [dBµV/m] | Quasi Reading Value [dBµV/m] | Quasi Peak [dBµV/m] | Distance Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Pol | Azimuth [deg] | Correction Factor [dB] |
|-----------------|-----------------------------|---------------|------------------------------|---------------------|----------------------|----------------|-------------|-------------|-----|---------------|------------------------|
| 0.03 | 26.73 | -32.87 | - | - | -80.00 | 37.71 | 70.58 | 100.00 | H | 358.00 | -59.60 |
| 0.53 | - | - | 36.04 | 16.34 | -40.00 | 33.10 | 16.75 | 100.00 | H | 284.00 | -19.70 |
| 8.38 | 11.87 | -7.03 | - | - | -40.00 | 29.54 | 36.57 | 100.00 | H | 57.00 | -18.90 |

Remarks

1. Quasi Peak(dBuV/m) = Quasi Peak Reading Value(dBuV/m) + Correction Factor(dB) + Distance Factor(dB)
2. Correction Factor(dB) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin(dB) = (Peak) Result (dBµV/m) – (Peak) Limit (dBµV/m)
4. Frequency of 530 kHz is the fundamental signal(Charging)

3.2.5.2 Radiated Emissions (Below 1 GHz)

RSE(Below 1 GHz)_Wireless Charging_Face on_(530 kHz)



| Frequency [MHz] | Peak Reading Value [dB _{µV/m}] | Peak Result [dB _{µV/m}] | AVG Reading Value [dB _{µV/m}] | AVG Result [dB _{µV/m}] | DCCF [dB] | Bandwidth [kHz] | Height [cm] | Pol [H/V] | Azimuth [deg] | Correction Factor [dB/m] | Margin [dB] | Limit [dB _{µV/m}] |
|-----------------|--|-----------------------------------|---|----------------------------------|-----------|-----------------|-------------|-----------|---------------|--------------------------|-------------|-----------------------------|
| 42.502 | 49.63 | 29.3 | --- | --- | 18.2 | --- | 100.0 | V | 358 | -20.3 | 10.7 | 40.0 |
| 44.966 | 47.5 | 27.5 | --- | --- | 18.2 | --- | 100.0 | V | 358 | -20.0 | 12.5 | 40.0 |
| 444.025 | 35.7 | 19.8 | --- | --- | 18.2 | --- | 100.0 | H | 251 | -15.9 | 26.3 | 46.0 |

3.3 AC Conducted Emissions (150 kHz to 30 MHz)

3.3.1 Regulation

§15.207(a) : Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

| Frequency of emission (MHz) | Conducted limit (dB μ V) | |
|-----------------------------|------------------------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

3.3.2 Test Procedure


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm / 50 μ H of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Remark : The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz – 30 MHz.

3.3.3 Deviation from Test Standard

No deviation.


3.3.4 Test Setup





3.3.5 Test Result

Wireless Charging_Face on_(530 kHz)



| Frequency [MHz] | Quasi Peak Reading Value [dBuV] | Quasi Peak Result [dBuV] | CAV Reading Value [dBuV] | CAV Result [dBuV] | Line | Correction Factor [dB/m] | Quasi Peak Margin [dBuV] | Quasi Peak Limit [dBuV] | CAV Margin [dBuV] | CAV Limit [dBuV] |
|-----------------|---------------------------------|--------------------------|--------------------------|-------------------|------|--------------------------|--------------------------|-------------------------|-------------------|------------------|
| 0.31 | - | - | 12.71 | 22.61 | L1 | 9.90 | - | - | 27.30 | 49.91 |
| 0.31 | 24.99 | 34.89 | - | - | L1 | 9.90 | 25.02 | 59.91 | - | - |
| 9.32 | - | - | 18.41 | 28.51 | L1 | 10.10 | - | - | 21.49 | 50.00 |
| 9.32 | 27.93 | 38.03 | - | - | L1 | 10.10 | 21.97 | 60.00 | - | - |
| 13.40 | - | - | 26.25 | 36.55 | L1 | 10.30 | - | - | 13.45 | 50.00 |
| 13.40 | 34.80 | 45.10 | - | - | L1 | 10.30 | 14.90 | 60.00 | - | - |
| 13.51 | - | - | 23.24 | 33.64 | N | 10.40 | - | - | 16.36 | 50.00 |
| 13.51 | 34.16 | 44.56 | - | - | N | 10.40 | 15.44 | 60.00 | - | - |
| 14.04 | - | - | 21.09 | 31.49 | N | 10.40 | - | - | 18.51 | 50.00 |
| 14.04 | 32.84 | 43.24 | - | - | N | 10.40 | 16.76 | 60.00 | - | - |
| 14.47 | - | - | 18.53 | 28.93 | N | 10.40 | - | - | 21.07 | 50.00 |
| 14.47 | 30.71 | 41.11 | - | - | N | 10.40 | 18.89 | 60.00 | - | - |

Remarks

1. Final Value (QP and/or CAV) = Reading Value (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Final Value (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

2. Two graphs measured for both Live (L1) and Neutral (N) of the LISN are combined into one graph.



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services Korea. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

Test Firm Name : BV CPS ADT Korea Ltd.

Address : Innoplex No.2 106, Sinwon-ro 306, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675 KOREA

FCC

Designation Number : KR0158

Test Firm Registration Number : 666061

ISED

Designation Number : KR0158

Test Firm Registration Number : 25944

If you have any comments, please feel free to contact us at the following:

Email: Meyer.Shin@bureauveritas.com

Web Site: www.bureauveritas.co.kr/cps/eaw

The address and road map of all our labs can be found in our web site also.

- End of report -