

# EMC TEST REPORT

<b>Project No.</b>	LBE20160683	<b>Issue No.</b>	0
<b>Applicant</b>	<b>Name of organization</b>	Samsung Electronics Co., Ltd.	
	<b>Address</b>	(Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea	
	<b>Date of application</b>	February 25, 2016	
<b>EUT</b>	<b>Type of device</b>	<input checked="" type="checkbox"/> Class B personal computers and peripherals <input type="checkbox"/> All other devices	
	<b>Equipment authorization</b>	<input type="checkbox"/> Declaration of Conformity <input checked="" type="checkbox"/> Certification <input type="checkbox"/> Verification	
	<b>FCC ID</b>	A3LSMW708Y	
	<b>Kind of product</b>	Portable Device	
	<b>Model No.</b>	SM-W708Y	
	<b>Variant Model No.</b>	Refer to clause 4.6	
	<b>Manufacturer</b>	SAMSUNG ELECTRONICS CO., LTD. 302, 3 Gongdan 3-ro, Gumi-si Gyengsangbuk-do, 39388, Republic of Korea  SAMSUNG ELECTRONICS VIETNAM CO., LTD. 730-722 Yenphong 1-I.P, YenTrung Commune, Yenphong Dist. Bacninh Province Vietnam	
<b>Applied Standards</b>	FCC Part 15, Subpart B, Class B / ANSI C63.4-2009		
<b>Test Period</b>	March 2, 2016 ~ March 7, 2016		
<b>Issue date</b>	March 7, 2016		

## Test result : Complied

The equipment under test has found to be compliant with the applied standards.  
(Refer to the attached test result for more detail.)

**Tested by** : Sung-Wook Choi

*S. W. Choi*

**Reviewed by** : Young-Hun Kim

*Y. H. Kim*

The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from CS & Environment center.



**CS & Environment Center of Samsung Electronics Co., Ltd.**

(Maetan dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea

# Table of contents

<b>1. Report Information .....</b>	<b>3</b>
1.1 Revision history .....	3
<b>2. Summary of test results .....</b>	<b>3</b>
2.1 Emission .....	3
<b>3. General Information .....</b>	<b>3</b>
3.1 Test facility.....	3
<b>4. Test Setup configuration .....</b>	<b>4</b>
4.1 Test Peripherals .....	4
4.2 EUT operating mode .....	5
4.3 Details of Sampling .....	5
4.4 Used cable description .....	6
4.5 Test arrangement .....	6
4.6 EUT Description .....	8
4.7 Clock Frequencies.....	9
4.8 Test configuration and condition.....	9
4.9 Measurement uncertainty.....	10
<b>5. Results of individual test .....</b>	<b>11</b>
5.1 Conducted disturbance .....	11
5.2 Radiated disturbance .....	14

# 1. Report Information

## 1.1 Revision history

No.	Revised detailed information
Issue 0	There are no revisions and this version is basic test report.

# 2. Summary of test results

## 2.1 Emission

The EUT has been tested according to the following specifications:

Applied	Test type	Applied standard	Result
<input checked="" type="checkbox"/>	Conducted Disturbance (Mains port)	FCC Part 15 Subpart B / ANSI C63.4-2009 (Class B)	Complied
<input checked="" type="checkbox"/>	Radiated Disturbance		Complied

# 3. General Information

## 3.1 Test facility

The CS & Environment center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea.

All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 22, 16-1 and 16-2. and Shielded rooms.

The CS & Environment center is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.

## 4. Test Setup configuration

### 4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Mark	Description	Model No.	Serial No.	Manufacturer / Trademark	FCC ID / DoC
A	Portable Device	SM-W708Y	-	SAMSUNG	A3LSMW708Y
B	Keyboard	EJ-CW700	-	SAMSUNG	-
C	Battery	EB-BW700ABE	-	SAMSUNG	-
D	Headset	EO-EG900BW	-	SAMSUNG	-
E	Data Cable	EP-DW700CWE	-	SAMSUNG	-
F	Travel Adapter	EP-TA300	R37H1CZHEK1SE3	SAMSUNG	-
G	Bluetooth Mouse	SMB-1000BS	TAKG900544L	SAMSUNG	-
H	UHD Monitor	LU32D97K	0VDQH3EG200117M	SAMSUNG	-
I	OTG Dongle	A1632	-	APPLE	-
J	Memory Stick	UV131	-	ADATA	-
K	LAN Dongle	-	-	KANGWON	-

## 4.2 EUT operating mode

To achieve compliance applied standard specification, the following mode(s) were made during compliance testing:

<b>Operating Mode 1</b>	<p style="text-align: center;"><b>Charging Mode</b></p> <p>(Internal Memory Read &amp; Write, Rear Camera Recording, H pattern on video, Video play, Audio play, Wi-Fi(2.4G), Bluetooth communication)</p>
<b>Operating Mode 2</b>	<p style="text-align: center;"><b>Charging Mode</b></p> <p>(Internal Memory Read &amp; Write, Front Camera Recording, H pattern on video, Video play, Audio play, Wi-Fi(5G), Bluetooth communication, GPS)</p>
<b>Operating Mode 3</b>	<p style="text-align: center;"><b>DP Mode</b></p> <p>(Internal Memory Read &amp; Write, Rear Camera Recording, H pattern on video, Video play, Audio play, Wi-Fi(2.4G), Bluetooth communication, DP display)</p>
<b>Operating Mode 4</b>	<p style="text-align: center;"><b>OTG Mode</b></p> <p>(External/Internal Memory Read &amp; Write, Rear Camera Recording, H pattern on video, Video play, Audio play, Wi-Fi(2.4G), Bluetooth communication, NFC)</p>
<b>Operating Mode 5</b>	<p style="text-align: center;"><b>LAN Mode</b></p> <p>(Internal Memory Read &amp; Write, Rear Camera Recording, H pattern on video, Video play, Audio play, Bluetooth communication, WCDMA FDD5 Idle, LAN)</p>

## 4.3 Details of Sampling

Customer selected, single unit.


#### 4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:


No.	Connected cable	Length [m]	Shielded [Y/N]	Note
1	Data Cable	1.2	Yes	From EUT to Travel Adapter
2	Headset	1.2	No	For EUT
3	DP Cable	1.8	Yes	From EUT to UHD Monitor
4	Power	1.8	No	For UHD Monitor
5	LAN	2.5	No	From LAN Dongle to Local Area Network

#### 4.5 Test arrangement


Operating Mode 1 ~ 2




### Operating Mode 3



### Operating Mode 4



### Operating Mode 5



## 4.6 EUT Description

Item	Specification	Remarks
CPU	Intel SKYLAKE Y CORE M3-6Y30	-
Main Memory	SEC, Samsung LPDDR3, Onboard, 4 GB	-
LCD DISPLAY	AMSA20JW01, 12" AMOLED, 2166X1440	-
Graphic Controller	Intel HD Graphics	-
SSD	Liteon 128GB SSD, M.2 SATA	-
LAN	N/A	-
WLAN/Bluetooth	Qualcomm QCA6174A-5, 802.11b/g/n/a/ac, BT4.1	-
Adapter	SEM, EP-TA300, 25W	-
Battery	Samsung SDI, EB-BW700ABE, Li-ion, 39.5 Wh (5200 mAh)	-
Camera	REAR: 5M CIS AF, Front : 5M CIS FF	-
Input Devices	Keyboard Cover, PS2 touch pad	-
Ports	1xUSB3.0 C-Type port	-

### 4.6.1 The variant models

- None

## 4.7 Clock Frequencies

Kind of Clocks	Frequency [ MHz ]
CPU	2 200

## 4.8 Test configuration and condition

The EUT exercise program was tested using the Samsung special test program for Windows. While the EMC testing was being done, the LCD panel was open and a pattern of “H” characters was written to the display on the LCD panel.

The system was configured for testing in a typical fashion that a customer would normally use. Cables were attached to each of the available I/O Ports. Where applicable, peripherals were attached to the I/O cables. All the external I/O ports was exercised, as well as internal and the USB3.0 Memory stick (OTG) by writing and reading a continuous stream of “H” characters. The music was repetitively played connected to the earphone. The webcam of the EUT was operated continuously.

The EUT’s GPS function was placed in a receiving before the test and then checked at the end of the test to see that the position and speed were correctly displayed.

The EUT’s NFC function was placed in a tag reading before the test and then checked at the end of the test to see that the correct tag reading was maintained.

The EUT’s Wi-Fi and Bluetooth functions connected to the Wi-Fi router and Bluetooth mouse. The EUT was connected to Local Area Network through the Ethernet port with Unshielded Twisted Pair Ethernet cable.

The EUT was placed in a standby before the test and then checked at the end of the test to see that there was no unintended transmission for idle mode

Power source for the EUT operating was supplied by CVCF made by the Pacific Corp.

**- Test Voltage : AC 120 V, 60 Hz**

## 4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4 and UKAS Lab 34.)

### 4.9.1 Emission

Test type		Measurement uncertainty (C.L. 95 %, $k = 2$ )
Conducted disturbance	AC Mains	2.86 dB
Radiated Disturbance (30 MHz ~ 1 GHz)	Horizontal	4.99 dB
	Vertical	4.90 dB
Radiated Disturbance (1 GHz ~ 6 GHz)	Horizontal	4.83 dB
	Vertical	4.84 dB

## 5. Results of individual test

### 5.1 Conducted disturbance

Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

#### Limits for conducted disturbance at the mains ports of Class B ITE

Frequency range Limits [ MHz ]	Resolution Bandwidth [ kHz ]	Limits [ dB(μV) ]	
		Quasi-peak	Average
0,15 to 0,50	9	66 to 56	56 to 46
0,50 to 5	9	56	46
5 to 30	9	60	50

NOTE 1 The lower limit shall apply at the transition frequency.  
NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

#### 5.1.1 Test instrumentation


EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Calibration	
					Date	Interval (Month)
E5I-010	LISN	ESH3-Z5	R&S	100263	2015-11-06	12
E5I-043	LISN	ENV216	R&S	101630	2015-06-27	12
E5I-018	EMI Test Receiver	ESU8	R&S	100484	2015-06-05	12
E5I-100	Notebook Computer	NT-BONEXT-AS2	SAMSUNG	Z9H893GS200016D	-	-
E5I-108	Wi-Fi Router	R7000	NETGEAR	3LN1437W00AA7	-	-

#### 5.1.2 Temperature and humidity condition

Test date	2016-03-04	Test engineer	Sung-Wook Choi
Climate condition	Ambient temperature	(23.1 ~ 23.4) °C	Limit (15.0 to 35.0) °C
	Relative humidity	(44.9 ~ 46.2) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(101.7 ~ 101.8) kPa	Limit (86.0 to 106.0) kPa
Test place	Shield Room (SR14)		

### 5.1.3 Test results

#### □ Operating Mode 1: AC Mains




Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP /CAV final measurement results table:

Frequency (MHz)	QuasiPeak (dBµV)	CISPR Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.494	---	31.4	46.1	14.7	N	10.2
0.499	38.5	---	56.0	17.5	L1	10.2
0.562	---	33.1	46.0	12.9	N	10.2
4.810	41.7	---	56.0	14.3	L1	9.8
6.089	43.7	---	60.0	16.3	L1	9.8
6.157	45.7	---	60.0	14.3	L1	9.8
6.227	45.5	---	60.0	14.5	L1	9.8
23.014	---	35.5	50.0	14.5	N	10.2
23.272	42.2	---	60.0	17.8	N	10.2
23.318	---	36.0	50.0	14.0	N	10.2
23.750	---	36.4	50.0	13.6	N	10.2

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)  
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)  
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

Operating Mode 2: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP /CAV final measurement results table:

Frequency (MHz)	QuasiPeak (dBµV)	CISPR Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.494	42.1	---	56.1	14.0	L1	10.2
0.557	---	31.5	46.0	14.5	N	10.2
0.562	---	32.9	46.0	13.1	N	10.2
3.198	39.2	---	56.0	16.8	L1	9.8
4.366	40.8	---	56.0	15.2	L1	9.7
4.721	37.5	---	56.0	18.5	L1	9.8
6.202	---	35.3	50.0	14.7	L1	9.8
6.207	43.8	---	60.0	16.2	L1	9.8
6.262	44.1	---	60.0	15.9	L1	9.8
22.829	---	33.3	50.0	16.7	N	10.2
23.435	---	33.9	50.0	16.1	N	10.2
24.373	---	35.0	50.0	15.0	N	10.2

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

## 5.2 Radiated disturbance

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

Antenna Height [ cm ]	Antenna Polarisation	Resolution Bandwidth [ kHz ]	Video Bandwidth [ kHz ]	Turntable position [ degrees ]
100 ~ 400	Horizontal, Vertical	120	300	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency in accordance with internal maximum operating frequency at a measurement distance of 3 m for the following antenna and turntable arrangements:

Antenna Height [ cm ]	Antenna Polarisation	Resolution Bandwidth [ MHz ]	Video Bandwidth [ MHz ]	Turntable position [ degrees ]
100 ~ 400	Horizontal, Vertical	1	3	0 ~ 345 (Step size: 15 degrees)

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using peak and CISPR-average detectors.

### Limits for radiated disturbance of Class B ITE at a measuring distance of 3 m and 10 m

Frequency range Limits [ MHz ]	Field Strength		
	3 m [ $\mu\text{V/m}$ ]	3 m [ dB( $\mu\text{V/m}$ ) ]	10 m [ dB( $\mu\text{V/m}$ ) ]
30 to 88	100	40.0	29.5
88 to 216	150	43.5	33.0
216 to 960	200	46.0	35.5
Above 960	500	54.0	43.5

Results checked manually; and points close to the limit line were re-measured.

## 5.2.1 Test instrumentation

EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Calibration	
					Date	Interval (Month)
E5I-123	EMI Test Receiver	ESU8	R&S	100475	2015-05-11	12
E5I-020	EMI Test Receiver	ESU40	R&S	100375	2015-06-01	12
E5I-035	Horn Antenna	HF907	R&S	100506	2015-05-07	24
E5I-073	Preamplifier	310N	SONOMA	332016	2015-06-01	12
E5I-074	Preamplifier	310N	SONOMA	332017	2015-06-01	12
E5I-039	Signal Conditioning Unit	SCU-18	R&S	10211	2015-01-22	12
E5I-070	BiLog Antenna	CBL6112D	TESEQ	35383	2015-06-15	24
E5I-121	BiLog Antenna	CBL6112D	TESEQ	36999	2014-06-26	24
E5I-109	Universal Radio Communicator	CMU200	R&S	110431	2015-11-16	12
E5I-100	Notebook Computer	NT-BONEXT-AS2	SAMSUNG	Z9H893GS200016D	-	-
E5I-108	Wi-Fi Router	R7000	NETGEAR	3LN1437W00AA7	-	-


## 5.2.2 Temperature and humidity condition

<b>Test date</b>	2016-03-02 ~ 2016-03-07	<b>Test engineer</b>	Sung-Wook Choi
<b>Climate condition</b>	Ambient temperature	(22.6 ~ 22.8) °C	Limit (15.0 to 35.0) °C
	Relative humidity	(42.7 ~ 43.4) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(101.9 ~ 102.1) kPa	Limit (86.0 to 106.0) kPa
<b>Test place</b>	Semi-Anechoic Chamber (SAC8)		

### 5.2.3 Test results


#### - Frequencies below 1 GHz

#### Operating Mode 1




Note) Receiving antenna polarization : Horizontal, Vertical  
 Test Distance : 10 m, Antenna Height : 1 to 4 meters  
 Level (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)  
 Margin (QP) = Limit - Level (QP)  
 QP = Quasi-Peak, c.f = Correction Factor

Operating Mode 2




Note) Receiving antenna polarization : Horizontal, Vertical  
 Test Distance : 10 m, Antenna Height : 1 to 4 meters  
 Level (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)  
 Margin (QP) = Limit - Level (QP)  
 QP = Quasi-Peak, c.f = Correction Factor

Operating Mode 3




Note) Receiving antenna polarization : Horizontal, Vertical  
 Test Distance : 10 m, Antenna Height : 1 to 4 meters  
 Level (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)  
 Margin (QP) = Limit - Level (QP)  
 QP = Quasi-Peak, c.f = Correction Factor

Operating Mode 4



Note) Receiving antenna polarization : Horizontal, Vertical  
 Test Distance : 10 m, Antenna Height : 1 to 4 meters  
 Level (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)  
 Margin (QP) = Limit - Level (QP)  
 QP = Quasi-Peak, c.f = Correction Factor

Operating Mode 5



\* Remark: Radiated emissions (Tx 870.020 MHz, 870.869 MHz frequency) from the transceiver shall be ignored.

Note) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters


Level (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

Operating Mode 1



\* Remark: Radiated emissions (Tx / Rx frequency and Harmonics) from the transceiver shall be ignored.

PK /CAV final measurement results table:

Frequency (MHz)	Peak (dB $\mu$ V/m)	CAV (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2 403.000	---	32.7	54.0	21.3	100.0	V	180.0	-1.9
2 403.000	76.7	---	74.0	-2.7	100.0	V	180.0	-1.9
2 408.500	---	78.7	54.0	-24.7	100.0	H	15.0	-1.9
2 408.500	84.5	---	74.0	-10.5	100.0	H	0.0	-1.9
2 414.500	70.8	---	74.0	3.2	100.0	H	270.0	-1.9
2 415.000	---	60.2	54.0	-6.2	100.0	H	240.0	-1.9
2 446.000	---	46.8	54.0	7.2	100.0	V	30.0	-1.7
2 446.000	75.6	---	74.0	-1.6	100.0	V	0.0	-1.7
2 467.000	74.9	---	74.0	-0.9	100.0	V	90.0	-1.7
2 467.000	---	42.6	54.0	11.4	100.0	V	45.0	-1.7
2 472.000	77.0	---	74.0	-3.0	100.0	V	180.0	-1.6
2 472.000	---	50.3	54.0	3.7	100.0	V	180.0	-1.6
4 827.500	---	37.0	54.0	17.0	100.0	H	345.0	7.9
4 837.000	61.9	---	74.0	12.1	100.0	H	330.0	7.9
4 876.500	57.1	---	74.0	16.9	100.0	V	0.0	8.0
4 880.000	---	35.5	54.0	18.5	100.0	V	120.0	8.0
4 880.000	57.7	---	74.0	16.3	100.0	V	150.0	8.0
4 894.500	60.0	---	74.0	14.0	100.0	H	0.0	8.1
4 941.000	54.0	---	74.0	20.0	100.0	H	180.0	8.3
9 650.500	57.0	---	74.0	17.0	100.0	V	0.0	18.8

Note) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

**Operating Mode 2**



\* Remark: Radiated emissions (Tx / Rx frequency and Harmonics) from the transceiver shall be ignored.

PK /CAV final measurement results table:

Frequency (MHz)	Peak (dB $\mu$ V/m)	CAV (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 920.000	---	26.9	54.0	27.1	100.0	V	15.0	-4.1
5 173.000	---	42.8	54.0	11.2	100.0	V	0.0	8.6
5 173.000	68.6	---	74.0	5.4	100.0	V	30.0	8.6
5 186.500	69.5	---	74.0	4.5	100.0	H	270.0	8.5
5 186.500	---	41.6	54.0	12.4	100.0	H	255.0	8.5
5 190.500	---	39.5	54.0	14.5	100.0	V	90.0	8.5
5 190.500	79.8	---	74.0	-5.8	100.0	V	120.0	8.5
7 593.500	48.8	---	74.0	25.2	100.0	V	315.0	14.8

Note) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

Operating Mode 3



\* Remark: Radiated emissions (Tx / Rx frequency and Harmonics) from the transceiver shall be ignored.

PK /CAV final measurement results table:

Frequency (MHz)	Peak (dB $\mu$ V/m)	CAV (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 372.000	---	27.3	54.0	26.7	100.0	V	180.0	-8.1
1 394.500	44.6	---	74.0	29.4	100.0	V	105.0	-7.6
1 537.500	46.4	---	74.0	27.6	100.0	V	30.0	-6.6
2 412.500	---	51.5	54.0	2.5	100.0	V	180.0	-1.9
2 412.500	80.3	---	74.0	-6.3	100.0	V	180.0	-1.9
2 444.000	78.2	---	74.0	-4.2	100.0	H	90.0	-1.7
2 444.000	---	60.7	54.0	-6.7	100.0	H	120.0	-1.7
2 452.000	72.0	---	74.0	2.0	100.0	H	330.0	-1.7
2 452.500	---	51.1	54.0	2.9	100.0	H	240.0	-1.7
2 457.500	---	46.2	54.0	7.8	100.0	H	300.0	-1.7
2 457.500	66.7	---	74.0	7.3	100.0	H	0.0	-1.7
2 787.000	44.1	---	74.0	29.9	100.0	V	15.0	-0.4
4 893.000	---	33.7	54.0	20.3	100.0	H	270.0	8.1
4 893.000	57.7	---	74.0	16.3	100.0	H	315.0	8.1
4 922.500	64.5	---	74.0	9.5	100.0	H	45.0	8.2
4 922.500	---	37.8	54.0	16.2	100.0	H	70.0	8.2
5 283.000	54.7	---	74.0	19.3	100.0	V	210.0	8.2
7 359.500	57.1	---	74.0	16.9	100.0	H	345.0	14.1
7 359.500	---	36.1	54.0	17.9	100.0	H	315.0	14.1
7 415.500	---	35.5	54.0	18.5	100.0	H	150.0	14.3
7 415.500	55.9	---	74.0	18.1	100.0	H	195.0	14.3
9 728.500	55.4	---	74.0	18.6	100.0	H	90.0	18.9

Note) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

**Operating Mode 4**



\* Remark: Radiated emissions (Tx / Rx frequency and Harmonics) from the transceiver shall be ignored.

PK /CAV final measurement results table:

Frequency (MHz)	Peak (dB $\mu$ V/m)	CAV (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2 400.500	---	24.6	54.0	29.4	100.0	H	90.0	-1.9
2 400.500	56.9	---	74.0	17.1	100.0	H	75.0	-1.9
2 408.000	---	64.9	54.0	-10.9	100.0	H	0.0	-1.9
2 408.000	73.9	---	74.0	0.1	100.0	H	0.0	-1.9
2 409.000	---	64.4	54.0	-10.4	100.0	H	180.0	-1.9
2 409.000	69.6	---	74.0	4.4	100.0	H	180.0	-1.9
2 412.000	69.7	---	74.0	4.3	100.0	V	300.0	-1.9
2 412.000	---	60.4	54.0	-6.4	100.0	V	270.0	-1.9
2 420.500	69.6	---	74.0	4.4	100.0	V	60.0	-1.8
2 420.500	---	50.3	54.0	3.7	100.0	V	90.0	-1.8
2 440.500	---	52.0	54.0	2.0	100.0	V	345.0	-1.8
2 440.500	81.2	---	74.0	-7.2	100.0	V	315.0	-1.8
2 476.000	---	33.2	54.0	20.8	100.0	V	150.0	-1.6
2 476.000	61.7	---	74.0	12.3	100.0	V	180.0	-1.6
4 894.500	62.0	---	74.0	12.0	100.0	H	210.0	8.1
4 894.500	---	36.4	54.0	17.6	100.0	H	225.0	8.1
4 958.000	---	41.0	54.0	13.0	100.0	H	0.0	8.4
4 958.000	65.8	---	74.0	8.2	100.0	H	0.0	8.4
7 219.000	57.3	---	74.0	16.7	100.0	H	90.0	13.7
7 249.000	60.8	---	74.0	13.2	100.0	H	135.0	13.8

Note) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

**Operating Mode 5**



\* Remark: Radiated emissions (Tx / Rx frequency and Harmonics) from the transceiver shall be ignored.

PK /CAV final measurement results table:

Frequency (MHz)	Peak (dB $\mu$ V/m)	CAV (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 215.500	---	30.2	54.0	23.8	100.0	V	0.0	-8.9
1 221.500	42.6	---	74.0	31.4	100.0	V	15.0	-8.9
2 283.000	---	33.6	54.0	20.4	100.0	H	270.0	-2.5
2 283.000	45.1	---	74.0	28.9	100.0	H	300.0	-2.5
2 404.000	---	45.7	54.0	8.3	100.0	V	105.0	-1.9
2 404.000	76.2	---	74.0	-2.2	100.0	V	120.0	-1.9
2 425.500	---	29.9	54.0	24.1	100.0	V	330.0	-1.8
2 425.500	60.0	---	74.0	14.0	100.0	V	315.0	-1.8
2 440.000	75.8	---	74.0	-1.8	100.0	V	0.0	-1.8
2 440.000	---	44.2	54.0	9.8	100.0	V	0.0	-1.8
2 474.000	60.0	---	74.0	14.0	100.0	V	240.0	-1.6
2 474.000	---	31.7	54.0	22.3	100.0	V	195.0	-1.6
4 944.000	63.5	---	74.0	10.5	100.0	H	90.0	8.4
4 944.000	---	39.0	54.0	15.0	100.0	H	135.0	8.4
7 383.000	51.2	---	74.0	22.8	100.0	H	210.0	14.2

Note) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor