



FCC 47 CFR PART 15 SUBPART E

UNII

CERTIFICATION TEST REPORT

FOR

WCDMA/LTE Tablet + BT/BLE and DTS/UNII a/b/g/n/ac

MODEL NUMBER : SM-W707N0, SM-W708N0, SM-W708

FCC ID: A3LSMW707

REPORT NUMBER: 16K22598-E4

ISSUE DATE: JAN 28, 2016

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 443-742, KOREA

Prepared by
UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-823, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



Revision History

| <u>Rev.</u> | <u>Issue Date</u> | <u>Revisions</u> | <u>Revised By</u> |
|-------------|-------------------|--|-------------------|
| -- | 01/22/16 | Initial issue | Junwhan Lee |
| 2 | 01/27/16 | Revised KDB revision number | Junwhan Lee |
| 3 | 01/28/16 | Revised UNII 3 HT20 MIMO power data (mW) | Junwhan Lee |

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. ATTESTATION OF TEST RESULTS | 5 |
| 2. TEST METHODOLOGY | 6 |
| 3. FACILITIES AND ACCREDITATION | 6 |
| 4. CALIBRATION AND UNCERTAINTY | 6 |
| 4.1. <i>MEASURING INSTRUMENT CALIBRATION</i> | <i>6</i> |
| 4.2. <i>SAMPLE CALCULATION</i> | <i>6</i> |
| 4.3. <i>MEASUREMENT UNCERTAINTY.....</i> | <i>7</i> |
| 5. EQUIPMENT UNDER TEST | 8 |
| 5.1. <i>DESCRIPTION OF EUT</i> | <i>8</i> |
| 5.2. <i>MAXIMUM OUTPUT POWER.....</i> | <i>9</i> |
| 5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i> | <i>10</i> |
| 5.4. <i>List of test reduction and modes covering other modes:</i> | <i>10</i> |
| 5.5. <i>WORST-CASE CONFIGURATION AND MODE.....</i> | <i>12</i> |
| 5.6. <i>DESCRIPTION OF TEST SETUP.....</i> | <i>13</i> |
| 6. TEST AND MEASUREMENT EQUIPMENT | 15 |
| 7. SUMMARY TABLE | 16 |
| 8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS | 17 |
| 8.1. <i>ON TIME AND DUTY CYCLE RESULTS.....</i> | <i>17</i> |
| 9. MEASUREMENT METHOD..... | 18 |
| 10. ANTENNA PORT TEST RESULTS | 19 |
| 10.1. <i>6 dB BANDWIDTH</i> | <i>19</i> |
| 10.2. <i>26 dB BANDWIDTH</i> | <i>19</i> |
| 10.3. <i>99% BANDWIDTH</i> | <i>19</i> |
| 10.4. <i>OUTPUT POWER AND PPSD</i> | <i>20</i> |
| 11. TRANSMITTER ABOVE 1 GHz..... | 21 |
| 11.1. <i>5.2 GHz.....</i> | <i>22</i> |
| 11.2. <i>5.3 GHz.....</i> | <i>22</i> |
| 11.3. <i>5.5-5.6 GHz.....</i> | <i>22</i> |
| 11.4. <i>5.8 GHz.....</i> | <i>22</i> |

| | |
|---|-----------|
| 12. WORST-CASE BELOW 1 GHz (in the 5.3 GHz Band) | 22 |
| 13. AC POWER LINE CONDUCTED EMISSIONS | 23 |
| 14. DYNAMIC FREQUENCY SELECTION | 24 |
| 14.1. OVERVIEW..... | 24 |
| 14.1.1. LIMITS..... | 24 |
| 14.1.1. TEST AND MEASUREMENT SYSTEM..... | 28 |
| 14.1.2. SETUP OF EUT..... | 31 |
| 14.1.3. DESCRIPTION OF EUT | 32 |
| 14.2. RESULTS FOR 20 MHz BANDWIDTH..... | 33 |
| 14.2.1. TEST CHANNEL | 33 |
| 14.2.2. RADAR WAVEFORM AND TRAFFIC..... | 33 |
| 14.2.3. OVERLAPPING CHANNEL TESTS..... | 33 |
| 14.2.4. MOVE AND CLOSING TIME | 33 |
| 14.3. RESULTS FOR 40 MHz BANDWIDTH..... | 34 |
| 14.3.1. TEST CHANNEL | 34 |
| 14.3.2. RADAR WAVEFORM AND TRAFFIC..... | 34 |
| 14.3.3. OVERLAPPING CHANNEL TESTS..... | 34 |
| 14.3.4. MOVE AND CLOSING TIME | 34 |
| 14.4. RESULTS FOR 80 MHz BANDWIDTH..... | 35 |
| 14.4.1. TEST CHANNEL | 35 |
| 14.4.2. RADAR WAVEFORM AND TRAFFIC..... | 35 |
| 14.4.3. OVERLAPPING CHANNEL TESTS..... | 35 |
| 14.4.4. MOVE AND CLOSING TIME | 35 |
| 15. SETUP PHOTOS | 36 |

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: WCDMA/LTE Tablet + BT/BLE and DTS/UNII a/b/g/n/ac
MODEL NUMBER: SM-W707N0, SM-W708N0, SM-W708
SERIAL NUMBER: 8JA3R32GB000LST, 8JA3R32GB000MZX (RADIATED);
123490EN400015 (CONDUCTED)
DATE TESTED: OCT 14, 2015 - JAN 19, 2016

| APPLICABLE STANDARDS | |
|--------------------------|--------------|
| STANDARD | TEST RESULTS |
| CFR 47 Part 15 Subpart E | Pass |

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, FCC 06-96, FCC KDB 789033 D02 v01r01, ANSI C63.10-2009.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-823, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

| 218 Maeyeong-ro | |
|-------------------------------------|-----------|
| <input checked="" type="checkbox"/> | Chamber 1 |
| <input checked="" type="checkbox"/> | Chamber 2 |

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| PARAMETER | UNCERTAINTY |
|---------------------------------------|-------------|
| Conducted Disturbance, 0.15 to 30 MHz | 2.32 dB |
| Radiated Disturbance, Below 1GHz | 4.14 dB |
| Radiated Disturbance, Above 1 GHz | 5.97 dB |

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a WCDMA/LTE Tablet + BT/BLE and DTS/UNII a/b/g/n/ac.
 This test report addresses the NII (UNII) operational mode.

SM-W707N0, SM-W708N0 and SM-W708 are same hardware and only difference is Window OS version. SM-W707N0 is Window Home version and SM-W708N0, SM-W708 are Window Professional version.
 Also SM-W708 support non-USA band enabled by S/W.(LTE Band20, WCDMA Band8).

WiFi MIMO Condition

| Frequency | Mode | Antenna 1 | Antenna 2 |
|-----------|-----------------|-----------|-----------|
| 2.4 GHz | 802.11b | TX / RX | TX / RX |
| | 802.11g | TX / RX | TX / RX |
| | 802.11n | TX / RX | TX / RX |
| | 802.11n MIMO | TX / RX | TX / RX |
| 5 GHz | 802.11a | TX / RX | TX / RX |
| | 802.11n | TX / RX | TX / RX |
| | 802.11ac | TX / RX | TX / RX |
| | 802.11n/ac MIMO | TX / RX | TX / RX |

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted average output power as follows:

| Frequency Range [MHz] | Mode | Output Power [dBm] | | Output Power [mW] | |
|-----------------------|---------------------|--------------------|----------|-------------------|----------|
| | | Antenna1 | Antenna2 | Antenna1 | Antenna2 |
| 5180 - 5240 | 802.11a SISO | 12.95 | 12.65 | 19.74 | 18.40 |
| | 802.11a MIMO | 15.81 | | 38.14 | |
| | 802.11n HT20 SISO | 13.15 | 13.24 | 20.64 | 21.10 |
| | 802.11n HT20 MIMO | 16.21 | | 41.74 | |
| 5190 - 5230 | 802.11n HT40 SISO | 11.40 | 11.45 | 13.79 | 13.95 |
| | 802.11n HT40 MIMO | 14.43 | | 27.74 | |
| 5210 | 802.11ac VHT80 SISO | 10.11 | 9.80 | 10.25 | 9.55 |
| | 802.11ac VHT80 MIMO | 12.97 | | 19.80 | |
| 5260 - 5320 | 802.11a SISO | 13.27 | 12.69 | 21.25 | 18.56 |
| | 802.11a MIMO | 16.00 | | 39.81 | |
| | 802.11n HT20 SISO | 13.14 | 13.41 | 20.59 | 21.92 |
| | 802.11n HT20 MIMO | 16.29 | | 42.51 | |
| 5270 - 5310 | 802.11n HT40 SISO | 10.52 | 11.02 | 11.28 | 12.64 |
| | 802.11n HT40 MIMO | 13.79 | | 23.92 | |
| 5290 | 802.11ac VHT80 SISO | 10.33 | 9.69 | 10.79 | 9.30 |
| | 802.11ac VHT80 MIMO | 13.03 | | 20.09 | |
| 5500 - 5720 | 802.11a SISO | 12.78 | 12.97 | 18.96 | 19.83 |
| | 802.11a MIMO | 15.89 | | 38.79 | |
| | 802.11n HT20 SISO | 13.33 | 12.76 | 21.52 | 18.89 |
| | 802.11n HT20 MIMO | 16.07 | | 40.42 | |
| 5510 - 5710 | 802.11n HT40 SISO | 11.40 | 11.39 | 13.80 | 13.77 |
| | 802.11n HT40 MIMO | 14.40 | | 27.57 | |
| 5530 - 5690 | 802.11ac VHT80 SISO | 9.77 | 10.07 | 9.48 | 10.16 |
| | 802.11ac VHT80 MIMO | 12.93 | | 19.63 | |
| 5745 - 5825 | 802.11a SISO | 12.85 | 12.94 | 19.25 | 19.67 |
| | 802.11a MIMO | 15.90 | | 38.92 | |
| | 802.11n HT20 SISO | 12.86 | 13.00 | 19.32 | 19.93 |
| | 802.11n HT20 MIMO | 15.94 | | 39.26 | |
| 5755 - 5795 | 802.11n HT40 SISO | 11.38 | 11.46 | 13.75 | 13.98 |
| | 802.11n HT40 MIMO | 14.43 | | 27.73 | |
| 5775 | 802.11ac VHT80 SISO | 10.02 | 10.47 | 10.04 | 11.15 |
| | 802.11ac VHT80 MIMO | 13.26 | | 21.19 | |

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of:

| Frequency Range [MHz] | Antenna Gain [dBi] | |
|------------------------|--------------------|-----------|
| | Antenna 1 | Antenna 2 |
| UNII 1 5150 – 5250 | 0.13 | -4.65 |
| UNII 2A 5250 – 5350 | -1.23 | -2.95 |
| UNII 2C 5470 – 5725 | -0.07 | -4.45 |
| UNII 3 5725 – 5850 | -1.05 | --1.94 |

5.4. List of test reduction and modes covering other modes:

The output power on covered modes is equal to or less than one referenced.

UNII 1

| 5150 - 5250 MHz Authorized Frequency Band (Antenna port & Radiated Testing) | | |
|---|-----------------------------------|------------------------|
| Frequency Range [MHz] | Mode | Covered by |
| 5180 - 5240 | 802.11a legacy 1TX/STBC 2TX | 802.11a 2TX CDD |
| 5180 - 5240 | 802.11HT20 1TX | 802.11n HT20 2TX CDD |
| 5180 - 5240 | 802.11HT20 2TX STBC/SDM | 802.11n HT20 2TX CDD |
| 5180 - 5240 | 802.11ac VHT20 1TX | 802.11n HT20 2TX CDD |
| 5180 - 5240 | 802.11ac VHT20 2TX STBC/SDM | 802.11n HT20 2TX CDD |
| 5180 - 5240 | 802.11ac VHT20 2TX CDD/Tx BF | 802.11n HT20 2TX CDD |
| 5190 - 5230 | 802.11n HT40 1TX | 802.11n HT40 2TX CDD |
| 5190 - 5230 | 802.11n HT40 2TX STBC/SDM | 802.11n HT40 2TX CDD |
| 5190 - 5230 | 802.11ac VHT40 1TX | 802.11n HT40 2TX CDD |
| 5190 - 5230 | 802.11ac VHT40 2TX STBC/SDM | 802.11n HT40 2TX CDD |
| 5190 - 5230 | 802.11ac VHT40 2TX CDD/Tx BF | 802.11n HT40 2TX CDD |
| 5210 | 802.11ac VHT80 1TX | 802.11ac VHT80 2TX CDD |
| 5210 | 802.11ac VHT80 2TX STBC/SDM/Tx BF | 802.11ac VHT80 2TX CDD |

UNII 2A

| 5250 - 5350 MHz Authorized Frequency Band (Antenna port & Radiated Testing) | | |
|--|-----------------------------------|------------------------|
| Frequency Range [MHz] | Mode | Covered by |
| 5260 - 5320 | 802.11a legacy 1TX/STBC 2TX | 802.11a 2TX CDD |
| 5260 - 5320 | 802.11HT20 1TX | 802.11n HT20 2TX CDD |
| 5260 - 5320 | 802.11HT20 2TX STBC/SDM | 802.11n HT20 2TX CDD |
| 5260 - 5320 | 802.11ac VHT20 1TX | 802.11n HT20 2TX CDD |
| 5260 - 5320 | 802.11ac VHT20 2TX STBC/SDM | 802.11n HT20 2TX CDD |
| 5260 - 5320 | 802.11ac VHT20 2TX CDD/Tx BF | 802.11n HT20 2TX CDD |
| 5270 - 5310 | 802.11n HT40 1TX | 802.11n HT40 2TX CDD |
| 5270 - 5310 | 802.11n HT40 2TX STBC/SDM | 802.11n HT40 2TX CDD |
| 5270 - 5310 | 802.11ac VHT40 1TX | 802.11n HT40 2TX CDD |
| 5270 - 5310 | 802.11ac VHT40 2TX STBC/SDM | 802.11n HT40 2TX CDD |
| 5270 - 5310 | 802.11ac VHT40 2TX CDD/Tx BF | 802.11n HT40 2TX CDD |
| 5290 | 802.11ac VHT80 1TX | 802.11ac VHT80 2TX CDD |
| 5290 | 802.11ac VHT80 2TX STBC/SDM/Tx BF | 802.11ac VHT80 2TX CDD |

UNII 2C

| 5470 - 5725 MHz Authorized Frequency Band (Antenna port & Radiated Testing) | | |
|--|-----------------------------------|------------------------|
| Frequency Range [MHz] | Mode | Covered by |
| 5500 - 5720 | 802.11a legacy 1TX/STBC 2TX | 802.11a 2TX CDD |
| 5500 - 5720 | 802.11HT20 1TX | 802.11n HT20 2TX CDD |
| 5500 - 5720 | 802.11HT20 2TX STBC/SDM | 802.11n HT20 2TX CDD |
| 5500 - 5720 | 802.11ac VHT20 1TX | 802.11n HT20 2TX CDD |
| 5500 - 5720 | 802.11ac VHT20 2TX STBC/SDM | 802.11n HT20 2TX CDD |
| 5500 - 5720 | 802.11ac VHT20 2TX CDD/Tx BF | 802.11n HT20 2TX CDD |
| 5510 - 5710 | 802.11n HT40 1TX | 802.11n HT40 2TX CDD |
| 5510 - 5710 | 802.11n HT40 2TX STBC/SDM | 802.11n HT40 2TX CDD |
| 5510 - 5710 | 802.11ac VHT40 1TX | 802.11n HT40 2TX CDD |
| 5510 - 5710 | 802.11ac VHT40 2TX STBC/SDM | 802.11n HT40 2TX CDD |
| 5510 - 5710 | 802.11ac VHT40 2TX CDD/Tx BF | 802.11n HT40 2TX CDD |
| 5530 - 5690 | 802.11ac VHT80 1TX | 802.11ac VHT80 2TX CDD |
| 5530 - 5690 | 802.11ac VHT80 2TX STBC/SDM/Tx BF | 802.11ac VHT80 2TX CDD |

UNII 3

| 5725 - 5850 MHz Authorized Frequency Band (Antenna port & Radiated Testing) | | |
|---|-----------------------------------|------------------------|
| Frequency Range [MHz] | Mode | Covered by |
| 5745 - 5825 | 802.11a legacy 1TX/STBC 2TX | 802.11a 2TX CDD |
| 5745 - 5825 | 802.11HT20 1TX | 802.11n HT20 2TX CDD |
| 5745 - 5825 | 802.11HT20 2TX STBC/SDM | 802.11n HT20 2TX CDD |
| 5745 - 5825 | 802.11ac VHT20 1TX | 802.11n HT20 2TX CDD |
| 5745 - 5825 | 802.11ac VHT20 2TX STBC/SDM | 802.11n HT20 2TX CDD |
| 5745 - 5825 | 802.11ac VHT20 2TX CDD/Tx BF | 802.11n HT20 2TX CDD |
| 5755 - 5795 | 802.11n HT40 1TX | 802.11n HT40 2TX CDD |
| 5755 - 5795 | 802.11n HT40 2TX STBC/SDM | 802.11n HT40 2TX CDD |
| 5755 - 5795 | 802.11ac VHT40 1TX | 802.11n HT40 2TX CDD |
| 5755 - 5795 | 802.11ac VHT40 2TX STBC/SDM | 802.11n HT40 2TX CDD |
| 5755 - 5795 | 802.11ac VHT40 2TX CDD/Tx BF | 802.11n HT40 2TX CDD |
| 5775 | 802.11ac VHT80 1TX | 802.11ac VHT80 2TX CDD |
| 5775 | 802.11ac VHT80 2TX STBC/SDM/Tx BF | 802.11ac VHT80 2TX CDD |

5.5. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that the X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in the X orientation.

Based on the baseline scan, the worst-case data rates were:

- 802.11a mode: 6 Mbps
- 802.11n HT20mode: MCS0
- 802.11n HT40mode: MCS0
- 802.11ac VHT80mode: MCS0

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

| Support Equipment List | | | | |
|------------------------|--------------|-------------|----------------|--------|
| Description | Manufacturer | Model | Serial Number | FCC ID |
| Charger | SAMSUNG | EP-TA300 | R37GALZGRB1SE3 | N/A |
| Data Cable | SAMSUNG | EP-DW700CWE | N/A | N/A |
| Earphone | SAMSUNG | EO-HS3303WE | N/A | N/A |


I/O CABLES

| I/O Cable List | | | | | | |
|----------------|----------|----------------------|----------------|------------|------------------|---------|
| Cable No | Port | # of identical ports | Connector Type | Cable Type | Cable Length (m) | Remarks |
| 1 | DC Power | 1 | Mini-USB | Shielded | 0.8m | N/A |
| 2 | Audio | 1 | Mini-Jack | Unshielded | 1.0m | N/A |

TEST SETUP

The EUT is a stand-alone unit during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

| Test Equipment List | | | | |
|----------------------------|---------------|------------------------|-------------|----------|
| Description | Manufacturer | Model | S/N | Cal Due |
| Antenna, Bilog, 30MHz-1GHz | SCHWARZBECK | VULB9163 | 750 | 11-17-16 |
| Antenna, Bilog, 30MHz-1GHz | SCHWARZBECK | VULB9163 | 749 | 04-25-17 |
| Antenna, Horn, 18 GHz | ETS | 3115 | 00167211 | 09-26-16 |
| Antenna, Horn, 18 GHz | ETS | 3115 | 00161451 | 05-17-17 |
| Antenna, Horn, 18 GHz | ETS | 3117 | 00168724 | 06-17-17 |
| Antenna, Horn, 18 GHz | ETS | 3117 | 00168717 | 06-17-17 |
| Antenna, Horn, 40 GHz | ETS | 3116C | 00166155 | 09-23-16 |
| Antenna, Horn, 40 GHz | ETS | 3116C-PA | 00168841 | 08-24-17 |
| Preamplifier, 1000 MHz | Sonoma | 310N | 341282 | 08-18-16 |
| Preamplifier, 1000 MHz | Sonoma | 310N | 351741 | 08-18-16 |
| Preamplifier, 18 GHz | Miteq | AFS42-00101800-25-S-42 | 1876511 | 08-18-16 |
| Preamplifier, 18 GHz | Miteq | AFS42-00101800-25-S-42 | 1896138 | 08-18-16 |
| Spectrum Analyzer, 44 GHz | Agilent / HP | N9030A | MY54170614 | 08-19-16 |
| Spectrum Analyzer, 44 GHz | Agilent / HP | N9030A | MY54490312 | 08-19-16 |
| Bluetooth Tester | TESCOM | TC-3000C | 3000C000546 | 08-18-16 |
| Average Power Sensor | R&S | NRZ-Z91 | 102681 | 08-18-16 |
| Average Power Sensor | Agilent / HP | U2000 | MY54270007 | 08-18-16 |
| EMI Test Receive, 40 GHz | R&S | ESU40 | 100439 | 08-19-16 |
| EMI Test Receive, 40 GHz | R&S | ESU40 | 100457 | 08-19-16 |
| EMI Test Receive, 3 GHz | R&S | ESR3 | 101832 | 08-19-16 |
| Attenuator / Switch driver | HP | 11713A | 3748A04272 | N/A |
| Low Pass Filter 3GHz | Micro-Tronics | LPS17541 | 009 | 08-18-16 |
| Low Pass Filter 3GHz | Micro-Tronics | LPS17541 | 015 | 08-18-16 |
| High Pass Filter 5GHz | Micro-Tronics | HPS17542 | 009 | 08-18-16 |
| High Pass Filter 6GHz | Micro-Tronics | HPM17543 | 010 | 08-18-16 |
| High Pass Filter 5GHz | Micro-Tronics | HPS17542 | 016 | 08-18-16 |
| High Pass Filter 6GHz | Micro-Tronics | HPM17543 | 015 | 08-18-16 |
| LISN | R&S | ENV-216 | 101836 | 08-19-16 |
| LISN | R&S | ENV-216 | 101837 | 08-19-16 |

7. SUMMARY TABLE

The FCC ID: A3LSMW707 shares the same enclosure and circuit board as FCC ID: A3LSMW700. The WLAN circuitry and layout, including antennas, are almost identical between the two units. The WLAN antennas and surrounding circuitry are the same between these two units.

After confirming through preliminary radiated emissions that the performance of the FCC ID: A3LSMW700 remains representative of FCC ID: A3LSMW707, test data for FCC ID: A3LSMW700 is being submitted for this application to cover WLAN features.

| FCC Part Section | Test Description | Test Limit | Test Condition | Test Result | Worst Case |
|---------------------|--|--------------------------|----------------------|-------------|---------------------|
| 15.407 (a) | Occupied Band width (26dB) | N/A | Conducted | Pass | 82.38 MHz |
| 15.407 | 6dB Band width (5.8Ghz) | 500KHz | | Pass | 1.93 MHz (Straddle) |
| 15.407 (a)(2) | TX Cond. Power 5.15-2.25, 5.25-5.35 & 5.47-5.725 | <24dBm or 11+10Log(OBW) | | Pass | 16.29 dBm |
| 15.407 (a)(3) | TX Cond. Power 5.725-5.825 | < 30dBm or 17+10Log(OBW) | | Pass | 15.94 dBm |
| 15.407 (a)(5) | PSD (5.2,5.3,5.5GHz) | <11dBm | | Pass | 6.19 dBm |
| 15.407 (a)(5) | PSD (5.8GHz) | 30dBm per 500kHz | | Pass | 2.94 dBm |
| 15.207 (a) | AC Power Line conducted emissions | Section 10 | Radiated | Pass | 41.36 dBuV (QP) |
| 15.407 (b) & 15.209 | Radiated Spurious Emission | < 54dBuV/m | | Pass | 50.93 BuV/m (AV) |
| 15.407 (h)(2) | Dynamic Frequency Selection | N/A | Radiated / Conducted | Pass | N/A |

8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None; for reporting purposes only.

PROCEDURE

KDB 789033 D02 v01r01 Zero-Span Spectrum Analyzer Method.

8.1. ON TIME AND DUTY CYCLE RESULTS

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

9. MEASUREMENT METHOD

KDB 789033 D02 General UNII Test Procedures New Rules v01r01
KDB 905462 D03 Clients Without Radar Detection New Rules v01r01

The Duty Cycle is less than 98% and consistent therefore KDB 789033 Method SA-2 is used for power and PPSD

The Duty Cycle is less than 98% and consistent, KDB 789033 Method AD with Power RMS Averaging and duty cycle correction is used.

MIMO Device: KDB 662911 v02r01

Straddle Channels: KDB 644545 D03 v01

10. ANTENNA PORT TEST RESULTS

10.1. 6 dB BANDWIDTH

LIMITS

FCC §15.407

The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

Reference to 789033 D02 General UNII Test Procedures New Rules v01r01: The transmitter output is connected to a spectrum analyzer with the RBW set to 100KHz, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

10.2. 26 dB BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

10.3. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

10.4. OUTPUT POWER AND PPSD

LIMITS

FCC §15.407 (a) (1) (2) (3)

For the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26-dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 11 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

DIRECTIONAL ANTENNA GAIN

For Power: The TX chains are uncorrelated and the antenna gain is the same for each chain. The directional gain is equal to the antenna gain.

For PSD: The TX chains are correlated and the antenna gain is unequal among the chains. The directional gain is:

5 GHz

| Frequency Band [MHz] | Chain 0 Antenna Gain [dBi] | Chain 1 Antenna Gain [dBi] | Uncorrelated Directional Gain [dBi] | Correlated Directional Gain [dBi] |
|----------------------|----------------------------|----------------------------|-------------------------------------|-----------------------------------|
| 5150 - 5250 | 0.13 | -4.65 | -1.63 | 1.08 |
| 5250 - 5350 | -1.23 | -2.95 | -2.01 | 0.96 |
| 5470 - 5725 | -0.07 | -4.45 | -1.73 | 1.02 |
| 5725 - 5850 | -1.05 | -1.94 | -1.47 | 1.53 |

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

11. TRANSMITTER ABOVE 1 GHz

LIMITS

FCC §15.205 and §15.209

| Frequency Range (MHz) | Field Strength Limit (uV/m) at 3 m | Field Strength Limit (dBuV/m) at 3 m |
|-----------------------|------------------------------------|--------------------------------------|
| 30 - 88 | 100 | 40 |
| 88 - 216 | 150 | 43.5 |
| 216 - 960 | 200 | 46 |
| Above 960 | 500 | 54 |

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

Reference to KDB 789033 D02 v01r01 UNII part G) 6) c) Method AD:

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor to the reading offset for average measurements.

The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

11.1. 5.2 GHz

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

11.2. 5.3 GHz

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

11.3. 5.5-5.6 GHz

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

11.4. 5.8 GHz

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

12. WORST-CASE BELOW 1 GHz (in the 5.3 GHz Band)

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

13. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

| Frequency of Emission (MHz) | Conducted Limit (dBuV) | |
|-----------------------------|------------------------|----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56 | 56 to 46 |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

14. DYNAMIC FREQUENCY SELECTION

14.1. OVERVIEW

14.1.1. LIMITS

INDUSTRY CANADA

IC RSS-247 is closely harmonized with FCC Part 15 DFS rules. The deviations are as follows:

RSS-247 Issue §6.3

Note: For the band 5600–5650 MHz, no operation is permitted.

Until further notice, devices subject to this annex shall not be capable of transmitting in the band 5600–5650 MHz. This restriction is for the protection of Environment Canada weather radars operating in this band.

FCC

§15.407 (h), FCC KDB 905462 D02 “COMPLIANCE MEASUREMENT PROCEDURES FOR UNLICENSED-NATIONAL INFORMATION INFRASTRUCTURE DEVICES OPERATING IN THE 5250-5350 MHz AND 5470-5725 MHz BANDS INCORPORATING DYNAMIC FREQUENCY SELECTION” and KDB 905462 D03 “U-NII CLIENT DEVICES WITHOUT RADAR DETECTION CAPABILITY”.

Table 1: Applicability of DFS requirements prior to use of a channel

| Requirement | Operational Mode | | |
|---------------------------------|------------------|----------------------------------|-------------------------------|
| | Master | Client (without radar detection) | Client (with radar detection) |
| Non-Occupancy Period | Yes | Not required | Yes |
| DFS Detection Threshold | Yes | Not required | Yes |
| Channel Availability Check Time | Yes | Not required | Not required |
| U-NII Detection Bandwidth | Yes | Not required | Yes |

Table 2: Applicability of DFS requirements during normal operation

| Requirement | Operational Mode | | |
|-----------------------------------|------------------|----------------------|-------------------|
| | Master | Client (without DFS) | Client (with DFS) |
| DFS Detection Threshold | Yes | Not required | Yes |
| Channel Closing Transmission Time | Yes | Yes | Yes |
| Channel Move Time | Yes | Yes | Yes |
| U-NII Detection Bandwidth | Yes | Not required | Yes |

| | | |
|--|--|--|
| Additional requirements for devices with multiple bandwidth modes | Master Device or Client with Radar DFS | Client (without DFS) |
| U-NII Detection Bandwidth and Statistical Performance Check | All BW modes must be tested | Not required |
| Channel Move Time and Channel Closing Transmission Time | Test using widest BW mode available | Test using the widest BW mode available for the link |
| All other tests | Any single BW mode | Not required |
| Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in all 20 MHz channel blocks and a null frequency between the bonded 20 MHz channel blocks. | | |

Table 3: Interference Threshold values, Master or Client incorporating In-Service Monitoring

| | |
|---|----------------------|
| Maximum Transmit Power | Value (see notes) |
| E.I.R.P. \geq 200 mill watt | -64 dBm |
| E.I.R.P. < 200 mill watt and power spectral density < 10 dBm/MHz | -62 dBm |
| E.I.R.P. < 200 mill watt that do not meet power spectral density requirement | -64 dBm |
| <p>Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna</p> <p>Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.</p> <p>Note 3: E.I.R.P. is based on the highest antenna gain. For MIMO devices refer to KDB publication 662911 D01.</p> | |

Table 4: DFS Response requirement values

| Parameter | Value |
|--|--|
| <i>Non-occupancy period</i> | 30 minutes |
| <i>Channel Availability Check Time</i> | 60 seconds |
| <i>Channel Move Time</i> | 10 seconds (See Note 1) |
| <i>Channel Closing Transmission Time</i> | 200 milliseconds + approx. 60 milliseconds over remaining 10 second period. (See Notes 1 and 2) |
| <i>U-NII Detection Bandwidth</i> | Minimum 100% of the U-NII 99% transmission power bandwidth. (See Note 3) |
| <p>Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.</p> <p>Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.</p> <p>Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.</p> | |

Table 5 – Short Pulse Radar Test Waveforms

| Radar Type | Pulse Width (usec) | PRI (usec) | Pulses | Minimum Percentage of Successful Detection | Minimum Trials |
|---|--------------------|---|---|--|----------------|
| 0 | 1 | 1428 | 18 | See Note 1 | See Note 1 |
| 1 | 1 | Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in table 5a | Roundup: $\{(1/360) \times (19 \times 10^6 \text{ PRI}_{\text{usec}})\}$ | 60% | 30 |
| | | Test B: 15 unique PRI values randomly selected within the range of 518-3066 usec. With a minimum increment of 1 usec, excluding PRI values selected in Test A | | | |
| 2 | 1-5 | 150-230 | 23-29 | 60% | 30 |
| 3 | 6-10 | 200-500 | 16-18 | 60% | 30 |
| 4 | 11-20 | 200-500 | 12-16 | 60% | 30 |
| Aggregate (Radar Types 1-4) | | | | 80% | 120 |
| Note 1: Short Pulse Radar Type 0 should be used for the <i>Detection Bandwidth</i> test, <i>Channel Move Time</i> , and <i>Channel Closing Time</i> tests. | | | | | |

Table 6 – Long Pulse Radar Test Signal


| Radar Waveform Type | Pulse Width (μsec) | Chirp Width (MHz) | PRI (μsec) | Pulses per Burst | Number of Bursts | Minimum Percentage of Successful Detection | Minimum Trials |
|---------------------|--------------------|-------------------|------------|------------------|------------------|--|----------------|
| 5 | 50-100 | 5-20 | 1000-2000 | 1-3 | 8-20 | 80% | 30 |

Table 7 – Frequency Hopping Radar Test Signal

| Radar Waveform Type | Pulse Width (μsec) | PRI (μsec) | Pulses per Hop | Hopping Rate (kHz) | Hopping Sequence Length (msec) | Minimum Percentage of Successful Detection | Minimum Trials |
|---------------------|--------------------|------------|----------------|--------------------|--------------------------------|--|----------------|
| 6 | 1 | 333 | 9 | 0.333 | 300 | 70% | 30 |

14.1.1. TEST AND MEASUREMENT SYSTEM

CONDUCTED METHOD SYSTEM BLOCK DIAGRAM



SYSTEM OVERVIEW

The short pulse and long pulse signal generating system utilizes the Keysite Signal Studio for Pulse Building as N5172B. The Vector Signal Generator has been validated by the NTIA. The hopping signal generating system utilizes the CCS simulated hopping method and system, which has been validated by the DoD, FCC and NTIA. The software selects waveform parameters from within the bounds of the signal type on a random basis using uniform distribution.

The short pulse types 1, 2, 3 and 4, and the long pulse type 5 parameters are randomized at run-time.

The hopping type 6 pulse parameters are fixed while the hopping sequence is based on the August 2005 NTIA Hopping Frequency List. The initial starting point randomized at run-time and each subsequent starting point is incremented by 475. Each frequency in the 100-length segment is compared to the boundaries of the EUT Detection Bandwidth and the software creates a hopping burst pattern in accordance with Section 7.4.1.3 Method #2 Simulated Frequency Hopping Radar Waveform Generating Subsystem of KDB 905462 D02. The frequency of the signal generator is incremented in 1 MHz steps from F_L to F_H for each successive trial. This incremental sequence is repeated as required to generate a minimum of 30 total trials and to maintain a uniform frequency distribution over the entire Detection Bandwidth.

The signal monitoring equipment consists of a spectrum analyzer. The aggregate ON time is calculated by multiplying the number of bins above a threshold during a particular observation period by the dwell time per bin, with the analyzer set to peak detection and max hold.

SYSTEM CALIBRATION

A 50-ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to a horn antenna via a coaxial cable, with the reference level offset set to (horn antenna gain – coaxial cable loss). The signal generator is set to CW mode. The amplitude of the signal generator is adjusted to yield a level of –64 dBm as measured on the spectrum analyzer.

Without changing any of the instrument settings, the spectrum analyzer is reconnected to the Common port of the Spectrum Analyzer Combiner/Divider. The Reference Level Offset of the spectrum analyzer is adjusted so that the displayed amplitude of the signal is –64 dBm.

The spectrum analyzer displays the level of the signal generator as received at the antenna ports of the Master Device. The interference detection threshold may be varied from the calibrated value of –64 dBm and the spectrum analyzer will still indicate the level as received by the Master Device.

ADJUSTMENT OF DISPLAYED TRAFFIC LEVEL

A link is established between the Master and Slave and the distance between the units is adjusted as needed to provide a suitable received level at the Master and Slave devices. The video test file is streamed to generate WLAN traffic. The monitoring antenna is adjusted so that the WLAN traffic level, as displayed on the spectrum analyzer, is at lower amplitude than the radar detection threshold.


TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the DFS tests documented in this report:

| TEST EQUIPMENT LIST | | | | |
|-------------------------------|---------------------|--------------|------------|----------------|
| Description | Manufacturer | Model | S/N | Cal Due |
| Spectrum Analyzer, 7 GHz | Agilent / HP | N9010A | MY54200580 | 08-19-16 |
| Vector Signal Generator, 6GHz | Agilent / HP | N5182B | MY53051241 | 08-19-16 |

14.1.2. SETUP OF EUT

CONDUCTED METHOD EUT TEST SETUP



SUPPORT EQUIPMENT

The following support equipment was utilized for the DFS tests documented in this report:

| PERIPHERAL SUPPORT EQUIPMENT LIST | | | | |
|------------------------------------|--------------|-------------------------|---------------|-----------|
| Description | Manufacturer | Model | Serial Number | FCC ID |
| Wireless Access Point | Cisco | AIR-CAP3702E-A-K9 | FTX182276QX | LDK102087 |
| Notebook PC (Controller/Server) | HP | HP EliteDesk 800 G1 TWR | CZC4125J25 | DoC |

14.1.3. DESCRIPTION OF EUT

The EUT operates over the 5250-5350 MHz and 5470-5725 MHz ranges.

The EUT is a Slave Device without Radar Detection.

The highest power level within these bands is 16.29 dBm in the 5250-5350 MHz band and 16.07 dBm in the 5470-5725 MHz band.

The antenna assembly utilized two antenna with the EUT one is -0.17 dBi, and the other is -2.95 dBi.

The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -64 dBm. After correction for procedural adjustments, the required conducted threshold at the antenna port is $-64 + 1 = -63$ dBm.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm. The tested level is lower than the required level hence it provides a margin to the limit.

The EUT uses one transmitter/receiver chain connected to an antenna to perform radiated tests.

WLAN traffic that meets or exceeds the minimum required loading was generated by transferring a data stream from the controller/server PC to the EUT using iPerf version 2.0.5 software package.

TPC is not required since the maximum EIRP is less than 500 mW (27 dBm).

The EUT utilizes the 802.11ac architecture. Three nominal channel bandwidths are implemented: 20 MHz, 40 MHz and 80 MHz.

The software installed in the access point is 12.4(25d)JA1.

UNIFORM CHANNEL SPREADING

This requirement is not applicable to Slave radio devices.

OVERVIEW OF MASTER DEVICE WITH RESPECT TO §15.407 (h) REQUIREMENTS

The Master Device is a Cisco Access Point, FCC ID: LDK102087. The minimum antenna gain for the Master Device is 6 dBi.

The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -64 dBm. After correction for procedural adjustments, the required radiated threshold at the antenna port is $-64 + 1 = -63$ dBm.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm. The tested level is lower than the required level hence it provides a margin to the limit.

14.2. RESULTS FOR 20 MHz BANDWIDTH

14.2.1. TEST CHANNEL

All tests were performed at a channel center frequency of 5500 MHz.

14.2.2. RADAR WAVEFORM AND TRAFFIC

Please refer to UNII test report of FCC ID : A3LSMW700

14.2.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

14.2.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

14.3. RESULTS FOR 40 MHz BANDWIDTH

14.3.1. TEST CHANNEL

All tests were performed at a channel center frequency of 5510 MHz.

14.3.2. RADAR WAVEFORM AND TRAFFIC

Please refer to UNII test report of FCC ID : A3LSMW700

14.3.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

14.3.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700

14.4. RESULTS FOR 80 MHz BANDWIDTH

14.4.1. TEST CHANNEL

All tests were performed at a channel center frequency of 5530 MHz.

14.4.2. RADAR WAVEFORM AND TRAFFIC

Please refer to UNII test report of FCC ID : A3LSMW700

14.4.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

14.4.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS

Please refer to UNII test report of FCC ID : A3LSMW700