

FCC/ISED BT LE REPORT

Certification

Applicant Name:

SAMSUNG Electronics Co., Ltd.

Date of Issue:

February 24, 2017

Test Site/Location:

HCT CO., LTD., 74,Seoicheon-ro 578beon-gil,Majang-myeo,Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Address:

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Report No.: HCT-R-1702-F029

HCT FRN: 0005866421

ISED Registration Number: 5944A-6

FCC ID	: A3LSMW723
IC	: 649E-SMW723
APPLICANT	: SAMSUNG Electronics Co., Ltd.

According to the Evaluation report, all of the data contained herein is reused from the reference FCC ID : A3LSMW727V report.

FCC/IC Model:	SM-W723
FCC Additional model(s):	SM-W720, SM-W720X
EUT Type:	Tablet
RF Peak Output Power:	2.997 dBm (1.994 mW)
Frequency Range:	2402 MHz -2480 MHz
Modulation type	GFSK
FCC Classification:	Digital Transmission System(DTS)
FCC Rule Part(s):	Part 15.247
ISED Rule Part(s):	RSS-247 Issue 1 (May 2015), RSS-GEN Issue 4(November 2014)

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)



Report prepared by : Kyung Soo Kang
Engineer of Telecommunication testing center

Approved by : Jong Seok Lee
Manager of Telecommunication testing center

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1702-F029	February 24, 2017	- First Approval Report

Table of Contents

1. GENERAL INFORMATION	4
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE	5
3.3 GENERAL TEST PROCEDURES	5
3.4 DESCRIPTION OF TEST MODES	6
4. INSTRUMENT CALIBRATION.....	6
5. FACILITIES AND ACCREDITATIONS	6
5.1 FACILITIES	6
5.2 EQUIPMENT	6
6. ANTENNA REQUIREMENTS	7
7. MEASUREMENT UNCERTAINTY	7
8. SUMMARY TEST OF RESULTS	8
8.1 FCC Part	8
8.2 ISED Part	9
9. TEST RESULT	10
9.1 DUTY CYCLE.....	10
9.2 6 dB BANDWIDTH MEASUREMENT	12
9.3 99% BANDWIDTH	15
9.4 OUTPUT POWER MEASUREMENT.....	18
9.5 POWER SPECTRAL DENSITY	25
9.6 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS	29
9.7 RADIATED MEASUREMENT.....	40
9.7.1 RADIATED SPURIOUS EMISSIONS.....	40
9.7.2 RADIATED RESTRICTED BAND EDGES	53
9.7.3 RECEIVER SPURIOUS EMISSIONS.....	57
9.8 POWERLINE CONDUCTED EMISSIONS	58
10. LIST OF TEST EQUIPMENT	67
10.1 LIST OF TEST EQUIPMENT(Conducted Test)	67
10.2 LIST OF TEST EQUIPMENT(Radiated Test).....	68

1. GENERAL INFORMATION

Applicant: SAMSUNG Electronics Co.,Ltd.
Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID: A3LSMW723
IC: 649E-SMW723
EUT Type: Tablet
FCC/IC Model: SM-W723
FCC Additional model(s): SM-W720, SM-W720X
Date(s) of Tests: December 22, 2016 ~ February 24, 2017
Place of Tests: HCT Co., Ltd.
 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea

2. EUT DESCRIPTION

FCC/IC Model	SM-W723	
FCC Additional model(s)	SM-W720, SM-W720X	
EUT Type	Tablet	
Power Supply	DC 7.7 V	
Battery Information	Model: EB-BW720ABA Type: Li-ion Battery	
Frequency Range	TX: 2402 MHz ~ 2480 MHz RX: 2402 MHz ~ 2480 MHz	
Max. RF Output Power	Peak	2.997 dBm (1.994 mW)
	Average	2.826 dBm (1.917 mW)
BT Operating Mode	BT_Low Energy Mode	
Modulation Type	GFSK	
Number of Channels	40 Channels	
Antenna Specification	Manufacturer: Ethertronics, Inc. Antenna type: INTERNAL ANTENNA Peak Gain : -0.75 dBi	

3. TEST METHODOLOGY

FCC KDB 558074 D01 DTS Meas Guidance v03r05 dated April 8, 2016 entitled “Guidance for Performing Compliance Measurements on Digital Transmission Systems(DTS) and the measurement procedure described in ANSI C63.10(Version : 2013) ‘the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices’.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C / RSS-GEN issue 4, RSS-247 issue 1.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 8 of ANSI C63.10. (Version: 2013)

Conducted Antenna Terminal

See Section from 9.1 to 9.2.(KDB 558074 v03r05)

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 07, 2015 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203 / RSS-Gen(Issue 4) Section 8.3:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203 / RSS-GEN.

7. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	6.07

8. SUMMARY TEST OF RESULTS

8.1 FCC Part

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	CONDUCTED	PASS
Conducted Maximum Peak Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge(Out of Band Emissions)	§15.247(d)	Conducted > 20 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 9.8		PASS
Radiated Spurious Emissions	§15.205, 15.209	cf. Section 9.7.1	RADIATED	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 9.7.2		PASS

8.2 ISED Part

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	RSS-247, 5.2	> 500 kHz	CONDUCTED	PASS
99% Bandwidth	RSS-GEN, 6.6	NA		NA
Conducted Maximum Peak Output Power And e.i.r.p.	RSS-247, 5.4.4	< 1 Watt <4 Watt(e.i.r.p.)		PASS
Power Spectral Density	RSS-247, 5.2	< 8 dBm / 3 kHz Band		PASS
Band Edge(Out of Band Emissions)	RSS-247, 5.5	Conducted > 20 dBc		PASS
AC Power line Conducted Emissions	RSS-GEN, 8.8	RSS-GEN section 8.8 table 3		PASS
Radiated Spurious Emissions	RSS-GEN, 8.9	RSS-GEN section 8.9 table 4, 5	RADIATED	PASS
Receiver Spurious Emissions	RSS-GEN, 5 RSS-GEN, 7.1.2	RSS-GEN section 7.1.2 table 2		PASS
Radiated Restricted Band Edge	RSS-GEN, 8.10	RSS-GEN section 8.10 table 6		PASS


9. TEST RESULT

9.1 DUTY CYCLE

According to Section 6.0)b) in KDB 558074 v03r05.

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0)b) in KDB 558074 v03r05.


The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz (\geq RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor = $10 \cdot \log(1/\text{Duty Cycle})$

LE Mode	T_{on}	T_{total}	Duty Cycle	Duty Cycle Factor
	(ms)	(ms)		
	0.4079	0.6245	0.6531	1.85

RESULT PLOTS




9.2 6 dB BANDWIDTH MEASUREMENT

Test Requirements and limit, §15.247(a)(2) / RSS-247(Issue 1) Section 5.2.

The bandwidth at 6 dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6 dB bandwidth is 500 kHz.

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 8.1 in KDB 558074 v03r05)

RBW = 100 kHz

VBW ≥ 3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize


Note : We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.

■ TEST RESULT

Mode	Channel	6 dB Bandwidth (kHz)	Limit (kHz)	Pass/Fail
BT LE	0	686.2	> 500	Pass
	19	687.1		Pass
	39	685.7		Pass

RESULT PLOTS


6 dB Bandwidth plot (Low-CH 0)



6 dB Bandwidth plot (Mid-CH 19)



6 dB Bandwidth plot (High-CH 39)




9.3 99% BANDWIDTH

Limit, RSS-Gen(Issue 4) Section 6.6

The 99 % bandwidth is used to determine the conducted power limits.

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer.

RBW = 1% ~ 5% of the occupied bandwidth

VBW = 3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize

Note : We tested OBW using the automatic bandwidth measurement capability of a spectrum analyzer.


■ TEST RESULTS

Conducted 99% Bandwidth Measurements for LE Mode


LE Mode		Measured Bandwidth [MHz]
Frequency [MHz]	Channel No.	
2402	0	1.0614
2440	19	1.0559
2480	39	1.0577

RESULT PLOTS


99% Bandwidth plot (Low-CH 0)



99% Bandwidth plot (Mid-CH 19)



99% Bandwidth plot (High-CH 39)




9.4 OUTPUT POWER MEASUREMENT

Test Requirements and limit, §15.247(b)(3) / RSS-247(Issue 1) Section 5.4.4.

A transmitter antenna terminal of EUT is connected to the input of a Spectrum Analyzer. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We use the spectrum analyzer's integrated band power measurement function.

This EUT TX condition is actual operating mode by BT LE mode test program.

The Spectrum Analyzer is set to

- Peak Power (Procedure 9.1.1 in KDB 558074 v03r05)
 - RBW \geq DTS Bandwidth
 - VBW $\geq 3 \times$ RBW
 - SPAN $\geq 3 \times$ RBW
 - Detector Mode = Peak
 - Sweep = auto couple
 - Trace Mode = max hold
 - Allow trace to fully stabilize.
 - Use peak marker function to determine the peak amplitude level

- Average Power (Procedure 9.2.2.4 in KDB 558074 v03r05)
 - Measure the duty cycle
 - Set span to at least 1.5 times the OBW
 - RBW = 1-5 % of the OBW, not to exceed 1 MHz.
 - VBW $\geq 3 \times$ RBW.
 - Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
 - Sweep time = auto.
 - Detector = RMS(i.e., power averaging)
 - Do not use sweep triggering. Allow the sweep to "free run".
 - Trace average at least 100 traces in power averaging(RMS) mode.

Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges.

Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

■ Sample Calculation

Output Power = Reading Value + ATT loss + Cable loss(1 ea) + Duty Cycle Factor

Output Power = 10 dBm + 10 dB + 0.8 dB + 0.2 dB = 21.0 dBm

Note :

1. Spectrum reading values are not plot data. The power results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.7 dB is offset for 2.4 GHz Band.

■ TEST RESULTS-Peak

Conducted Output Power Measurements

LE Mode		Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.		
2402	0	2.654	30
2440	19	2.997	30
2480	39	2.494	30


■ TEST RESULTS-Average

Conducted Output Power Measurements


LE Mode		Measured Power(dBm)	Duty Cycle Factor (dB)	Measured Power(dBm) + Duty Cycle Factor(dB)	Limit (dBm)
Frequency[MHz]	Channel No.				
2402	0	0.73	1.85	2.58	30
2440	19	0.98	1.85	2.83	30
2480	39	0.42	1.85	2.27	30

RESULT PLOTS-Peak


Conducted Output Power (Low-CH 0)



Conducted Output Power (Mid-CH 19)




Conducted Output Power (High-CH 39)




RESULT PLOTS-Average

Conducted Output Power (Low-CH 0)



Conducted Output Power (Mid-CH 19)



Conducted Output Power (High-CH 39)




9.5 POWER SPECTRAL DENSITY

Test Requirements and limit, §15.247(e) / RSS-247(Issue 1) Section 5.2.

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard – The transmitter power density average over 1-second interval shall not be greater than 8dBm in any 3kHz BW.

■ TEST CONFIGURATION



■ TEST PROCEDURE

We tested according to Procedure 10.2 in KDB 558074, issued 01/07/2016

The spectrum analyzer is set to :

Set analyzer center frequency to DTS channel center frequency.

Span = 1.5 times the DTS channel bandwidth.

RBW = 3 kHz ≤ RBW ≤ 100 kHz.

VBW ≥ 3 x RBW.

Sweep = auto couple

Detector = peak

Trace Mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

■ Sample Calculation

PSD = Reading Value + ATT loss + Cable loss(1 ea)

Output Power = -5 dBm + 10 dB + 0.8 dB = 5.8 dBm

Note :

1. Spectrum reading values are not plot data. The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.7 dB is offset for 2.4 GHz Band.


■ TEST RESULTS

Conducted Power Density Measurements


Frequency (MHz)	Channel No.	Mode	Test Result		
			PSD (dBm)	Limit (dBm)	Pass/ Fail
2402	0	LE	-11.942	8	Pass
2440	19		-11.564	8	Pass
2480	39		-12.188	8	Pass

RESULT PLOTS


Power Spectral Density (Low-CH 0)



Power Spectral Density (Mid-CH 19)




Power Spectral Density (High-CH 39)



9.6 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS**Test Requirements and limit, §15.247(d) / RSS-247(Issue 1) Section 5.5.**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit : 20 dBc**■ TEST CONFIGURATION****■ TEST PROCEDURE**

The transmitter output is connected to the spectrum analyzer. (Procedure 11.0 in KDB 558074 v03r05)

RBW = 100 kHz

VBW $\geq 3 \times$ RBW

Set span to encompass the spectrum to be examined

Detector = Peak

Trace Mode = max hold

Sweep time = auto couple

Ensure that the number of measurement points $\geq 2 \times$ Span/RBW

Allow trace to fully stabilize.

Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 10th harmonic range with the transmitter set to the lowest, middle, and highest channels.

Note :

1. The maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1(KDB558074 v03r05), so the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
2. The band edge results in plot is already including the actual values of loss for the attenuator and cable combination.
3. Spectrum offset = Attenuator loss + Cable loss
4. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.7 dB is offset for 2.4 GHz Band.
5. In case of conducted spurious emissions test, please check factors blow table.
6. In order to simplify the report, attached plots were only the worst case channel and data rate.

■ FACTORS FOR FREQUENCY

Freq(MHz)	Factor(dB)
30	11.30
100	9.83
200	10.19
300	10.13
400	10.23
500	10.25
600	10.32
700	10.35
800	10.35
900	10.34
1000	10.39
2000	10.64
2400*	10.65
2500*	10.67
3000	10.68
4000	10.89
5000	11.07
6000	11.06
7000	11.35
8000	11.32
9000	11.48
10000	11.56

11000	11.56
12000	11.68
13000	11.83
14000	11.90
15000	11.98
16000	12.04
17000	12.02
18000	12.08
19000	12.07
20000	12.14
21000	12.17
22000	12.31
23000	12.60
24000	12.34
25000	12.53

Note : 1. ** is fundamental frequency range.


2. Factor = Cable loss + Attenuator loss

RESULT PLOTS

BandEdge (Low-CH 0)




BandEdge (High-CH 39)




30 MHz ~ 1 GHz

Conducted Spurious Emission (Mid-CH 19)




1 GHz ~ 3 GHz

Conducted Spurious Emission (Mid-CH 19)




3 GHz ~ 5 GHz

Conducted Spurious Emission (Mid-CH 19)




5 GHz ~ 7 GHz

Conducted Spurious Emission (Mid-CH 19)




7 GHz ~ 9 GHz

Conducted Spurious Emission (Mid-CH 19)




9 GHz ~ 11 GHz

Conducted Spurious Emission (Mid-CH 19)




11 GHz ~ 13 GHz

Conducted Spurious Emission (Mid-CH 19)




13 GHz ~ 15 GHz

Conducted Spurious Emission (Mid-CH 19)




15 GHz ~ 17 GHz

Conducted Spurious Emission (Mid-CH 19)




17 GHz ~ 19 GHz

Conducted Spurious Emission (Mid-CH 19)




19 GHz ~ 21 GHz

Conducted Spurious Emission (Mid-CH 19)




21 GHz ~ 23 GHz

Conducted Spurious Emission (Mid-CH 19)



23 GHz ~ 25 GHz

Conducted Spurious Emission (Mid-CH 19)




9.7 RADIATED MEASUREMENT.**9.7.1 RADIATED SPURIOUS EMISSIONS.**

Test Requirements and limit, §15.205, §15.209, RSS-Gen(Issue 4) Section 8.9


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE USED

Method 12.1 in KDB 558074 v03r05

Spectrum Setting

- Peak

Peak emission levels are measured by setting the instrument as follows:

RBW = cf. Table 1.

VBW $\geq 3 \times$ RBW.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes.

(Note that the required measurement time may be longer for low duty cycle applications).

Table 1 —RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

- Average (duty cycle < 98%, duty cycle variations are less than ±2%)

Set RBW = 1 MHz

Set VBW ≥ 3 x RBW

Detector = RMS.

Averaging type = power (*i.e.*, RMS).

Sweep time = auto.

Trace mode = average (at least 100 traces).

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.

Note :

1. We are performed the RSE and radiated band edge using standard radiated method(RMS).
2. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).
3. Distance extrapolation factor = $20 \log (\text{test distance} / \text{specific distance})$ (dB)

LE Mode	T _{on}	T _{total}	Duty Cycle	Duty Cycle Factor (dB)
	(ms)	(ms)		
	0.4079	0.6245	0.6531	1.85

TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
4. Limit line = specific Limits (dBuV) + Distance extrapolation factor
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

TEST RESULTS

Below 1 GHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

[Only tablet]
Above 1 GHz

Operation Mode: CH.0

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	47.54	0.00	-0.61	V	46.93	73.98	27.05	PK
4804	36.05	1.85	-0.61	V	37.29	53.98	16.69	AV
7206	43.67	0.00	8.78	V	52.45	73.98	21.53	PK
7206	32.79	1.85	8.78	V	43.42	53.98	10.56	AV
4804	48.47	0.00	-0.61	H	47.86	73.98	26.12	PK
4804	36.13	1.85	-0.61	H	37.37	53.98	16.61	AV
7206	44.80	0.00	8.78	H	53.58	73.98	20.40	PK
7206	32.86	1.85	8.78	H	43.49	53.98	10.49	AV

*A.F. : Antenna Factor / C.L. : Cable Loss / A.G. : Amplifier Gain / D.F. : Distance Factor

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor
+ Duty Cycle Factor
5. Distance extrapolation factor = $20 \log(\text{test distance} / \text{specific distance})$ (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH.19

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4880	48.44	0.00	0.19	V	48.63	73.98	25.35	PK
4880	36.65	1.85	0.19	V	38.69	53.98	15.29	AV
7320	44.56	0.00	8.85	V	53.41	73.98	20.57	PK
7320	33.09	1.85	8.85	V	43.79	53.98	10.19	AV
4880	48.61	0.00	0.19	H	48.8	73.98	25.18	PK
4880	36.71	1.85	0.19	H	38.75	53.98	15.23	AV
7320	45.00	0.00	8.85	H	53.85	73.98	20.13	PK
7320	33.17	1.85	8.85	H	43.87	53.98	10.11	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor + Duty Cycle Factor
5. Distance extrapolation factor = $20 \log (\text{test distance} / \text{specific distance})$ (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH.39

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	48.11	0.00	0.92	V	49.03	73.98	24.95	PK
4960	36.37	1.85	0.92	V	39.14	53.98	14.84	AV
7440	45.20	0.00	9.03	V	54.23	73.98	19.75	PK
7440	33.02	1.85	9.03	V	43.9	53.98	10.08	AV
4960	48.35	0.00	0.92	H	49.27	73.98	24.71	PK
4960	36.49	1.85	0.92	H	39.26	53.98	14.72	AV
7440	45.41	0.00	9.03	H	54.44	73.98	19.54	PK
7440	33.08	1.85	9.03	H	43.96	53.98	10.02	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor + Duty Cycle Factor
5. Distance extrapolation factor = 20 log (test distance / specific distance) (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

[Tablet+keyboard cover(kickstand)]

Above 1 GHz

Operation Mode: CH.0

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	48.14	0.00	-0.61	V	47.53	73.98	26.45	PK
4804	36.13	1.85	-0.61	V	37.37	53.98	16.61	AV
7206	43.88	0.00	8.78	V	52.66	73.98	21.32	PK
7206	32.69	1.85	8.78	V	43.32	53.98	10.66	AV
4804	48.52	0.00	-0.61	H	47.91	73.98	26.07	PK
4804	36.21	1.85	-0.61	H	37.45	53.98	16.53	AV
7206	44.16	0.00	8.78	H	52.94	73.98	21.04	PK
7206	32.75	1.85	8.78	H	43.38	53.98	10.60	AV

*A.F. : Antenna Factor / C.L. : Cable Loss / A.G. : Amplifier Gain / D.F. : Distance Factor

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor
+ Duty Cycle Factor
5. Distance extrapolation factor = 20 log (test distance / specific distance) (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH.19

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4880	48.37	0.00	0.19	V	48.56	73.98	25.42	PK
4880	36.59	1.85	0.19	V	38.63	53.98	15.35	AV
7320	44.93	0.00	8.85	V	53.78	73.98	20.20	PK
7320	33.14	1.85	8.85	V	43.84	53.98	10.14	AV
4880	48.56	0.00	0.19	H	48.75	73.98	25.23	PK
4880	36.74	1.85	0.19	H	38.78	53.98	15.20	AV
7320	45.22	0.00	8.85	H	54.07	73.98	19.91	PK
7320	33.20	1.85	8.85	H	43.9	53.98	10.08	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor + Duty Cycle Factor
5. Distance extrapolation factor = $20 \log (\text{test distance} / \text{specific distance})$ (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH.39


Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G.+D.F. [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	48.13	0.00	0.92	V	49.05	73.98	24.93	PK
4960	36.42	1.85	0.92	V	39.19	53.98	14.79	AV
7440	45.16	0.00	9.03	V	54.19	73.98	19.79	PK
7440	32.96	1.85	9.03	V	43.84	53.98	10.14	AV
4960	48.42	0.00	0.92	H	49.34	73.98	24.64	PK
4960	36.51	1.85	0.92	H	39.28	53.98	14.70	AV
7440	45.29	0.00	9.03	H	54.32	73.98	19.66	PK
7440	33.03	1.85	9.03	H	43.91	53.98	10.07	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain + Distance Factor + Duty Cycle Factor
5. Distance extrapolation factor = 20 log (test distance / specific distance) (dB)
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.


■ **RESULT PLOTS (Worst case : X-H, Only tablet)**

Radiated Spurious Emissions plot – Average Reading (Ch.39 3rd Harmonic)



Date: 25.JAN.2017 16:28:00

Radiated Spurious Emissions plot – Peak Reading (Ch.39 3rd Harmonic)



Date: 25.JAN.2017 16:28:32

Note : Only the worst case plots for Radiated Spurious Emissions.

9.7.2 RADIATED RESTRICTED BAND EDGES

Test Requirements and limit, §15.247(d) §15.205, §15.209, RSS-Gen(Issue 4) 8.10

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operation Mode BT_LE_Only tablet
 Operating Frequency 2402 MHz
 Channel No. 0

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	15.88	0.00	32.68	H	48.56	73.98	25.42	PK
2390.0	4.39	1.85	32.68	H	38.92	53.98	15.06	AV
2390.0	15.69	0.00	32.68	V	48.37	73.98	25.61	PK
2390.0	4.36	1.85	32.68	V	38.89	53.98	15.09	AV

Operation Mode BT_LE_Tablet+keyboard cover(kickstand)
 Operating Frequency 2402 MHz
 Channel No. 0

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	15.70	0.00	32.68	H	48.38	73.98	25.60	PK
2390.0	4.41	1.85	32.68	H	38.94	53.98	15.04	AV
2390.0	15.29	0.00	32.68	V	47.97	73.98	26.01	PK
2390.0	4.33	1.85	32.68	V	38.86	53.98	15.12	AV

Notes:

1. Frequency range of measurement = 2310 MHz ~ 2390 MHz
2. Total = Reading Value + Antenna Factor + Cable Loss + Duty Cycle Factor + Distance Factor
3. Distance extrapolation factor = $20 \log (\text{test distance} / \text{specific distance})$ (dB)
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode BT_LE_Only tablet
 Operating Frequency 2480 MHz
 Channel No. 39

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	16.04	0.00	33.05	H	49.09	73.98	24.90	PK
2483.5	4.65	1.85	33.05	H	39.55	53.98	14.43	AV
2483.5	15.39	0.00	33.05	V	48.44	73.98	25.54	PK
2483.5	4.44	1.85	33.05	V	39.34	53.98	14.64	AV

Operation Mode BT_LE_Tablet+keyboard cover(kickstand)
 Operating Frequency 2480 MHz
 Channel No. 39


Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	15.30	0.00	33.05	H	48.35	73.98	25.63	PK
2483.5	4.35	1.85	33.05	H	39.25	53.98	14.73	AV
2483.5	15.62	0.00	33.05	V	48.67	73.98	25.31	PK
2483.5	4.50	1.85	33.05	V	39.40	53.98	14.58	AV

Notes:


1. Frequency range of measurement = 2483.5 MHz ~ 2500 MHz
2. Total = Reading Value + Antenna Factor + Cable Loss + Duty Cycle Factor + Distance Factor
3. Distance extrapolation factor = 20 log (test distance / specific distance) (dB)
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

RESULT PLOTS_Data packet length (Worst case : X-H, Only tablet)

Radiated Restricted Band Edges plot – Average Reading (Ch.39)



Radiated Restricted Band Edges plot – Peak Reading (Ch.39)



Note : Only the worst case plots for Radiated Restricted Band Edges.

9.7.3 RECEIVER SPURIOUS EMISSIONS

ISED Rule(s) **RSS-GEN**
Test Requirements: **Blow the table**
Operating conditions: **Under normal test conditions**
Method of testing: **Radiated**

S/A. Settings: **F < 1 GHz: RBW: 120 kHz, VBW: 300 kHz (Quasi Peak)**
 F > 1 GHz: RBW: 1 MHz, VBW: 1 MHz (Peak)
Mode of operation: **Receive**

Frequency (MHz)	Field Strength (microvolts/m at 3 meters)
30 – 88	100
88 - 216	150
216 – 960	200
Above 960	500

Operation Mode: Receive:

30 MHz ~ 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No critical peaks found							

Above 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No critical peaks found							

9.8 POWERLINE CONDUCTED EMISSIONS

Test Requirements and limit, §15.207, RSS-Gen(Issue 4) Section 8.8

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

RESULT PLOTS (Only tablet)
Conducted Emissions (Line 1)

EMI Auto Test(4)


1 / 2

HCT TEST Report

Common Information

EUT: SM-W727V
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: BT LE_L1

FCC CLASS B



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG X Final Result 1-QPK X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	38.0	9.000	Off	L1	9.6	28.0	66.0
0.194000	31.7	9.000	Off	L1	9.6	32.2	63.9
0.200000	30.5	9.000	Off	L1	9.6	33.1	63.6
0.208000	29.1	9.000	Off	L1	9.6	34.2	63.3
0.216000	27.7	9.000	Off	L1	9.6	35.3	63.0
0.222000	28.1	9.000	Off	L1	9.6	34.7	62.7
0.884000	27.0	9.000	Off	L1	9.7	29.0	56.0
0.888000	27.3	9.000	Off	L1	9.7	28.7	56.0
1.012000	30.4	9.000	Off	L1	9.7	25.6	56.0
1.056000	30.4	9.000	Off	L1	9.7	25.6	56.0
2.164000	29.2	9.000	Off	L1	9.8	26.8	56.0
2.484000	25.8	9.000	Off	L1	9.8	30.2	56.0
5.156000	24.7	9.000	Off	L1	9.9	35.3	60.0
5.808000	24.3	9.000	Off	L1	9.9	35.7	60.0
5.890000	25.2	9.000	Off	L1	9.9	34.8	60.0
6.568000	26.5	9.000	Off	L1	10.0	33.5	60.0
6.572000	27.3	9.000	Off	L1	10.0	32.7	60.0
6.578000	26.2	9.000	Off	L1	10.0	33.8	60.0

Final Result 2

2017-01-20

오전 10:00:50

EMI Auto Test(4)

2 / 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	21.1	9.000	Off	L1	9.6	34.9	56.0
0.186000	17.4	9.000	Off	L1	9.6	36.8	54.2
0.198000	19.0	9.000	Off	L1	9.6	34.7	53.7
0.202000	18.9	9.000	Off	L1	9.6	34.6	53.5
0.208000	17.4	9.000	Off	L1	9.6	35.9	53.3
0.212000	18.1	9.000	Off	L1	9.6	35.1	53.1
0.884000	21.1	9.000	Off	L1	9.7	24.9	46.0
0.888000	21.8	9.000	Off	L1	9.7	24.2	46.0
1.060000	25.2	9.000	Off	L1	9.7	20.8	46.0
2.068000	23.3	9.000	Off	L1	9.8	22.7	46.0
2.482000	21.0	9.000	Off	L1	9.8	25.0	46.0
2.716000	22.5	9.000	Off	L1	9.8	23.5	46.0
5.154000	19.2	9.000	Off	L1	9.9	30.8	50.0
5.616000	19.2	9.000	Off	L1	9.9	30.8	50.0
5.808000	18.4	9.000	Off	L1	9.9	31.6	50.0
6.568000	22.3	9.000	Off	L1	10.0	27.7	50.0
6.578000	20.8	9.000	Off	L1	10.0	29.2	50.0
6.622000	22.1	9.000	Off	L1	10.0	27.9	50.0

2017-01-20

오전 10:00:50

Conducted Emissions (Line 2)

EMI Auto Test(4)


1 / 2

HCT TEST Report

Common Information

EUT: SM-W727V
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: BT LE_N

FCC CLASS B



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG × Final Result 1-QPK × Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154000	43.7	9.000	Off	N	9.6	22.1	65.8
0.162000	43.0	9.000	Off	N	9.6	22.3	65.4
0.174000	41.2	9.000	Off	N	9.6	23.6	64.8
0.178000	41.1	9.000	Off	N	9.6	23.4	64.6
0.186000	40.1	9.000	Off	N	9.6	24.1	64.2
0.192000	39.5	9.000	Off	N	9.6	24.4	63.9
3.348000	36.2	9.000	Off	N	9.8	19.8	56.0
3.486000	32.8	9.000	Off	N	9.8	23.2	56.0
3.868000	35.3	9.000	Off	N	9.8	20.7	56.0
3.932000	33.7	9.000	Off	N	9.8	22.3	56.0
3.944000	34.2	9.000	Off	N	9.8	21.8	56.0
4.010000	34.5	9.000	Off	N	9.8	21.5	56.0
5.734000	29.6	9.000	Off	N	9.9	30.4	60.0
5.982000	30.2	9.000	Off	N	9.9	29.8	60.0
6.272000	29.3	9.000	Off	N	9.9	30.7	60.0
6.290000	30.6	9.000	Off	N	9.9	29.4	60.0
29.312000	29.1	9.000	Off	N	10.4	30.9	60.0
29.316000	29.0	9.000	Off	N	10.4	31.0	60.0

Final Result 2

2017-01-20

오전 9:45:35

EMI Auto Test(4)

2 / 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	21.8	9.000	Off	N	9.6	34.2	56.0
0.154000	19.9	9.000	Off	N	9.6	35.9	55.8
0.158000	20.7	9.000	Off	N	9.6	34.9	55.6
0.162000	20.6	9.000	Off	N	9.6	34.8	55.4
0.166000	19.9	9.000	Off	N	9.6	35.2	55.2
0.170000	19.2	9.000	Off	N	9.6	35.8	55.0
3.350000	26.3	9.000	Off	N	9.8	19.7	46.0
3.428000	22.2	9.000	Off	N	9.8	23.8	46.0
3.486000	23.7	9.000	Off	N	9.8	22.3	46.0
3.868000	23.9	9.000	Off	N	9.8	22.1	46.0
3.934000	22.6	9.000	Off	N	9.8	23.4	46.0
4.010000	23.0	9.000	Off	N	9.8	23.0	46.0
6.088000	24.4	9.000	Off	N	9.9	25.6	50.0
6.092000	24.0	9.000	Off	N	9.9	26.0	50.0
6.158000	26.9	9.000	Off	N	9.9	23.1	50.0
6.290000	22.8	9.000	Off	N	9.9	27.2	50.0
6.554000	19.7	9.000	Off	N	10.0	30.3	50.0
29.312000	21.7	9.000	Off	N	10.4	28.3	50.0

2017-01-20

오전 9:45:35

RESULT PLOTS (Tablet+keyboard cover(kickstand))
Conducted Emissions (Line 1)

EMI Auto Test(4)


1 / 2

HCT TEST Report

Common Information

EUT: SM-W727V
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: BT LE_L1 (KEYBOARD)

FCC CLASS B



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG x Final Result 1-QPK x Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	36.7	9.000	Off	L1	9.6	29.3	66.0
0.158000	35.6	9.000	Off	L1	9.6	30.0	65.6
0.206000	29.5	9.000	Off	L1	9.6	33.9	63.4
0.210000	28.4	9.000	Off	L1	9.6	34.8	63.2
0.220000	28.2	9.000	Off	L1	9.6	34.6	62.8
0.234000	27.0	9.000	Off	L1	9.6	35.3	62.3
0.882000	32.6	9.000	Off	L1	9.7	23.4	56.0
1.018000	30.3	9.000	Off	L1	9.7	25.7	56.0
1.170000	29.0	9.000	Off	L1	9.7	27.0	56.0
2.766000	25.4	9.000	Off	L1	9.8	30.6	56.0
3.080000	20.1	9.000	Off	L1	9.8	35.9	56.0
3.878000	25.1	9.000	Off	L1	9.9	30.9	56.0
6.014000	22.1	9.000	Off	L1	10.0	37.9	60.0
25.588000	31.6	9.000	Off	L1	10.4	28.4	60.0
25.934000	27.9	9.000	Off	L1	10.4	32.1	60.0
25.938000	30.4	9.000	Off	L1	10.4	29.6	60.0
26.448000	28.8	9.000	Off	L1	10.4	31.2	60.0
27.412000	25.4	9.000	Off	L1	10.4	34.6	60.0

Final Result 2

2017-01-20

오전 10:22:42

EMI Auto Test(4)

2 / 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	20.7	9.000	Off	L1	9.6	35.3	56.0
0.202000	18.7	9.000	Off	L1	9.6	34.8	53.5
0.206000	18.5	9.000	Off	L1	9.6	34.9	53.4
0.210000	18.3	9.000	Off	L1	9.6	34.9	53.2
0.222000	19.6	9.000	Off	L1	9.6	33.1	52.7
0.294000	25.4	9.000	Off	L1	9.7	25.0	50.4
0.882000	23.7	9.000	Off	L1	9.7	22.3	46.0
1.088000	25.2	9.000	Off	L1	9.7	20.8	46.0
2.728000	18.9	9.000	Off	L1	9.8	27.1	46.0
2.754000	18.8	9.000	Off	L1	9.8	27.2	46.0
2.766000	21.9	9.000	Off	L1	9.8	24.1	46.0
3.080000	14.0	9.000	Off	L1	9.8	32.0	46.0
6.014000	17.4	9.000	Off	L1	10.0	32.6	50.0
25.584000	26.6	9.000	Off	L1	10.4	23.4	50.0
25.632000	26.9	9.000	Off	L1	10.4	23.1	50.0
25.934000	22.7	9.000	Off	L1	10.4	27.3	50.0
26.448000	24.7	9.000	Off	L1	10.4	25.3	50.0
26.930000	21.9	9.000	Off	L1	10.4	28.1	50.0

2017-01-20

오전 10:22:42

Conducted Emissions (Line 2)

BT LE_N (KEYBOARD)


1 / 2

HCT TEST Report

Common Information

EUT: SM-W727V
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: BT LE_N (KEYBOARD)

FCC CLASS B



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG x Final Result 1-QPK x Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	34.2	9.000	Off	N	9.6	31.8	66.0
0.200000	27.8	9.000	Off	N	9.6	35.8	63.6
0.552000	35.5	9.000	Off	N	9.7	20.5	56.0
0.562000	33.1	9.000	Off	N	9.7	22.9	56.0
0.568000	34.4	9.000	Off	N	9.7	21.6	56.0
0.572000	36.5	9.000	Off	N	9.7	19.5	56.0
1.100000	29.2	9.000	Off	N	9.7	26.8	56.0
1.166000	28.3	9.000	Off	N	9.7	27.7	56.0
3.710000	28.4	9.000	Off	N	9.8	27.6	56.0
3.716000	25.6	9.000	Off	N	9.8	30.4	56.0
3.856000	26.1	9.000	Off	N	9.8	29.9	56.0
4.622000	24.2	9.000	Off	N	9.9	31.8	56.0
5.300000	22.0	9.000	Off	N	9.9	38.0	60.0
5.448000	20.7	9.000	Off	N	9.9	39.3	60.0
5.508000	24.1	9.000	Off	N	9.9	35.9	60.0
5.538000	22.5	9.000	Off	N	9.9	37.5	60.0
5.578000	20.9	9.000	Off	N	9.9	39.1	60.0
6.350000	22.0	9.000	Off	N	10.0	38.0	60.0

Final Result 2

2017-01-20

오전 10:39:35

BT LE_N (KEYBOARD)

2 / 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	20.6	9.000	Off	N	9.6	35.4	56.0
0.550000	26.8	9.000	Off	N	9.7	19.2	46.0
0.554000	26.6	9.000	Off	N	9.7	19.4	46.0
0.562000	22.8	9.000	Off	N	9.7	23.2	46.0
0.566000	23.5	9.000	Off	N	9.7	22.5	46.0
0.574000	26.7	9.000	Off	N	9.7	19.3	46.0
1.042000	23.7	9.000	Off	N	9.7	22.3	46.0
1.140000	23.2	9.000	Off	N	9.7	22.8	46.0
1.148000	22.8	9.000	Off	N	9.7	23.2	46.0
2.874000	20.3	9.000	Off	N	9.8	25.7	46.0
3.280000	13.2	9.000	Off	N	9.8	32.8	46.0
3.952000	14.9	9.000	Off	N	9.8	31.1	46.0
5.448000	11.4	9.000	Off	N	9.9	38.6	50.0
5.478000	17.4	9.000	Off	N	9.9	32.6	50.0
5.508000	13.8	9.000	Off	N	9.9	36.2	50.0
5.576000	12.1	9.000	Off	N	9.9	37.9	50.0
6.160000	18.0	9.000	Off	N	9.9	32.0	50.0
26.980000	16.4	9.000	Off	N	10.4	33.6	50.0

2017-01-20

오전 10:39:35

10. LIST OF TEST EQUIPMENT**10.1 LIST OF TEST EQUIPMENT(Conducted Test)**

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	12/23/2016	Annual	100073
Rohde & Schwarz	ESCI / Test Receiver	12/23/2016	Annual	100584
Agilent	N9020A / Signal Analyzer	06/24/2016	Annual	MY51110085
Agilent	N9030A / Signal Analyzer	11/30/2016	Annual	MY49431210
Agilent	N1911A / Power Meter	03/11/2016	Annual	MY45100523
Agilent	N1921A / Power Sensor	03/11/2016	Annual	MY52260025
Agilent	87300B / Directional Coupler	11/23/2016	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	06/14/2016	Annual	05001
Hewlett Packard	E3632A / DC Power Supply	03/09/2016	Annual	KR75303962
Agilent	8493C / Attenuator(10 dB)	07/15/2016	Annual	07560
Rohde & Schwarz	CBT / Bluetooth Tester	05/16/2016	Annual	100422

10.2 LIST OF TEST EQUIPMENT(Radiated Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Audix	AM4000 / Antenna Position Tower	N/A	N/A	N/A
Audix	Turn Table	N/A	N/A	N/A
Audix	EM1000 / Controller	N/A	N/A	060520
Rohde & Schwarz	Loop Antenna	02/23/2016	Biennial	1513-175
Schwarzbeck	VULB 9168 / Hybrid Antenna	04/15/2015	Biennial	255
Schwarzbeck	BBHA 9120D / Horn Antenna	05/07/2015	Biennial	937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	09/03/2015	Biennial	BBHA9170541
Rohde & Schwarz	FSP / Spectrum Analyzer	09/10/2016	Annual	100688
Rohde & Schwarz	FSV40-N / Spectrum Analyzer	09/23/2016	Annual	101068-SZ
Wainwright Instruments	WHK3.0/18G-10EF / High Pass Filter	06/24/2016	Annual	8
Wainwright Instruments	WHFX7.0/18G-8SS / High Pass Filter	05/13/2016	Annual	29
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	07/06/2016	Annual	2
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	01/24/2017	Annual	2
Agilent	8493C-10 / Attenuator(10 dB)	08/11/2016	Annual	76649
CERNEX	CBLU1183540 / Power Amplifier	07/15/2016	Annual	22964
CERNEX	CBL06185030 / Power Amplifier	07/15/2016	Annual	22965
CERNEX	CBL18265035 / Power Amplifier	01/23/2017	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	07/11/2016	Annual	25956
TESCOM	TC-3000C / Bluetooth Tester	04/01/2016	Annual	3000C000276