



FCC CFR47 PART 22 SUBPART H
FCC CFR47 PART 24 SUBPART E
FCC CFR47 PART 27 SUBPART D/F/H/L/M/N
FCC CFR47 PART 90 SUBPART R/S

WWAN

CERTIFICATION TEST REPORT

FOR

WCDMA/LTE Tablet + BT/BLE and DTS/UNII a/b/g/n/ac

MODEL NUMBER : SM-W737N0

FCC ID: A3LSMW737N0

REPORT NUMBER: 4788556585-E5V2

ISSUE DATE: SEP 10, 2018

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Prepared by
UL Korea, Ltd.
26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea
Suwon Test Site: UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



ACCREDITED*

Testing
Laboratory

TL-637

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	09/04/18	Initial issue	Hoonpyo Lee
V2	09/10/18	Applied about the TCB's requests	Hoonpyo Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION.....	6
4.2. SAMPLE CALCULATION.....	6
4.3. MEASUREMENT UNCERTAINTY	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT.....	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	15
5.4. WORST-CASE ORIENTATION.....	16
5.5. DESCRIPTION OF TEST SETUP	18
6. TEST AND MEASUREMENT EQUIPMENT	20
7. Summary Table	21
8. PEAK TO AVERAGE RATIO	22
8.1. CONDUCTED PEAK TO AVERAGE RESULT.....	23
9. LIMITS AND CONDUCTED RESULTS	37
9.1. OCCUPIED BANDWIDTH.....	37
9.1.1. OCCUPIED BANDWIDTH RESULTS	38
9.2. BAND EDGE EMISSIONS	83
9.2.1. BAND EDGE RESULT.....	86
9.2.2. EMISSION MASK RESULT	122
9.3. OUT OF BAND EMISSIONS.....	141
9.3.1. OUT OF BAND EMISSIONS RESULT	143
9.4. FREQUENCY STABILITY.....	159
9.4.1. FREQUENCY STABILITY RESULTS	160
10. RADIATED TEST RESULTS	167
10.1. RADIATED POWER (ERP & EIRP)	167
10.1.1. ERP/EIRP Results.....	168
10.1.2. ERP/EIRP DATA	177
10.2. FIELD STRENGTH OF SPURIOUS RADIATION.....	223

10.2.1. SPURIOUS RADIATION PLOTS.....	225
11. SETUP PHOTOS	239

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: WCDMA/LTE Tablet + BT/BLE and DTS/UNII a/b/g/n/ac
MODEL NUMBER: SM-W737N0
SERIAL NUMBER: BBMGR34K500613H (RADIATED)
BBMGR34K50061VZ (CONDUCTED)
DATE TESTED: JUL 24, 2018 - SEP 10, 2018

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 22H, 24E, 27D, 27F, 27H, 27L, 27M, 27N, 90S and 90R	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



SungGil Park
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Hoonpyo Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 22.
3. FCC CFR 47 Part 24.
4. FCC CFR 47 Part 27.
5. ANSI TIA-603-E, 2016
6. KDB 971168 D01 Power Meas License Digital Systems v03r01

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input checked="" type="checkbox"/>	Chamber 2
<input type="checkbox"/>	Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$EIRP = \text{PSA reading with EUT worst orientation (dBm)} + \text{Path loss (dB)} - \text{cable loss (between the SG and substitution antenna)} + \text{Substitution Antenna Factor (dBi)}$

$ERP = \text{PSA reading with EUT worst orientation (dBm)} + \text{Path loss (dB)} - \text{cable loss (between the SG and substitution antenna)}$

(Path loss = Signal generator output – PSA reading with substitution antenna)

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	3.86 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a WCDMA/LTE Tablet + BT/BLE and DTS/UNII a/b/g/n/ac.
 This test report addresses the WWAN operational mode.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum average radiated ERP / EIRP output powers as follows:

WCDMA

FCC Part 22/24				
Band	Frequency Range	Modulation	Radiated	
	[MHz]		Avg [dBm]	Avg [mW]
Band 5	824~849	REL99	19.89	97.50
		HSDPA	18.71	74.30
Band 4	1710~1755	REL99	23.21	209.41
		HSDPA	22.27	168.66
Band 2	1850~1910	REL99	22.18	165.20
		HSDPA	20.68	116.95

LTE Band 7

FCC Part 27					
Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Radiated	
				Avg [dBm]	Avg [mW]
Band 7	2500-2570	20	QPSK	22.33	171.00
			16QAM	21.56	143.22
		15	QPSK	22.73	187.50
			16QAM	21.76	149.97
		10	QPSK	23.01	199.99
			16QAM	22.07	161.06
		5	QPSK	22.86	193.20
			16QAM	22.03	159.59

LTE Band 12

FCC Part 27					
Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation	Radiated	
				Avg [dBm]	Avg [mW]
Band 12	699 ~ 716	10	QPSK	17.24	52.97
			16QAM	16.14	41.11
		5	QPSK	17.21	52.60
			16QAM	16.20	41.69
		3	QPSK	17.76	59.70
			16QAM	16.21	41.78
		1.4	QPSK	17.44	55.46
			16QAM	16.78	47.64

LTE Band 17

LTE Band 17 (Frequency range: 704-716 MHz) is covered by LTE Band 12 (Frequency range: 699-716 MHz) due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth.

LTE Band 13

FCC Part 27					
Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Radiated	
				Avg [dBm]	Avg [mW]
Band 13	777 ~ 787	10	QPSK	18.65	73.28
			16QAM	17.62	57.81
		5	QPSK	18.82	76.21
			16QAM	18.20	66.07

LTE Band 14

FCC Part 90					
Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Radiated	
				Avg [dBm]	Avg [mW]
Band 14	788 ~ 798	10	QPSK	19.57	90.57
			16QAM	19.02	79.80
		5	QPSK	19.15	82.22
			16QAM	18.33	68.08

LTE Band 25

FCC Part 24					
Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Radiated	
				Avg [dBm]	Avg [mW]
Band 25	1850 ~ 1915	20	QPSK	22.63	183.23
			16QAM	21.63	145.55
		15	QPSK	21.81	151.71
			16QAM	20.81	120.50
		10	QPSK	21.15	130.32
			16QAM	20.13	103.04
		5	QPSK	20.96	124.74
			16QAM	20.45	110.92
		3	QPSK	23.00	199.53
			16QAM	22.00	158.49
		1.4	QPSK	21.60	144.54
			16QAM	20.58	114.29

LTE Band 2

LTE Band 2 (Frequency range: 1850-1910 MHz) is covered by LTE Band 25 (Frequency range: 1850-1915 MHz) due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth.

LTE Band 26 (Part90)

Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Radiated	
				Avg [dBm]	Avg [mW]
Band 26	814 ~ 824	15	QPSK	18.22	66.37
			16QAM	17.10	51.29
		10	QPSK	18.75	74.99
			16QAM	17.94	62.23
		5	QPSK	18.20	66.07
			16QAM	17.11	51.40
		3	QPSK	18.07	64.12
			16QAM	16.94	49.43
		1.4	QPSK	18.43	69.66
			16QAM	16.97	49.77

* This band is only supported in the USA.

LTE Band 26 (Part22)

Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Radiated	
				Avg [dBm]	Avg [mW]
Band 26	824 ~ 849	15	QPSK	19.67	92.68
			16QAM	18.65	73.28
		10	QPSK	19.68	92.90
			16QAM	18.52	71.12
		5	QPSK	19.14	82.04
			16QAM	18.50	70.79
		3	QPSK	19.42	87.50
			16QAM	18.06	63.97
		1.4	QPSK	19.13	81.85
			16QAM	18.11	64.71

LTE Band 5

LTE Band 5 (Frequency range: 824-849 MHz) is covered by LTE Band 26 (Frequency range: 814-849 MHz) due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth.

Note: For 15MHz channel which would mean the channel straddles both Part 90 and Part 22H, the emission mask was only considered at the edge of low side. And power and spurious emissions meet both the requirements Part 90 and Part 22H.

LTE Band 30

FCC Part 27					
Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Radiated	
				Avg [dBm]	Avg [mW]
Band 30	2305~2315	10	QPSK	14.90	30.90
			16QAM	13.20	20.89
		5	QPSK	16.10	40.74
			16QAM	15.07	32.14

LTE Band 41

FCC Part 27					
Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Radiated	
				Avg [dBm]	Avg [mW]
Band 41	2496 - 2690	20	QPSK	24.40	275.42
			16QAM	24.68	293.76
		15	QPSK	25.03	318.42
			16QAM	24.69	294.44
		10	QPSK	24.28	267.92
			16QAM	24.08	255.86
		5	QPSK	24.57	286.42
			16QAM	24.31	269.77

LTE Band 66

FCC Part 27					
Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Radiated	
				Avg [dBm]	Avg [mW]
Band 66	1710 ~ 1780	20	QPSK	23.11	204.64
			16QAM	23.28	212.81
		15	QPSK	23.42	219.79
			16QAM	22.53	179.06
		10	QPSK	22.90	194.98
			16QAM	21.71	148.25
		5	QPSK	23.29	213.30
			16QAM	22.28	169.04
		3	QPSK	22.55	179.89
			16QAM	21.50	141.25
		1.4	QPSK	22.84	192.31
			16QAM	21.39	137.72

LTE Band 4

LTE Band 4 (Frequency range: 1710-1755 MHz) is covered by LTE Band 66 (Frequency range: 1710-1780 MHz) due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth.

LTE Band 71

FCC Part 27					
Band	Frequency Range [MHz]	BandWidth [MHz]	Modulation Peak	Radiated	
				Avg [dBm]	Avg [mW]
Band 71	663 ~ 698	20	QPSK	16.88	48.75
			16QAM	15.98	39.63
		15	QPSK	16.49	44.57
			16QAM	15.48	35.32
		10	QPSK	16.51	44.77
			16QAM	15.41	34.75
		5	QPSK	16.18	41.50
			16QAM	15.42	34.83

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a internal antenna for the [List the bands supported] with a maximum peak gain as follow:

Frequency (MHz)	Peak Gain (dBi)
WCDMA Band 2 / LTE Band 2 / LTE Band 25 1850 ~ 1915 MHz	0.4
WCDMA Band 5 / LTE Band 5 / LTE Band 26 814 ~ 849 MHz	0.2
LTE Band 4 / LTE Band 66 1710 ~ 1780 MHz	-0.1
LTE Band 7 2500 ~ 2570 MHz	0.4
LTE Band 12 / LTE Band 17 699~ 716 MHz	-3.8
LTE Band 13 777 ~ 787 MHz	-1.2
LTE Band 14 788 ~ 798 MHz	-1.2
LTE Band 30 2305 ~ 2315 MHz	-1.8
LTE Band 41 2496 ~ 2690 MHz	1.8
LTE Band 71 663 ~ 698 MHz	-3.5

5.4. WORST-CASE ORIENTATION

Following modes should be considered as worst-case scenario for all other measurements.

- UMTS REL 99/HSDPA

For all LTE Bands, the worst-case scenario for all measurements is based on the average conducted output power measurement investigation results. Output power measurements were measured on QPSK, 16QAM and 64QAM modulations. It was found that QPSK and 16QAM results were worst case. All testing was performed using QPSK and 16QAM modulations to represent the worst case. However, the out of band emissions and spurious radiation were only performed on bandwidth and RB offset(with RB size 1) with the highest power in QPSK.

Highest power setting for each bands				
LTE Band	Channel (MHz)	Bandwidth (MHz)	RB size	RB offset
7	2510	20	1	0
	2535		1	0
	2560		1	0
12	701.5	5	1	24
	707.5		1	24
	713.5		1	12
13	779.5	5	1	0
	782		1	12
	784.5		1	0
14	790.5	5	1	0
	793		1	24
	796.5		1	12
25	1860	5	1	0
	1882.5		1	0
	1905		1	0
26	821.5	15	1	37
	831.5		1	37
	841.5		1	0
30	2307.5	5	1	12
	2310		1	24
	2312.5		1	24
41	2506	20	1	0
	2593		1	0
	2680		1	0
66	1720	20	1	0
	1745		1	0
	1770		1	49
71	670.5	15	1	37
	680.5		1	74
	695.5		1	37

- ERP/EIRP

For WCDMA Band 4 / WCDMA Band 2 / LTE Band 7 / LTE Band 12 / LTE Band 13 / LTE Band 14 / LTE Band 30 / LTE Band 41 / LTE Band 66 / LTE Band 71, the fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation.

For WCDMA Band 5 / LTE Band 25 / LTE Band 26, the fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Z orientation was worst-case orientation.

- Radiated spurious emissions

For LTE Band 25, the spurious emissions was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation.

For LTE Band 7 / LTE Band 12 / LTE Band 13 / LTE Band 14, the spurious emissions was investigated in three orthogonal orientations X, Y and Z it was determined that Y orientation was worst-case orientation.

For WCDMA Band 5 / WCDMA Band 4 / WCDMA Band 2 / LTE Band 26 / LTE Band 30 / LTE Band 41 / LTE Band 66 / LTE Band 71, the spurious emissions was investigated in three orthogonal orientations X, Y and Z it was determined that Z orientation was worst-case orientation.

Note : All radiated spurious tests were performed connected with earphone and charger for evaluation of worst case mode.(For erp/eirp tests, the EUT didn't connected with earphone and charger)

Additionally, all radiated tests were investigated equipped with keyboard configuration also, it was reported only the worst case data. Whether the keyboard was attached to the EUT is indicated in each test datas.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA300	R37K3AD0AC3SE3	N/A
Data Cable	SAMSUNG	EP-DG915UWZ	N/A	N/A
Earphone	SAMSUNG	EP-DW720CWE	N/A	N/A
Keyboard	SAMSUNG	EJ-CW730	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type	Shielded	1.1m	N/A
2	Audio	2	Mini-Jack	Unshielded	1.2m	N/A


TEST SETUP

The EUT is continuously communicated to the call box during the tests.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List					
Description	Manufacturer	Model	S/N	Old Cal Due	New Cal Due
Antenna, Tuned Dipole 400-1000 MHz	ETS	3121D DB4	00164753	06-30-19	
Antenna, Horn, 40 GHz	ETS	3116C	00166155	12-04-19	
Preamplifier	ETS	3116C-PA	00168841	11-13-19	08-09-19
Antenna, Horn, 40 GHz	ETS	3116C	00168645	12-04-19	12-04-19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	08-31-19	08-04-20
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	08-31-19	08-04-20
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	09-14-19	08-04-20
Antenna, Horn, 18 GHz	ETS	3115	00167211	10-14-18	08-04-20
Antenna, Horn, 18 GHz	ETS	3115	00161451	03-10-19	08-04-20
Antenna, Horn, 18 GHz	ETS	3117	00168724	05-31-19	08-04-20
Antenna, Horn, 18 GHz	ETS	3117	00205959	11-29-18	08-04-20
Antenna, Horn, 18 GHz	ETS	3117	00168717	05-31-19	08-04-20
Combiner	WEINSCHTEL	1575	2152	08-08-18	08-08-19
Communications Test Set	R&S	CMW500	115331	08-07-18	08-07-19
DC Power Supply	Agilent / HP	E3640A	MY54226395	08-07-18	08-06-19
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-09-18	08-07-19
Preamplifier, 1000 MHz	Sonoma	310N	370599	08-10-18	08-06-19
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-07-18	08-07-19
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-08-18	08-07-19
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	08-11-18	08-07-19
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-08-18	08-07-19
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-08-18	08-06-19
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-08-18	08-06-19
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-08-18	08-06-19
EMI Test Receive, 44 GHz	R&S	ESW40	101590	08-09-18	08-06-19
High Pass Filter 1.2GHz	Micro-Tronics	HPM50108-02	G005	08-09-18	08-08-19
High Pass Filter 1.2GHz	Micro-Tronics	HPM50108-02	G006	08-08-18	08-08-19
High Pass Filter 2.8GHz	Micro-Tronics	HPM50111-02	010	08-09-18	08-08-19
High Pass Filter 2.8GHz	Micro-Tronics	HPM50111-02	011	08-08-18	08-08-19
High Pass Filter 4GHz	Micro-Tronics	HPM50118-02	G001	08-09-18	08-08-19
High Pass Filter 4GHz	Micro-Tronics	HPM50118-02	G002	08-08-18	08-08-19
Attenuator	PASTERNAK	PE7087-10	A009	08-08-18	08-08-19
Attenuator	PASTERNAK	PE7087-10	A001	08-08-18	08-08-19
Attenuator	PASTERNAK	PE7087-10	A008	08-08-18	08-08-19
Attenuator	PASTERNAK	PE7087-10	2	08-10-18	08-07-19
Attenuator	PASTERNAK	PE7395-10	A011	02-12-19	08-08-19
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	10-26-19	
Temperature Chamber	ESPEC	SH-642	93001109	08-08-18	08-06-19
UL Software					
Description	Manufacturer	Model	Version		
Antenna port test software	UL	CLT	Ver 2.4		

7. Summary Table

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
2.1049	Occupied Band width (99%)	N/A	Conducted	Pass
22.917(a) 24.238(a) 27.53(c),(g),(h) 90.543(c) 90.691	Band Edge / Conducted Spurious Emission	-13dBm		Pass
90.543(e)		-35dBm		Pass
27.53(a)	Conducted Spurious Emission	-40 dBm		Pass
27.53(m)		-25 dBm		Pass
27.53(a) 27.53(m) 90.691	Emission mask	Section 9.2.2		Pass
2.1046	Conducted output power	N/A		See the RF exposure test report. (4788556585-S1 FCC Report SAR)
22.355 24.235 27.54 90.213 90.539(e)	Frequency Stability	2.5PPM		Pass
22.913(a)(5)	Effective Radiated Power	38.5 dBm		Pass
27.50(c)(10) 27.50(b)(10) 90.542(a)(7)		34.77 dBm		Pass
90.635(b)		50 dBm	Pass	
24.232(c) 27.50(h)(2)	Equivalent Isotropic Radiated Power	33dBm	Pass	
27.50(a)		24dBm	Pass	
27.50(d)(4)		30dBm	Pass	
22.917(a) 24.238(a) 27.53(a),(c),(g),(h) 90.543(c) 90.691	Radiated Spurious Emission	-13dBm	Pass	
27.53(a) 27.53(f) 90.543(f)		-40dBm	Pass	
27.53 (m)		-25dBm	Pass	

8. PEAK TO AVERAGE RATIO

Test Procedure

Per KDB 971168 D01 Power Meas License Digital Systems v03r01;

The transmitter output was connected to a CMW500 Test Set and configured to operate at maximum power. The PAR were measured on the Spectrum Analyzer.


Test Spec

In addition, when the transmitter power is measured in terms of average value, the peak-to-average ratio of the power shall not exceed 13 dB.


RESULTS

8.1. CONDUCTED PEAK TO AVERAGE RESULT


WCDMA




LTE Band 7




LTE Band 12








LTE Band 13









LTE Band 14





LTE Band 25

<p>LTE Band 25 20 MHz</p>	 <p>LTE B25 20MHz QPSK Mid channel</p>	 <p>LTE B25 20MHz 16QAM Mid channel</p>
<p>LTE Band 25 15 MHz</p>	 <p>LTE B25 15MHz QPSK Mid channel</p>	 <p>LTE B25 15MHz 16QAM Mid channel</p>
<p>LTE Band 25 10 MHz</p>	 <p>LTE B25 10MHz QPSK Mid channel</p>	 <p>LTE B25 10MHz 16QAM Mid channel</p>


<p>LTE Band 25 5 MHz</p>	 <p>LTE B25 5MHz QPSK Mid channel</p>	 <p>LTE B25 5MHz 16QAM Mid channel</p>
<p>LTE Band 25 3 MHz</p>	 <p>LTE B25 3MHz QPSK Mid channel</p>	 <p>LTE B25 3MHz 16QAM Mid channel</p>
<p>LTE Band 25 1.4 MHz</p>	 <p>LTE B25 1.4MHz QPSK Mid channel</p>	 <p>LTE B25 1.4MHz 16QAM Mid channel</p>

LTE Band 26


<p>LTE Band 26 15 MHz</p>	 <p>LTE B26 15MHz QPSK Mid channel</p>	 <p>LTE B26 15MHz 16QAM Mid channel</p>
<p>LTE Band 26 10 MHz</p>	 <p>LTE B26 10MHz QPSK Mid channel</p>	 <p>LTE B26 10MHz 16QAM Mid channel</p>
<p>LTE Band 26 5 MHz</p>	 <p>LTE B26 5MHz QPSK Mid channel</p>	 <p>LTE B26 5MHz 16QAM Mid channel</p>









LTE Band 30









LTE Band 41




LTE Band 66

<p>LTE Band 66 20 MHz</p>	 <p>LTE B66 20MHz QPSK Mid channel</p>	 <p>LTE B66 20MHz 16QAM Mid channel</p>
<p>LTE Band 66 15 MHz</p>	 <p>LTE B66 15MHz QPSK Mid channel</p>	 <p>LTE B66 15MHz 16QAM Mid channel</p>
<p>LTE Band 66 10 MHz</p>	 <p>LTE B66 10MHz QPSK Mid channel</p>	 <p>LTE B66 10MHz 16QAM Mid channel</p>

<p>LTE Band 66 5 MHz</p>	 <p>LTE B66 5MHz QPSK Mid channel</p>	 <p>LTE B66 5MHz 16QAM Mid channel</p>
<p>LTE Band 66 3 MHz</p>	 <p>LTE B66 3MHz QPSK Mid channel</p>	 <p>LTE B66 3MHz 16QAM Mid channel</p>
<p>LTE Band 66 1.4 MHz</p>	 <p>LTE B66 1.4MHz QPSK Mid channel</p>	 <p>LTE B66 1.4MHz 16QAM Mid channel</p>

LTE Band 71



9. LIMITS AND CONDUCTED RESULTS

9.1. OCCUPIED BANDWIDTH

RULE PART(S)

FCC: §2.1049

LIMITS

For reporting purposes only

TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the low, middle and high channel in each band. The -26dB bandwidth was also measured and recorded.


(KDB 971168 D01 Power Meas License Digital Systems v03r01)

RESULTS

See the following pages.

9.1.1. OCCUPIED BANDWIDTH RESULTS


WCDMA Band 5



WCDMA Band 4



WCDMA Band 2



LTE Band 7

