

TEST REPORT

FCC LTE B25(2) Test for SM-X528U
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2502-FC007

DATE OF ISSUE
February 10, 2025

Tested by
Jae Mun Do



Technical Manager
Jong Seok Lee



HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2502-FC007

DATE OF ISSUE

February 10, 2025

Applicant**SAMSUNG Electronics Co., Ltd.**

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Product Name

Tablet

Model Name

SM-X528U

Date of Test

January 02, 2025 ~ February 07, 2025

FCC ID

A3LSMX528U

Location of Test

☒ Permanent Testing Lab ☐ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

FCC Classification:

PCS Licensed Transmitter (PCB)

Test Standard Used

FCC Rule Part: § 24

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	February 10, 2025	Initial Release

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C. 853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

CONTENTS

1. GENERAL INFORMATION	5
1.1. MAXIMUM OUTPUT POWER.....	6
2. INTRODUCTION	8
2.1. DESCRIPTION OF EUT	8
2.2. MEASURING INSTRUMENT CALIBRATION	8
2.3. TEST FACILITY	8
3. DESCRIPTION OF TESTS	9
3.1 TEST PROCEDURE.....	9
3.2 RADIATED POWER	10
3.3 RADIATED SPURIOUS EMISSIONS	11
3.4 PEAK- TO- AVERAGE RATIO.....	12
3.5 OCCUPIED BANDWIDTH.	14
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	15
3.7 BAND EDGE.....	16
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	18
3.9 WORST CASE(RADIATED TEST).....	19
3.10 WORST CASE(CONDUCTED TEST)	20
4. LIST OF TEST EQUIPMENT	21
5. MEASUREMENT UNCERTAINTY	22
6. SUMMARY OF TEST RESULTS	23
7. SAMPLE CALCULATION	24
8. TEST DATA(Main 1 ANT)	26
8.1 EQUIVALENT ISOTROPIC RADIATED POWER	26
8.2 RADIATED SPURIOUS EMISSIONS	29
8.3 PEAK-TO-AVERAGE RATIO	30
8.4 OCCUPIED BANDWIDTH	31
8.5 CONDUCTED SPURIOUS EMISSIONS.....	32
8.6 BAND EDGE.....	32
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	33
9. TEST DATA(Sub 1 ANT).....	51
9.1 EQUIVALENT ISOTROPIC RADIATED POWER	51
9.2 RADIATED SPURIOUS EMISSIONS	54
9.3 PEAK-TO-AVERAGE RATIO	55
9.4 OCCUPIED BANDWIDTH	56
9.5 CONDUCTED SPURIOUS EMISSIONS.....	57
9.6 BAND EDGE.....	57
9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	58
10. TEST PLOTS(Main 1 ANT)	76
11. TEST PLOTS(Sub 1 ANT).....	197
12. ANNEX A_ TEST SETUP PHOTO	318

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMX528U
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter (PCB)
FCC Rule Part(s):	§ 24
EUT Type:	Tablet
Model(s):	SM-X528U
Tx Frequency:	1850.7 MHz – 1914.3 MHz (LTE – Band25/2 (1.4 MHz)) 1851.5 MHz – 1913.5 MHz (LTE – Band25/2 (3 MHz)) 1852.5 MHz – 1912.5 MHz (LTE – Band25/2 (5 MHz)) 1855.0 MHz – 1910.0 MHz (LTE – Band25/2 (10 MHz)) 1857.5 MHz – 1907.5 MHz (LTE – Band25/2 (15 MHz)) 1860.0 MHz – 1905.0 MHz (LTE – Band25/2 (20 MHz))
Date(s) of Tests:	January 02, 2025 ~ February 07, 2025
Serial number:	Radiated : R32XC00A68K Conducted : R32XC00A9JV

1.1. MAXIMUM OUTPUT POWER

Main 1 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band25/2 (1.4)	1850.7 - 1914.3	1M10G7D	QPSK	0.336	25.26
		1M09W7D	16QAM	0.282	24.51
		1M09W7D	64QAM	0.218	23.38
		1M09W7D	256QAM	0.105	20.23
LTE – Band25/2 (3)	1851.5 - 1913.5	2M72G7D	QPSK	0.334	25.24
		2M70W7D	16QAM	0.283	24.52
		2M70W7D	64QAM	0.218	23.39
		2M71W7D	256QAM	0.106	20.25
LTE – Band25/2 (5)	1852.5 - 1912.5	4M52G7D	QPSK	0.336	25.26
		4M50W7D	16QAM	0.284	24.53
		4M52W7D	64QAM	0.219	23.41
		4M54W7D	256QAM	0.106	20.27
LTE – Band25/2 (10)	1855.0 - 1910.0	8M99G7D	QPSK	0.336	25.26
		9M00W7D	16QAM	0.280	24.47
		9M00W7D	64QAM	0.216	23.35
		9M01W7D	256QAM	0.108	20.32
LTE – Band25/2 (15)	1857.5 - 1907.5	13M4G7D	QPSK	0.337	25.28
		13M5W7D	16QAM	0.287	24.58
		13M5W7D	64QAM	0.221	23.44
		13M5W7D	256QAM	0.108	20.34
LTE – Band25/2 (20)	1860.0 - 1905.0	18M0G7D	QPSK	0.354	25.49
		17M9W7D	16QAM	0.294	24.69
		17M9W7D	64QAM	0.228	23.57
		17M9W7D	256QAM	0.112	20.51

Sub 1 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band25/2 (1.4)	1850.7 - 1914.3	1M10G7D	QPSK	0.097	19.88
		1M09W7D	16QAM	0.083	19.18
		1M09W7D	64QAM	0.064	18.07
		1M09W7D	256QAM	0.031	14.96
LTE – Band25/2 (3)	1851.5 - 1913.5	2M71G7D	QPSK	0.100	19.99
		2M70W7D	16QAM	0.084	19.25
		2M70W7D	64QAM	0.065	18.13
		2M71W7D	256QAM	0.031	14.98
LTE – Band25/2 (5)	1852.5 - 1912.5	4M52G7D	QPSK	0.096	19.84
		4M50W7D	16QAM	0.083	19.18
		4M52W7D	64QAM	0.064	18.06
		4M54W7D	256QAM	0.031	14.98
LTE – Band25/2 (10)	1855.0 - 1910.0	9M00G7D	QPSK	0.095	19.78
		8M99W7D	16QAM	0.079	18.99
		8M99W7D	64QAM	0.062	17.89
		9M01W7D	256QAM	0.030	14.83
LTE – Band25/2 (15)	1857.5 - 1907.5	13M5G7D	QPSK	0.095	19.80
		13M5W7D	16QAM	0.080	19.04
		13M5W7D	64QAM	0.062	17.92
		13M5W7D	256QAM	0.031	14.87
LTE – Band25/2 (20)	1860.0 - 1905.0	18M1G7D	QPSK	0.094	19.74
		17M9W7D	16QAM	0.079	18.99
		18M0W7D	64QAM	0.061	17.87
		17M9W7D	256QAM	0.030	14.79

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

Please refer to the [3G] Test Report.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Radiated Power	- ANSI C63.26-2015 – Section 5.2.4.4 - KDB 971168 D01 v03r01 – Section 5.8
Radiated Spurious and Harmonic Emissions	- ANSI C63.26-2015 – Section 5.5.3 - KDB 971168 D01 v03r01 – Section 5.8

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW $\geq$ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW $\geq$ 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $>$ 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser
if no specific emissions from the EUT are recorded (ie: margin $>$ 20 dB from the applicable limit)
and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets,
and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is
driven by a signal generator and the previously recorded signal was duplicated.
The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_{\text{g}}_{(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_{g} is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - .- for continuous transmissions, set to 1 ms,
 - .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R. (dB) = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW $\geq$ OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) $\times$ (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW $\geq$ OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is a constant 25 %.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.


The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW $\geq$ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = Peak
4. Trace Mode = max hold
5. Sweep time = auto
6. Number of points in sweep $\geq 2 \times \text{Span} / \text{RBW}$

3.7 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1 % of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes


According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

Where Margin < 1 dB the emission level is either corrected by $10 \log(1 \text{ MHz} / \text{RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- .- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter.
Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- In the case of radiated spurious emissions, all bandwidth of operation were investigated and the worst case bandwidth results are reported. (Worst case : 20 MHz(Main 1 ANT), 3 MHz(Sub 1 ANT))
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- LTE BAND 25 (1850 – 1915 MHz) overlaps the entire frequency range of LTE BAND 2 (1850 - 1910 MHz) and they have the same Tune-up power.
Therefore, test data provided in this report covers BAND 2 as well as BAND 25.
- All modes of operation were investigated and the worst case configuration results are reported.
Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)
Worst case : Stand alone
- All simultaneous transmission scenarios of operation were investigated, and the test results showed no additional significant emissions relative to the least restrictive limit were observed.
Therefore, only the worst case(stand-alone) results were reported.

[Main 1 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 8.1		Z
Radiated Spurious and Harmonic Emissions	QPSK	See Section 8.2		Z

[Sub 1 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 9.1		Z
Radiated Spurious and Harmonic Emissions	QPSK	See Section 9.2		Z

3.10 WORST CASE(CONDUCTED TEST)

- All modes of operation were investigated and the worst case configuration results are reported.
 - LTE BAND 25 (1850 – 1915 MHz) overlaps the entire frequency range of LTE BAND 2 (1850 - 1910 MHz) and they have the same Tune-up power.
- Therefore, test data provided in this report covers BAND 2 as well as BAND 25.

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Peak-To-Average Ratio	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Band Edge	QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
		1.4, 3, 5, 10, 15, 20	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	QPSK	1.4, 3, 5, 10, 15, 20	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacture	Serial No.	Due to Calibration	Calibration Interval
RF Switching System	Switch box(1.2 G HPF+LNA)	HCT CO., LTD.,	F1L1	11/11/2025	Annual
RF Switching System	Switch box(3.3 G HPF+LNA)	HCT CO., LTD.,	F1L2	11/11/2025	Annual
RF Switching System	Switch box(LNA)	HCT CO., LTD.,	F1L4	11/11/2025	Annual
RF Switching System	Switch box(6 G HPF+LNA)	HCT CO., LTD.,	F1L7	11/11/2025	Annual
Power Amplifier	CBL18265035	CERNEX	22966	11/07/2025	Annual
Power Amplifier	CBL26405040	CERNEX	25956	02/26/2025	Annual
Power Splitter(DC ~ 26.5 GHz)	11667B	Hewlett Packard	5001	04/17/2025	Annual
DC Power Supply	E3632A	Agilent	MY40010147	08/06/2025	Annual
Dipole Antenna	UHAP	Schwarzbeck	01274	03/10/2026	Biennial
Dipole Antenna	UHAP	Schwarzbeck	01288	08/07/2026	Biennial
Chamber	SU-642	ESPEC	93008124	02/19/2025	Annual
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	147	08/17/2025	Biennial
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1298	09/11/2025	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/20/2026	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/28/2025	Biennial
Signal Analyzer(10 Hz ~ 26.5 GHz)	N9020A	Agilent	MY52090906	04/19/2025	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/17/2025	Annual
Spectrum Analyzer(10 Hz ~ 40 GHz)	FSV40	REOHDE & SCHWARZ	100931	08/06/2025	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/05/2025	Annual
Loop Antenna(9 kHz ~ 30 MHz)	FMZB1513	Schwarzbeck	1513-333	03/07/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	895	08/28/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	1135	08/19/2026	Biennial
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262094331	11/13/2025	Annual
Radio Communication Test Station	MT8000A	Anritsu Corp.	6272613402	08/28/2025	Annual
SIGNAL GENERATOR (100 kHz ~ 40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	07/26/2025	Annual
Signal Analyzer(5 Hz ~ 40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/17/2025	Annual
Signal & Spectrum Analyzer (2 Hz~67 GHz)	FSW67	REOHDE & SCHWARZ	101736	05/23/2025	Annual
FCC LTE Mobile Conducted RF Automation Test Software	-	HCT CO., LTD.,	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ kHz)
Occupied Bandwidth	95 (Confidence level about 95 %, $k=2$)
Frequency stability	28 (Confidence level about 95 %, $k=2$)

Parameter	Expanded Uncertainty ($\pm$ dB)
Block Edge	0.70 (Confidence level about 95 %, $k=2$)
Conducted Spurious Emissions	1.18 (Confidence level about 95 %, $k=2$)
Peak- to- Average Ratio	0.68 (Confidence level about 95 %, $k=2$)
Radiated Power	4.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.70 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.52 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.66 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

6.1 Test Condition: Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 24.238(a)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§ 2.1046	N/A	<u>See Note1</u>
Peak- to- Average Ratio	§ 24.232(d)	< 13 dB	PASS
Frequency stability / variation of ambient temperature	§ 24.235	Emission must remain in band	PASS

Note:

1. See SAR Report

6.2 Test Condition: Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§ 24.232(c)	< 2 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 24.238(a)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW
GSM BW = 249 kHz
G = Phase Modulation
X = Cases not otherwise covered
W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W
GSM BW = 249 kHz
G = Phase Modulation
7 = Quantized/Digital Info
W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W
WCDMA BW = 4.17 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D
LTE BW = 4.48 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D
LTE BW = 4.48 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

8. TEST DATA(Main 1 ANT)

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1850.7	LTE B25/B2 (1.4 MHz)	QPSK	-17.59	16.93	10.40	2.07	V	<2.00	0.336	25.26	1	0
		16-QAM	-18.34	16.18	10.40	2.07	V		0.282	24.51		
		64-QAM	-19.47	15.05	10.40	2.07	V		0.218	23.38		
		256-QAM	-22.62	11.90	10.40	2.07	V		0.105	20.23		
1882.5		QPSK	-18.29	16.69	10.40	2.21	V		0.308	24.88	1	0
		16-QAM	-18.99	15.99	10.40	2.21	V		0.262	24.18		
		64-QAM	-20.14	14.84	10.40	2.21	V		0.201	23.03		
		256-QAM	-23.27	11.71	10.40	2.21	V		0.098	19.90		
1914.3		QPSK	-19.24	15.77	10.40	2.17	V		0.251	24.00	1	0
		16-QAM	-20.00	15.01	10.40	2.17	V		0.211	23.24		
		64-QAM	-21.19	13.82	10.40	2.17	V		0.160	22.05		
		256-QAM	-24.23	10.78	10.40	2.17	V		0.080	19.01		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1851.5	LTE B25/B2 (3 MHz)	QPSK	-17.61	16.91	10.40	2.07	V	<2.00	0.334	25.24	1	0
		16-QAM	-18.33	16.19	10.40	2.07	V		0.283	24.52		
		64-QAM	-19.46	15.06	10.40	2.07	V		0.218	23.39		
		256-QAM	-22.60	11.92	10.40	2.07	V		0.106	20.25		
1882.5		QPSK	-18.21	16.77	10.40	2.21	V		0.313	24.96	1	0
		16-QAM	-18.86	16.12	10.40	2.21	V		0.270	24.31		
		64-QAM	-19.99	14.99	10.40	2.21	V		0.208	23.18		
		256-QAM	-23.13	11.85	10.40	2.21	V		0.101	20.04		
1913.5		QPSK	-19.04	15.97	10.40	2.17	V		0.263	24.20	1	0
		16-QAM	-19.82	15.19	10.40	2.17	V		0.220	23.42		
		64-QAM	-20.95	14.06	10.40	2.17	V		0.169	22.29		
		256-QAM	-24.07	10.94	10.40	2.17	V		0.083	19.17		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1852.5	LTE B25/B2 (5 MHz)	QPSK	-17.63	16.94	10.40	2.08	V	<2.00	0.336	25.26	1	0
		16-QAM	-18.36	16.21	10.40	2.08	V		0.284	24.53		
		64-QAM	-19.48	15.09	10.40	2.08	V		0.219	23.41		
		256-QAM	-22.62	11.95	10.40	2.08	V		0.106	20.27		
1882.5		QPSK	-17.98	17.00	10.40	2.21	V		0.330	25.19	1	0
		16-QAM	-18.74	16.24	10.40	2.21	V		0.277	24.43		
		64-QAM	-19.86	15.12	10.40	2.21	V		0.214	23.31		
		256-QAM	-22.98	12.00	10.40	2.21	V		0.104	20.19		
1912.5		QPSK	-18.99	16.02	10.40	2.17	V		0.266	24.25	1	0
		16-QAM	-19.69	15.32	10.40	2.17	V		0.226	23.55		
		64-QAM	-20.82	14.19	10.40	2.17	V		0.175	22.42		
		256-QAM	-23.96	11.05	10.40	2.17	V		0.085	19.28		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1855	LTE B25/B2 (10 MHz)	QPSK	-17.63	16.94	10.40	2.08	V	< 2.00	0.336	25.26	1	0
		16-QAM	-18.42	16.15	10.40	2.08	V		0.280	24.47		
		64-QAM	-19.54	15.03	10.40	2.08	V		0.216	23.35		
		256-QAM	-22.57	12.00	10.40	2.08	V		0.108	20.32		
1882.5		QPSK	-18.08	16.90	10.40	2.21	V		0.323	25.09	1	0
		16-QAM	-18.87	16.11	10.40	2.21	V		0.269	24.30		
		64-QAM	-19.98	15.00	10.40	2.21	V		0.208	23.19		
		256-QAM	-23.01	11.97	10.40	2.21	V		0.104	20.16		
1910		QPSK	-18.95	15.99	10.40	2.17	V		0.264	24.22	1	0
		16-QAM	-19.76	15.18	10.40	2.17	V		0.219	23.41		
		64-QAM	-20.87	14.07	10.40	2.17	V		0.170	22.30		
		256-QAM	-23.89	11.05	10.40	2.17	V		0.085	19.28		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1857.5	LTE B25/B2 (15 MHz)	QPSK	-17.66	16.98	10.40	2.10	V	<2.00	0.337	25.28	1	0
		16-QAM	-18.36	16.28	10.40	2.10	V		0.287	24.58		
		64-QAM	-19.50	15.14	10.40	2.10	V		0.221	23.44		
		256-QAM	-22.60	12.04	10.40	2.10	V		0.108	20.34		
1882.5		QPSK	-17.98	17.00	10.40	2.21	V		0.330	25.19	1	0
		16-QAM	-18.72	16.26	10.40	2.21	V		0.279	24.45		
		64-QAM	-19.84	15.14	10.40	2.21	V		0.215	23.33		
		256-QAM	-22.94	12.04	10.40	2.21	V		0.105	20.23		
1907.5		QPSK	-18.85	16.09	10.40	2.17	V		0.270	24.32	1	0
		16-QAM	-19.62	15.32	10.40	2.17	V		0.226	23.55		
		64-QAM	-20.74	14.20	10.40	2.17	V		0.175	22.43		
		256-QAM	-23.84	11.10	10.40	2.17	V		0.086	19.33		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1860	LTE B25/B2 (20 MHz)	QPSK	-17.56	17.08	10.40	2.10	V	<2.00	0.345	25.38	1	0
		16-QAM	-18.35	16.29	10.40	2.10	V		0.288	24.59		
		64-QAM	-19.47	15.17	10.40	2.10	V		0.222	23.47		
		256-QAM	-22.54	12.10	10.40	2.10	V		0.110	20.40		
1882.5		QPSK	-17.68	17.30	10.40	2.21	V		0.354	25.49	1	0
		16-QAM	-18.48	16.50	10.40	2.21	V		0.294	24.69		
		64-QAM	-19.60	15.38	10.40	2.21	V		0.228	23.57		
		256-QAM	-22.66	12.32	10.40	2.21	V		0.112	20.51		
1905		QPSK	-18.84	16.08	10.40	2.19	V		0.269	24.29	1	0
		16-QAM	-19.63	15.29	10.40	2.19	V		0.224	23.50		
		64-QAM	-20.76	14.16	10.40	2.19	V		0.173	22.37		
		256-QAM	-23.82	11.10	10.40	2.19	V		0.085	19.31		

8.2 RADIATED SPURIOUS EMISSIONS

▣ OPERATING FREQUENCY:	<u>1882.5 MHz</u>
▣ MEASURED OUTPUT POWER:	<u>25.49 dBm = 0.354 W</u>
▣ MOD:	<u>LTE B25/B2</u>
▣ MODULATION SIGNAL:	<u>20 MHz QPSK</u>
▣ DISTANCE:	<u>3 meters</u>
▣ LIMIT:	<u>-13 dBm</u>

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	RB	
								Size	Offset
26140 (1860.0)	3720.00	-45.05	12.28	-62.06	3.13	V	-52.91	1	0
	5580.00	-45.87	13.07	-58.15	3.91	V	-48.99		
	7440.00	-44.39	10.78	-46.80	4.58	V	-40.60		
26365 (1882.5)	3765.00	-45.44	12.22	-61.28	3.11	V	-52.17	1	0
	5647.50	-44.22	13.12	-56.39	3.96	V	-47.23		
	7530.00	-45.20	10.85	-47.84	4.60	V	-41.59		
26590 (1905.0)	3810.00	-43.51	12.15	-59.75	3.20	V	-50.80	1	0
	5715.00	-43.92	13.08	-56.35	4.01	V	-47.28		
	7620.00	-45.40	11.14	-48.19	4.65	V	-41.70		

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
25/2	1.4 MHz	1882.5	QPSK	6	0	5.50
			16-QAM			6.11
			64-QAM			6.50
			256-QAM			6.35
	3 MHz		QPSK	15		5.58
			16-QAM			6.15
			64-QAM			6.27
			256-QAM			6.42
	5 MHz		QPSK	25		5.54
			16-QAM			6.24
			64-QAM			6.32
			256-QAM			6.43
	10 MHz		QPSK	50		5.69
			16-QAM			6.18
			64-QAM			6.34
			256-QAM			6.44
	15 MHz		QPSK	75		5.51
			16-QAM			6.15
			64-QAM			6.32
			256-QAM			6.42
	20 MHz		QPSK	100		5.49
			16-QAM			6.20
			64-QAM			6.37
			256-QAM			6.47

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 77 ~ 100.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
25/2	1.4 MHz	1882.5	QPSK	6	0	1.0963
			16-QAM			1.0929
			64-QAM			1.0940
			256-QAM			1.0939
	3 MHz		QPSK	15		2.7147
			16-QAM			2.7022
			64-QAM			2.7007
			256-QAM			2.7071
	5 MHz		QPSK	25		4.5208
			16-QAM			4.5017
			64-QAM			4.5192
			256-QAM			4.5428
	10 MHz		QPSK	50		8.9910
			16-QAM			9.0017
			64-QAM			9.0007
			256-QAM			9.0074
	15 MHz		QPSK	75		13.434
			16-QAM			13.488
			64-QAM			13.461
			256-QAM			13.465
	20 MHz		QPSK	100		18.033
			16-QAM			17.935
			64-QAM			17.927
			256-QAM			17.932

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 101 ~ 124.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
25/2	1.4	1850.70	9.6710	28.5910	-68.125	-39.534	-13.00
		1882.50	4.5664	27.9760	-68.046	-40.070	
		1914.30	9.0927	28.5910	-65.561	-36.970	
	3	1851.50	9.0329	28.5910	-67.838	-39.247	
		1882.50	7.9661	28.5910	-67.034	-38.443	
		1913.50	4.0479	27.9760	-67.522	-39.546	
	5	1852.50	9.7009	28.5910	-66.828	-38.237	
		1882.50	9.1924	28.5910	-67.279	-38.688	
		1912.50	7.2084	28.5910	-68.254	-39.663	
	10	1855.00	9.1526	28.5910	-67.131	-38.540	
		1882.50	7.7069	28.5910	-67.806	-39.215	
		1910.00	9.9601	28.5910	-67.076	-38.485	
	15	1857.50	9.6411	28.5910	-66.735	-38.144	
		1882.50	8.7338	28.5910	-67.395	-38.804	
		1907.50	8.3250	28.5910	-66.976	-38.385	
	20	1860.00	9.7109	28.5910	-67.331	-38.740	
		1882.50	6.0419	28.5910	-67.218	-38.627	
		1905.00	8.3250	28.5910	-67.378	-38.787	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 125 ~ 160.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Ext. Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131


8.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 161 ~ 196.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


MODE:	<u>LTE B25/B2</u>
OPERATING FREQUENCY:	<u>1850,700,000 Hz</u>
CHANNEL:	<u>26047 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.860 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.860	+20(Ref)	1850 700 004	0.0	0.000 000	0.000
100 %		-30	1850 700 001	-3.1	0.000 000	-0.002
100 %		-20	1850 700 011	6.7	0.000 000	0.004
100 %		-10	1850 700 008	3.7	0.000 000	0.002
100 %		0	1850 700 008	4.2	0.000 000	0.002
100 %		+10	1850 699 999	-4.6	0.000 000	-0.002
100 %		+30	1850 700 009	5.0	0.000 000	0.003
100 %		+40	1850 700 008	4.1	0.000 000	0.002
100 %		+50	1850 700 007	2.6	0.000 000	0.001
Batt. Endpoint	3.400	+20	1850 700 000	-3.5	0.000 000	-0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1851,500,000 Hz
- ▣ CHANNEL: 26055 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1851 500 004	0.0	0.000 000	0.000
100 %		-30	1851 500 009	4.2	0.000 000	0.002
100 %		-20	1851 500 009	4.3	0.000 000	0.002
100 %		-10	1851 499 999	-5.4	0.000 000	-0.003
100 %		0	1851 500 010	5.1	0.000 000	0.003
100 %		+10	1851 500 011	6.7	0.000 000	0.004
100 %		+30	1851 500 009	4.9	0.000 000	0.003
100 %		+40	1851 500 000	-4.3	0.000 000	-0.002
100 %		+50	1851 500 008	3.8	0.000 000	0.002
Batt. Endpoint	3.400	+20	1851 500 009	4.6	0.000 000	0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1852,500,000 Hz
- ▣ CHANNEL: 26065 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1852 500 005	0.0	0.000 000	0.000
100 %		-30	1852 500 011	6.4	0.000 000	0.003
100 %		-20	1852 500 000	-5.1	0.000 000	-0.003
100 %		-10	1852 500 008	3.3	0.000 000	0.002
100 %		0	1852 500 008	2.9	0.000 000	0.002
100 %		+10	1852 500 008	2.8	0.000 000	0.002
100 %		+30	1852 500 010	5.2	0.000 000	0.003
100 %		+40	1852 500 010	5.2	0.000 000	0.003
100 %		+50	1852 500 007	1.9	0.000 000	0.001
Batt. Endpoint	3.400	+20	1852 500 010	5.1	0.000 000	0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1855,000,000 Hz
- ▣ CHANNEL: 26090 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1855 000 006	0.0	0.000 000	0.000
100 %		-30	1855 000 011	5.3	0.000 000	0.003
100 %		-20	1855 000 001	-5.0	0.000 000	-0.003
100 %		-10	1855 000 011	5.5	0.000 000	0.003
100 %		0	1855 000 011	4.8	0.000 000	0.003
100 %		+10	1855 000 003	-3.2	0.000 000	-0.002
100 %		+30	1855 000 010	4.5	0.000 000	0.002
100 %		+40	1855 000 001	-4.5	0.000 000	-0.002
100 %		+50	1855 000 011	5.7	0.000 000	0.003
Batt. Endpoint	3.400	+20	1855 000 001	-4.4	0.000 000	-0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1857,500,000 Hz
- ▣ CHANNEL: 26115 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1857 500 003	0.0	0.000 000	0.000
100 %		-30	1857 499 999	-4.1	0.000 000	-0.002
100 %		-20	1857 499 999	-3.7	0.000 000	-0.002
100 %		-10	1857 500 007	3.9	0.000 000	0.002
100 %		0	1857 500 008	4.8	0.000 000	0.003
100 %		+10	1857 500 008	5.0	0.000 000	0.003
100 %		+30	1857 500 007	3.6	0.000 000	0.002
100 %		+40	1857 500 006	3.2	0.000 000	0.002
100 %		+50	1857 499 999	-4.1	0.000 000	-0.002
Batt. Endpoint	3.400	+20	1857 499 999	-4.5	0.000 000	-0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1860,000,000 Hz
- ▣ CHANNEL: 26140 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1860 000 004	0.0	0.000 000	0.000
100 %		-30	1859 999 999	-4.8	0.000 000	-0.003
100 %		-20	1859 999 999	-4.6	0.000 000	-0.002
100 %		-10	1860 000 000	-4.2	0.000 000	-0.002
100 %		0	1859 999 999	-4.5	0.000 000	-0.002
100 %		+10	1859 999 999	-4.6	0.000 000	-0.002
100 %		+30	1860 000 009	5.0	0.000 000	0.003
100 %		+40	1860 000 009	4.8	0.000 000	0.003
100 %		+50	1860 000 007	2.9	0.000 000	0.002
Batt. Endpoint	3.400	+20	1860 000 010	6.2	0.000 000	0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1882 500 005	0.0	0.000 000	0.000
100 %		-30	1882 500 000	-4.4	0.000 000	-0.002
100 %		-20	1882 500 008	3.4	0.000 000	0.002
100 %		-10	1882 500 008	2.7	0.000 000	0.001
100 %		0	1882 500 002	-3.2	0.000 000	-0.002
100 %		+10	1882 500 007	2.5	0.000 000	0.001
100 %		+30	1882 500 008	2.7	0.000 000	0.001
100 %		+40	1882 500 008	3.6	0.000 000	0.002
100 %		+50	1882 500 009	4.0	0.000 000	0.002
Batt. Endpoint	3.400	+20	1882 500 002	-3.0	0.000 000	-0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1882 500 004	0.0	0.000 000	0.000
100 %		-30	1882 500 007	3.2	0.000 000	0.002
100 %		-20	1882 500 001	-2.8	0.000 000	-0.001
100 %		-10	1882 500 009	5.5	0.000 000	0.003
100 %		0	1882 500 000	-3.9	0.000 000	-0.002
100 %		+10	1882 500 009	4.9	0.000 000	0.003
100 %		+30	1882 500 008	4.7	0.000 000	0.002
100 %		+40	1882 500 008	3.9	0.000 000	0.002
100 %		+50	1882 500 010	6.4	0.000 000	0.003
Batt. Endpoint	3.400	+20	1882 500 008	4.2	0.000 000	0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1882 500 005	0.0	0.000 000	0.000
100 %		-30	1882 500 010	4.8	0.000 000	0.003
100 %		-20	1882 500 002	-2.7	0.000 000	-0.001
100 %		-10	1882 500 010	4.8	0.000 000	0.003
100 %		0	1882 500 001	-3.8	0.000 000	-0.002
100 %		+10	1882 500 002	-3.0	0.000 000	-0.002
100 %		+30	1882 500 008	2.8	0.000 000	0.001
100 %		+40	1882 500 003	-2.0	0.000 000	-0.001
100 %		+50	1882 500 001	-4.1	0.000 000	-0.002
Batt. Endpoint	3.400	+20	1882 500 008	3.1	0.000 000	0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1882 500 003	0.0	0.000 000	0.000
100 %		-30	1882 500 008	5.1	0.000 000	0.003
100 %		-20	1882 500 007	3.9	0.000 000	0.002
100 %		-10	1882 500 008	4.7	0.000 000	0.002
100 %		0	1882 499 998	-5.7	0.000 000	-0.003
100 %		+10	1882 500 008	4.4	0.000 000	0.002
100 %		+30	1882 500 008	4.4	0.000 000	0.002
100 %		+40	1882 500 008	4.3	0.000 000	0.002
100 %		+50	1882 500 007	3.7	0.000 000	0.002
Batt. Endpoint	3.400	+20	1882 499 999	-4.4	0.000 000	-0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1882 500 003	0.0	0.000 000	0.000
100 %		-30	1882 500 008	4.9	0.000 000	0.003
100 %		-20	1882 499 998	-4.9	0.000 000	-0.003
100 %		-10	1882 500 000	-3.0	0.000 000	-0.002
100 %		0	1882 500 007	4.4	0.000 000	0.002
100 %		+10	1882 499 999	-3.6	0.000 000	-0.002
100 %		+30	1882 500 010	6.7	0.000 000	0.004
100 %		+40	1882 500 006	3.3	0.000 000	0.002
100 %		+50	1882 500 007	3.9	0.000 000	0.002
Batt. Endpoint	3.400	+20	1882 499 998	-5.0	0.000 000	-0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1882 499 996	0.0	0.000 000	0.000
100 %		-30	1882 499 999	3.3	0.000 000	0.002
100 %		-20	1882 499 992	-3.7	0.000 000	-0.002
100 %		-10	1882 500 001	4.9	0.000 000	0.003
100 %		0	1882 499 992	-3.5	0.000 000	-0.002
100 %		+10	1882 499 992	-3.9	0.000 000	-0.002
100 %		+30	1882 499 992	-3.9	0.000 000	-0.002
100 %		+40	1882 499 989	-6.5	0.000 000	-0.003
100 %		+50	1882 499 992	-3.9	0.000 000	-0.002
Batt. Endpoint	3.400	+20	1882 500 000	4.5	0.000 000	0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1914,300,000 Hz
- ▣ CHANNEL: 26683 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1914 299 997	0.0	0.000 000	0.000
100 %		-30	1914 300 004	7.2	0.000 000	0.004
100 %		-20	1914 300 003	6.1	0.000 000	0.003
100 %		-10	1914 299 994	-2.4	0.000 000	-0.001
100 %		0	1914 299 998	1.6	0.000 000	0.001
100 %		+10	1914 299 994	-2.9	0.000 000	-0.002
100 %		+30	1914 299 991	-5.5	0.000 000	-0.003
100 %		+40	1914 299 993	-3.4	0.000 000	-0.002
100 %		+50	1914 299 993	-3.5	0.000 000	-0.002
Batt. Endpoint	3.400	+20	1914 300 001	4.2	0.000 000	0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1913,500,000 Hz
- ▣ CHANNEL: 26675 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1913 500 009	0.0	0.000 000	0.000
100 %		-30	1913 500 018	8.4	0.000 000	0.004
100 %		-20	1913 500 004	-5.2	0.000 000	-0.003
100 %		-10	1913 500 001	-8.5	0.000 000	-0.004
100 %		0	1913 500 019	9.4	0.000 000	0.005
100 %		+10	1913 500 020	10.5	0.000 001	0.005
100 %		+30	1913 500 005	-4.1	0.000 000	-0.002
100 %		+40	1913 500 002	-7.2	0.000 000	-0.004
100 %		+50	1913 500 005	-4.3	0.000 000	-0.002
Batt. Endpoint	3.400	+20	1913 500 018	8.4	0.000 000	0.004




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1912,500,000 Hz
- ▣ CHANNEL: 26665 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1912 500 005	0.0	0.000 000	0.000
100 %		-30	1912 500 009	4.0	0.000 000	0.002
100 %		-20	1912 500 013	8.2	0.000 000	0.004
100 %		-10	1912 500 001	-3.8	0.000 000	-0.002
100 %		0	1912 500 010	5.0	0.000 000	0.003
100 %		+10	1912 500 008	3.7	0.000 000	0.002
100 %		+30	1912 500 009	4.6	0.000 000	0.002
100 %		+40	1912 500 002	-2.6	0.000 000	-0.001
100 %		+50	1912 500 010	5.1	0.000 000	0.003
Batt. Endpoint	3.400	+20	1912 499 999	-5.2	0.000 000	-0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1910,000,000 Hz
- ▣ CHANNEL: 26640 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1910 000 004	0.0	0.000 000	0.000
100 %		-30	1909 999 999	-5.1	0.000 000	-0.003
100 %		-20	1910 000 000	-4.2	0.000 000	-0.002
100 %		-10	1910 000 007	3.0	0.000 000	0.002
100 %		0	1910 000 008	3.9	0.000 000	0.002
100 %		+10	1910 000 001	-3.0	0.000 000	-0.002
100 %		+30	1910 000 009	4.8	0.000 000	0.003
100 %		+40	1910 000 009	5.3	0.000 000	0.003
100 %		+50	1910 000 007	3.3	0.000 000	0.002
Batt. Endpoint	3.400	+20	1910 000 001	-3.6	0.000 000	-0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1907,500,000 Hz
- ▣ CHANNEL: 26615 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1907 500 004	0.0	0.000 000	0.000
100 %		-30	1907 500 006	2.6	0.000 000	0.001
100 %		-20	1907 500 000	-3.6	0.000 000	-0.002
100 %		-10	1907 500 008	3.9	0.000 000	0.002
100 %		0	1907 500 008	4.3	0.000 000	0.002
100 %		+10	1907 500 008	3.9	0.000 000	0.002
100 %		+30	1907 499 999	-5.1	0.000 000	-0.003
100 %		+40	1907 500 001	-2.6	0.000 000	-0.001
100 %		+50	1907 500 000	-3.7	0.000 000	-0.002
Batt. Endpoint	3.400	+20	1907 500 000	-4.0	0.000 000	-0.002



- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1905,000,000 Hz
- ▣ CHANNEL: 26590 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.860	+20(Ref)	1905 000 003	0.0	0.000 000	0.000
100 %		-30	1905 000 007	3.6	0.000 000	0.002
100 %		-20	1904 999 999	-4.5	0.000 000	-0.002
100 %		-10	1905 000 008	4.4	0.000 000	0.002
100 %		0	1905 000 000	-3.5	0.000 000	-0.002
100 %		+10	1905 000 008	4.6	0.000 000	0.002
100 %		+30	1905 000 006	3.1	0.000 000	0.002
100 %		+40	1904 999 996	-7.6	0.000 000	-0.004
100 %		+50	1904 999 999	-4.6	0.000 000	-0.002
Batt. Endpoint	3.400	+20	1904 999 998	-5.7	0.000 000	-0.003



9. TEST DATA(Sub 1 ANT)

9.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1850.7	LTE B25/B2 (1.4 MHz)	QPSK	-25.26	9.26	10.40	2.07	H	<2.00	0.057	17.59	1	5
		16-QAM	-25.98	8.54	10.40	2.07	H		0.049	16.87		
		64-QAM	-27.10	7.42	10.40	2.07	H		0.038	15.75		
		256-QAM	-30.18	4.34	10.40	2.07	H		0.018	12.67		
1882.5		QPSK	-24.63	10.35	10.40	2.21	H		0.071	18.54	1	5
		16-QAM	-25.35	9.63	10.40	2.21	H		0.061	17.82		
		64-QAM	-26.46	8.52	10.40	2.21	H		0.047	16.71		
		256-QAM	-29.56	5.42	10.40	2.21	H		0.023	13.61		
1914.3		QPSK	-23.36	11.65	10.40	2.17	H		0.097	19.88	1	5
		16-QAM	-24.06	10.95	10.40	2.17	H		0.083	19.18		
		64-QAM	-25.17	9.84	10.40	2.17	H		0.064	18.07		
		256-QAM	-28.28	6.73	10.40	2.17	H		0.031	14.96		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1851.5	LTE B25/B2 (3 MHz)	QPSK	-25.22	9.30	10.40	2.07	H	<2.00	0.058	17.63	1	14
		16-QAM	-25.91	8.61	10.40	2.07	H		0.049	16.94		
		64-QAM	-27.03	7.49	10.40	2.07	H		0.038	15.82		
		256-QAM	-30.17	4.35	10.40	2.07	H		0.019	12.68		
1882.5		QPSK	-24.63	10.35	10.40	2.21	H		0.071	18.54	1	14
		16-QAM	-25.29	9.69	10.40	2.21	H		0.061	17.88		
		64-QAM	-26.41	8.57	10.40	2.21	H		0.047	16.76		
		256-QAM	-29.56	5.42	10.40	2.21	H		0.023	13.61		
1913.5		QPSK	-23.25	11.76	10.40	2.17	H		0.100	19.99	1	14
		16-QAM	-23.99	11.02	10.40	2.17	H		0.084	19.25		
		64-QAM	-25.11	9.90	10.40	2.17	H		0.065	18.13		
		256-QAM	-28.26	6.75	10.40	2.17	H		0.031	14.98		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1852.5	LTE B25/B2 (5 MHz)	QPSK	-25.14	9.43	10.40	2.08	H	<2.00	0.060	17.75	1	24
		16-QAM	-25.89	8.68	10.40	2.08	H		0.050	17.00		
		64-QAM	-27.00	7.57	10.40	2.08	H		0.039	15.89		
		256-QAM	-30.08	4.49	10.40	2.08	H		0.019	12.81		
1882.5		QPSK	-24.52	10.46	10.40	2.21	H		0.073	18.65	1	24
		16-QAM	-25.24	9.74	10.40	2.21	H		0.062	17.93		
		64-QAM	-26.35	8.63	10.40	2.21	H		0.048	16.82		
		256-QAM	-29.42	5.56	10.40	2.21	H		0.024	13.75		
1912.5		QPSK	-23.40	11.61	10.40	2.17	H		0.096	19.84	1	24
		16-QAM	-24.06	10.95	10.40	2.17	H		0.083	19.18		
		64-QAM	-25.18	9.83	10.40	2.17	H		0.064	18.06		
		256-QAM	-28.26	6.75	10.40	2.17	H		0.031	14.98		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1855	LTE B25/B2 (10 MHz)	QPSK	-25.17	9.40	10.40	2.08	H	<2.00	0.059	17.72	1	49
		16-QAM	-25.94	8.63	10.40	2.08	H		0.050	16.95		
		64-QAM	-27.05	7.52	10.40	2.08	H		0.038	15.84		
		256-QAM	-30.12	4.45	10.40	2.08	H		0.019	12.77		
1882.5		QPSK	-24.26	10.72	10.40	2.21	H		0.078	18.91	1	49
		16-QAM	-25.05	9.93	10.40	2.21	H		0.065	18.12		
		64-QAM	-26.14	8.84	10.40	2.21	H		0.050	17.03		
		256-QAM	-29.21	5.77	10.40	2.21	H		0.025	13.96		
1910		QPSK	-23.39	11.55	10.40	2.17	H		0.095	19.78	1	49
		16-QAM	-24.18	10.76	10.40	2.17	H		0.079	18.99		
		64-QAM	-25.28	9.66	10.40	2.17	H		0.062	17.89		
		256-QAM	-28.34	6.60	10.40	2.17	H		0.030	14.83		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1857.5	LTE B25/B2 (15 MHz)	QPSK	-24.89	9.75	10.40	2.10	H	<2.00	0.064	18.05	1	74
		16-QAM	-25.66	8.98	10.40	2.10	H		0.053	17.28		
		64-QAM	-26.77	7.87	10.40	2.10	H		0.041	16.17		
		256-QAM	-29.82	4.82	10.40	2.10	H		0.021	13.12		
1882.5		QPSK	-24.46	10.52	10.40	2.21	H		0.074	18.71	1	74
		16-QAM	-25.23	9.75	10.40	2.21	H		0.062	17.94		
		64-QAM	-26.36	8.62	10.40	2.21	H		0.048	16.81		
		256-QAM	-29.41	5.57	10.40	2.21	H		0.024	13.76		
1907.5		QPSK	-23.37	11.57	10.40	2.17	H		0.095	19.80	1	74
		16-QAM	-24.13	10.81	10.40	2.17	H		0.080	19.04		
		64-QAM	-25.25	9.69	10.40	2.17	H		0.062	17.92		
		256-QAM	-28.30	6.64	10.40	2.17	H		0.031	14.87		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1860	LTE B25/B2 (20 MHz)	QPSK	-24.72	9.92	10.40	2.10	H	<2.00	0.066	18.22	1	99
		16-QAM	-25.46	9.18	10.40	2.10	H		0.056	17.48		
		64-QAM	-26.59	8.05	10.40	2.10	H		0.043	16.35		
		256-QAM	-29.68	4.96	10.40	2.10	H		0.021	13.26		
1882.5		QPSK	-24.19	10.79	10.40	2.21	H		0.079	18.98	1	99
		16-QAM	-24.94	10.04	10.40	2.21	H		0.067	18.23		
		64-QAM	-26.06	8.92	10.40	2.21	H		0.051	17.11		
		256-QAM	-29.15	5.83	10.40	2.21	H		0.025	14.02		
1905		QPSK	-23.39	11.53	10.40	2.19	H		0.094	19.74	1	99
		16-QAM	-24.14	10.78	10.40	2.19	H		0.079	18.99		
		64-QAM	-25.26	9.66	10.40	2.19	H		0.061	17.87		
		256-QAM	-28.34	6.58	10.40	2.19	H		0.030	14.79		

9.2 RADIATED SPURIOUS EMISSIONS

▣ OPERATING FREQUENCY:	<u>1913.5 MHz</u>
▣ MEASURED OUTPUT POWER:	<u>19.99 dBm = 0.100 W</u>
▣ MOD:	<u>LTE B25/B2</u>
▣ MODULATION SIGNAL:	<u>20 MHz QPSK</u>
▣ DISTANCE:	<u>3 meters</u>
▣ LIMIT:	<u>-13 dBm</u>

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	RB	
								Size	Offset
26055 (1851.5)	3703.00	-43.97	12.28	-61.10	3.08	V	-51.90	1	14
	5554.50	-44.14	13.03	-56.24	3.88	V	-47.09		
	7406.00	-44.25	10.79	-47.10	4.57	V	-40.88		
26365 (1882.5)	3765.00	-45.31	12.22	-61.15	3.11	V	-52.04	1	14
	5647.50	-44.64	13.12	-56.81	3.96	V	-47.65		
	7530.00	-44.82	10.85	-47.46	4.60	V	-41.21		
26675 (1913.5)	3827.00	-43.51	12.16	-60.18	3.18	V	-51.20	1	14
	5740.50	-45.28	13.01	-57.26	3.99	V	-48.24		
	7654.00	-44.47	11.25	-47.60	4.69	V	-41.04		

9.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
25/2	1.4 MHz	1882.5	QPSK	6	0	5.71
			16-QAM			6.38
			64-QAM			6.46
			256-QAM			6.37
	3 MHz		QPSK	15		5.79
			16-QAM			6.25
			64-QAM			6.48
			256-QAM			6.47
	5 MHz		QPSK	25		5.63
			16-QAM			6.31
			64-QAM			6.39
			256-QAM			6.45
	10 MHz		QPSK	50		5.73
			16-QAM			6.33
			64-QAM			6.48
			256-QAM			6.43
	15 MHz		QPSK	75		5.65
			16-QAM			6.27
			64-QAM			6.37
			256-QAM			6.41
	20 MHz		QPSK	100		5.62
			16-QAM			6.28
			64-QAM			6.45
			256-QAM			6.50

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 198 ~ 221.

9.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
25/2	1.4 MHz	1882.5	QPSK	6	0	1.0956
			16-QAM			1.0925
			64-QAM			1.0938
			256-QAM			1.0929
	3 MHz		QPSK	15		2.7134
			16-QAM			2.7013
			64-QAM			2.7017
			256-QAM			2.7093
	5 MHz		QPSK	25		4.5224
			16-QAM			4.5026
			64-QAM			4.5201
			256-QAM			4.5419
	10 MHz		QPSK	50		8.9992
			16-QAM			8.9901
			64-QAM			8.9917
			256-QAM			9.0133
	15 MHz		QPSK	75		13.458
			16-QAM			13.473
			64-QAM			13.489
			256-QAM			13.454
	20 MHz		QPSK	100		18.055
			16-QAM			17.907
			64-QAM			17.950
			256-QAM			17.926

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 222 ~ 245.

9.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
25/2	1.4	1850.70	8.0060	28.5910	-67.740	-39.149	-13.00
		1882.50	9.6511	28.5910	-67.144	-38.553	
		1914.30	8.9133	28.5910	-67.330	-38.739	
	3	1851.50	8.8834	28.5910	-66.534	-37.943	
		1882.50	9.7208	28.5910	-67.423	-38.832	
		1913.50	9.7109	28.5910	-67.471	-38.880	
	5	1852.50	7.9761	28.5910	-68.237	-39.646	
		1882.50	4.0280	27.9760	-65.707	-37.731	
		1912.50	6.0020	28.5910	-68.030	-39.439	
	10	1855.00	4.8854	27.9760	-66.262	-38.286	
		1882.50	4.0679	27.9760	-67.046	-39.070	
		1910.00	4.8854	27.9760	-68.226	-40.250	
	15	1857.50	9.6411	28.5910	-68.439	-39.848	
		1882.50	9.9601	28.5910	-66.748	-38.157	
		1907.50	7.2084	28.5910	-67.525	-38.934	
	20	1860.00	6.0220	28.5910	-68.246	-39.655	
		1882.50	4.3570	27.9760	-68.579	-40.603	
		1905.00	9.0828	28.5910	-67.597	-39.006	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 246 ~ 281.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Ext. Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131


9.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 282 ~ 317.

9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


MODE:	<u>LTE B25/B2</u>
OPERATING FREQUENCY:	<u>1850,700,000 Hz</u>
CHANNEL:	<u>26047 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.860 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.840	+20(Ref)	1850 700 005	0.0	0.000 000	0.000
100 %		-30	1850 700 002	-3.4	0.000 000	-0.002
100 %		-20	1850 700 012	6.7	0.000 000	0.004
100 %		-10	1850 700 001	-3.8	0.000 000	-0.002
100 %		0	1850 700 002	-3.1	0.000 000	-0.002
100 %		+10	1850 699 998	-7.0	0.000 000	-0.004
100 %		+30	1850 700 001	-4.4	0.000 000	-0.002
100 %		+40	1850 700 011	6.1	0.000 000	0.003
100 %		+50	1850 700 012	6.6	0.000 000	0.004
Batt. Endpoint	3.400	+20	1850 700 008	3.5	0.000 000	0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1851,500,000 Hz
- ▣ CHANNEL: 26055 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1851 500 004	0.0	0.000 000	0.000
100 %		-30	1851 500 008	3.6	0.000 000	0.002
100 %		-20	1851 499 999	-4.8	0.000 000	-0.003
100 %		-10	1851 500 009	4.7	0.000 000	0.003
100 %		0	1851 500 009	4.7	0.000 000	0.003
100 %		+10	1851 500 007	3.3	0.000 000	0.002
100 %		+30	1851 499 998	-5.7	0.000 000	-0.003
100 %		+40	1851 499 998	-5.6	0.000 000	-0.003
100 %		+50	1851 500 007	3.2	0.000 000	0.002
Batt. Endpoint	3.400	+20	1851 499 999	-5.2	0.000 000	-0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1852,500,000 Hz
- ▣ CHANNEL: 26065 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1852 499 996	0.0	0.000 000	0.000
100 %		-30	1852 499 991	-5.1	0.000 000	-0.003
100 %		-20	1852 499 993	-2.9	0.000 000	-0.002
100 %		-10	1852 500 000	3.8	0.000 000	0.002
100 %		0	1852 499 993	-3.0	0.000 000	-0.002
100 %		+10	1852 499 993	-2.5	0.000 000	-0.001
100 %		+30	1852 500 000	4.4	0.000 000	0.002
100 %		+40	1852 500 000	3.8	0.000 000	0.002
100 %		+50	1852 499 992	-3.5	0.000 000	-0.002
Batt. Endpoint	3.400	+20	1852 499 992	-4.1	0.000 000	-0.002




MODE:	<u>LTE B25/B2</u>
OPERATING FREQUENCY:	<u>1855,000,000 Hz</u>
CHANNEL:	<u>26090 (10 MHz)</u>
REFERENCE VOLTAGE:	<u>3.860 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1855 000 004	0.0	0.000 000	0.000
100 %		-30	1854 999 999	-5.1	0.000 000	-0.003
100 %		-20	1855 000 009	5.3	0.000 000	0.003
100 %		-10	1855 000 010	6.1	0.000 000	0.003
100 %		0	1855 000 008	3.8	0.000 000	0.002
100 %		+10	1855 000 009	5.4	0.000 000	0.003
100 %		+30	1855 000 000	-4.5	0.000 000	-0.002
100 %		+40	1855 000 009	5.4	0.000 000	0.003
100 %		+50	1855 000 008	4.0	0.000 000	0.002
Batt. Endpoint	3.400	+20	1855 000 009	5.1	0.000 000	0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1857,500,000 Hz
- ▣ CHANNEL: 26115 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1857 500 004	0.0	0.000 000	0.000
100 %		-30	1857 500 008	4.3	0.000 000	0.002
100 %		-20	1857 500 007	3.5	0.000 000	0.002
100 %		-10	1857 500 008	4.6	0.000 000	0.002
100 %		0	1857 500 008	4.4	0.000 000	0.002
100 %		+10	1857 500 009	4.9	0.000 000	0.003
100 %		+30	1857 500 000	-3.5	0.000 000	-0.002
100 %		+40	1857 500 008	4.6	0.000 000	0.002
100 %		+50	1857 500 007	2.8	0.000 000	0.002
Batt. Endpoint	3.400	+20	1857 500 007	3.2	0.000 000	0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1860,000,000 Hz
- ▣ CHANNEL: 26140 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1859 999 995	0.0	0.000 000	0.000
100 %		-30	1859 999 999	4.0	0.000 000	0.002
100 %		-20	1860 000 000	4.8	0.000 000	0.003
100 %		-10	1860 000 002	7.1	0.000 000	0.004
100 %		0	1859 999 991	-3.9	0.000 000	-0.002
100 %		+10	1859 999 991	-3.9	0.000 000	-0.002
100 %		+30	1860 000 000	5.3	0.000 000	0.003
100 %		+40	1860 000 000	4.5	0.000 000	0.002
100 %		+50	1859 999 998	2.7	0.000 000	0.001
Batt. Endpoint	3.400	+20	1859 999 991	-3.7	0.000 000	-0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1882 500 004	0.0	0.000 000	0.000
100 %		-30	1882 499 999	-4.9	0.000 000	-0.003
100 %		-20	1882 500 007	3.1	0.000 000	0.002
100 %		-10	1882 499 999	-4.9	0.000 000	-0.003
100 %		0	1882 499 999	-4.5	0.000 000	-0.002
100 %		+10	1882 500 000	-3.2	0.000 000	-0.002
100 %		+30	1882 500 000	-3.9	0.000 000	-0.002
100 %		+40	1882 500 007	3.3	0.000 000	0.002
100 %		+50	1882 500 000	-3.6	0.000 000	-0.002
Batt. Endpoint	3.400	+20	1882 500 008	4.2	0.000 000	0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1882 499 994	0.0	0.000 000	0.000
100 %		-30	1882 499 991	-2.9	0.000 000	-0.002
100 %		-20	1882 499 998	3.7	0.000 000	0.002
100 %		-10	1882 499 990	-4.4	0.000 000	-0.002
100 %		0	1882 499 989	-5.0	0.000 000	-0.003
100 %		+10	1882 499 999	5.3	0.000 000	0.003
100 %		+30	1882 500 000	5.9	0.000 000	0.003
100 %		+40	1882 500 000	6.1	0.000 000	0.003
100 %		+50	1882 500 000	5.9	0.000 000	0.003
Batt. Endpoint	3.400	+20	1882 499 990	-4.2	0.000 000	-0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1882 499 997	0.0	0.000 000	0.000
100 %		-30	1882 499 993	-3.5	0.000 000	-0.002
100 %		-20	1882 500 002	4.7	0.000 000	0.002
100 %		-10	1882 500 001	4.3	0.000 000	0.002
100 %		0	1882 500 000	2.6	0.000 000	0.001
100 %		+10	1882 500 000	3.1	0.000 000	0.002
100 %		+30	1882 499 995	-2.1	0.000 000	-0.001
100 %		+40	1882 499 993	-3.8	0.000 000	-0.002
100 %		+50	1882 499 993	-3.7	0.000 000	-0.002
Batt. Endpoint	3.400	+20	1882 500 000	3.1	0.000 000	0.002




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1882 500 006	0.0	0.000 000	0.000
100 %		-30	1882 500 014	7.3	0.000 000	0.004
100 %		-20	1882 500 011	4.9	0.000 000	0.003
100 %		-10	1882 500 002	-4.0	0.000 000	-0.002
100 %		0	1882 500 009	2.6	0.000 000	0.001
100 %		+10	1882 500 001	-5.0	0.000 000	-0.003
100 %		+30	1882 500 011	4.3	0.000 000	0.002
100 %		+40	1882 500 011	5.2	0.000 000	0.003
100 %		+50	1882 500 003	-3.6	0.000 000	-0.002
Batt. Endpoint	3.400	+20	1882 500 011	4.8	0.000 000	0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1882 500 005	0.0	0.000 000	0.000
100 %		-30	1882 500 001	-4.1	0.000 000	-0.002
100 %		-20	1882 500 008	2.7	0.000 000	0.001
100 %		-10	1882 500 002	-3.4	0.000 000	-0.002
100 %		0	1882 500 008	3.1	0.000 000	0.002
100 %		+10	1882 500 009	3.6	0.000 000	0.002
100 %		+30	1882 500 001	-4.6	0.000 000	-0.002
100 %		+40	1882 500 008	2.6	0.000 000	0.001
100 %		+50	1882 500 010	5.2	0.000 000	0.003
Batt. Endpoint	3.400	+20	1882 500 011	5.4	0.000 000	0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1882 499 996	0.0	0.000 000	0.000
100 %		-30	1882 499 992	-4.1	0.000 000	-0.002
100 %		-20	1882 500 002	6.4	0.000 000	0.003
100 %		-10	1882 500 001	5.7	0.000 000	0.003
100 %		0	1882 500 000	4.5	0.000 000	0.002
100 %		+10	1882 500 001	5.6	0.000 000	0.003
100 %		+30	1882 500 002	6.3	0.000 000	0.003
100 %		+40	1882 499 992	-4.0	0.000 000	-0.002
100 %		+50	1882 500 001	4.8	0.000 000	0.003
Batt. Endpoint	3.400	+20	1882 500 002	6.5	0.000 000	0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1914,300,000 Hz
- ▣ CHANNEL: 26683 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1914 300 005	0.0	0.000 000	0.000
100 %		-30	1914 300 009	4.4	0.000 000	0.002
100 %		-20	1914 300 009	4.8	0.000 000	0.003
100 %		-10	1914 299 999	-5.3	0.000 000	-0.003
100 %		0	1914 300 009	4.1	0.000 000	0.002
100 %		+10	1914 300 010	5.2	0.000 000	0.003
100 %		+30	1914 300 009	4.6	0.000 000	0.002
100 %		+40	1914 300 009	4.5	0.000 000	0.002
100 %		+50	1914 300 009	4.7	0.000 000	0.002
Batt. Endpoint	3.400	+20	1914 300 010	5.6	0.000 000	0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1913,500,000 Hz
- ▣ CHANNEL: 26675 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1913 500 008	0.0	0.000 000	0.000
100 %		-30	1913 500 016	7.7	0.000 000	0.004
100 %		-20	1913 500 014	5.6	0.000 000	0.003
100 %		-10	1913 500 019	10.6	0.000 001	0.006
100 %		0	1913 500 015	6.7	0.000 000	0.004
100 %		+10	1913 500 015	6.9	0.000 000	0.004
100 %		+30	1913 500 015	6.5	0.000 000	0.003
100 %		+40	1913 500 016	8.0	0.000 000	0.004
100 %		+50	1913 500 014	5.5	0.000 000	0.003
Batt. Endpoint	3.400	+20	1913 500 002	-5.8	0.000 000	-0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1912,500,000 Hz
- ▣ CHANNEL: 26665 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1912 500 005	0.0	0.000 000	0.000
100 %		-30	1912 500 009	3.9	0.000 000	0.002
100 %		-20	1912 500 011	5.1	0.000 000	0.003
100 %		-10	1912 500 010	4.8	0.000 000	0.003
100 %		0	1912 500 001	-4.8	0.000 000	-0.003
100 %		+10	1912 500 002	-3.7	0.000 000	-0.002
100 %		+30	1912 500 001	-4.0	0.000 000	-0.002
100 %		+40	1912 499 999	-6.0	0.000 000	-0.003
100 %		+50	1912 500 011	5.2	0.000 000	0.003
Batt. Endpoint	3.400	+20	1912 500 010	4.3	0.000 000	0.002




MODE:	<u>LTE B25/B2</u>
OPERATING FREQUENCY:	<u>1910,000,000 Hz</u>
CHANNEL:	<u>26640 (10 MHz)</u>
REFERENCE VOLTAGE:	<u>3.860 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1910 000 005	0.0	0.000 000	0.000
100 %		-30	1910 000 000	-5.7	0.000 000	-0.003
100 %		-20	1910 000 002	-3.5	0.000 000	-0.002
100 %		-10	1910 000 000	-5.0	0.000 000	-0.003
100 %		0	1910 000 002	-3.3	0.000 000	-0.002
100 %		+10	1910 000 010	4.6	0.000 000	0.002
100 %		+30	1910 000 011	5.3	0.000 000	0.003
100 %		+40	1910 000 001	-4.3	0.000 000	-0.002
100 %		+50	1910 000 011	5.2	0.000 000	0.003
Batt. Endpoint	3.400	+20	1910 000 010	5.1	0.000 000	0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1907,500,000 Hz
- ▣ CHANNEL: 26615 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1907 500 005	0.0	0.000 000	0.000
100 %		-30	1907 500 001	-3.4	0.000 000	-0.002
100 %		-20	1907 500 010	5.2	0.000 000	0.003
100 %		-10	1907 500 008	3.3	0.000 000	0.002
100 %		0	1907 500 000	-4.4	0.000 000	-0.002
100 %		+10	1907 500 010	5.7	0.000 000	0.003
100 %		+30	1907 500 010	5.1	0.000 000	0.003
100 %		+40	1907 499 997	-8.0	0.000 000	-0.004
100 %		+50	1907 500 012	7.1	0.000 000	0.004
Batt. Endpoint	3.400	+20	1907 500 011	6.1	0.000 000	0.003




- ▣ MODE: LTE B25/B2
- ▣ OPERATING FREQUENCY: 1905,000,000 Hz
- ▣ CHANNEL: 26590 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.860 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	Error (Hz)	(%)	
100 %	3.840	+20(Ref)	1905 000 004	0.0	0.000 000	0.000
100 %		-30	1905 000 008	4.7	0.000 000	0.002
100 %		-20	1905 000 000	-4.2	0.000 000	-0.002
100 %		-10	1905 000 008	4.6	0.000 000	0.002
100 %		0	1905 000 007	3.4	0.000 000	0.002
100 %		+10	1905 000 008	4.3	0.000 000	0.002
100 %		+30	1905 000 007	3.3	0.000 000	0.002
100 %		+40	1905 000 008	4.0	0.000 000	0.002
100 %		+50	1904 999 999	-5.0	0.000 000	-0.003
Batt. Endpoint	3.400	+20	1905 000 000	-3.8	0.000 000	-0.002



10. TEST PLOTS(Main 1 ANT)

LTE B25_1.4M_PAR_Mid_QPSK_FullRB



LTE B25_1.4M_PAR_Mid_16QAM_FullRB




LTE B25_1.4M_PAR_Mid_64QAM_FullRB



LTE B25_1.4M_PAR_Mid_256QAM_FullRB



LTE B25_3 M_PAR_Mid_QPSK_FullRB



LTE B25_3 M_PAR_Mid_16QAM_FullRB




LTE B25_3 M_PAR_Mid_64QAM_FullRB



LTE B25_3 M_PAR_Mid_256QAM_FullRB



LTE B25_5 M_PAR_Mid_QPSK_FullRB



LTE B25_5 M_PAR_Mid_16QAM_FullRB




LTE B25_5 M_PAR_Mid_64QAM_FullRB




LTE B25_5 M_PAR_Mid_256QAM_FullRB



LTE B25_10 M_PAR_Mid_QPSK_FullRB



LTE B25_10 M_PAR_Mid_16QAM_FullRB




LTE B25_10 M_PAR_Mid_64QAM_FullRB




LTE B25_10 M_PAR_Mid_256QAM_FullRB



LTE B25_15 M_PAR_Mid_QPSK_FullRB



LTE B25_15 M_PAR_Mid_16QAM_FullRB




LTE B25_15 M_PAR_Mid_64QAM_FullRB



LTE B25_15 M_PAR_Mid_256QAM_FullRB



LTE B25_20 M_PAR_Mid_QPSK_FullRB



LTE B25_20 M_PAR_Mid_16QAM_FullRB




LTE B25_20 M_PAR_Mid_64QAM_FullRB



LTE B25_20 M_PAR_Mid_256QAM_FullRB



LTE B25_1.4M_OBW_Mid_QPSK_FullRB




LTE B25_1.4M_OBW_Mid_16QAM_FullIRB




LTE B25_1.4M_OBW_Mid_64QAM_FullRB




LTE B25_1.4M_OBW_Mid_256QAM_FullRB




LTE B25_3 M_OBW_Mid_QPSK_FullRB




LTE B25_3 M_OBW_Mid_16QAM_FullRB




LTE B25_3 M_OBW_Mid_64QAM_FullRB




LTE B25_3 M_OBW_Mid_256QAM_FullRB




LTE B25_5 M_OBW_Mid_QPSK_FullRB




LTE B25_5 M_OBW_Mid_16QAM_FullRB




LTE B25_5 M_OBW_Mid_64QAM_FullRB




LTE B25_5 M_OBW_Mid_256QAM_FullRB



LTE B25_10 M_OBW_Mid_QPSK_FullRB



LTE B25_10 M_OBW_Mid_16QAM_FullRB



LTE B25_10 M_OBW_Mid_64QAM_FullRB



LTE B25_10 M_OBW_Mid_256QAM_FullRB



LTE B25_15 M_OBW_Mid_QPSK_FullRB




LTE B25_15 M_OBW_Mid_16QAM_FullRB




LTE B25_15 M_OBW_Mid_64QAM_FullRB



LTE B25_15 M_OBW_Mid_256QAM_FullRB



LTE B25_20 M_OBW_Mid_QPSK_FullRB



LTE B25_20 M_OBW_Mid_16QAM_FullRB




LTE B25_20 M_OBW_Mid_64QAM_FullRB




LTE B25_20 M_OBW_Mid_256QAM_FullRB




LTE B25_1.4M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B25_1.4M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB




LTE B25_1.4M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB




LTE B25_3 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B25_3 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB




LTE B25_3 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB




LTE B25_5 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B25_5 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB



LTE B25_5 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB



LTE B25_10 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB



LTE B25_10 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB

