

MEASUREMENT REPORT FCC Part 22, 24 & 27 LTE

Applicant Name:
 Samsung Electronics, Co. Ltd.
 129, Samsung-ro, Maetan dong,
 Yeongtong-gu, Suwon-si
 Gyeonggi-do 443-742, Korea

Date of Testing:
 09/04 - 09/16/2013
Test Site/Location:
 PCTEST Lab., Columbia, MD, USA
Test Report Serial No.:
 0Y1309031731.A3L

FCC ID :	A3LSPHL720T
APPLICANT:	SAMSUNG ELECTRONICS, CO. LTD.


FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): §2; §22; §24; §27
EUT Type: Portable Handset
Model(s): SPH-L720T
Test Device Serial No.: *identical prototype* [S/N: EMC Rad. (All Bands)]

Mode	Tx Frequency (MHz)	Emission Designator	Modulation	ERP/EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE Band 26	824.7 - 848.3	1M13G7D	QPSK	0.133	21.24
LTE Band 26	824.7 - 848.3	1M13W7D	16QAM	0.102	20.08
LTE Band 26	825.5 - 847.5	2M73G7D	QPSK	0.144	21.59
LTE Band 26	825.5 - 847.5	2M72W7D	16QAM	0.110	20.43
LTE Band 26	826.5 - 846.5	4M51G7D	QPSK	0.147	21.67
LTE Band 26	826.5 - 846.5	4M53W7D	16QAM	0.114	20.57
LTE Band 26	829 - 844	9M02G7D	QPSK	0.192	22.82
LTE Band 26	829 - 844	9M02W7D	16QAM	0.149	21.72
LTE Band 25	1851.5 - 1913.5	2M72G7D	QPSK	0.120	20.78
LTE Band 25	1851.5 - 1913.5	2M72W7D	16QAM	0.085	19.29
LTE Band 25	1852.5 - 1912.5	4M51G7D	QPSK	0.144	21.58
LTE Band 25	1852.5 - 1912.5	4M51W7D	16QAM	0.107	20.29
LTE Band 25	1855 - 1910	8M99G7D	QPSK	0.150	21.75
LTE Band 25	1855 - 1910	9M01W7D	16QAM	0.117	20.68
LTE Band 41	2501 - 2685	8M99G7D	QPSK	0.119	20.76
LTE Band 41	2501 - 2685	8M96W7D	16QAM	0.090	19.53
LTE Band 41	2503.5 - 2682.5	13M4G7D	QPSK	0.111	20.46
LTE Band 41	2503.5 - 2682.5	13M5W7D	16QAM	0.097	19.88
LTE Band 41	2506 - 2680	17M9G7D	QPSK	0.126	21.00
LTE Band 41	2506 - 2680	17M9W7D	16QAM	0.095	19.76

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested. I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


 Randy Ortañez
 President




FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 1 of 79	

T A B L E O F C O N T E N T S


FCC PART 22, 24 & 27 MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 SCOPE	4
1.2 TESTING FACILITY	4
2.0 PRODUCT INFORMATION.....	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 DEVICE CAPABILITIES.....	5
2.3 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
2.4 LABELING REQUIREMENTS.....	5
3.0 DESCRIPTION OF TESTS	6
3.1 MEASUREMENT PROCEDURE	6
3.2 CELLULAR - BASE FREQUENCY BLOCKS.....	6
3.3 CELLULAR - MOBILE FREQUENCY BLOCKS.....	6
3.4 PCS - BASE FREQUENCY BLOCKS.....	6
3.5 PCS - MOBILE FREQUENCY BLOCKS.....	7
3.6 OCCUPIED BANDWIDTH	7
3.7 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	7
3.8 PEAK-AVERAGE RATIO.....	7
3.9 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	8
3.10 FREQUENCY STABILITY / TEMPERATURE VARIATION	9
4.0 TEST EQUIPMENT CALIBRATION DATA	10
5.0 SAMPLE CALCULATIONS	11
6.0 TEST RESULTS.....	12
6.1 SUMMARY.....	12
6.2 EFFECTIVE RADIATED POWER (ERP).....	13
6.3 EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)	14
6.4 BAND 26 RADIATED SPURIOUS EMISSIONS	16
6.5 BAND 25 RADIATED SPURIOUS EMISSIONS	20
6.6 BAND 41 RADIATED SPURIOUS EMISSIONS	24
6.7 BAND 26 FREQUENCY STABILITY MEASUREMENTS.....	28
6.8 BAND 25 FREQUENCY STABILITY MEASUREMENTS.....	30
6.9 BAND 41 FREQUENCY STABILITY MEASUREMENTS.....	32
7.0 BAND 26 PLOTS OF EMISSIONS.....	34
8.0 BAND 25 PLOTS OF EMISSIONS.....	46
9.0 BAND 41 PLOTS OF EMISSIONS.....	62
10.0 CONCLUSION.....	79

FCC ID: A3LSPHL720T	 <small>ENGINEERING LABORATORY, INC.</small>	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 2 of 79	



MEASUREMENT REPORT

FCC Part 22, 24 & 27





§2.1033 General Information


APPLICANT: Samsung Electronics, Co. Ltd.
APPLICANT ADDRESS: 129, Samsung-ro, Maetan dong,
 Yeongtong-gu, Suwon-si, Gyeonggi-do 443-742, Korea
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21045 USA
FCC RULE PART(S): §2; §22; §24; §27
BASE MODEL: SPH-L720T
FCC ID: A3LSPHL720T
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
FREQUENCY TOLERANCE: ±0.00025 % (2.5 ppm)
Test Device Serial No.: EMC Rad. (All Bands) Production Pre-Production Engineering
DATE(S) OF TEST: 09/04 - 09/16/2013
TEST REPORT S/N: 0Y1309031731.A3L

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 3 of 79	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on February 15, 2012.






Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 4 of 79	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSPHL720T**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev 0/A, 1x Advanced (BC0, BC1, BC10), 850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Band 25 (3/5/10 MHz BW), 26 (1.4/3/5/10 MHz BW), 41 (10/15/20 MHz BW) LTE, 802.11a/b/g/n/ac WLAN (DTS/NII), Bluetooth (1x,EDR, LE), NFC, ANT+, Wireless Charging Capabilities (WCC)

Additional spurious emission testing was performed per KDB 648474 D03 v01r02 and the additional worst case emissions are reported herein and identified as WCC. The handset was placed on the verified charging pad under normal conditions and in a simulated call configuration. Only worst case emissions are shown in this report.



2.3 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

2.4 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 5 of 79	


3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-C-2004) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168) were used in the measurement of the **Samsung Portable Handset FCC ID: A3LSPHL720T**.

3.2 Cellular - Base Frequency Blocks

§24.905



BLOCK 1: 869 – 880 MHz (A* Low + A)


BLOCK 2: 880 – 890 MHz (B)

BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks

§24.905



BLOCK 1: 824 – 835 MHz (A* Low + A)


BLOCK 2: 835 – 845 MHz (B)

BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 4: 846.5 – 849 MHz (B*)

3.4 PCS - Base Frequency Blocks

§24.229



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 4: 1965 – 1970 MHz (E)


BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 6: 1975 – 1990 MHz (C)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 6 of 79

3.5 PCS - Mobile Frequency Blocks

§24.229



3.6 Occupied Bandwidth

§2.1049 RSS-Gen(4.6.1)

The implementation of this test is performed by the spectrum analyzer’s occupied bandwidth function. The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

3.7 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a)(b) §24.238(a)(b) §27.53(m) RSS-132(4.5.1)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Cell band, or 1 MHz or greater for PCS band, BRS and EBS stations. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed for PCS band, BRS and EBS stations. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

3.8 Peak-Average Ratio

§24.232(d) RSS-132(5.4)

A peak to average ratio measurement is performed at the conducted port of the EUT. For LTE signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 7 of 79	

3.9 Radiated Power and Radiated Spurious Emissions

§2.1053 §22.913(a.2) §22.917(a) §27.53(h) RSS-132(4.4) RSS-132(4.5.1)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.


The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168.

Per the guidance of ANSI/TIA-603-C-2004, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power}_{\text{[Watts]}})$ specified in 22.917(a) and 24.238(a).

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 8 of 79	

3.10 Frequency Stability / Temperature Variation

§2.1055 §22.863 §22.905 §27.5(i) §27.54 RSS-132(4.3)



The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block for Part 24 and 27. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency for Part 22.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A sufficient stabilization period at each temperature shall be used prior to each frequency requirement.



FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 9 of 79	

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx1	Licensed Transmitter Cable Set	1/17/2013	Annual	1/17/2014	N/A
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	3/29/2013	Annual	3/29/2014	N/A
Agilent	8447D	Broadband Amplifier	5/31/2013	Annual	5/31/2014	2443A01900
Agilent	N9020A	MXA Signal Analyzer	10/9/2012	Annual	10/9/2013	US46470561
Espec	ESX-2CA	Environmental Chamber	4/16/2013	Annual	4/16/2014	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	7/24/2013	Biennial	7/24/2015	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	5/30/2012	Biennial	5/30/2014	135427
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	11/7/2012	Biennial	11/7/2014	128338
Mini-Circuits	VHF-1300+	High Pass Filter	1/21/2013	Annual	1/21/2014	30716
Mini-Circuits	VHF-3100+	High Pass Filter	1/17/2013	Annual	1/17/2014	30841
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	10/7/2011	Biennial	10/7/2013	103962
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	5/31/2013	Annual	5/31/2014	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	5/31/2013	Annual	5/31/2014	100040
Rohde & Schwarz	ESU26	EMI Test Receiver	2/25/2013	Annual	2/25/2014	100342
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	10/3/2011	Biennial	10/3/2013	91052523RX
Seekonk	NC-100	Torque Wrench (8" lb)	3/5/2012	Triennial	3/5/2015	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/26/2012	Biennial	1/26/2014	A051107

Table 4-1. Test Equipment

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 10 of 79	

5.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz
 G = Phase Modulation
 7 = Quantized/Digital Info
 D = Amplitude/Angle Modulated

16QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz
 W = Amplitude/Angle Modulated
 7 = Quantized/Digital Info
 D = Combination (Audio/Data)

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80).

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 11 of 79	

6.0 TEST RESULTS

6.1 Summary


Company Name: Samsung Electronics, Co. Ltd.
 FCC ID: A3LSPHL720T
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Result	Reference
TRANSMITTER MODE (TX)					
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section, 7.0, 8.0, 9.0
2.1051 22.917(a) 24.238(a) 27.53(m)	Band Edge / Conducted Spurious Emissions	$> 43 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions		PASS	Section, 7.0, 8.0, 9.0
24.232(d)	Peak-Average Ratio	< 13 dB		PASS	Section, 8.0
2.1046	Transmitter Conducted Output Power	N/A		PASS	See RF Exposure Report
22.913(a.2)	Effective Radiated Power (Band 5)	< 7 Watts max. ERP	RADIATED	PASS	Section 6.2
24.232(c) 27.50(h.2)	Equivalent Isotropic Radiated Power (Band 25 EBS)	< 2 Watts max. EIRP		PASS	Section 6.3
2.1053 22.917(a) 24.238(a) 27.53(m)	Undesirable Emissions	$> 43 + 10\log_{10}(P[\text{Watts}])$ for all out-of-band emissions		PASS	Section, 6.4, 6.5, 6.6
2.1055. 22.35527.5(i) 27.54	Frequency Stability	< 2.5 ppm (Part 22) and fundamental emissions stay within authorized frequency block (Part 24, 27)		PASS	Section, 6.7, 6.8, 6.9

Table 6-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 8.0 9.0 were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 12 of 79	

6.2 Effective Radiated Power (ERP)

§22.913(a.2) RSS-132(4.4)

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Antenna Gain [dBd]	Pol [H/V]	ERP [dBm]	ERP [Watts]	Margin [dB]
824.70	1.4	QPSK	Standard	1/0	14.41	6.83	V	21.24	0.133	-17.21
836.50	1.4	QPSK	Standard	1/5	14.08	6.97	V	21.05	0.127	-17.40
848.30	1.4	QPSK	Standard	1/0	13.84	7.11	V	20.95	0.124	-17.50
824.70	1.4	16-QAM	Standard	1/0	13.25	6.83	V	20.08	0.102	-18.37
836.50	1.4	16-QAM	Standard	1/5	13.00	6.97	V	19.97	0.099	-18.48
848.30	1.4	16-QAM	Standard	1/0	12.52	7.11	V	19.63	0.092	-18.82
825.50	3	QPSK	Standard	1/0	14.53	6.83	V	21.36	0.137	-17.09
836.50	3	QPSK	Standard	1/14	14.62	6.97	V	21.59	0.144	-16.86
847.50	3	QPSK	Standard	1/14	13.86	7.11	V	20.97	0.125	-17.48
825.50	3	16-QAM	Standard	1/0	13.32	6.83	V	20.15	0.104	-18.30
836.50	3	16-QAM	Standard	1/14	13.46	6.97	V	20.43	0.110	-18.02
847.50	3	16-QAM	Standard	1/14	12.80	7.11	V	19.91	0.098	-18.54
826.50	5	QPSK	Standard	1/12	14.42	6.83	V	21.25	0.133	-17.20
836.50	5	QPSK	Standard	1/12	14.70	6.97	V	21.67	0.147	-16.78
846.50	5	QPSK	Standard	1/0	13.96	7.11	V	21.07	0.128	-17.38
826.50	5	16-QAM	Standard	1/12	13.28	6.83	V	20.11	0.103	-18.34
836.50	5	16-QAM	Standard	1/12	13.60	6.97	V	20.57	0.114	-17.88
846.50	5	16-QAM	Standard	1/0	12.89	7.11	V	20.00	0.100	-18.45
829.00	10	QPSK	Standard	1/0	15.02	6.83	V	21.85	0.153	-16.60
836.50	10	QPSK	Standard	1/0	15.85	6.97	V	22.82	0.192	-15.63
844.00	10	QPSK	Standard	1/25	13.64	7.11	V	20.75	0.119	-17.70
829.00	10	16-QAM	Standard	1/0	13.98	6.83	V	20.81	0.121	-17.64
836.50	10	16-QAM	Standard	1/0	14.75	6.97	V	21.72	0.149	-16.73
844.00	10	16-QAM	Standard	1/25	12.57	7.11	V	19.68	0.093	-18.77

Table 6-2. ERP Data (Band 26)

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.
4. Emissions with the wireless charging cover were investigated and determined to be less than or equal to that of the standard charging cover.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 13 of 79	

6.3 Equivalent Isotropic Radiated Power (EIRP)

§24.232(c) §27.50(h.2) RSS-133(6.4)

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	Margin [dB]
1851.50	3	QPSK	Standard	1/0	11.19	9.59	V	20.78	0.120	-12.23
1882.50	3	QPSK	Standard	1/0	10.69	9.53	V	20.22	0.105	-12.79
1913.50	3	QPSK	Standard	1/0	11.13	9.47	V	20.60	0.115	-12.41
1851.50	3	16-QAM	Standard	1/0	9.70	9.59	V	19.29	0.085	-13.72
1882.50	3	16-QAM	Standard	1/0	9.58	9.53	V	19.11	0.081	-13.90
1913.50	3	16-QAM	Standard	1/0	9.63	9.47	V	19.10	0.081	-13.91
1852.50	5	QPSK	Standard	1/0	11.99	9.59	V	21.58	0.144	-11.43
1882.50	5	QPSK	Standard	1/12	11.69	9.53	V	21.22	0.132	-11.79
1912.50	5	QPSK	Standard	1/12	11.15	9.47	V	20.62	0.115	-12.39
1852.50	5	16-QAM	Standard	1/0	10.70	9.59	V	20.29	0.107	-12.72
1882.50	5	16-QAM	Standard	1/12	10.72	9.53	V	20.25	0.106	-12.76
1912.50	5	16-QAM	Standard	1/12	10.13	9.47	V	19.60	0.091	-13.41
1855.00	10	QPSK	Standard	1/0	11.40	9.59	V	20.99	0.126	-12.02
1882.50	10	QPSK	Standard	1/0	12.22	9.53	V	21.75	0.150	-11.26
1910.00	10	QPSK	Standard	1/25	11.61	9.47	V	21.08	0.128	-11.93
1855.00	10	16-QAM	Standard	1/0	10.24	9.59	V	19.83	0.096	-13.18
1882.50	10	16-QAM	Standard	1/0	11.15	9.53	V	20.68	0.117	-12.33
1910.00	10	16-QAM	Standard	1/25	10.45	9.47	V	19.92	0.098	-13.09

Table 6-3. EIRP Data (Band 25)

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The “H” positioning is defined with the EUT lying flat on the test surface, the “H2” positioning is defined with the EUT standing up on its side, and the “V” positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.
4. Emissions with the wireless charging cover were investigated and determined to be less than or equal to that of the standard charging cover.



FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 14 of 79	

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	Margin [dB]
2502.00	10	QPSK	Standard	1/25	12.10	8.66	H2	20.76	0.119	-12.25
2590.00	10	QPSK	Standard	1/25	10.23	8.72	H2	18.95	0.078	-14.06
2684.50	10	QPSK	Standard	1/25	11.58	8.82	H2	20.40	0.110	-12.61
2502.00	10	16-QAM	Standard	1/25	10.84	8.66	H2	19.50	0.089	-13.51
2590.00	10	16-QAM	Standard	1/25	8.72	8.72	H2	17.44	0.055	-15.57
2684.50	10	16-QAM	Standard	1/25	10.71	8.82	H2	19.53	0.090	-13.48
2504.70	15	QPSK	Standard	1/37	11.80	8.66	H2	20.46	0.111	-12.55
2593.00	15	QPSK	Standard	1/37	11.41	8.72	H2	20.13	0.103	-12.88
2681.80	15	QPSK	Standard	1/37	10.93	8.82	H2	19.75	0.094	-13.26
2504.70	15	16-QAM	Standard	1/37	11.22	8.66	H2	19.88	0.097	-13.13
2593.00	15	16-QAM	Standard	1/37	10.32	8.72	H2	19.04	0.080	-13.97
2681.80	15	16-QAM	Standard	1/37	10.03	8.82	H2	18.85	0.077	-14.16
2507.50	20	QPSK	Standard	1/37	11.90	8.66	H2	20.56	0.114	-12.45
2590.00	20	QPSK	Standard	1/37	12.28	8.72	H2	21.00	0.126	-12.01
2679.00	20	QPSK	Standard	1/37	11.42	8.82	H2	20.24	0.106	-12.77
2507.50	20	16-QAM	Standard	1/37	10.72	8.66	H2	19.38	0.087	-13.63
2590.00	20	16-QAM	Standard	1/37	11.04	8.72	H2	19.76	0.095	-13.25
2679.00	20	16-QAM	Standard	1/37	10.67	8.82	H2	19.49	0.089	-13.52

Table 6-4. EIRP Data (Band 41)

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The “H” positioning is defined with the EUT lying flat on the test surface, the “H2” positioning is defined with the EUT standing up on its side, and the “V” positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.
4. Emissions with the wireless charging cover were investigated and determined to be less than or equal to that of the standard charging cover.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 15 of 79	

6.4 Band 26 Radiated Spurious Emissions

§2.1053 §22.917(a) RSS-132(4.5.1)

Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 829.00 MHz
 MEASURED OUTPUT POWER: 21.85 dBm = 0.153 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 34.85 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1658.00	-33.41	2.50	-30.92	H	52.77
2487.00	-47.39	2.82	-44.58	H	66.43
3316.00	-79.72	5.52	-74.19	H	96.05
4145.00	-79.41	7.08	-72.33	H	94.18
4974.00	-78.88	7.91	-70.97	H	92.82
5803.00	-76.96	8.51	-68.45	H	90.31

Table 6-5. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 16 of 79	

Band 26 Radiated Spurious Measurements (continued)
§2.1053 §22.917(a) RSS-132(4.5.1)

Field Strength of SPURIOUS Radiation


OPERATING FREQUENCY: 836.50 MHz
 MEASURED OUTPUT POWER: 22.82 dBm = 0.192 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 35.82 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1673.00	-34.70	2.34	-32.37	H	55.19
2509.50	-48.06	2.84	-45.22	H	68.04
3346.00	-79.83	5.64	-74.18	H	97.01
4182.50	-79.50	7.14	-72.36	H	95.18
5019.00	-78.86	7.97	-70.89	H	93.72
5855.50	-76.66	8.46	-68.20	H	91.02

Table 6-6. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 17 of 79	

Band 26 Radiated Spurious Measurements (continued)
§2.1053 §22.917(a) RSS-132(4.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 844.00 MHz
 MEASURED OUTPUT POWER: 20.75 dBm = 0.119 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 33.75 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1688.00	-35.02	2.18	-32.84	H	53.59
2532.00	-48.19	3.04	-45.15	H	65.90
3376.00	-79.94	5.76	-74.17	H	94.92
4220.00	-79.59	7.20	-72.39	H	93.14
5064.00	-78.72	8.00	-70.72	H	91.47
5908.00	-76.37	8.42	-67.95	H	88.70

Table 6-7. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The “H” positioning is defined with the EUT lying flat on the test surface, the “H2” positioning is defined with the EUT standing up on its side, and the “V” positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 18 of 79	

Band 26 Radiated Spurious Measurements w/ WCC
§2.1053 §22.917(a) RSS-132(4.5.1)

Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 829.00 MHz
 MEASURED OUTPUT POWER: 21.85 dBm = 0.153 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 34.85 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1658.00	-33.60	2.50	-31.11	H	52.96
2487.00	-47.47	2.82	-44.66	H	66.51
3316.00	-79.72	5.52	-74.19	H	96.05
4145.00	-79.41	7.08	-72.33	H	94.18
4974.00	-78.88	7.91	-70.97	H	92.82
5803.00	-76.96	8.51	-68.45	H	90.31

Table 6-8. Radiated Spurious Data w/ WCC

NOTES:

- This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
- This unit was tested with its standard battery.
- The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 19 of 79	

6.5 Band 25 Radiated Spurious Emissions

§2.1053 §24.238(a) RSS-133(6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1851.50 MHz
 MEASURED OUTPUT POWER: 20.78 dBm = 0.120 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 33.78 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3703.00	-52.16	8.40	-43.76	H2	64.54
5554.50	-56.11	10.63	-45.48	H2	66.26
7406.00	-80.00	11.84	-68.16	H2	88.94
9257.50	-53.79	13.29	-40.50	H2	61.28
11109.00	-75.99	13.50	-62.49	H2	83.27
12960.50	-72.44	13.68	-58.76	H2	79.54

Table 6-9. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 20 of 79	

Band 25 Radiated Spurious Measurements (continued)
§2.1053 §24.238(a) RSS-133(6.5.1)

Field Strength of SPURIOUS Radiation


OPERATING FREQUENCY: 1882.50 MHz
 MEASURED OUTPUT POWER: 20.22 dBm = 0.105 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 33.22 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3765.00	-52.36	8.44	-43.92	H2	64.14
5647.50	-57.01	10.66	-46.35	H2	66.57
7530.00	-79.89	11.94	-67.95	H2	88.17
9412.50	-55.49	13.23	-42.26	H2	62.48
11295.00	-75.76	13.48	-62.28	H2	82.50
13177.50	-72.05	13.84	-58.21	H2	78.43

Table 6-10. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The “H” positioning is defined with the EUT lying flat on the test surface, the “H2” positioning is defined with the EUT standing up on its side, and the “V” positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 21 of 79	

Band 25 Radiated Spurious Measurements (continued)
§2.1053 §24.238(a) RSS-133(6.5.1)

Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 1913.50 MHz
 MEASURED OUTPUT POWER: 20.60 dBm = 0.115 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 33.60 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3827.00	-53.11	8.57	-44.54	H2	65.14
5740.50	-55.10	10.69	-44.41	H2	65.01
7654.00	-79.89	12.07	-67.82	H2	88.42
9567.50	-53.59	13.20	-40.39	H2	60.99
11481.00	-75.69	13.42	-62.28	H2	82.88
13394.50	-72.55	14.04	-58.51	H2	79.11

Table 6-11. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The “H” positioning is defined with the EUT lying flat on the test surface, the “H2” positioning is defined with the EUT standing up on its side, and the “V” positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 22 of 79	

Band 25 Radiated Spurious Measurements w/ WCC
§2.1053 §24.238(a) RSS-133(6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1851.50 MHz
 MEASURED OUTPUT POWER: 20.78 dBm = 0.120 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 3 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 33.78 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3703.00	-54.89	8.40	-46.49	H2	67.27
5554.50	-56.11	10.63	-45.48	H2	66.26
7406.00	-80.00	11.84	-68.16	H2	88.94
9257.50	-54.37	13.29	-41.08	H2	61.86
11109.00	-75.99	13.50	-62.49	H2	83.27
12960.50	-72.44	13.68	-58.76	H2	79.54

Table 6-12. Radiated Spurious Data w/ WCC

NOTES:

- This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
- This unit was tested with its standard battery.
- The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 23 of 79	

6.6 Band 41 Radiated Spurious Emissions

§2.1053 §27.53(m)

Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 2507.50 MHz
 MEASURED OUTPUT POWER: 20.76 dBm = 0.119 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 20 MHz
 DISTANCE: 3 meters
 LIMIT: $55 + 10 \log_{10}(W) =$ 45.76 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
5015.00	-47.33	10.10	-37.22	H2	58.00
7522.50	-50.37	11.91	-38.46	H2	59.24
10030.00	-77.23	13.19	-64.03	H2	84.81
12537.50	-73.67	13.40	-60.27	H2	81.05
15045.00	-70.44	14.09	-56.35	H2	77.13
17552.50	-66.36	13.99	-52.37	H2	73.15

Table 6-13. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 24 of 79	

Band 41 Radiated Spurious Measurements (continued)
§2.1053 §27.53(m)

Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 2590.00 MHz
 MEASURED OUTPUT POWER: 18.95 dBm = 0.078 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 20 MHz
 DISTANCE: 3 meters
 LIMIT: $55 + 10 \log_{10}(W) =$ 43.95 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
5180.00	-45.33	10.24	-35.09	H2	55.31
7770.00	-46.21	12.22	-34.00	H2	54.22
10360.00	-77.02	13.09	-63.93	H2	84.15
12950.00	-72.58	13.62	-58.96	H2	79.18
15540.00	-66.94	13.88	-53.06	H2	73.28
18130.00	-66.36	14.51	-51.86	H2	72.08

Table 6-14. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 25 of 79	

Band 41 Radiated Spurious Measurements (continued)
§2.1053 §27.53(m)

Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 2679.00 MHz
 MEASURED OUTPUT POWER: 20.40 dBm = 0.110 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 20 MHz
 DISTANCE: 3 meters
 LIMIT: $55 + 10 \log_{10} (W) =$ 45.40 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
5358.00	-47.64	10.44	-37.20	H2	57.60
8037.00	-48.84	12.49	-36.35	H2	56.75
10716.00	-75.68	13.20	-62.48	H2	82.88
13395.00	-72.82	14.11	-58.72	H2	79.12
16074.00	-63.89	13.63	-50.26	H2	70.66
18753.00	-67.08	15.53	-51.55	H2	71.95

Table 6-15. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 26 of 79	

Band 41 Radiated Spurious Measurements w/ WCC
§2.1053 §27.53(m)

Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 2590.00 MHz
 MEASURED OUTPUT POWER: 18.95 dBm = 0.078 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 20 MHz
 DISTANCE: 3 meters
 LIMIT: $55 + 10 \log_{10}(W) =$ 43.95 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
5180.00	-49.71	10.24	-39.47	H2	59.69
7770.00	-51.25	12.22	-39.04	H2	59.26
10360.00	-77.02	13.09	-63.93	H2	84.15
12950.00	-72.58	13.62	-58.96	H2	79.18
15540.00	-66.94	13.88	-53.06	H2	73.28
18130.00	-66.36	14.51	-51.86	H2	72.08

Table 6-16. Radiated Spurious Data w/ WCC

NOTES:

- This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1RB for all bands.
- This unit was tested with its standard battery.
- The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The data reported in the table above was measured in this test setup.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 27 of 79	

6.7 Band 26 Frequency Stability Measurements

§2.1055 §22.355 RSS-132(4.3)


OPERATING FREQUENCY: 836,500,000 Hz
 CHANNEL: 20525
 REFERENCE VOLTAGE: 3.8 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,500,021	21	0.0000025
100 %		- 30	836,500,014	14	0.0000017
100 %		- 20	836,499,987	-13	-0.0000016
100 %		- 10	836,500,025	25	0.0000030
100 %		0	836,499,988	-12	-0.0000014
100 %		+ 10	836,500,021	21	0.0000025
100 %		+ 20	836,500,001	1	0.0000001
100 %		+ 30	836,499,993	-7	-0.0000008
100 %		+ 40	836,499,997	-3	-0.0000004
100 %		+ 50	836,499,988	-12	-0.0000014
115 %	4.37	+ 20	836,500,025	25	0.0000030
BATT. ENDPOINT	3.40	+ 20	836,499,996	-4	-0.0000005

Table 6-17. Frequency Stability Data (Band 5)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 28 of 79	

Band 26 Frequency Stability Measurements (Cont'd)
§2.1055 §22.355 RSS-132(4.3)






Figure 6-1. Frequency Stability Graph (Band 5)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 29 of 79

6.8 Band 25 Frequency Stability Measurements

§2.1055 §24.235 RSS-133(6.3)



OPERATING FREQUENCY: 1,882,500,000 Hz
 CHANNEL: 26365
 REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,882,500,013	13	0.0000007
100 %		- 30	1,882,500,013	13	0.0000007
100 %		- 20	1,882,500,010	10	0.0000005
100 %		- 10	1,882,499,986	-14	-0.0000007
100 %		0	1,882,499,993	-7	-0.0000004
100 %		+ 10	1,882,499,978	-22	-0.0000012
100 %		+ 20	1,882,500,006	6	0.0000003
100 %		+ 30	1,882,499,979	-21	-0.0000011
100 %		+ 40	1,882,500,024	24	0.0000013
100 %		+ 50	1,882,499,970	-30	-0.0000016
115 %	4.37	+ 20	1,882,499,980	-20	-0.0000011
BATT. ENDPOINT	3.40	+ 20	1,882,500,015	15	0.0000008

Table 6-18. Frequency Stability Data (Band 25)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 30 of 79	

Band 25 Frequency Stability Measurements (Cont'd)
§2.1055 §24.235 RSS-133(6.3)






Figure 6-2. Frequency Stability Graph (Band 25)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 31 of 79

6.9 Band 41 Frequency Stability Measurements

§2.1055 §27.5(i) §27.54

OPERATING FREQUENCY: 2,590,000,000 Hz

CHANNEL: 40590


REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	2,589,999,997	-3	-0.0000001
100 %		- 30	2,589,999,985	-15	-0.0000006
100 %		- 20	2,589,999,982	-18	-0.0000007
100 %		- 10	2,589,999,987	-13	-0.0000005
100 %		0	2,590,000,025	25	0.0000010
100 %		+ 10	2,590,000,010	10	0.0000004
100 %		+ 20	2,590,000,028	28	0.0000011
100 %		+ 30	2,589,999,996	-4	-0.0000002
100 %		+ 40	2,590,000,028	28	0.0000011
100 %		+ 50	2,589,999,998	-2	-0.0000001
115 %	4.37	+ 20	2,589,999,992	-8	-0.0000003
BATT. ENDPOINT	3.40	+ 20	2,589,999,971	-29	-0.0000011

Table 6-19. Frequency Stability Data (Band 41)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 32 of 79	

Band 41 Frequency Stability Measurements (Cont'd)
§2.1055 §27.5(i) §27.54







Figure 6-3. Frequency Stability Graph (Band 41)


FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 33 of 79

7.0 BAND 26 PLOTS OF EMISSIONS


Note: All bandwidths, RB configurations, and modulations were investigated. The worst case test results are reported below.



FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 34 of 79




Plot 7-2. Occupied Bandwidth Plot (1.4MHz QPSK – RB Size 6)




Plot 7-3. Occupied Bandwidth Plot (1.4MHz 16-QAM – RB Size 6)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 35 of 79




Plot 7-4. Upper Band Edge Plot (1.4MHz QPSK – RB Size 6)




Plot 7-5. Lower Band Edge Plot (3.0MHz QPSK – RB Size 15)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 36 of 79




Plot 7-6. Occupied Bandwidth Plot (3.0MHz QPSK – RB Size 15)




Plot 7-7. Occupied Bandwidth Plot (3.0MHz 16-QAM – RB Size 15)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 37 of 79




Plot 7-8. Upper Band Edge Plot (3.0MHz QPSK – RB Size 15)




Plot 7-9. Lower Band Edge Plot (5.0MHz QPSK – RB Size 25)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 38 of 79




Plot 7-10. Occupied Bandwidth Plot (5.0MHz QPSK – RB Size 25)




Plot 7-11. Occupied Bandwidth Plot (5.0MHz 16-QAM – RB Size 25)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 39 of 79




Plot 7-12. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-13. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 40 of 79




Plot 7-14. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)




Plot 7-15. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 41 of 79




Plot 7-16. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)




Plot 7-17. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 42 of 79




Plot 7-18. Upper Band Edge Plot (5.0MHz QPSK – RB Size 25)




Plot 7-19. Lower Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 43 of 79



Plot 7-20. Occupied Bandwidth Plot (10.0MHz QPSK – RB Size 50)





Plot 7-21. Occupied Bandwidth Plot (10.0MHz 16-QAM – RB Size 50)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 44 of 79




Plot 7-22. Upper Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 45 of 79


8.0 BAND 25 PLOTS OF EMISSIONS

Note: All bandwidths, RB configurations, and modulations were investigated. The worst case test results are reported below.




Plot 8-1. Lower Band Edge Plot (3.0MHz QPSK – RB Size 15)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 46 of 79




Plot 8-2. Lower Extended Band Edge Plot (3.0MHz QPSK – RB Size 15)




Plot 8-3. Occupied Bandwidth Plot (3.0MHz QPSK – RB Size 15)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 47 of 79




Plot 8-4. Occupied Bandwidth Plot (3.0MHz 16-QAM – RB Size 15)




Plot 8-5. Upper Band Edge Plot (3.0MHz QPSK – RB Size 15)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 48 of 79




Plot 8-6. Upper Extended Band Edge Plot (3.0MHz QPSK – RB Size 15)




Plot 8-7. PAR Plot (3.0MHz QPSK – RB Size 15)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 49 of 79




Plot 8-8. PAR Plot (3.0MHz 16-QAM – RB Size 15)




Plot 8-9. Lower Band Edge Plot (5.0MHz QPSK – RB Size 25)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 50 of 79




Plot 8-10. Lower Extended Band Edge Plot (5.0MHz QPSK – RB Size 25)




Plot 8-11. Occupied Bandwidth Plot (5.0MHz QPSK – RB Size 25)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 51 of 79




Plot 8-12. Occupied Bandwidth Plot (5.0MHz 16-QAM – RB Size 25)




Plot 8-13. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 52 of 79




Plot 8-14. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 8-15. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 53 of 79




Plot 8-16. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)



Plot 8-17. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 54 of 79




Plot 8-18. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)




Plot 8-19. Upper Band Edge Plot (5.0MHz QPSK – RB Size 25)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 55 of 79




Plot 8-20. Upper Extended Band Edge Plot (5.0MHz QPSK – RB Size 25)




Plot 8-21. PAR Plot (5.0MHz QPSK – RB Size 25)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 56 of 79




Plot 8-22. PAR Plot (5.0MHz 16-QAM – RB Size 25)




Plot 8-23. Lower Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 57 of 79




Plot 8-24. Lower Extended Band Edge Plot (10.0MHz QPSK – RB Size 50)




Plot 8-25. Occupied Bandwidth Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 58 of 79



Plot 8-26. Occupied Bandwidth Plot (10.0MHz 16-QAM – RB Size 50)




Plot 8-27. Upper Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 59 of 79




Plot 8-28. Upper Extended Band Edge Plot (10.0MHz QPSK – RB Size 50)



Plot 8-29. PAR Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 60 of 79




Plot 8-30. PAR Plot (10.0MHz 16-QAM – RB Size 50)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 61 of 79


9.0 BAND 41 PLOTS OF EMISSIONS

Note: All bandwidths, RB configurations, and modulations were investigated. The worst case test results are reported below.




Plot 9-1. Lower Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 62 of 79



Plot 9-2. Occupied Bandwidth Plot (10.0MHz QPSK – RB Size 50)




Plot 9-3. Occupied Bandwidth Plot (10.0MHz 16-QAM – RB Size 50)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 63 of 79




Plot 9-4. Upper Band Edge Plot (10.0MHz QPSK – RB Size 50)




Plot 9-5. PAR Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 64 of 79




Plot 9-6. PAR Plot (10.0MHz 16-QAM – RB Size 50)




Plot 9-7. ACP Plot (10.0MHz QPSK – RB Size 50 – Low Chanel)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 65 of 79




Plot 9-8. ACP Plot (10.0MHz QPSK – RB Size 50 – Mid Chanel)




Plot 9-9. ACP Plot (10.0MHz QPSK – RB Size 50 – High Chanel)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 66 of 79




Plot 9-10. Lower Band Edge Plot (15.0MHz QPSK – RB Size 75)




Plot 9-11. Occupied Bandwidth Plot (15.0MHz QPSK – RB Size 75)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 67 of 79




Plot 9-12. Occupied Bandwidth Plot (15.0MHz 16-QAM – RB Size 75)




Plot 9-13. Conducted Spurious Plot (15.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 68 of 79




Plot 9-14. Conducted Spurious Plot (15.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 9-15. Conducted Spurious Plot (15.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 69 of 79




Plot 9-16. Conducted Spurious Plot (15.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)



Plot 9-17. Conducted Spurious Plot (15.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 70 of 79




Plot 9-18. Conducted Spurious Plot (15.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)




Plot 9-19. Upper Band Edge Plot (15.0MHz QPSK – RB Size 75)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 71 of 79




Plot 9-20. PAR Plot (15.0MHz QPSK – RB Size 75)




Plot 9-21. PAR Plot (15.0MHz 16-QAM – RB Size 75)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 72 of 79




Plot 9-22. ACP Plot (15.0MHz QPSK – RB Size 75 – Low Channel)




Plot 9-23. ACP Plot (15.0MHz QPSK – RB Size 75 – Mid Channel)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 73 of 79




Plot 9-24. ACP Plot (15.0MHz QPSK – RB Size 75 – High Channel)




Plot 9-25. Lower Band Edge Plot (20.0MHz QPSK – RB Size 100)

FCC ID: A3LSPHL720T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 74 of 79




Plot 9-26. Occupied Bandwidth Plot (20.0MHz QPSK – RB Size 100)




Plot 9-27. Occupied Bandwidth Plot (20.0MHz 16-QAM – RB Size 100)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 75 of 79




Plot 9-28. Upper Band Edge Plot (20.0MHz QPSK – RB Size 100)




Plot 9-29. PAR Plot (20.0MHz QPSK – RB Size 100)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 76 of 79




Plot 9-30. PAR Plot (20.0MHz 16-QAM – RB Size 100)




Plot 9-31. ACP Plot (20.0MHz QPSK – RB Size 100 – Low Chanel)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 77 of 79



Plot 9-32. ACP Plot (20.0MHz QPSK – RB Size 100 – Mid Channel)





Plot 9-33. ACP Plot (20.0MHz QPSK – RB Size 100 – High Channel)

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset		Page 78 of 79

10.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSPHL720T** complies with all the requirements of Parts 2, 22, 24, 27 of the FCC rules for LTE operation only.

FCC ID: A3LSPHL720T		FCC Pt. 22, 24 & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1309031731.A3L	Test Dates: 09/04 - 09/16/2013	EUT Type: Portable Handset	Page 79 of 79	