

RADIO PERFORMANCE TEST REPORT

Test Report No. : OT-241-RWD-034

Reception No. : 2401000225

Applicant : Samsung Electronics Co Ltd

Address : 19 Chapin Rd., Building D, Pine Brook, New Jersey, United States, 07058

Manufacturer : Samsung Electronics Co., Ltd.

Address : 129 Samsung-ro, Yeongtong-gu, Suwon-Si, Gyeonggi-do, 16677, Korea

Type of Equipment : Smart Control

FCC ID. : A3LVGTM2460

Model Name : VG-TM2460

Multiple Model Name : N/A

Serial number : N/A

Total page of Report : 25 pages (including this page)

Date of Incoming : January 17, 2024

Date of issue : January 26, 2024

SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247*

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.





Tested by
Si-eon Lee / Sr. Engineer
ONETECH Corp.

Reviewed by
Tae-Ho, Kim / Chief Engineer
ONETECH Corp.

Approved by
Jae-Ho, Lee / Chief Engineer
ONETECH Corp.

CONTENTS**PAGE**

1. VERIFICATION OF COMPLIANCE	5
2. TEST SUMMARY.....	6
2.1 TEST ITEMS AND RESULTS	6
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	6
2.3 RELATED SUBMITTAL(S) / GRANT(S)	6
2.4 PURPOSE OF THE TEST	6
2.5 TEST METHODOLOGY.....	6
2.6 TEST FACILITY.....	6
3. GENERAL INFORMATION.....	7
3.1 PRODUCT DESCRIPTION.....	7
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	7
4. EUT MODIFICATIONS.....	7
5. SYSTEM TEST CONFIGURATION	8
5.1 JUSTIFICATION.....	8
5.2 PERIPHERAL EQUIPMENT	8
5.3 MODE OF OPERATION DURING THE TEST	9
5.4 CONFIGURATION OF TEST SYSTEM.....	10
5.5 ANTENNA REQUIREMENT	10
6. PRELIMINARY TEST	10
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	10
6.2 GENERAL RADIATED EMISSIONS TESTS	10
7. MIMIMUM 6 DB BANDWIDTH	11
7.1 OPERATING ENVIRONMENT	11
7.2 TEST SET-UP	11
7.3 MEASUREMENT UNCERTAINTY	11
7.4 TEST DATE.....	11
7.5 TEST DATA.....	11
8. MAXIMUM CONDUCTED(PEAK) OUTPUT POWER.....	12
8.1 OPERATING ENVIRONMENT	12
8.2 TEST SET-UP	12
8.3 MEASUREMENT UNCERTAINTY	12
8.4 TEST DATE.....	12

8.5 TEST DATA	12
9. 100 KHZ BANDWIDTH OUTSIDE THE FREQUENCY BAND.....	13
9.1 OPERATING ENVIRONMENT	13
9.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	13
9.3 TEST SET-UP FOR RADIATED MEASUREMENT.....	13
9.4 MEASUREMENT UNCERTAINTY	13
9.5 TEST DATE.....	13
9.6 TEST DATA FOR CONDUCTED EMISSION	13
9.7 TEST DATA FOR RADIATED EMISSION	14
9.7.1 Radiated Emission which fall in the Restricted Band.....	14
9.7.2 Spurious & Harmonic Radiated Emission.....	15
10. POWER SPECTRAL DENSITY	17
10.1 OPERATING ENVIRONMENT	17
10.2 TEST SET-UP	17
10.3 MEASUREMENT UNCERTAINTY	17
10.4 TEST DATE.....	17
10.5 TEST DATA.....	17
11. RADIATED EMISSION TEST	18
11.1 OPERATING ENVIRONMENT	18
11.2 TEST SET-UP	18
11.3 MEASUREMENT UNCERTAINTY	19
11.4 TEST DATE.....	19
11.5 TEST DATA FOR 30 MHZ ~ 1 000 MHZ	20
11.6 TEST DATA FOR BELOW 30 MHZ	21
11.7 TEST DATA FOR ABOVE 1 GHZ	21
12. CONDUCTED EMISSION TEST.....	22
12.1 OPERATING ENVIRONMENT	22
12.2 TEST SET-UP	22
12.3 MEASUREMENT UNCERTAINTY	22
12.4 TEST DATE.....	22
12.5 TEST DATA.....	23
13. LIST OF TEST EQUIPMENT	25

※ Please refer to the Annex section for All test plots

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-241-RWD-034	January 26, 2024	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : Samsung Electronics Co Ltd
 Address : 19 Chapin Rd., Building D, Pine Brook, New Jersey, United States, 07058
 Contact Person : Jenni Chun / General Manager
 Telephone No. : +973-808-6375
 FCC ID : A3LVGTM2460
 Model Name : VG-TM2460
 Brand Name : Samsung
 Serial Number : N/A
 Date : January 26, 2024

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Smart Control
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247 (a) (2)	Minimum 6 dB Bandwidth	Met the Limit / PASS
15.247 (b) (3)	Maximum Conducted Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.247 (e)	Power Spectral Density	Met the Limit / PASS
15.209	Radiated Emission Limits	Met the Limit / PASS
15.207	Conducted Limits	Met the Limit / PASS
15.203	Antenna Requirement	Met requirement / PASS

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247.

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-20122/ C-14617/ G-10666/ T-11842

ISED (Innovation, Science and Economic Development Canada) – Registration No. Site# 3736A-3

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The Samsung Electronics Co Ltd, Model VG-TM2460 (referred to as the EUT in this report) is a Smart Control. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Smart Control
OPERATING FREQUENCY	2 402 MHz ~ 2 480 MHz
MODULATION TYPE	GFSK
RF OUTPUT POWER	6.06 dBm
ANTENNA TYPE	Chip Antenna
ANTENNA GAIN	0.97 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	40 MHz
RATED SUPPLY VOLTAGE	DC 3.85 V

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	Samsung Electronics Co., Ltd.	N/A	N/A

5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
VG-TM2460	Samsung Electronics Co., Ltd.	Smart Control (EUT)	-
RTL8852BE	HP	Notebook PC	EUT

5.3 Mode of operation during the test

-. Channel List (Bluetooth LE)

Channel	Frequency[MHz]	Channel	Frequency[MHz]	Channel	Frequency[MHz]
0	2 402.00	14	2 430.00	28	2 458.00
1	2 404.00	15	2 432.00	29	2 460.00
2	2 406.00	16	2 434.00	30	2 462.00
3	2 408.00	17	2 436.00	31	2 464.00
4	2 410.00	18	2 438.00	32	2 466.00
5	2 412.00	19	2 440.00	33	2 468.00
6	2 414.00	20	2 442.00	34	2 470.00
7	2 416.00	21	2 444.00	35	2 472.00
8	2 418.00	22	2 446.00	36	2 474.00
9	2 420.00	23	2 448.00	37	2 476.00
10	2 422.00	24	2 450.00	38	2 478.00
11	2 424.00	25	2 452.00	39	2 480.00
12	2 426.00	26	2 454.00		
13	2 428.00	27	2 456.00		

-. Duty Cycle

Mode	Tx On Time [ms]	Tx Off Time [ms]	Duty Cycle [%]	Correction Factor [dB]
Bluetooth LE	-	-	100	0.00

Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) * 100

Correction Factor : 10 * Log(1 / (Duty Cycle / 100))

5.4 Configuration of Test System

Line Conducted Test: The EUT was connected to adaptor and the power of adaptor was connected to LISN. All supporting equipment were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions.

Radiated Emission Test: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter Semi Anechoic Chamber.
The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The antenna of the EUT is a Chip Antenna on the main board in the EUT, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Charging Mode / Transmitting Mode	X

6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Charging Mode / Transmitting Mode	X


7. MIMIMUM 6 dB BANDWIDTH

7.1 Operating environment

Temperature : 22 °C
 Relative humidity : 41 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, and peak detection was used. The 6 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 6 dB.



7.3 Measurement uncertainty

The uncertainty for Minimum 6 dB bandwidth is $\pm 6\,924.15$ Hz

7.4 Test date

January 17, 2024 ~ January 23, 2024

7.5 Test data

-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (kHz)	LIMIT (kHz)	Margin (kHz)
Low	2 402.00	709.30	500.00	209.30
Middle	2 440.00	729.30	500.00	229.30
High	2 480.00	709.30	500.00	209.30

Remark. Margin = Measured Value – Limit


8. MAXIMUM CONDUCTED(PEAK) OUTPUT POWER

8.1 Operating environment

Temperature : 22 °C
 Relative humidity : 41 % R.H.

8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer.
 The resolution bandwidth is set to 1 MHz, the video bandwidth is set to 3 times the resolution bandwidth.



8.3 Measurement uncertainty

The uncertainty for Maximum conducted(Peak) output power is ± 1.55 dBm

8.4 Test date

January 17, 2024 ~ January 23, 2024

8.5 Test data

-. Test Result : Pass
 -. Duty Cycle : 100 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402.00	6.06	30.00	23.94
MIDDLE	2 440.00	5.82	30.00	24.18
HIGH	2 480.00	5.58	30.00	24.42

Remark. Margin = Limit –Measured Value

9. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND


9.1 Operating environment

Temperature : 22 °C

Relative humidity : 41 % R.H.

9.2 Test set-up for conducted measurement

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz and video bandwidth is set to 300 kHz, and peak detection was used.



9.3 Test set-up for radiated measurement

The radiated emissions measurements were performed on the 3 m semi anechoic chamber. The EUT was placed on turntable approximately 1.5 m above the ground plane.

The frequency spectrum from 30 MHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.

9.4 Measurement uncertainty

The uncertainty for 100 kHz bandwidth outside the frequency band is ± 1.60 dBm

9.5 Test date

January 17, 2024 ~ January 23, 2024

9.6 Test data for conducted emission

Please refer to the Annex

9.7 Test data for radiated emission

9.7.1 Radiated Emission which fall in the Restricted Band

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : 100 %
- Result : PASSED

Frequency (MHz)	Reading (dBµV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	ATT (dB)	Duty Factor (dB)	Total (dBµV/m)	Limits (dBµV/m)	Margin (dB)
Test Data for Low Channel											
2 388.260	59.66	Peak	H	27.50	2.46	42.80	-	-	46.82	74.00	27.18
2 362.250	48.73	Average	H	27.50	2.46	42.80	-	-	35.89	54.00	18.11
2 360.220	59.65	Peak	V	27.50	2.46	42.80	-	-	46.81	74.00	27.19
2 361.790	48.83	Average	V	27.50	2.46	42.80	-	-	35.99	54.00	18.01
Test Data for High Channel											
2 483.920	64.29	Peak	H	27.50	2.53	42.80	-	-	51.52	74.00	22.48
2 483.520	52.33	Average	H	27.50	2.53	42.80	-	-	39.56	54.00	14.44
2 483.600	65.40	Peak	V	27.50	2.53	42.80	-	-	52.63	74.00	21.37
2 483.620	53.04	Average	V	27.50	2.53	42.80	-	-	40.27	54.00	13.73

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dBµV/m)} - \text{Total Level (dBµV/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{ATT} + \text{Duty Factor} - \text{AMP Gain}$$

9.7.2 Spurious & Harmonic Radiated Emission

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Duty Cycle : 100 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel										
4 803.650	64.46	Peak	H	31.40	3.30	44.10	-	55.06	74.00	18.94
4 803.970	60.22	Average	H	31.40	3.30	44.10	-	50.82	54.00	3.18
7 206.640	54.76	Peak	H	36.20	4.18	44.80	-	50.34	74.00	23.66
7 205.590	44.57	Average	H	36.20	4.18	44.80	-	40.15	54.00	13.85
4 803.620	64.98	Peak	V	31.40	3.30	44.10	-	55.58	74.00	18.42
4 803.990	60.84	Average	V	31.40	3.30	44.10	-	51.44	54.00	2.56
7 206.900	57.56	Peak	V	36.20	4.18	44.80	-	53.14	74.00	20.86
7 206.570	49.67	Average	V	36.20	4.18	44.80	-	45.25	54.00	8.75
Test Data for Middle Channel										
4 880.530	62.47	Peak	H	31.40	3.40	44.10	-	53.17	74.00	20.83
4 879.990	57.23	Average	H	31.40	3.40	44.10	-	47.93	54.00	6.07
7 319.970	54.29	Peak	H	36.40	4.23	44.80	-	50.12	74.00	23.88
7 319.670	43.05	Average	H	36.40	4.23	44.80	-	38.88	54.00	15.12
4 880.610	63.44	Peak	V	31.40	3.40	44.10	-	54.14	74.00	19.86
4 880.090	59.27	Average	V	31.40	3.40	44.10	-	49.97	54.00	4.03
7 320.960	57.02	Peak	V	36.40	4.23	44.80	-	52.85	74.00	21.15
7 319.510	47.04	Average	V	36.40	4.23	44.80	-	42.87	54.00	11.13

Test Data for High Channel										
4 960.440	60.14	Peak	H	31.40	3.50	44.10	-	50.94	74.00	23.06
4 959.900	54.10	Average	H	31.40	3.50	44.10	-	44.90	54.00	9.10
7 440.690	54.25	Peak	H	36.40	4.23	44.80	-	50.08	74.00	23.92
7 440.790	42.91	Average	H	36.40	4.23	44.80	-	38.74	54.00	15.26
4 960.560	63.24	Peak	V	31.40	3.50	44.10	-	54.04	74.00	19.96
4 960.050	58.72	Average	V	31.40	3.50	44.10	-	49.52	54.00	4.48
7 440.430	54.95	Peak	V	36.40	4.23	44.80	-	50.78	74.00	23.22
7 439.440	44.05	Average	V	36.40	4.23	44.80	-	39.88	54.00	14.12

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{Duty Factor} - \text{AMP Factor}$$

10. POWER SPECTRAL DENSITY


10.1 Operating environment

Temperature : 22 °C
 Relative humidity : 41 % R.H.

10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer.

The resolution bandwidth is set to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$, the video bandwidth is set to 3 times the resolution bandwidth.



10.3 Measurement uncertainty

The uncertainty for Power spectral density is $\pm 1.55 \text{ dB}$

10.4 Test date

January 17, 2024 ~ January 23, 2024

10.5 Test data

-. Test Result : Pass
 -. Duty Cycle : 100 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm / 3 kHz)	MARGIN (dB)
LOW	2 402.00	-5.41	8.00	13.41
MIDDLE	2 440.00	-5.68	8.00	13.68
HIGH	2 480.00	-5.88	8.00	13.88

Remark. Margin = Limit – Measured Value

11. RADIATED EMISSION TEST

11.1 Operating environment

Temperature : 22 °C

Relative humidity : 41 % R.H.


11.2 Test set-up

The radiated emissions measurements were on the 3 m semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.


The frequency spectrum from 30 MHz to 26.5 GHz was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

- Test Configuration


1. Below 30 MHz



2. 30 MHz - 1 GHz



3. Above 1 GHz



11.3 Measurement uncertainty

The uncertainty for Radiated emission test is ± 4.09 dB below 30 MHz

The uncertainty for Radiated emission test is ± 3.98 dB in 30 MHz ~ 1GHz

The uncertainty for Radiated emission test is ± 5.56 dB above 1 GHz

11.4 Test date

January 17, 2024 ~ January 23, 2024


11.5 Test data for 30 MHz ~ 1 000 MHz

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247

Result : PASSED

EUT : Smart Control

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	167.740	37.1	17.3	2.5	33.1	23.8	43.5	19.7	200	359
2	239.520	41.2	17.1	3.0	33.3	28.0	46.0	18.0	200	359
3	347.190	38.6	19.8	3.6	33.1	28.9	46.0	17.1	100	0
----- Vertical -----										
4	42.610	41.0	15.9	1.3	33.1	25.1	40.0	14.9	100	260
5	81.410	44.9	13.1	1.8	33.1	26.7	40.0	13.3	100	174
6	148.340	35.8	18.9	2.4	33.1	24.0	43.5	19.5	100	359

11.6 Test data for Below 30 MHz

- Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)
- Frequency range : 9 kHz ~ 30 MHz
- Measurement distance : 3 m
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.									

11.7 Test data for above 1 GHz

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.									

12. CONDUCTED EMISSION TEST

12.1 Operating environment

Temperature : 22 °C

Relative humidity : 41 % R.H.

12.2 Test set-up

The EUT was placed on a wooden table, 0.8 m height above the floor. Power was fed to the EUT through a 50 Ω / 50 μ H + 5 Ω Artificial Mains Network (AMN). The ground plane was electrically bonded to the reference ground system and all power lines were filtered from ambient.

12.3 Measurement uncertainty


The uncertainty for Conducted emission test is ± 1.6 dB

12.4 Test date

January 17, 2024 ~ January 23, 2024

12.5 Test data


- Resolution bandwidth : 9 kHz
- Frequency range : 0.15 MHz ~ 30 MHz
- Tested Line : HOT LINE



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.181	---	11.81	54.42	42.61	3000.0	9.0	L1	10.23
0.186	29.10	---	64.24	35.13	3000.0	9.0	L1	10.22
0.513	---	20.39	46.00	25.61	3000.0	9.0	L1	10.22
0.525	26.91	---	56.00	29.09	3000.0	9.0	L1	10.22
1.477	19.40	---	56.00	36.60	3000.0	9.0	L1	10.29
1.491	---	11.28	46.00	34.72	3000.0	9.0	L1	10.29
2.703	---	12.88	46.00	33.12	3000.0	9.0	L1	10.33
2.723	19.58	---	56.00	36.42	3000.0	9.0	L1	10.33
5.879	---	14.90	50.00	35.10	3000.0	9.0	L1	10.47
5.962	19.75	---	60.00	40.25	3000.0	9.0	L1	10.47
20.308	33.91	---	60.00	26.09	3000.0	9.0	L1	11.12
20.468	---	24.33	50.00	25.67	3000.0	9.0	L1	11.12

-. Tested Line : NEUTRAL LINE



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.222	28.12	---	62.76	34.64	3000.0	9.0	N	10.23
0.223	---	13.84	52.73	38.89	3000.0	9.0	N	10.23
0.513	---	29.18	46.00	16.82	3000.0	9.0	N	10.22
0.525	37.33	---	56.00	18.67	3000.0	9.0	N	10.22
1.428	29.06	---	56.00	26.94	3000.0	9.0	N	10.28
1.448	---	20.93	46.00	25.07	3000.0	9.0	N	10.28
2.742	27.39	---	56.00	28.61	3000.0	9.0	N	10.32
2.778	---	18.88	46.00	27.12	3000.0	9.0	N	10.32
5.990	---	19.70	50.00	30.30	3000.0	9.0	N	10.48
6.133	27.27	---	60.00	32.73	3000.0	9.0	N	10.49
17.400	---	29.21	50.00	20.79	3000.0	9.0	N	11.04
17.424	41.24	---	60.00	18.76	3000.0	9.0	N	11.04

Remark: Margin (dB) = Limit – Level (Result)

The emission level in above table is included the transducer factor that means insertion loss (LISN), cable loss and attenuator.

13. LIST OF TEST EQUIPMENT

Model Number	Manufacturer	Description	Serial Number	Last Cal.(Interval)
FSV30	Rohde & Schwarz	Signal Analyzer	101199	Jan. 15, 2024 (1Y)
ESR	Rohde & Schwarz	EMI Test Receiver	101470	Jun. 16, 2023 (1Y)
310N	Sonoma Instrument	Pre-Amplifier	312544	Mar. 14, 2023 (1Y)
ELNA18	EXYNOD	RF Pre Amplifier	27594	Jan. 16, 2024 (1Y)
ELNA40	EXYNOD	RF Pre Amplifier	25339-27648	Apr. 05, 2023 (1Y)
HPF 3GHz	Rohde & Schwarz	High Pass Filter (1-3 GHz)	N/A	Jan. 15, 2024 (1Y)
FMZB 1513	Schwarzbeck	Loop Antenna	1513-235	Mar. 24, 2022 (2Y)
HLP-2008	TDK	Hybrid Antenna	131314	Mar. 07, 2023 (2Y)
BBHA9120D	Schwarzbeck	Horn Antenna	9120D-1349	Jul. 04, 2023 (1Y)
BBHA9170	Schwarzbeck	Horn Antenna	BBHA9170178	Jan. 04, 2024 (1Y)
ESR3	Rohde & Schwarz	EMI Test Receiver	102602	Mar. 15, 2023 (1Y)
ESH3-Z2	Rohde & Schwarz	Pulse Limiter	357.8810.52	Mar. 14, 2023 (1Y)
NSLK8126	Schwarzbeck	LISN	8126404	Mar. 15, 2023 (1Y)
DT3000	Innco System	Turn Table	DT3000/093	N/A
MA4000-EP	Innco System	Antenna Master	MA4000/332	N/A
CO3000	Innco System	Controller	CO3000/904	N/A