

# ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

**Test Report No.** : OT-209-RWD-066  
**Reception No.** : 2008003233  
**Applicant** : Samsung Electronics Co Ltd  
**Address** : 19 Chapin Rd., Building D, Pine Brook, New Jersey, 07058, United States  
**Manufacturer** : Samsung Electronics Co Ltd  
**Address** : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do 16677, Korea  
**Type of Equipment** : Wi-Fi/BT Transceiver  
**FCC ID.** : A3LWCA732M  
**Model Name** : WCA732M  
**Serial number** : N/A  
**Total page of Report** : 17 pages (including this page)  
**Date of Incoming** : August 20, 2020  
**Date of issue** : September 21, 2020


## SUMMARY

The equipment complies with the regulation; ***FCC PART 15 SUBPART C Section 15.247 and FCC PART 15 SUBPART E Section 15.407***

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.





Tested by  
 Ju Yun Park / Assistant Manager  
 ONETECH Corp.

Reviewed by  
 Tae-Ho, Kim / Senior Manager  
 ONETECH Corp.

Approved by  
 Ki-Hong, Nam / General Manager  
 ONETECH Corp.


## CONTENTS

	PAGE
<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
<b>2.1 PRODUCT DESCRIPTION.....</b>	<b>5</b>
<b>2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT. ....</b>	<b>10</b>
<b>3. EUT MODIFICATIONS.....</b>	<b>10</b>
<b>4. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>11</b>
<b>4.1 RF EXPOSURE CALCULATION .....</b>	<b>11</b>
<b>4.2 EUT DESCRIPTION.....</b>	<b>11</b>
<b>4.3 CALCULATED MPE SAFE DISTANCE FOR WLAN .....</b>	<b>12</b>
<b>4.3.1 DATA for Antenna 0.....</b>	<b>12</b>
<b>4.3.2 DATA for Antenna 1.....</b>	<b>13</b>
<b>4.3.3 DATA for Multiple Transmit.....</b>	<b>14</b>
<b>4.4 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH LE .....</b>	<b>16</b>
<b>4.5 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH .....</b>	<b>16</b>
<b>4.6 DATA FOR INTERMODULATION TRANSMIT .....</b>	<b>17</b>

**Revision History**

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-209-RWD-066	September 21, 2020	Initial Release	All

**1. VERIFICATION OF COMPLIANCE**

Applicant : Samsung Electronics Co Ltd  
 Address : 19 Chapin Rd., Building D, Pine Brook, New Jersey, 07058, United States  
 Contact Person : Youngjoong Noh / Principal Engineer  
 Telephone No. : +82-31-277-0598  
 FCC ID : A3LWCA732M  
 Model Name : WCA732M  
 Brand Name :   
 Serial Number : N/A  
 Date : September 21, 2020

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM Unlicensed National Information infrastructure(UNII)
E.U.T. DESCRIPTION	Modular Transmitter, Wi-Fi/BT Transceiver
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 FCC PART 15 SUBPART E Section 15.407 789033 D02 General UNII Test Procedures New Rules v02r01
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

## 2. GENERAL INFORMATION

### 2.1 Product Description

The Samsung Electronics Co Ltd, Model WCA732M (referred to as the EUT in this report) is a Wi-Fi/BT Transceiver. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Wi-Fi/BT Transceiver		
Temperature Range	-20 °C ~ 50 °C		
OPERATING FREQUENCY	Bluetooth LE	2 402 MHz ~ 2 480 MHz	
	Bluetooth	2 402 MHz ~ 2 480 MHz	
	WLAN 2.4 GHz	2 412 MHz ~ 2 472 MHz (802.11b/g/n(HT20))	
		2 422 MHz ~ 2 462 MHz (802.11n(HT40))	
	5 150 MHz ~ 5 250 MHz Band	5 180 MHz ~ 5 240 MHz (802.11a/n(HT20)/ac(VHT20))	
		5 190 MHz ~ 5 230 MHz (802.11n(HT40)/ac(VHT40))	
		5 210 MHz (802.11ac(VHT80))	
	5 250 MHz ~ 5 350 MHz Band	5 260 MHz ~ 5 320 MHz (802.11a/n(HT20)/ac(VHT20))	
		5 270 MHz ~ 5 310 MHz (802.11n(HT40)/ac(VHT40))	
		5 290 MHz (802.11ac(VHT80))	
	5 470 MHz ~ 5 725 MHz Band	5 500 MHz ~ 5 700 MHz (802.11a/n(HT20)/ac(VHT20))	
		5 510 MHz ~ 5 670 MHz (802.11n(HT40)/ac(VHT40))	
		5 530 MHz (802.11ac(VHT80))	
	5 725 MHz ~ 5 850 MHz Band	5 745 MHz ~ 5 825 MHz (802.11a/n(HT20)/ac(VHT20))	
5 755 MHz ~ 5 795 MHz (802.11n(HT40)/ac(VHT40))			
5 775 MHz (802.11ac(VHT80))			
MODULATION TYPE	Bluetooth LE	GFSK for 1 Mbps / 2 Mbps	
	Bluetooth	GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8-DPSK for 3Mbps	
	WLAN 2.4 GHz	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK)	
		802.11g/n(HT20)/n(HT40): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)	
	WLAN 5 GHz	802.11a/n(HT20)/n(HT40)/ac(VHT80): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)	

RF OUTPUT POWER	Bluetooth LE	1 Mbps	9.85 dBm
		2 Mbps	9.82 dBm
	Bluetooth	1 Mbps	9.93 dBm
		2 Mbps	9.60 dBm
		3 Mbps	9.67 dBm
	WLAN 2.4 GHz	Antenna 0	18.65 dBm(802.11b)
			15.81 dBm(802.11g)
			15.71 dBm(802.11n_HT20)
			13.39 dBm(802.11n_HT40)
		Antenna 1	18.55 dBm(802.11b)
15.40 dBm(802.11g)			
15.14 dBm(802.11n_HT20)			
Multiple Antenna	13.25 dBm(802.11n_HT40)		
	18.41 dBm(802.11g)		
		18.21 dBm(802.11n_HT20)	
		16.31 dBm(802.11n_HT40)	

RF OUTPUT POWER	5 150 MHz ~ 5 250 MHz Band	Antenna 0	12.21 dBm(802.11a) 11.95 dBm(802.11n_HT20) 10.15 dBm(802.11n_HT40) 9.97 dBm(802.11ac_VHT80)
		Antenna 1	12.42 dBm(802.11a) 12.11 dBm(802.11n_HT20) 10.14 dBm(802.11n_HT40) 9.84 dBm(802.11ac_VHT80)
		Multiple Antenna	15.33 dBm(802.11a) 15.01 dBm(802.11n_HT20) 13.16 dBm(802.11n_HT40) 12.92 dBm(802.11ac_VHT80)
	5 250 MHz ~ 5 350 MHz Band	Antenna 0	13.65 dBm(802.11a) 13.57 dBm(802.11n_HT20) 11.60 dBm(802.11n_HT40) 11.17 dBm(802.11ac_VHT80)
		Antenna 1	12.18 dBm(802.11a) 11.88 dBm(802.11n_HT20) 10.35 dBm(802.11n_HT40) 9.71 dBm(802.11ac_VHT80)
		Multiple Antenna	15.83 dBm(802.11a) 15.64 dBm(802.11n_HT20) 13.81 dBm(802.11n_HT40) 13.51 dBm(802.11ac_VHT80)

RF OUTPUT POWER	5 470 MHz ~ 5 725 MHz Band	Antenna 0	14.11 dBm(802.11a) 13.95 dBm(802.11n_HT20) 12.16 dBm(802.11n_HT40) 11.80 dBm(802.11ac_VHT80)
		Antenna 0_Straddle	12.10 dBm(802.11a) 12.27 dBm(802.11n_HT20) 10.69 dBm(802.11n_HT40) 11.65 dBm(802.11ac_VHT80)
		Antenna 1	11.16 dBm(802.11a) 10.89 dBm(802.11n_HT20) 11.38 dBm(802.11n_HT40) 10.95 dBm(802.11ac_VHT80)
		Antenna 1_Straddle	13.12 dBm(802.11a) 13.00 dBm(802.11n_HT20) 10.79 dBm(802.11n_HT40) 12.23 dBm(802.11ac_VHT80)
		Multiple Antenna	15.89 dBm(802.11a) 15.69 dBm(802.11n_HT20) 14.66 dBm(802.11n_HT40) 14.41 dBm(802.11ac_VHT80)
		Multiple Antenna _Straddle	15.65 dBm(802.11a) 15.66 dBm(802.11n_HT20) 13.75 dBm(802.11n_HT40) 14.96 dBm(802.11ac_VHT80)



RF OUTPUT POWER	5 725 MHz ~ 5 850 MHz Band	Antenna 0	13.21 dBm(802.11a) 12.93 dBm(802.11n_HT20) 11.03 dBm(802.11n_HT40) 10.95 dBm(802.11ac_VHT80)
		Antenna 0_Straddle	4.04 dBm(802.11a) 4.66 dBm(802.11n_HT20) -1.44 dBm(802.11n_HT40) -3.22 dBm(802.11ac_VHT80)
		Antenna 1	10.11 dBm(802.11a) 9.58 dBm(802.11n_HT20) 11.07 dBm(802.11n_HT40) 10.91 dBm(802.11ac_VHT80)
		Antenna 1_Straddle	5.07 dBm(802.11a) 5.45 dBm(802.11n_HT20) -1.40 dBm(802.11n_HT40) -2.70 dBm(802.11ac_VHT80)
		Multiple Antenna	14.88 dBm(802.11a) 14.58 dBm(802.11n_HT20) 14.06 dBm(802.11n_HT40) 13.94 dBm(802.11ac_VHT80)
		Multiple Antenna _Straddle	7.60 dBm(802.11a) 8.08 dBm(802.11n_HT20) 1.59 dBm(802.11n_HT40) 0.06 dBm(802.11ac_VHT80)

ANTENNA TYPE	Chip Antenna			
ANTENNA GAIN	Bluetooth LE	0.28 dBi		
	Bluetooth	0.28 dBi		
	WLAN 2.4 GHz	Antenna 0	1.80 dBi	
		Antenna 1	1.83 dBi	
		Multiple Antenna	4.83 dBi	
	5 150 MHz ~ 5 250 MHz Band	Antenna 0	-0.54 dBi	
		Antenna 1	-3.09 dBi	
		Multiple Antenna	1.38 dBi	
	5 250 MHz ~ 5 350 MHz Band	Antenna 0	0.00 dBi	
		Antenna 1	-1.42 dBi	
		Multiple Antenna	2.36 dBi	
	5 470 MHz ~ 5 725 MHz Band	Antenna 0	2.34 dBi	
		Antenna 1	0.37 dBi	
		Multiple Antenna	4.48 dBi	
	5 725 MHz ~ 5 850 MHz Band	Antenna 0	-0.30 dBi	
		Antenna 1	-1.37 dBi	
		Multiple Antenna	2.21 dBi	
	List of each Osc. or crystal Freq.(Freq. >= 1 MHz)		40 MHz	

**2.2 Alternative type(s)/model(s); also covered by this test report.**

-. None

**3. EUT MODIFICATIONS**

-. None

## 4. MAXIMUM PERMISSIBLE EXPOSURE

### 4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are  $f/1500$  mW/cm<sup>2</sup> for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm<sup>2</sup> for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm<sup>2</sup> exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm<sup>2</sup>, Z = Impedance of free space, 377 Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using  $P \text{ (mW)} = P \text{ (W)} / 1 000$ ,  $d \text{ (cm)} = 0.01 * d \text{ (m)}$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm<sup>2</sup>

### 4.2 EUT Description

Kind of EUT	Wi-Fi/BT Transceiver
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

### 4.3 Calculated MPE Safe Distance for WLAN

#### 4.3.1 DATA for Antenna 0

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
2 400 ~ 2 483.5	802.11b	18.65 ± 1.0	19.65	92.26	1.80	1.51	3.33	0.027 8	1
	802.11g	15.81 ± 1.0	16.81	47.97			2.40	0.014 4	1
	802.11n_HT20	15.71 ± 1.0	16.71	46.88			2.38	0.014 1	1
	802.11n_HT40	13.39 ± 1.0	14.39	27.48			1.82	0.008 3	1
5 150 ~ 5 250	802.11a	12.21 ± 1.0	13.21	20.94	-0.54	0.88	1.21	0.003 7	1
	802.11n_HT20	11.95 ± 1.0	12.95	19.72			1.18	0.003 5	1
	802.11n_HT40	10.15 ± 1.0	11.15	13.03			0.96	0.002 3	1
	802.11ac80	9.97 ± 1.0	10.97	12.50			0.94	0.002 2	1
5 250 ~ 5 350	802.11a	13.65 ± 1.0	14.65	29.17	0.00	1.00	1.52	0.005 8	1
	802.11n_HT20	13.57 ± 1.0	14.57	28.64			1.51	0.005 7	1
	802.11n_HT40	11.60 ± 1.0	12.60	18.20			1.20	0.003 6	1
	802.11ac80	11.17 ± 1.0	12.17	16.48			1.14	0.003 3	1
5 470 ~ 5 725	802.11a	14.11 ± 1.0	15.11	32.43	2.34	1.71	2.10	0.011 1	1
	802.11n_HT20	13.95 ± 1.0	14.95	31.26			2.06	0.010 7	1
	802.11n_HT40	12.16 ± 1.0	13.16	20.70			1.68	0.007 1	1
	802.11ac80	11.80 ± 1.0	12.80	19.05			1.61	0.006 5	1
5 725 ~ 5 850	802.11a	13.21 ± 1.0	14.21	26.36	-0.30	0.93	1.40	0.004 9	1
	802.11n_HT20	12.93 ± 1.0	13.93	24.72			1.35	0.004 6	1
	802.11n_HT40	11.03 ± 1.0	12.03	15.96			1.09	0.003 0	1
	802.11ac80	10.95 ± 1.0	11.95	15.67			1.08	0.002 9	1

According to above table, for 2 400 ~ 2483.5 MHz Band(802.11 b), safe distance,

$$D = 0.282 * \sqrt{(92.26 * 1.51)/1.00} = 3.33 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 92.26 * 1.51 / (4 * \pi * 20^2) = 0.027 8$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

### 4.3.2 DATA for Antenna 1

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
2 400 ~ 2 483.5	802.11b	18.55 ± 1.0	19.55	90.16	1.83	1.52	3.31	0.027 3	1
	802.11g	15.40 ± 1.0	16.40	43.65			2.30	0.013 2	1
	802.11n_HT20	15.14 ± 1.0	16.14	41.11			2.23	0.012 5	1
	802.11n_HT40	13.25 ± 1.0	14.25	26.61			1.80	0.008 1	1
5 150 ~ 5 250	802.11a	12.42 ± 1.0	13.42	21.98	-3.09	0.49	0.93	0.002 1	1
	802.11n_HT20	12.11 ± 1.0	13.11	20.46			0.89	0.002 0	1
	802.11n_HT40	10.14 ± 1.0	11.14	13.00			0.71	0.001 3	1
	802.11ac80	9.84 ± 1.0	10.84	12.13			0.69	0.001 2	1
5 250 ~ 5 350	802.11a	12.18 ± 1.0	13.18	20.80	-1.42	0.72	1.09	0.003 0	1
	802.11n_HT20	11.88 ± 1.0	12.88	19.41			1.05	0.002 8	1
	802.11n_HT40	10.35 ± 1.0	11.35	13.65			0.88	0.002 0	1
	802.11ac80	9.71 ± 1.0	10.71	11.78			0.82	0.001 7	1
5 470 ~ 5 725	802.11a	11.16 ± 1.0	12.16	16.44	0.37	1.09	1.19	0.003 6	1
	802.11n_HT20	10.89 ± 1.0	11.89	15.45			1.16	0.003 3	1
	802.11n_HT40	11.38 ± 1.0	12.38	17.30			1.22	0.003 7	1
	802.11ac80	10.95 ± 1.0	11.95	15.67			1.16	0.003 4	1
5 725 ~ 5 850	802.11a	10.11 ± 1.0	11.11	12.91	-1.37	0.73	0.87	0.001 9	1
	802.11n_HT20	9.58 ± 1.0	10.58	11.43			0.81	0.001 7	1
	802.11n_HT40	11.07 ± 1.0	12.07	16.11			0.97	0.002 3	1
	802.11ac80	10.91 ± 1.0	11.91	15.52			0.95	0.002 3	1

According to above table, for 2 400 ~ 2483.5 MHz Band(802.11 b), safe distance,

$$D = 0.282 * \sqrt{(90.16 * 1.52)/1.00} = 3.31 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 90.16 * 1.52 / (4 * \pi * 20^2) = 0.027 3$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

### 4.3.3 DATA for Multiple Transmit

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Sum Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)			
2 400 ~ 2 483.5	802.11g	15.81 ± 1.0	16.81	47.97	0.014 4	0.027 6	1.00
		15.40 ± 1.0	16.40	43.65	0.013 2		
	802.11n_ HT20	15.71 ± 1.0	16.71	46.88	0.014 1	0.026 6	1.00
		15.14 ± 1.0	16.14	41.11	0.012 5		
	802.11n_ HT40	13.39 ± 1.0	14.39	27.48	0.008 3	0.016 4	1.00
		13.25 ± 1.0	14.25	26.61	0.008 1		
5 150 ~ 5 250	802.11a	12.21 ± 1.0	13.21	20.94	0.003 7	0.005 8	1.00
		12.42 ± 1.0	13.42	21.98	0.002 1		
	802.11n_ HT20	11.95 ± 1.0	12.95	19.72	0.003 5	0.005 5	1.00
		12.11 ± 1.0	13.11	20.46	0.002 0		
	802.11n_ HT40	10.15 ± 1.0	11.15	13.03	0.002 3	0.003 6	1.00
		10.14 ± 1.0	11.14	13.00	0.001 3		
	802.11ac80	9.97 ± 1.0	10.97	12.50	0.002 2	0.003 4	1.00
		9.84 ± 1.0	10.84	12.13	0.001 2		
5 250 ~ 5 350	802.11a	13.65 ± 1.0	14.65	29.17	0.005 8	0.008 8	1.00
		12.18 ± 1.0	13.18	20.80	0.003 0		
	802.11n_ HT20	13.57 ± 1.0	14.57	28.64	0.005 7	0.008 5	1.00
		11.88 ± 1.0	12.88	19.41	0.002 8		
	802.11n_ HT40	11.60 ± 1.0	12.60	18.20	0.003 6	0.005 6	1.00
		10.35 ± 1.0	11.35	13.65	0.002 0		
	802.11ac80	11.17 ± 1.0	12.17	16.48	0.003 3	0.005 0	1.00
		9.71 ± 1.0	10.71	11.78	0.001 7		

5 470 ~ 5 725	802.11a	14.11 ± 1.0	15.11	32.43	0.011 1	0.014 7	1.00
		11.16 ± 1.0	12.16	16.44	0.003 6		
	802.11n_HT20	13.95 ± 1.0	14.95	31.26	0.010 7	0.001 4	1.00
		10.89 ± 1.0	11.89	15.45	0.003 3		
	802.11n_HT40	12.16 ± 1.0	13.16	20.70	0.007 1	0.010 8	1.00
		11.38 ± 1.0	12.38	17.30	0.003 7		
	802.11ac80	11.80 ± 1.0	12.80	19.05	0.006 5	0.009 9	1.00
		10.95 ± 1.0	11.95	15.67	0.003 4		
5 725 ~ 5 850	802.11a	13.21 ± 1.0	14.21	26.36	0.004 9	0.006 8	1.00
		10.11 ± 1.0	11.11	12.91	0.001 9		
	802.11n_HT20	12.93 ± 1.0	13.93	24.72	0.004 6	0.006 3	1.00
		9.58 ± 1.0	10.58	11.43	0.001 7		
	802.11n_HT40	11.03 ± 1.0	12.03	15.96	0.003 0	0.005 3	1.00
		11.07 ± 1.0	12.07	16.11	0.002 3		
	802.11ac80	10.95 ± 1.0	11.95	15.67	0.002 9	0.005 2	1.00
		10.91 ± 1.0	11.91	15.52	0.002 3		

WLAN 2 GHz(802.11 g) = (0.014 4/1) + (0.013 2/1) = 0.027 6

#### 4.4 Calculated MPE Safe Distance for Bluetooth LE

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	9.85 ± 1.0	10.85	12.16	0.28	1.07	1.02	0.002 6	1.00
	2 Mbps	9.82 ± 1.0	10.82	12.08			1.01	0.002 6	1.00

According to above table, for 2 402 ~ 2480 MHz Band(1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(12.16 * 1.07)/1.00} = 1.02 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 12.16 * 1.07 / (4 * \pi * 20^2) = 0.002 6$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

#### 4.5 Calculated MPE Safe Distance for Bluetooth

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	9.93 ± 1.0	10.93	12.39	0.28	1.07	1.03	0.002 6	1.00
	2 Mbps	9.60 ± 1.0	10.60	11.48			0.99	0.002 4	1.00
	3 Mbps	9.64 ± 1.0	10.64	11.59			0.99	0.002 5	1.00

According to above table, for 2 402 ~ 2480 MHz Band(1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(12.39 * 1.07)/1.00} = 1.03 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 12.39 * 1.07 / (4 * \pi * 20^2) = 0.002 6$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna



#### 4.6 DATA for Intermodulation Transmit

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Sum Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)			
Bluetooth + WLAN 2 G + WLAN 5 G	Bluetooth (1 Mbps)	9.93 ± 1.0	10.93	12.39	0.002 6	0.041 0	1.00
	WLAN 2 G (802.11 b_Ant 1)	18.55 ± 1.0	19.55	90.16	0.027 3		
	WLAN 5 G (UNII 2C 802.11 a Ant 0)	14.11 ± 1.0	15.11	32.43	0.011 1		
Bluetooth LE + WLAN 2 G + WLAN 5 G	Bluetooth LE (1 Mbps)	9.85 ± 1.0	10.85	12.16	0.002 6	0.041 0	1.00
	WLAN 2 G (802.11 b_Ant 1)	18.55 ± 1.0	19.55	90.16	0.027 3		
	WLAN 5 G (UNII 2C 802.11 a Ant 0)	14.11 ± 1.0	15.11	32.43	0.011 1		