19 Chapin Rd, Building D. Pine Brook, New Jersey

Fax No:-

## **MODULAR APPROVAL LETTER**

2020-11-23

Applicant: Samsung Electronics Co., Ltd.

FCC ID: A3LWCA942M

We would like to answer for Single Modular Approval in accordance with the requirement of rule part 15.212 as described below

No.	Requirements	Comment	Comply (Y/N)
1	The radio element of the modular transmitter has its own shielding	Refer to the external photo	Υ
2	The modular transmitter must have buffered modulation	All input to the modules are	Υ
	data/inputs (if such inputs are provided)  The modular transmitter must have its own power supply	buffered through microprocessor inputs.  Internal power regulators	
3	regulation.	Refer to the Block-diagram	Υ
4	The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204(c).	Refer to the internal photo	Υ
5	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing.	The EUT was tested in a standalone configuration via a SD extension cable Refer to the test setup photo	Y
6	The modular transmitter must be labeled with its own FCC ID.  If the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module	Refer to the user manual	Υ
7	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements	Refer to the user manual	Y
8	The modular transmitter must comply with any applicable RF exposure requirements	Refer to the RF exposure statement for more details.	Υ

Sincerely,

Youngjoong Noh / Staff Engineer Samsung Electronics Co., Ltd.