

# EMF TEST REPORT

**Test Report No.** : OT-21O-RWD-035  
**Reception No.** : 2110004558  
**Applicant** : Samsung Electronics Co Ltd  
**Address** : 19 Chapin Rd., Building D, Pine Brook, New Jersey, 07058, United States  
**Manufacturer** : Samsung Electronics Co Ltd  
**Address** : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do 16677, Korea  
**Type of Equipment** : Wi-Fi/BT Transceiver  
**FCC ID.** : A3LWCB731M  
**Model Name** : WCB731M  
**Multiple Model Name** : WCB730M, WCB737M, WCB736M  
**Serial number** : N/A  
**Total page of Report** : 17 pages (including this page)  
**Date of Incoming** : October 07, 2021  
**Date of issue** : October 25, 2021


## SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247 and FCC PART 15 SUBPART E Section 15.407*

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.





Tested by  
Youngyong Kim/ Assistant Manager  
ONETECH Corp.

Reviewed by  
Tae-Ho, Kim / Senior Manager  
ONETECH Corp.

Approved by  
Ki-Hong, Nam / General Manager  
ONETECH Corp.


## CONTENTS

	<b>PAGE</b>
<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
<b>2.1 PRODUCT DESCRIPTION.....</b>	<b>5</b>
<b>2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....</b>	<b>10</b>
<b>3. EUT MODIFICATIONS.....</b>	<b>10</b>
<b>4. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>11</b>
<b>4.1 RF EXPOSURE CALCULATION .....</b>	<b>11</b>
<b>4.2 EUT DESCRIPTION.....</b>	<b>11</b>
<b>4.3 CALCULATED MPE SAFE DISTANCE FOR WLAN.....</b>	<b>12</b>
<i>4.3.1 DATA for Antenna 0.....</i>	<i>12</i>
<i>4.3.2 DATA for Antenna 1.....</i>	<i>13</i>
<i>4.3.3 DATA for Multiple Transmit.....</i>	<i>14</i>
<b>4.4 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH LE .....</b>	<b>16</b>
<b>4.5 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH .....</b>	<b>16</b>
<b>4.6 DATA FOR INTERMODULATION TRANSMIT .....</b>	<b>17</b>

**Revision History**

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-21O-RWD-035	October 25, 2021	Initial Release	All

**1. VERIFICATION OF COMPLIANCE**

Applicant : Samsung Electronics Co Ltd  
 Address : 19 Chapin Rd., Building D, Pine Brook, New Jersey, 07058, United States  
 Contact Person : Jenni Chun / General Manager  
 Telephone No. : 973-808-6375  
 FCC ID : A3LWCB731M  
 Model Name : WCB731M  
 Brand Name :   
 Serial Number : N/A  
 Date : October 25, 2021

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM Unlicensed National Information infrastructure(UNII)
E.U.T. DESCRIPTION	Modular Transmitter, Wi-Fi/BT Transceiver
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2020
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 FCC PART 15 SUBPART E Section 15.407 789033 D02 General UNII Test Procedures New Rules v02r01
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

## 2. GENERAL INFORMATION

### 2.1 Product Description

The Samsung Electronics Co Ltd, Model WCB731M (referred to as the EUT in this report) is a Wi-Fi/BT Transceiver. The product specification described herein was obtained from product data sheet or user’s manual.

DEVICE TYPE	Wi-Fi/BT Transceiver		
Temperature Range	-20 °C ~ 50 °C		
OPERATING FREQUENCY	Bluetooth LE	2 402 MHz ~ 2 480 MHz	
	Bluetooth	2 402 MHz ~ 2 480 MHz	
	WLAN 2.4 GHz	2 412 MHz ~ 2 472 MHz (802.11b/g/n(HT20))	
		2 422 MHz ~ 2 462 MHz (802.11n(HT40))	
	WLAN 5 150 MHz ~ 5 250 MHz Band	5 180 MHz ~ 5 240 MHz (802.11a/n(HT20)/ac(VHT20))	
		5 190 MHz ~ 5 230 MHz (802.11n(HT40)/ac(VHT40))	
		5 210 MHz (802.11ac(VHT80))	
	WLAN 5 250 MHz ~ 5 350 MHz Band	5 260 MHz ~ 5 320 MHz (802.11a/n(HT20)/ac(VHT20))	
		5 270 MHz ~ 5 310 MHz (802.11n(HT40)/ac(VHT40))	
		5 290 MHz (802.11ac(VHT80))	
	WLAN 5 470 MHz ~ 5 725 MHz Band	5 500 MHz ~ 5 720 MHz (802.11a/n(HT20)/ac(VHT20))	
		5 510 MHz ~ 5 710 MHz (802.11n(HT40)/ac(VHT40))	
		5 530 MHz ~ 5 690 MHz (802.11ac(VHT80))	
	WLAN 5 725 MHz ~ 5 850 MHz Band	5 745 MHz ~ 5 825 MHz (802.11a/n(HT20)/ac(VHT20))	
5 755 MHz ~ 5 795 MHz (802.11n(HT40)/ac(VHT40))			
5 775 MHz (802.11ac(VHT80))			
MODULATION TYPE	Bluetooth LE	GFSK for 1 Mbps / 2 Mbps	
	Bluetooth	GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8-DPSK for 3Mbps	
	WLAN 2.4 GHz	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK)	
		802.11g/n(HT20)/n(HT40): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)	
	WLAN 5 GHz	802.11a/n(HT20)/n(HT40)/ac(VHT80): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)	

RF OUTPUT POWER	Bluetooth LE	1 Mbps	11.26 dBm		
		2 Mbps	11.25 dBm		
	Bluetooth	1 Mbps	11.26 dBm		
		2 Mbps	10.89 dBm		
		3 Mbps	11.19 dBm		
	WLAN 2.4 GHz	Antenna 0	17.30 dBm(802.11b)	11.15 dBm(802.11g)	
			10.75 dBm(802.11n_HT20)	9.49 dBm(802.11n_HT40)	
			Antenna 1	17.32 dBm(802.11b)	14.60 dBm(802.11g)
				14.31 dBm(802.11n_HT20)	13.54 dBm(802.11n_HT40)
		Multiple Antenna	16.22 dBm(802.11g)	15.90 dBm(802.11n_HT20)	
			14.98 dBm(802.11n_HT40)		
	WLAN 5 150 MHz ~ 5 250 MHz Band	Antenna 0	8.73 dBm(802.11a)	8.77 dBm(802.11n_HT20)	
			10.33 dBm(802.11n_HT40)	8.88 dBm(802.11ac_VHT80)	
			Antenna 1	9.02 dBm(802.11a)	8.88 dBm(802.11n_HT20)
				10.46 dBm(802.11n_HT40)	9.22 dBm(802.11ac_VHT80)
Multiple Antenna		11.79 dBm(802.11a)	11.69 dBm(802.11n_HT20)		
		13.27 dBm(802.11n_HT40)	12.06 dBm(802.11ac_VHT80)		

RF OUTPUT POWER	WLAN 5 250 MHz ~ 5 350 MHz Band	Antenna 0	9.82 dBm(802.11a) 9.67 dBm(802.11n_HT20) 9.69 dBm(802.11n_HT40) 10.53 dBm(802.11ac_VHT80)
		Antenna 1	9.12 dBm(802.11a) 9.05 dBm(802.11n_HT20) 8.95 dBm(802.11n_HT40) 10.35 dBm(802.11ac_VHT80)
		Multiple Antenna	12.40 dBm(802.11a) 12.27 dBm(802.11n_HT20) 12.35 dBm(802.11n_HT40) 13.45 dBm(802.11ac_VHT80)
	WLAN 5 470 MHz ~ 5 725 MHz Band	Antenna 0	9.83 dBm(802.11a) 9.80 dBm(802.11n_HT20) 10.16 dBm(802.11n_HT40) 10.28 dBm(802.11ac_VHT80)
		Antenna 0_Straddle	8.38 dBm(802.11a) 8.23 dBm(802.11n_HT20) 9.65 dBm(802.11n_HT40) 10.80 dBm(802.11ac_VHT80)
		Antenna 1	10.68 dBm(802.11a) 11.18 dBm(802.11n_HT20) 11.77 dBm(802.11n_HT40) 10.50 dBm(802.11ac_VHT80)
		Antenna 1_Straddle	11.29 dBm(802.11a) 11.07 dBm(802.11n_HT20) 12.29 dBm(802.11n_HT40) 14.30 dBm(802.11ac_VHT80)

RF OUTPUT POWER	WLAN 5 470 MHz ~ 5 725 MHz Band	Multiple Antenna	13.00 dBm(802.11a) 13.47 dBm(802.11n_HT20) 13.89 dBm(802.11n_HT40) 13.40 dBm(802.11ac_VHT80)
		Multiple Antenna _Straddle	13.08 dBm(802.11a) 12.89 dBm(802.11n_HT20) 14.18 dBm(802.11n_HT40) 15.90 dBm(802.11ac_VHT80)
	WLAN 5 725 MHz ~ 5 850 MHz Band	Antenna 0	8.85 dBm(802.11a) 8.93 dBm(802.11n_HT20) 7.67 dBm(802.11n_HT40) 7.83 dBm(802.11ac_VHT80)
		Antenna 0_Straddle	0.54 dBm(802.11a) 0.90 dBm(802.11n_HT20) -2.66 dBm(802.11n_HT40) -4.53 dBm(802.11ac_VHT80)
		Antenna 1	10.67 dBm(802.11a) 10.78 dBm(802.11n_HT20) 10.94 dBm(802.11n_HT40) 10.77 dBm(802.11ac_VHT80)
		Antenna 1_Straddle	3.53 dBm(802.11a) 3.78 dBm(802.11n_HT20) 0.13 dBm(802.11n_HT40) -0.95 dBm(802.11ac_VHT80)
		Multiple Antenna	12.86 dBm(802.11a) 12.77 dBm(802.11n_HT20) 12.62 dBm(802.11n_HT40) 12.55 dBm(802.11ac_VHT80)
		Multiple Antenna _Straddle	5.30 dBm(802.11a) 5.58 dBm(802.11n_HT20) 1.97 dBm(802.11n_HT40) 0.63 dBm(802.11ac_VHT80)



ANTENNA TYPE	Chip Antenna			
ANTENNA GAIN	Bluetooth LE	-0.44 dBi		
	Bluetooth	-0.44 dBi		
	WLAN 2.4 GHz	Antenna 0	1.54 dBi	
		Antenna 1	1.35 dBi	
		Multiple Antenna	4.46 dBi	
	5 150 MHz ~ 5 250 MHz Band	Antenna 0	1.00 dBi	
		Antenna 1	1.25 dBi	
		Multiple Antenna	4.14 dBi	
	5 250 MHz ~ 5 350 MHz Band	Antenna 0	1.53 dBi	
		Antenna 1	1.42 dBi	
		Multiple Antenna	4.49 dBi	
	5 470 MHz ~ 5 725 MHz Band	Antenna 0	1.51 dBi	
		Antenna 1	1.50 dBi	
		Multiple Antenna	4.52 dBi	
	5 725 MHz ~ 5 850 MHz Band	Antenna 0	0.86 dBi	
		Antenna 1	1.51 dBi	
		Multiple Antenna	4.21 dBi	
	List of each Osc. or crystal Freq.(Freq. >= 1 MHz)		40 MHz	

**2.2 Alternative type(s)/model(s); also covered by this test report.**

-. The following lists consist of the added model and their differences.

Model Name	Differences	Tested
WCB731M	Basic Model (2 MIC, IRB at the Top)	<input checked="" type="checkbox"/>
WCB730M	This model is identical to the basic model except for the removal of MIC.	<input type="checkbox"/>
WCB737M	This model is identical to the basic model except for the IRB at the Bottom	<input type="checkbox"/>
WCB736M	This model is identical to the basic model except for IRB at the Bottom and the removal of MIC	<input type="checkbox"/>

Note: 1. Applicant consigns only basic model to test. Therefore this test report just guarantees the units, which have been tested.

2. The Applicant/manufacturer is responsible for the compliance of all variants.

**3. EUT MODIFICATIONS**

-. None

## 4. MAXIMUM PERMISSIBLE EXPOSURE

### 4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are  $f/1500$  mW/cm<sup>2</sup> for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm<sup>2</sup> for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm<sup>2</sup> exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm<sup>2</sup>, Z = Impedance of free space, 377 Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using  $P \text{ (mW)} = P \text{ (W)} / 1 000$ ,  $d \text{ (cm)} = 0.01 * d \text{ (m)}$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm<sup>2</sup>

### 4.2 EUT Description

Kind of EUT	Wi-Fi/BT Transceiver
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

### 4.3 Calculated MPE Safe Distance for WLAN

#### 4.3.1 DATA for Antenna 0

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
2 400 ~ 2 483.5	802.11b	17.30 ± 1.0	18.30	67.61	1.54	1.43	2.77	0.019 2	1
	802.11g	11.15 ± 1.0	12.15	16.41			1.36	0.004 7	1
	802.11n_HT20	10.75 ± 1.0	11.75	14.96			1.30	0.004 2	1
	802.11n_HT40	9.49 ± 1.0	10.49	11.19			1.13	0.003 2	1
5 150 ~ 5 250	802.11a	8.73 ± 1.0	9.73	9.40	1.00	1.26	0.97	0.002 4	1
	802.11n_HT20	8.77 ± 1.0	9.77	9.48			0.97	0.002 4	1
	802.11n_HT40	10.33 ± 1.0	11.33	13.58			1.17	0.003 4	1
	802.11ac80	8.88 ± 1.0	9.88	9.73			0.99	0.002 4	1
5 250 ~ 5 350	802.11a	9.82 ± 1.0	10.82	12.08	1.53	1.42	1.17	0.003 4	1
	802.11n_HT20	9.67 ± 1.0	10.67	11.67			1.15	0.003 3	1
	802.11n_HT40	9.69 ± 1.0	10.69	11.72			1.15	0.003 3	1
	802.11ac80	10.53 ± 1.0	11.53	14.22			1.27	0.004 0	1
5 470 ~ 5 725	802.11a	9.83 ± 1.0	10.83	12.11	1.51	1.42	1.17	0.003 4	1
	802.11n_HT20	9.80 ± 1.0	10.80	12.02			1.16	0.003 4	1
	802.11n_HT40	10.16 ± 1.0	11.16	13.06			1.21	0.003 7	1
	802.11ac80	10.28 ± 1.0	11.28	13.43			1.23	0.003 8	1
5 725 ~ 5 850	802.11a	8.85 ± 1.0	9.85	9.66	0.86	1.22	0.97	0.002 3	1
	802.11n_HT20	8.93 ± 1.0	9.93	9.84			0.98	0.002 4	1
	802.11n_HT40	7.67 ± 1.0	8.67	7.36			0.84	0.001 8	1
	802.11ac80	7.83 ± 1.0	8.83	7.64			0.86	0.001 9	1

According to above table, for 2 400 ~ 2483.5 MHz Band(802.11 b), safe distance,

$$D = 0.282 * \sqrt{(67.61 * 1.43)/1.00} = 2.77 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 67.61 * 1.43 / (4 * \pi * 20^2) = 0.019 2$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

### 4.3.2 DATA for Antenna 1

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
2 400 ~ 2 483.5	802.11b	17.32 ± 1.0	18.32	67.92	1.35	1.36	2.71	0.018 4	1
	802.11g	14.60 ± 1.0	15.60	36.31			1.98	0.009 9	1
	802.11n_HT20	14.31 ± 1.0	15.31	33.96			1.92	0.009 2	1
	802.11n_HT40	13.54 ± 1.0	14.54	28.44			1.76	0.007 7	1
5 150 ~ 5 250	802.11a	9.02 ± 1.0	10.02	10.05	1.25	1.33	1.03	0.002 7	1
	802.11n_HT20	8.88 ± 1.0	9.88	9.73			1.02	0.002 6	1
	802.11n_HT40	10.46 ± 1.0	11.46	14.00			1.22	0.003 7	1
	802.11ac80	9.22 ± 1.0	10.22	10.52			1.06	0.002 8	1
5 250 ~ 5 350	802.11a	9.12 ± 1.0	10.12	10.28	1.42	1.39	1.06	0.002 8	1
	802.11n_HT20	9.05 ± 1.0	10.05	10.12			1.06	0.002 8	1
	802.11n_HT40	8.95 ± 1.0	9.95	9.89			1.04	0.002 7	1
	802.11ac80	10.35 ± 1.0	11.35	13.65			1.23	0.003 8	1
5 470 ~ 5 725	802.11a	10.68 ± 1.0	11.68	14.72	1.50	1.41	1.29	0.004 1	1
	802.11n_HT20	11.18 ± 1.0	12.18	16.52			1.36	0.004 6	1
	802.11n_HT40	11.77 ± 1.0	12.77	18.92			1.46	0.005 3	1
	802.11ac80	10.50 ± 1.0	11.50	14.13			1.26	0.004 0	1
5 725 ~ 5 850	802.11a	10.67 ± 1.0	11.67	14.69	1.51	1.42	1.29	0.004 1	1
	802.11n_HT20	10.78 ± 1.0	11.78	15.07			1.30	0.004 2	1
	802.11n_HT40	10.94 ± 1.0	11.94	15.63			1.33	0.004 4	1
	802.11ac80	10.77 ± 1.0	11.77	15.03			1.30	0.004 2	1

According to above table, for 2 400 ~ 2483.5 MHz Band(802.11 b), safe distance,

$$D = 0.282 * \sqrt{(67.92 * 1.36)/1.00} = 2.71 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 67.92 * 1.36 / (4 * \pi * 20^2) = 0.018 4$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

### 4.3.3 DATA for Multiple Transmit

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Sum Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)			
2 400 ~ 2 483.5	802.11g	11.15 ± 1.0	12.15	16.41	0.004 7	0.014 6	1.00
		14.60 ± 1.0	15.60	36.31	0.009 9		
	802.11n_HT20	10.75 ± 1.0	11.75	14.96	0.004 2	0.013 4	1.00
		14.31 ± 1.0	15.31	33.96	0.009 2		
	802.11n_HT40	9.49 ± 1.0	10.49	11.19	0.003 2	0.010 9	1.00
		13.54 ± 1.0	14.54	28.44	0.007 7		
5 150 ~ 5 250	802.11a	8.73 ± 1.0	9.73	9.4	0.002 4	0.005 1	1.00
		9.02 ± 1.0	10.02	10.05	0.002 7		
	802.11n_HT20	8.77 ± 1.0	9.77	9.48	0.002 4	0.005 0	1.00
		8.88 ± 1.0	9.88	9.73	0.002 6		
	802.11n_HT40	10.33 ± 1.0	11.33	13.58	0.003 4	0.007 1	1.00
		10.46 ± 1.0	11.46	14	0.003 7		
	802.11ac80	8.88 ± 1.0	9.88	9.73	0.002 4	0.005 2	1.00
		9.22 ± 1.0	10.22	10.52	0.002 8		
5 250 ~ 5 350	802.11a	9.82 ± 1.0	10.82	12.08	0.003 4	0.006 2	1.00
		9.12 ± 1.0	10.12	10.28	0.002 8		
	802.11n_HT20	9.67 ± 1.0	10.67	11.67	0.003 3	0.006 1	1.00
		9.05 ± 1.0	10.05	10.12	0.002 8		
	802.11n_HT40	9.69 ± 1.0	10.69	11.72	0.003 3	0.006 0	1.00
		8.95 ± 1.0	9.95	9.89	0.002 7		
	802.11ac80	10.53 ± 1.0	11.53	14.22	0.004 0	0.007 8	1.00
		10.35 ± 1.0	11.35	13.65	0.003 8		

5 470 ~ 5 725	802.11a	9.83 ± 1.0	10.83	12.11	0.003 4	0.007 5	1.00
		10.68 ± 1.0	11.68	14.72	0.004 1		
	802.11n_HT20	9.80 ± 1.0	10.8	12.02	0.003 4	0.008 0	1.00
		11.18 ± 1.0	12.18	16.52	0.004 6		
	802.11n_HT40	10.16 ± 1.0	11.16	13.06	0.003 7	0.009 0	1.00
		11.77 ± 1.0	12.77	18.92	0.005 3		
	802.11ac80	10.28 ± 1.0	11.28	13.43	0.003 8	0.007 8	1.00
		10.50 ± 1.0	11.5	14.13	0.004 0		
5 725 ~ 5 850	802.11a	8.85 ± 1.0	9.85	9.66	0.002 3	0.006 4	1.00
		10.67 ± 1.0	11.67	14.69	0.004 1		
	802.11n_HT20	8.93 ± 1.0	9.93	9.84	0.002 4	0.006 6	1.00
		10.78 ± 1.0	11.78	15.07	0.004 2		
	802.11n_HT40	7.67 ± 1.0	8.67	7.36	0.001 8	0.006 2	1.00
		10.94 ± 1.0	11.94	15.63	0.004 4		
	802.11ac80	7.83 ± 1.0	8.83	7.64	0.001 9	0.006 1	1.00
		10.77 ± 1.0	11.77	15.03	0.004 2		

WLAN 2 GHz(802.11 g) = (0.004 7/1) + (0.009 9/1) = 0.014 6

#### 4.4 Calculated MPE Safe Distance for Bluetooth LE

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	11.26 ± 1.0	12.26	16.83	-0.44	0.90	1.10	0.003 0	1
	2 Mbps	11.25 ± 1.0	12.25	16.79			1.10	0.003 0	1

According to above table, for 2 402 ~ 2480 MHz Band(1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(16.83 * 0.90)/1.00} = 1.10 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 16.83 * 0.90 / (4 * \pi * 20^2) = 0.003 0$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

#### 4.5 Calculated MPE Safe Distance for Bluetooth

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	11.26 ± 1.0	12.26	16.83	-0.44	0.90	1.10	0.003 0	1
	2 Mbps	10.89 ± 1.0	11.89	15.45			1.05	0.002 8	1
	3 Mbps	11.19 ± 1.0	12.19	16.56			1.09	0.003 0	1

According to above table, for 2 402 ~ 2480 MHz Band(1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(16.83 * 0.90)/1.00} = 1.10 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 16.83 * 0.90 / (4 * \pi * 20^2) = 0.003 0$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna



#### 4.6 DATA for Intermodulation Transmit

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Sum Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)			
Bluetooth + WLAN 2 G + WLAN 5 G	Bluetooth (1 Mbps)	11.26 ± 1.0	12.26	16.83	0.003 0	0.027 5	1.00
	WLAN 2 G (802.11 b_Ant 0)	17.30 ± 1.0	18.30	67.61	0.019 2		
	WLAN 5 G (UNII 2C 802.11 n_HT40 Ant 1)	11.77 ± 1.0	12.77	18.92	0.005 3		
Bluetooth LE + WLAN 2 G + WLAN 5 G	Bluetooth LE (2 Mbps)	11.26 ± 1.0	12.26	16.83	0.003 0	0.027 5	1.00
	WLAN 2 G (802.11 b_Ant 0)	17.30 ± 1.0	18.30	67.61	0.019 2		
	WLAN 5 G (UNII 2C 802.11 n_HT40 Ant 1)	11.77 ± 1.0	12.77	18.92	0.005 3		