

RADIO PERFORMANCE TEST REPORT

Test Report No. : OT-19D-RWD-053

AGR No. : A19NA-376

Applicant : Samsung Electronics Co Ltd

Address : 19 Chapin Rd., Building D, Pine Brook, New Jersey, 07058, United States

Manufacturer : Samsung Electronics Co., Ltd.

Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do 16677, Korea

Type of Equipment : Wi-Fi/BT Transceiver

FCC ID. : A3LWCT732M

Model Name : WCT732M

Serial number : N/A

Total page of Report : 20 pages (including this page)

Date of Incoming : November 29, 2019

Date of issue : December 16, 2019

SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247 and FCC PART 15 SUBPART E Section 15.407**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by: 

Yu-Seog Sim / Assistant Manager
ONETECH Corp.

Approved by: 

Jae-Ho Lee / Chief Engineer
ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	10
3. EUT MODIFICATIONS.....	10
4. MAXIMUM PERMISSIBLE EXPOSURE	11
4.1 RF EXPOSURE CALCULATION	11
4.2 EUT DESCRIPTION.....	11
4.3 CALCULATED MPE SAFE DISTANCE FOR WLAN.....	12
4.3.1 DATA for Antenna 0.....	12
4.3.2 DATA for Antenna 1.....	14
4.3.3 DATA for Multiple Transmit.....	16
4.4 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH LE	18
4.5 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH	19
4.6 DATA FOR INTERMODULATION TRANSMIT	20

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-19D-RWD-053	December 16, 2019	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : Samsung Electronics Co Ltd

Address : 19 Chapin Rd., Building D, Pine Brook, New Jersey, 07058, United States

Contact Person : Jenni Chun / General Engineer

Telephone No. : +82-31-277-2688

FCC ID : A3LWCT732M

Model Name : WCT732M

Brand Name : 

Serial Number : N/A

Date : December 16, 2019

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM Unlicensed National Information infrastructure(UNII)
E.U.T. DESCRIPTION	Modular Transmitter, Wi-Fi/BT Transceiver
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 FCC PART 15 SUBPART E Section 15.407 789033 D02 General UNII Test Procedures New Rules v02r01
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The Samsung Electronics Co Ltd, Model WCT732M (referred to as the EUT in this report) is a Wi-Fi/BT Transceiver. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Wi-Fi/BT Transceiver	
Temperature Range	-20 °C ~ 50 °C	
OPERATING FREQUENCY	Bluetooth LE	2 402 MHz ~ 2 480 MHz
	Bluetooth	2 402 MHz ~ 2 480 MHz
	WLAN 2.4 GHz	2 412 MHz ~ 2 472 MHz (802.11b/g/n(HT20))
		2 422 MHz ~ 2 462 MHz (802.11n(HT40))
	5 150 MHz ~ 5 250 MHz Band	5 180 MHz ~ 5 240 MHz (802.11a/n(HT20)/ac(VHT20))
		5 190 MHz ~ 5 230 MHz (802.11n(HT40)/ac(VHT40))
		5 210 MHz (802.11ac(VHT80))
	5 250 MHz ~ 5 350 MHz Band	5 260 MHz ~ 5 320 MHz (802.11a/n(HT20)/ac(VHT20))
		5 270 MHz ~ 5 310 MHz (802.11n(HT40)/ac(VHT40))
		5 290 MHz (802.11ac(VHT80))
	5 470 MHz ~ 5 725 MHz Band	5 500 MHz ~ 5 700 MHz (802.11a/n(HT20)/ac(VHT20))
		5 510 MHz ~ 5 670 MHz (802.11n(HT40)/ac(VHT40))
		5 530 MHz (802.11ac(VHT80))
	5 725 MHz ~ 5 850 MHz Band	5 745 MHz ~ 5 825 MHz (802.11a/n(HT20)/ac(VHT20))
		5 755 MHz ~ 5 795 MHz (802.11n(HT40)/ac(VHT40))
		5 775 MHz (802.11ac(VHT80))
MODULATION TYPE	Bluetooth LE	GFSK for 1 Mbps / 2 Mbps
	Bluetooth	GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8-DPSK for 3Mbps
	WLAN 2.4 GHz	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK)
		802.11g/n(HT20)/n(HT40): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)
	WLAN 5 GHz	802.11a/n(HT20)/n(HT40)/ac(VHT80): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)

RF OUTPUT POWER	Bluetooth LE	1 Mbps	12.27 dBm
		2 Mbps	12.26 dBm
	Bluetooth	1 Mbps	11.23 dBm
		2 Mbps	10.79 dBm
		3 Mbps	10.99 dBm
	WLAN 2.4 GHz	Antenna 0	19.25 dBm(802.11b) 15.07 dBm(802.11g) 14.01 dBm(802.11n_HT20) 12.23 dBm(802.11n_HT40)
		Antenna 1	20.53 dBm(802.11b) 16.02 dBm(802.11g) 14.99 dBm(802.11n_HT20) 13.61 dBm(802.11n_HT40)
		Multiple Antenna	18.53 dBm(802.11g) 17.49 dBm(802.11n_HT20) 15.95 dBm(802.11n_HT40)

RF OUTPUT POWER	5 150 MHz ~ 5 250 MHz Band	Antenna 0	11.73 dBm(802.11a) 10.58 dBm(802.11n_HT20) 9.20 dBm(802.11n_HT40) 8.70 dBm(802.11ac_VHT80)
		Antenna 1	11.46 dBm(802.11a) 10.27 dBm(802.11n_HT20) 8.87 dBm(802.11n_HT40) 8.43 dBm(802.11ac_VHT80)
		Multiple Antenna	14.61 dBm(802.11a) 13.44 dBm(802.11n_HT20) 12.05 dBm(802.11n_HT40) 11.58 dBm(802.11ac_VHT80)
	5 250 MHz ~ 5 350 MHz Band	Antenna 0	12.13 dBm(802.11a) 10.80 dBm(802.11n_HT20) 9.80 dBm(802.11n_HT40) 9.26 dBm(802.11ac_VHT80)
		Antenna 1	11.85 dBm(802.11a) 10.42 dBm(802.11n_HT20) 9.22 dBm(802.11n_HT40) 8.51 dBm(802.11ac_VHT80)
		Multiple Antenna	15.00 dBm(802.11a) 13.59 dBm(802.11n_HT20) 12.53 dBm(802.11n_HT40) 11.91 dBm(802.11ac_VHT80)

RF OUTPUT POWER	5 470 MHz ~ 5 725 MHz Band	Antenna 0	11.93 dBm(802.11a) 10.72 dBm(802.11n_HT20) 9.11 dBm(802.11n_HT40) 9.09 dBm(802.11ac_VHT80)
		Antenna 0_Straddle	10.89 dBm(802.11a) 10.44 dBm(802.11n_HT20) 9.48 dBm(802.11n_HT40) 8.78 dBm(802.11ac_VHT80)
		Antenna 1	12.09 dBm(802.11a) 11.10 dBm(802.11n_HT20) 9.45 dBm(802.11n_HT40) 9.20 dBm(802.11ac_VHT80)
		Antenna 1_Straddle	11.19 dBm(802.11a) 10.83 dBm(802.11n_HT20) 9.83 dBm(802.11n_HT40) 8.98 dBm(802.11ac_VHT80)
		Multiple Antenna	15.02 dBm(802.11a) 13.86 dBm(802.11n_HT20) 12.23 dBm(802.11n_HT40) 12.16 dBm(802.11ac_VHT80)
		Multiple Antenna _Straddle	14.05 dBm(802.11a) 13.65 dBm(802.11n_HT20) 12.67 dBm(802.11n_HT40) 11.89 dBm(802.11ac_VHT80)

RF OUTPUT POWER	5 725 MHz ~ 5 850 MHz Band	Antenna 0	11.98 dBm(802.11a) 10.75 dBm(802.11n_HT20) 9.56 dBm(802.11n_HT40) 9.15 dBm(802.11ac_VHT80)
		Antenna 0_Straddle	3.57 dBm(802.11a) 3.57 dBm(802.11n_HT20) -1.86 dBm(802.11n_HT40) -5.51 dBm(802.11ac_VHT80)
		Antenna 1	12.16 dBm(802.11a) 11.39 dBm(802.11n_HT20) 10.02 dBm(802.11n_HT40) 9.80 dBm(802.11ac_VHT80)
		Antenna 1_Straddle	4.09 dBm(802.11a) 3.89 dBm(802.11n_HT20) -1.53 dBm(802.11n_HT40) -5.42 dBm(802.11ac_VHT80)
		Multiple Antenna	15.08 dBm(802.11a) 14.09 dBm(802.11n_HT20) 12.81 dBm(802.11n_HT40) 12.50 dBm(802.11ac_VHT80)
		Multiple Antenna _Straddle	6.85 dBm(802.11a) 6.74 dBm(802.11n_HT20) 1.32 dBm(802.11n_HT40) -2.45 dBm(802.11ac_VHT80)

ANTENNA TYPE	Chip Antenna		
ANTENNA GAIN	Bluetooth LE	-0.94 dBi	
	Bluetooth	-0.94 dBi	
	WLAN 2.4 GHz	Antenna 0	2.01 dBi
		Antenna 1	2.06 dBi
		Multiple Antenna	5.05 dBi
	5 150 MHz ~ 5 250 MHz Band	Antenna 0	0.92 dBi
		Antenna 1	1.24 dBi
		Multiple Antenna	4.09 dBi
	5 250 MHz ~ 5 350 MHz Band	Antenna 0	1.79 dBi
		Antenna 1	2.66 dBi
		Multiple Antenna	5.25 dBi
	5 470 MHz ~ 5 725 MHz Band	Antenna 0	2.73 dBi
		Antenna 1	1.72 dBi
		Multiple Antenna	5.25 dBi
	5 725 MHz ~ 5 850 MHz Band	Antenna 0	1.71 dBi
		Antenna 1	0.69 dBi
		Multiple Antenna	4.23 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)		40 MHz	

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500 \text{ mW/cm}^2$ for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm^2 for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm^2 exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm^2 , Z = Impedance of free space, 377Ω

E = Electric field strength in V/m , G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm , using $P (\text{mW}) = P (\text{W}) / 1 000$, $d (\text{cm}) = 0.01 * d (\text{m})$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm , P = Power in mW , G = Numeric antenna gain, and S = Power density in mW/cm^2

4.2 EUT Description

Kind of EUT	Wi-Fi/BT Transceiver
Device Category	☐ Portable (< 20 cm separation) ☐ Mobile (> 20 cm separation) ☒ Others
Exposure Evaluation Applied	☒ MPE ☐ SAR ☐ N/A

4.3 Calculated MPE Safe Distance for WLAN

4.3.1 DATA for Antenna 0

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/ cm ²)
		(dBm)	(dBm)	(mW)	Log	Linear			
2 400 ~ 2 483.5	802.11b	19.25 ± 0.5	19.75	94.41	2.01	1.589	3.45	0.029 8	1.00
	802.11g	15.07 ± 0.5	15.57	36.06			2.13	0.011 4	1.00
	802.11n_HT20	14.01 ± 0.5	14.51	28.25			1.89	0.008 9	1.00
	802.11n_HT40	12.23 ± 0.5	12.73	18.75			1.54	0.005 9	1.00
5 150 ~ 5 250	802.11a	11.73 ± 0.5	12.23	16.71	0.92	1.236	1.28	0.004 1	1.00
	802.11n_HT20	10.58 ± 0.5	11.08	12.82			1.12	0.003 2	1.00
	802.11n_HT40	9.20 ± 0.5	9.70	9.33			0.96	0.002 3	1.00
	802.11ac80	8.70 ± 0.5	9.20	8.32			0.90	0.002 0	1.00
5 250 ~ 5 350	802.11a	12.13 ± 0.5	12.63	18.32	1.79	1.510	1.48	0.005 5	1.00
	802.11n_HT20	10.80 ± 0.5	11.30	13.49			1.27	0.004 1	1.00
	802.11n_HT40	9.80 ± 0.5	10.30	10.72			1.13	0.003 2	1.00
	802.11ac80	9.26 ± 0.5	9.76	9.46			1.07	0.002 8	1.00

5 470 ~ 5 725	802.11a	11.98 ± 0.5	12.48	17.70	2.73	1.875	1.50	0.005 6	1.00
	802.11n_HT20	10.72 ± 0.5	11.22	13.24			1.41	0.004 9	1.00
	802.11n_HT40	9.11 ± 0.5	9.61	9.14			1.17	0.003 4	1.00
	802.11ac80	9.09 ± 0.5	9.59	9.10			1.16	0.003 4	1.00
5 725 ~ 5 850	802.11a	11.91 ± 0.5	12.41	17.42	1.71	1.483	1.43	0.005 1	1.00
	802.11n_HT20	10.75 ± 0.5	11.25	13.34			1.25	0.003 9	1.00
	802.11n_HT40	9.56 ± 0.5	10.06	10.14			1.09	0.003 0	1.00
	802.11ac80	9.15 ± 0.5	9.65	9.23			1.04	0.002 7	1.00

According to above table, for 2 400 ~ 2483.5 MHz Band(802.11 b), safe distance,

$$D = 0.282 * \sqrt{(94.41 * 1.589)/1.00} = 3.45 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 94.41 * 1.589 / (4 * 3.14 * 20^2) = 0.029 8$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna



Tested by: Ha-Ram, Lee / Assistant Manager

4.3.2 DATA for Antenna 1

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
		(dBm)	(dBm)	(mW)	Log	Linear			
2 400 ~ 2 483.5	802.11b	20.53 ± 0.5	21.03	126.77	2.06	1.607	4.02	0.040 5	1.00
	802.11g	16.02 ± 0.5	16.52	44.87			2.39	0.014 3	1.00
	802.11n_HT20	14.99 ± 0.5	15.49	35.40			2.13	0.011 3	1.00
	802.11n_HT40	13.61 ± 0.5	14.11	25.76			1.81	0.008 2	1.00
5 150 ~ 5 250	802.11a	11.46 ± 0.5	11.96	15.70	1.24	1.330	1.29	0.004 2	1.00
	802.11n_HT20	10.27 ± 0.5	10.77	11.94			1.12	0.003 2	1.00
	802.11n_HT40	8.87 ± 0.5	9.37	8.65			0.96	0.002 3	1.00
	802.11ac80	8.43 ± 0.5	8.93	7.82			0.91	0.002 1	1.00
5 250 ~ 5 350	802.11a	11.85 ± 0.5	12.35	17.18	2.66	1.845	1.59	0.006 3	1.00
	802.11n_HT20	10.42 ± 0.5	10.92	12.36			1.35	0.004 5	1.00
	802.11n_HT40	9.22 ± 0.5	9.72	9.38			1.17	0.003 4	1.00
	802.11ac80	8.51 ± 0.5	9.01	7.96			1.08	0.002 9	1.00

5 470 ~ 5 725	802.11a	12.09 ± 0.5	12.59	18.16	1.72	1.486	1.46	0.005 4	1.00
	802.11n_HT20	11.10 ± 0.5	11.60	14.45			1.28	0.004 1	1.00
	802.11n_HT40	9.45 ± 0.5	9.95	9.89			1.08	0.002 9	1.00
	802.11ac80	9.20 ± 0.5	9.70	9.33			1.05	0.002 8	1.00
5 725 ~ 5 850	802.11a	12.16 ± 0.5	12.66	18.45	0.69	1.172	1.30	0.004 2	1.00
	802.11n_HT20	11.39 ± 0.5	11.89	15.45			1.20	0.003 6	1.00
	802.11n_HT40	10.02 ± 0.5	10.52	11.27			1.03	0.002 6	1.00
	802.11ac80	9.80 ± 0.5	10.30	10.72			1.00	0.002 5	1.00

According to above table, for 2 400 ~ 2483.5 MHz Band(802.11 b), safe distance,

$$D = 0.282 * \sqrt{(126.77 * 1.607)/1.00} = 4.02 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 126.77 * 1.607 / (4 * 3.14 * 20^2) = 0.040 5$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna



Tested by: Ha-Ram, Lee / Assistant Manager

4.3.3 DATA for Multiple Transmit

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance	Max tune up power		Power Density (mW/cm ²) @ 20 cm Separation	Sum Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/ cm ²)
		(dBm)	(dBm)	(mW)			
2 400 ~ 2 483.5	802.11g	15.07 ± 0.5	15.57	36.06	0.011 4	0.025 7	1.00
		16.02 ± 0.5	16.52	44.87	0.014 3		
	802.11n_ HT20	14.01 ± 0.5	14.51	28.25	0.008 9	0.020 2	1.00
		14.99 ± 0.5	15.49	35.40	0.011 3		
	802.11n_ HT40	12.23 ± 0.5	12.73	18.75	0.005 9	0.014 1	1.00
		13.61 ± 0.5	14.11	25.76	0.008 2		
5 150 ~ 5 250	802.11a	11.73 ± 0.5	12.23	16.71	0.004 1	0.008 3	1.00
		11.46 ± 0.5	11.96	15.70	0.004 2		
	802.11n_ HT20	10.58 ± 0.5	11.08	12.82	0.003 2	0.006 4	1.00
		10.27 ± 0.5	10.77	11.94	0.003 2		
	802.11n_ HT40	9.20 ± 0.5	9.70	9.33	0.002 3	0.004 6	1.00
		8.87 ± 0.5	9.37	8.65	0.002 3		
	802.11ac80	8.70 ± 0.5	9.20	8.32	0.002 0	0.004 1	1.00
		8.43 ± 0.5	8.93	7.82	0.002 1		
5 250 ~ 5 350	802.11a	12.13 ± 0.5	12.63	18.32	0.005 5	0.011 8	1.00
		11.85 ± 0.5	12.35	17.18	0.006 3		
	802.11n_ HT20	10.80 ± 0.5	11.30	13.49	0.004 1	0.008 6	1.00
		10.42 ± 0.5	10.92	12.36	0.004 5		
	802.11n_ HT40	9.80 ± 0.5	10.30	10.72	0.003 2	0.006 6	1.00
		9.22 ± 0.5	9.72	9.38	0.003 4		
	802.11ac80	9.26 ± 0.5	9.76	9.46	0.002 8	0.005 7	1.00
		8.51 ± 0.5	9.01	7.96	0.002 9		

5 470 ~ 5 725	802.11a	11.93 ± 0.5	12.43	17.50	0.006 5	0.011 9	1.00
		12.09 ± 0.5	12.59	18.16	0.005 4		
	802.11n_HT20	10.72 ± 0.5	11.22	13.24	0.004 9	0.009 0	1.00
		11.10 ± 0.5	11.60	14.45	0.004 1		
	802.11n_HT40	9.11 ± 0.5	9.61	9.14	0.003 4	0.006 3	1.00
		9.45 ± 0.5	9.95	9.89	0.002 9		
	802.11ac80	9.09 ± 0.5	9.59	9.10	0.003 4	0.006 2	1.00
		9.20 ± 0.5	9.70	9.33	0.002 8		
5 725 ~ 5 850	802.11a	11.98 ± 0.5	12.48	17.70	0.005 6	0.009 8	1.00
		12.16 ± 0.5	12.66	18.45	0.004 2		
	802.11n_HT20	10.75 ± 0.5	11.25	13.34	0.003 9	0.007 5	1.00
		11.39 ± 0.5	11.89	15.45	0.003 6		
	802.11n_HT40	9.56 ± 0.5	10.06	10.14	0.003 0	0.005 6	1.00
		10.02 ± 0.5	10.52	11.27	0.002 6		
	802.11ac80	9.15 ± 0.5	9.65	9.23	0.002 7	0.005 2	1.00
		9.80 ± 0.5	10.30	10.72	0.002 5		

WLAN 2.4 GHz (802.11 g) = (0.011 4/1) + (0.014 3/1) = 0.025 7



Tested by: Ha-Ram, Lee / Assistant Manager

4.4 Calculated MPE Safe Distance for Bluetooth LE

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
		(dBm)	(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	12.27 ± 0.5	12.77	18.92	-0.94	0.805	1.10	0.003 0	1.00
	2 Mbps	12.26 ± 0.5	12.76	18.88			1.10	0.003 0	1.00

According to above table, for 2 402 ~ 2480 MHz Band(1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(18.92 * 0.805)/1.00} = 1.10 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 15.85 * 0.94 / (4 * 3.14 * 20^2) = 0.003 0$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna



Tested by: Ha-Ram, Lee / Assistant Manager

4.5 Calculated MPE Safe Distance for Bluetooth

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
		(dBm)	(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	11.23 ± 0.5	11.73	14.89	-0.94	0.805	0.98	0.002 4	1.00
	2 Mbps	10.79 ± 0.5	11.29	13.46			0.93	0.002 2	1.00
	3 Mbps	10.99 ± 0.5	11.49	14.09			0.95	0.002 3	1.00

According to above table, for 2 402 ~ 2480 MHz Band(1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(14.89 * 0.805)/1.00} = 0.98 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 14.89 * 0.94 / (4 * 3.14 * 20^2) = 0.002 4$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna



Tested by: Ha-Ram, Lee / Assistant Manager

4.6 DATA for Intermodulation Transmit

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance	Max tune up power		Power Density (mW/cm ²) @ 20 cm Separation	Sum Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
		(dBm)	(dBm)	(mW)			
Bluetooth + WLAN 2 G + WLAN 5 G	Bluetooth (1 Mbps)	11.23 ± 0.5	11.73	14.89	0.002 4	0.049 4	1.00
	WLAN 2.4 G (802.11 b_Ant 1)	20.53 ± 0.5	21.03	126.77	0.040 5		
	WLAN 5 G UNII 2C (802.11a Ant 0)	11.93 ± 0.5	12.43	17.50	0.006 5		
Bluetooth LE + WLAN 2 G + WLAN 5 G	Bluetooth LE (1 Mbps)	12.27 ± 0.5	12.77	18.92	0.003 0	0.050 0	1.00
	WLAN 2.4 G (802.11 b_Ant 1)	20.53 ± 0.5	21.03	126.77	0.040 5		
	WLAN 5 G (UNII 2A 802.11 a Ant 1)	11.93 ± 0.5	12.43	17.50	0.006 5		



Tested by: Ha-Ram, Lee / Assistant Manager