

FCC Part 15 EMI TEST REPORT

of

E.U.T. : Bluetooth headset

MODEL : WEP130DSE

FCC ID. : A3LWEP130DSE

for

APPLICANT : Samsung Electronics CO., Ltd.

ADDRESS : 9th F1, Samsung Main Bldg. 250, 2-Ka, Taepyung-Ro,
Chung-Ku, Seoul, Korea 100-742

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN
NO. 8 LANE 29, WENMIMG ROAD,
LOSHAN TSUN, KWEISHAN HSIANG,
TAOYUAN, TAIWAN, R.O.C.

Tel:(03)3280026#570~576

Fax:(03)3276188

Report Number : ET92S-08-174-01

TEST REPORT CERTIFICATION

Applicant : Samsung Electronics CO., Ltd.
9th F1, Samsung Main Bldg. 250, 2-Ka, Taepyung-Ro, Chung-Ku, Seoul, Korea
100-742

Manufacturer : Samsung Electronics CO., Ltd.
9th F1, Samsung Main Bldg. 250, 2-Ka, Taepyung-Ro, Chung-Ku, Seoul, Korea
100-742

Description of EUT :

- a) Type of EUT : Bluetooth headset
- b) Trade Name : Samsung Bluetooth Headset
- c) Model No. : WEP130DSE
- d) Power Supply : 3.80VDC (Rechargeable Battery)
AC Adaptor (SAMSUNG/TAD037EBE)
Input: 100-240VAC, 50/60Hz ; Output: 5VDC, 0.7A

Regulation Applied : FCC Rules and Regulations Part 15 Subpart B & C (2003)

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

- Note: 1. The result of the testing report relate only to the item tested.
2. The testing report shall not be reproduced expect in full, without the written approval of ETC.

Issued Date : Sep. 13, 2003

Test Engineer : 

Approve & Authorized Signer : 

Signature

Win-Po Tsai

Manager of EMC Testing Department

Electronics Testing Center, Taiwan

Table of Contents	Page
1 GENERAL INFORMATION	1
1.1 Product Description	1
1.2 Characteristics of Device	1
1.3 Test Methodology	1
1.4 Modification List of EUT	1
1.5 Test Facility	1
2 PROVISIONS APPLICABLE	2
2.1 Definition	2
2.2 Requirement for Compliance	3
2.3 Restricted Bands of Operation	5
2.4 Labeling Requirement	5
2.5 User Information	6
3. SYSTEM TEST CONFIGURATION	7
3.1 Justification	7
3.2 Devices for Tested System	7
4 RADIATED EMISSION MEASUREMENT	8
4.1 Applicable Standard	8
4.2 Measurement Procedure	8
4.3 Measuring Instrument	10
4.4 Radiated Emission Data	11
4.4.1 RF Portion	11
4.4.2 Other Emission	20
4.5 Field Strength Calculation	21
4.6 Photos of Radiation Measuring Setup	22

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : Bluetooth headset
- b) Trade Name : Samsung Bluetooth Headset
- c) Model No. : WEP130DSE
- d) Power Supply : 3.80VDC (Rechargeable Battery)
AC Adaptor (SAMSUNG/TAD037EBE)
Input: 100-240VAC, 50/60Hz ; Output: 5VDC, 0.7A

1.2 Characteristics of Device

The EUT is a Bluetooth headset.

1.3 Test Methodology

The Bluetooth headset designed with a transmitting method of Frequency Hopping spread spectrum, which operates at 2.4 GHz ISM band. The rated output power is 1.83 dBm (1.524 mW).

1.4 Modification List of EUT

No modifications were required. (That is the EUT complied with the requirements as tested.)

1.5 Test Facility

The semi-anechoic chamber and conducted measurement facility used to collect the radiated and conducted data are located inside the Building at No.8, Lane 29, Wen-ming Road, Lo-shan Tsun, Kweishan Hsiang, Taoyuan, Taiwan, R.O.C.

This site has been accreditation as a FCC filing site.

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business or industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following:

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

*Decreases with the logarithm of the frequency.

For intentional device, according to § 15.207(a) Line Conducted Emission Limits is same as above table.

(2) Radiated Emission Requirement

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

(4) 20dB Bandwidth Requirement

For frequency hopping systems, according to 15.247(a)(1), hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

(5) Output Power Requirement

For frequency hopping systems, according to 15.247(1), operating in the 2400-2483.5MHz band employing at least 75 hopping channels. The maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(6) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in § 15.209(a), whichever results in the lesser attenuation.

(7) Number of Hopping Channels

According to 15.247(b)(1), for frequency hopping systems, operating in the 2400-2483.5MHz band employing at least 75 hopping channels.

(8) Channel Carrier Frequencies Separation

According to 15.247(a)(1)(iii), the frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

(9) Dwell Time

According to 15.247(a)(1)(iii), frequency hopping system in the 2400-2483.5MHz band employing at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 second multiplied by the number of hopping channels employed.

(10) RF Exposure Evaluation

According to 15.247(b)(5), system operating under the provisions of this section(15.247) shall operated in a manner that ensures that the public is not exposed to radio frequency levels in excess of the commission guidelines, 1.1307(b)(1)

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

3. SYSTEM TEST CONFIGURATION


3.1 Justification

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT during the test. Notebook computer was used to control the RF channel under the highest, middle and lowest frequency and transmit the maximum RF power. Customer would not normally use it. But nevertheless Ancillary Equipment can influence the test results.

3.2 Devices for Tested System

Device	Manufacture	Model	Cable Description
*Bluetooth headset	Samsung	WEP130DSE	1.8m, Unshielded Power Line (Adaptor)
Notebook PC	ASUS	L7300/L7200	1.8m, Unshielded Power Line (Adaptor) 0.3m, Unshielded RS-232 Cable
Test Jig	Samsung	----	2.0m, Unshielded Control Cable
DC Power Supply	GW	GPC-3030D	1.8m, Unshielded Power Line

Remark “*” means equipment under test.



4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with § 15.109(a).

For intentional radiators, according to § 15.247 (a), operation under this provision is limited to frequency hopping and frequency hopping spread spectrum, and the out band emission shall be comply with § 15.247 (c)

4.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
2. For emission frequencies measured below 1 GHz, it is performed in a semi-anechoic chamber to determine the accurate frequencies of higher emissions. For emission frequencies measured above 1 GHz, a pre-scan be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.

Note : A band pass filter was used to avoid pre-amplifier saturated when measure TX operation mode in frequency band above 1 GHz.

5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the datarate, placement of ANT. cables associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement :

Equipment	Manufacturer	Model No.	Next Cal. Due
EMI Test Receiver	Hewlett-Packard	8546A	08/27/2004
Horn Antenna	EMCO	3115	06/05/2004
LogBicone Antenna	Schwarzbeck	9160	10/28/2003
Horn Antenna	EMCO	3116	06/28/2004
Preamplifier	Hewlett-Packard	8449B	09/04/2004
Spectrum Analyzer	Hewlett-Packard	8564EC	09/10/2004

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

4.4 Radiated Emission Data

4.4.1 RF Portion

a) Channel 1

EUT azimuth : x axis

Operation Mode : Transmitting

Fundamental Frequency : 2402 MHz

Test Date : Sep. 9, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave.			
4804.000	46.8	---	46.7	---	4.5	51.3	---	74.0	54.0	2.7	180	1.0
7206.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9608.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12010.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14412.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
16814.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19216.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21618.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24020.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

EUT azimuth : y axis

Operation Mode : Receiving

Fundamental Frequency : 2402 MHz

Test Date : Sep. 9, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m) Peak Ave (H/V Max.)		Limit @3m (dBUV/m) Peak Ave.		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave.			
4804.000	46.5	---	46.4	---	4.5	51.0	---	74.0	54.0	2.0	180	1.0
7206.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9608.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12010.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14412.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
16814.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19216.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21618.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24020.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

EUT azimuth : z axis

Operation Mode : Transmitting

Fundamental Frequency : 2402 MHz

Test Date : Sep. 9, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m) Peak Ave (H/V Max.)		Limit @3m (dBUV/m) Peak Ave.		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	Ave	V Peak	Ave		Peak	Ave	Peak	Ave.			
4804.000	46.4	---	46.1	---	4.5	50.9	---	74.0	54.0	3.1	180	1.0
7206.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9608.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12010.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14412.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
16814.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19216.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21618.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24020.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

b) Channel 40

EUT azimuth : x axis

Operation Mode : Transmitting

Fundamental Frequency : 2441 MHz

Test Date : Sep. 9, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	Ave	V Peak	Ave		Peak	Ave	Peak	Ave.			
4882.000	48.0	---	47.0	---	4.5	52.5	---	74.0	54.0	1.5	180	1.0
7323.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9764.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12205.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14646.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17087.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19528.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21969.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24410.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

EUT azimuth : y axis

Operation Mode : Transmitting

Fundamental Frequency : 2441 MHz

Test Date : Sep. 9, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m) Peak Ave (H/V Max.)		Limit @3m (dBUV/m) Peak Ave.		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave.			
4882.000	47.6	---	46.7	---	4.5	52.1	---	74.0	54.0	1.9	180	1.0
7323.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9764.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12205.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14646.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17087.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19528.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21969.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24410.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

EUT azimuth : z axis

Operation Mode : Transmitting

Fundamental Frequency : 2441 MHz

Test Date : Sep. 9, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m) Peak Ave (H/V Max.)		Limit @3m (dBUV/m) Peak Ave.		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave.			
4882.000	46.6	---	45.9	---	4.5	51.1	---	74.0	54.0	3.9	180	1.0
7323.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9764.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12205.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14646.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17087.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19528.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21969.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24410.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

c) Channel 79

EUT azimuth : x axis

Operation Mode : Transmitting

Fundamental Frequency : 2480 MHz

Test Date : Sep. 9, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave.			
4960.000	48.3	---	46.5	---	4.5	52.8	---	74.0	54.0	1.2	180	1.0
7440.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9920.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12400.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14880.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17360.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19840.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
22320.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24800.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

EUT azimuth : y axis

Operation Mode : Transmitting

Fundamental Frequency : 2480 MHz

Test Date : Sep. 9, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m) Peak Ave (H/V Max.)		Limit @3m (dBUV/m) Peak Ave.		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave.			
4960.000	47.9	---	46.2	---	4.5	52.4	---	74.0	54.0	1.6	180	1.0
7440.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9920.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12400.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14880.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17360.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19840.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
22320.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24800.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

EUT azimuth : z axis

Operation Mode : Transmitting

Fundamental Frequency : 2480 MHz

Test Date : Sep. 9, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave.			
	Peak	Ave	Peak	Ave		Peak	Ave	Peak	Ave.			
4960.000	48.0	---	47.0	---	4.5	52.5	---	74.0	54.0	1.5	180	1.0
7440.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9920.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12400.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14880.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17360.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19840.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
22320.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24800.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

4.4.2 Other Emission

a) Operation Mode: Receiving / Transmitting Mode

Test Date : Sep. 9, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
87.230	V	22.5	10.1	32.6	40.0	-7.4	185	1.0
286.080	V	16.3	16.5	32.8	46.0	-13.2	144	1.0
339.430	H	16.8	17.5	34.3	46.0	-11.7	186	1.0
436.430	V	15.7	20.6	36.3	46.0	-9.7	86	1.0
504.330	H	13.1	22.3	35.4	46.0	-10.6	170	1.0
706.090	V	12.9	26.6	39.5	46.0	-6.5	180	1.0
706.090	H	11.8	26.6	38.4	46.0	-7.6	180	1.0

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark "---" means that the emissions level is too low to be measured.
3. Item "Margin" referred to Q.P. limit while there is only peak result.
4. *The EUT is a body worn device. In order to get the worse data, EUT direction (X, Y, Z axes) were adjusted during the prescan measurement. For final measurement, EUT was setup under the maximum emission direction.*

b) Operation Mode: Charge Mode

Test Date : Sep. 9, 2003

Temperature : 24

Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
No Emissions found.								

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Q.P. limit while there is only peak result.
4. *The EUT is a body worn device. In order to get the worse data, EUT direction (X, Y, Z axes) were adjusted during the prescan measurement. For final measurement, EUT was setup under the maximum emission direction.*

4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\mathbf{Result = Reading + Corrected Factor}$$

where

$$\text{Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

4.6 Photos of Radiation Measuring Setup

a. EUT Position : X axial



b. EUT Position : Y axial



c. EUT Position : Z axial

