

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: A3LWIDT30Q

Equipment Under Test : WiFi Module
Model Name : WIDT30Q
Applicant : Samsung Electronics Co., Ltd.
Manufacturer#1 : Wisol Co., Ltd.
Manufacturer#2 : Wisol Hanoi Co., Ltd.
Date of Test(s) : 2016.05.30 ~ 2016.06.01
Date of Issue : 2016.06.02

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Date:

2016.06.02

Patrick Kang

Approved By:



Date:

2016.06.02

Alvin Kim

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

INDEX

<u>Table of Contents</u>	Page
1. General Information -----	3
2. RF Exposure Evaluation -----	5

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

-Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Telephone : +82 31 688 0901

FAX : +82 31 688 0921

1.2. Details of applicant

Applicant : Samsung Electronics Co., Ltd.

Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea

Contact Person : Cho, Min-Hyeong

Phone No. : +82 31 277 2688

1.3. Description of EUT

Kind of Product	Wi-Fi Module	
Model Name	WIDT30Q	
Power Supply	DC 5.0 V	
Frequency Range	5 745 MHz ~ 5 825 MHz (Band 3: 11a/n_HT20), 5 755 MHz ~ 5 795 MHz (Band 3: 11n_HT40)	
Modulation Technique	OFDM	
Number of Channels	5 channels (Band 3: 11a/n_HT20), 2 channels (Band 3: 11n_HT40)	
Antenna Type	Fixed type (MIMO - 2 Tx / 2 Rx)	
Antenna Gain	Port#0	5 745 MHz ~ 5 825 MHz: 1.35 dB i
	Port#1	5 745 MHz ~ 5 825 MHz: -0.90 dB i

1.4. Declaration by the manufacturer

- The device supports 2.4 GHz WLAN and 5 GHz WLAN(Band 1, Band 2A, Band 2C and Band 3).
- There is no increase in authorized power for UNII bands (Band 1, 2A, 2C, and 3) compared to original output power.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.5. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL009895	2016.06.01	Initial
1	F690501/RF-RTL009895-1	2016.06.02	Modified antenna gain

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30 - 300	61.4	0.163	1.0	6
300 – 1 500	-	-	f/300	6
1 500 – 100 000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 – 1 500	-	-	f/1500	30
1 500 – 100 000	-	-	1.0	30

2.1.1. Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

WLAN (2.4 GHz)

- Maximum tune up tolerance

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
6	2 437	19.50	3.77	0.042 241	1

WLAN (5 GHz)

- Maximum tune up tolerance

U-NII band 1

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
36	5 180	13.50	4.31	0.012 015	1

U-NII band 2A

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
52	5 260	15.50	4.31	0.019 043	1

U-NII band 2C

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
116	5 580	17.00	2.08	0.016 096	1

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

U-NII band 3

Channel	Channel Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
149	5 745	17.00	3.31	0.021 366	1

Note :

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- Unequal antenna gains, with equal transmit powers. For antenna gains given by G₁, G₂, ..., G_N dB i
 - If transmit signals are correlated, then
 Directional gain = $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dB i [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

Antenna gain

Antenna \ Frequency	2.4 GHz	5 GHz (band 1)	5 GHz (band 2A)	5 GHz (band 2C)	5 GHz (band 3)
ANT 0 (dB i)	2.05	2.69	2.69	-0.26	1.35
ANT 1 (dB i)	0.94	2.50	2.50	-1.66	-0.90
ANT 0+ ANT 1 (dB i) (Calculated)	3.77	4.31	4.31	2.08	3.31

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.