


Report Number: F690501/RF-RTL005848 Page: 50 of 191

5.8 GHz


OFDM: 802.11a(6 Mbps)

Low Channel





Report Number: F690501/RF-RTL005848 Page: 51 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

	,,		
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
5 725.00	23.49	-66.65	-43.16
7 659.87	23.90	-65.44	-41.54
20 394.73	-	Noise level	-
38 234.60	-	Noise level	=




Report Number: F690501/RF-RTL005848 Page: 52 of 191

Middle Channel





Report Number: F690501/RF-RTL005848 Page: 53 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
7 713.05	23.91	-67.72	-43.81
20 392.53	=	Noise level	-
38 746.70	=	Noise level	=




Report Number: F690501/RF-RTL005848 Page: 54 of 191

High Channel





Report Number: F690501/RF-RTL005848 Page: 55 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)


	,,		
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
5 850.00	23.82	-74.80	-50.98
7 769.86	-	Noise level	
20 395.83	-	Noise level	-
39 987.40	-	Noise level	=



Report Number: F690501/RF-RTL005848 Page: 56 of 191


OFDM: 802.11n_HT20(MCS0)

Low Channel





Report Number: F690501/RF-RTL005848 Page: 57 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

	,,		
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
5 725.00	23.49	-66.95	-43.46
7 659.87	23.91	-65.89	-41.98
20 390.88	-	Noise level	-
38 284.10	-	Noise level	=




Report Number: F690501/RF-RTL005848 Page: 58 of 191

Middle Channel





Report Number: F690501/RF-RTL005848 Page: 59 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
7 712.95	23.91	-67.44	-43.53
20 378.78	=	Noise level	=
39 986.90	=	Noise level	=




Report Number: F690501/RF-RTL005848 Page: 60 of 191

High Channel





Report Number: F690501/RF-RTL005848 Page: 61 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)


	,,		
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
5 850.00	23.82	-75.75	-51.93
7 767.55	23.91	-68.28	-44.37
20 386.48	-	Noise level	-
38 784.50	=	Noise level	=



Report Number: F690501/RF-RTL005848 Page: 62 of 191


OFDM: 802.11n_HT40(MCS0)

Low Channel





Report Number: F690501/RF-RTL005848 Page: 63 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

	,,		
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
5 725.00	23.49	-68.29	-44.80
7 673.89	23.91	-66.91	-43.00
20 388.13	-	Noise level	-
35 712.70	-	Noise level	=




Report Number: F690501/RF-RTL005848 Page: 64 of 191

High Channel





Report Number: F690501/RF-RTL005848 Page: 65 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)

	,,		
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
5.850.00	23.82	-74.91	-51.09
7 727.08	23.91	-66.64	-42.73
20 396.38	-	Noise level	=
39 225.50	=	Noise level	=




Report Number: F690501/RF-RTL005848 Page: 66 of 191

ANT1


DSSS: 802.11b(1 Mbps)

Low Channel





Report Number: F690501/RF-RTL005848 Page: 67 of 191



Note:

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
2 390.00	22.62	-73.65	-51.03
2 400.00	22.62	-57.23	-34.61
4 824.41	23.06	-58.39	-35.33
20 390.88	-	Noise level	-




Report Number: F690501/RF-RTL005848 Page: 68 of 191

Middle Channel





Report Number: F690501/RF-RTL005848 Page: 69 of 191



Note:

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
4 873.92	23.06	-59.99	=
20 378.78	=	Noise level	-




Report Number: F690501/RF-RTL005848 Page: 70 of 191

High Channel





Report Number: F690501/RF-RTL005848 Page: 71 of 191



Note:

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)


Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
2 483.50	22.57	-71.17	-48.60
2 486.33	22.57	-69.23	-46.66
4 924.11	23.06	-64.20	-41.14
20 387.03	-	Noise level	-



Report Number: F690501/RF-RTL005848 Page: 72 of 191


OFDM: 802.11g(6 Mbps)

Low Channel





Report Number: F690501/RF-RTL005848 Page: 73 of 191



Note:

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
2 390.00	22.62	-74.33	-51.71
2 399.900	22.62	-61.65	-39.03
6 986.90	-	Noise level	-
20 396.93	-	Noise level	-




Report Number: F690501/RF-RTL005848 Page: 74 of 191

Middle Channel





Report Number: F690501/RF-RTL005848 Page: 75 of 191



Note:

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
6 898.17	=	Noise level	-
20 398.03	-	Noise level	-




Report Number: F690501/RF-RTL005848 Page: 76 of 191

High Channel





Report Number: F690501/RF-RTL005848 Page: 77 of 191



Note:

Offset ($^{\text{dB}}$) = Power Divider ($^{\text{dB}}$) + Attenuator ($^{\text{dB}}$) + Cable loss ($^{\text{dB}}$)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)


Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
2 483.50	22.57	-69.39	-43.62
6 918.17	=	Noise level	-
20 384.83	=	Noise level	-



Report Number: F690501/RF-RTL005848 Page: 78 of 191


OFDM: 802.11n_HT20(MCS0)

Low Channel





Report Number: F690501/RF-RTL005848 Page: 79 of 191



Note:

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
2 390.00	22.62	-75.84	-53.22
2 400.00	22.62	-53.33	-30.71
6 632.96		Noise level	
20 38538	-	Noise level	-




Report Number: F690501/RF-RTL005848 Page: 80 of 191

Middle Channel





Report Number: F690501/RF-RTL005848 Page: 81 of 191



Note:

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
6 907.80	=	Noise level	-
20 352.38	=	Noise level	-




Report Number: F690501/RF-RTL005848 Page: 82 of 191

High Channel





Report Number: F690501/RF-RTL005848 Page: 83 of 191



Note:

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)


Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
2 483.50	23.57	-65.65	-42.08
6 947.68	=	Noise level	-
20 380.98	=	Noise level	-



Report Number: F690501/RF-RTL005848 Page: 84 of 191


OFDM: 802.11n_HT40(MCS0)

Low Channel





Report Number: F690501/RF-RTL005848 Page: 85 of 191



Note:

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
2 390.00	22.62	-68.38	-45.76
2 400.00	22.62	-61.32	-38.70
6 411.63	23.88	-63.47	-39.59
20 355.13	-	Noise level	-




Report Number: F690501/RF-RTL005848 Page: 86 of 191

Middle Channel





Report Number: F690501/RF-RTL005848 Page: 87 of 191



Note:

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
6 412.96	23.88	-63.44	-39.56
20 393.63	=	Noise level	-




Report Number: F690501/RF-RTL005848 Page: 88 of 191

High Channel





Report Number: F690501/RF-RTL005848 Page: 89 of 191



Note:

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
2 483.50	23.57	-63.31	-39.74
2 485.07	23.57	-59.18	-35.61
6 505.35	-	Noise level	-
20 372.73	-	Noise level	-




Report Number: F690501/RF-RTL005848 Page: 90 of 191

5.8 GHz


OFDM: 802.11a(6 Mbps)

Low Channel





Report Number: F690501/RF-RTL005848 Page: 91 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

result (** m) Opunous onset (**) * recauling values (** m)				
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)	
5 724.37	23.49	-71.89	-48.40	
5 725.00	23.49	-73.95	-50.46	
6 779.19	-	Noise level	-	
20 398.58	-	Noise level	=	
38 392.50		Noise level	-	




Report Number: F690501/RF-RTL005848 Page: 92 of 191

Middle Channel





Report Number: F690501/RF-RTL005848 Page: 93 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
6 913.79	=	Noise level	=
20 372.18	=	Noise level	=
38 794.00	=	Noise level	=




Report Number: F690501/RF-RTL005848 Page: 94 of 191

High Channel





Report Number: F690501/RF-RTL005848 Page: 95 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)


result (iii) Spails as silest (, riodanig raidos (iii)		
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
5 850.00	23.82	-76.02	-52.20
6 961.97	-	Noise level	-
20 379.88	-	Noise level	-
39 065.30	-	Noise level	-



Report Number: F690501/RF-RTL005848 Page: 96 of 191


OFDM: 802.11n_HT20(MCS0)

Low Channel





Report Number: F690501/RF-RTL005848 Page: 97 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

	,,		
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
5 725.00	23.49	-73.63	-50.14
6 924.09	23.90	-63.01	-39.11
20 397.48	-	Noise level	-
39 102.20	-	Noise level	=




Report Number: F690501/RF-RTL005848 Page: 98 of 191

Middle Channel





Report Number: F690501/RF-RTL005848 Page: 99 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
6 564.50	-	Noise level	-
20 395.28	=	Noise level	-
39 144.50	=	Noise level	-




Report Number: F690501/RF-RTL005848 Page: 100 of 191

High Channel





Report Number: F690501/RF-RTL005848 Page: 101 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)


	,,		
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
5 850 00	23.82	-75.09	-51.27
6 853.27	-	Noise level	
20 388.68	-	Noise level	=
38 758.40	-	Noise level	=



Report Number: F690501/RF-RTL005848 Page: 102 of 191


OFDM: 802.11n_HT40(MCS0)

Low Channel





Report Number: F690501/RF-RTL005848 Page: 103 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

	,,		
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
5 725.00	23.49	-69.26	-36.68
6 976.93	-	Noise level	=
20 399.68	-	Noise level	=
38 829.10	-	Noise level	=




Report Number: F690501/RF-RTL005848 Page: 104 of 191

High Channel





Report Number: F690501/RF-RTL005848 Page: 105 of 191



Note

Offset (dB) = Power Divider (dB) + Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)

, , ,	, ,		
Frequency (Mb)	offset (dB)	Reading values (dB m)	Result (dB m)
5 850.00	23.82	-74.83	-51.01
6 985.48	=	Noise level	=
20.391.43	=	Noise level	=
38 370.50	=	Noise level	=