



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

# RF Exposure Evaluation Report

**Report No. :** CQASZ20190400254E-04

**Applicant:** RM ACQUISITIONS LLC

**Address of Applicant:** 9855 Woods Drive Skokie. IL 60077 U.S.A

**Manufacturer:** SHEN ZHEN APICAL TECHNOLOGY CO., LTD

**Address of Manufacturer:** Address: 9/F,B Building, Tinghua Unis Infoport, Langshan RD, North district, Hi-tech Industrial Park, Nanshan, Shenzhen

**Equipment Under Test (EUT):**

**Product:** Transportation Tablet

**Model No.:** TND740

**Brand Name:** N/A

**FCC ID:** A4C-10010A

**Standards:** 47 CFR Part 1.1307  
47 CFR Part 1.1310  
KDB447498D01 General RF Exposure Guidance v06

**Date of Test:** 2019-04-17 to 2019-05-29

**Date of Issue:** 2019-05-29

**Test Result :** PASS\*

**Tested By:**

(Daisy Qin)

**Reviewed By:**

(Aaron Ma)

**Approved By:**

( Jack Ai)



\* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190400254E-04	Rev.01	Initial report	2019-05-29

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
3.3 GENERAL DESCRIPTION OF WIFI.....	4
3.4 GENERAL DESCRIPTION OF BT .....	5
3.5 GENERAL DESCRIPTION OF BLE .....	5
4 RF EXPOSURE EVALUATION.....	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	6
4.1.1 <i>Limits</i> .....	6
4.1.2 <i>Test Procedure</i> .....	6
4.2 1.1.3 EUT RF EXPOSURE EVALUATION .....	7

### 3 General Information

#### 3.1 Client Information

Applicant:	RM ACQUISITIONS LLC
Address of Applicant:	9855 Woods Drive Skokie. IL 60077 U.S.A
Manufacturer:	SHEN ZHEN APICAL TECHNOLOGY CO., LTD
Address of Manufacturer:	Address: 9/F,B Building, Tinghua Unis Infoport, Langshan RD, North district, Hi-tech Industrial Park, Nanshan, Shenzhen

#### 3.2 General Description of EUT

Product Name:	Transportation Tablet
Model No.:	TND740
Trade Mark:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Sample Type:	Mobile production
Power Supply:	DC3.7V, 2400mAh; Charge by DV5V

#### 3.3 General Description of WIFI

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11n(HT40) : 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps
Test Software of EUT:	adb tool (manufacturer declare )
Antenna Type:	PCB antenna with ipex connector
Antenna Gain:	0dBi

### 3.4 General Description of BT

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Test Software of EUT:	adb tool (manufacturer declare )
Antenna Type:	PCB antenna with ipex connector
Antenna Gain:	0dBi

### 3.5 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.2
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	40
Test Software of EUT:	adb tool (manufacturer declare )
Antenna Type:	PCB antenna with ipex connector
Antenna Gain:	0dBi

## 4 RF Exposure Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 4.2 1.1.3 EUT RF Exposure Evaluation

### 1) For WIFI

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

### Measurement Data

802.11b mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	12.43	13±1	14	25.119
Middle(2437MHz)	12.68	13±1	14	25.119
Highest(2462MHz)	13.00	13±1	14	25.119
802.11g mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	12.01	12±1.0	13	19.953
Middle(2437MHz)	12.06	12±1.0	13	19.953
Highest(2462MHz)	12.6	12±1.0	13	19.953
802.11n(HT20)mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	11.95	12±1.0	13	19.953
Middle(2437MHz)	12.24	12±1.0	13	19.953
Highest(2462MHz)	12.38	12±1.0	13	19.953
802.11n(HT40)mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2422MHz)	11.77	12±1.0	13	19.953
Middle(2437MHz)	12.03	12±1.0	13	19.953
Highest(2452MHz)	12.14	12±1.0	13	19.953

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
25.119	0	0.0063	1.0	PASS

Note: 1) Refer to report No. CQASZ20190400254E-01 for EUT test Max Conducted average Output Power value.

2)  $Pd = (Pout * G) / (4 * \pi * R^2) = (25.119 * 1) / (4 * 3.1416 * 20^2) = 0.005$



**2) For BT**

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

**Measurement Data**

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-1.710	-0±2	2	1.585
Middle(2441MHz)	0.790	1±2	3	1.995
Highest(2480MHz)	2.070	1±2	3	1.995
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-3.680	-2±2	0	1
Middle(2441MHz)	0.020	0±2	2	1.585
Highest(2480MHz)	1.470	0±2	2	1.585
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-3.490	-2±2	0	1
Middle(2441MHz)	0.210	0±2	2	1.585
Highest(2480MHz)	1.520	0±2	2	1.585

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
1.995	0	0.0004	1.0	PASS

Note: 1) Refer to report No. CQASZ20190400254E-02 for EUT test Max Conducted Peak Output Power value.

2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (1.995 * 1) / (4 * 3.1416 * 20^2) = 0.0004$

## 2) For BLE

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

### Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-0.93	1±2	3	1.995
Middle(2440MHz)	0.85	1±2	3	1.995
Highest(2480MHz)	2.23	1±2	3	1.995

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
1.995	0	0.0004	1.0	PASS

Note: 1) Refer to report No. CQASZ20190400254E-03 for EUT test Max Conducted Peak Output Power value.

2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (1.995 * 1) / (4 * 3.1416 * 20^2) = 0.0004$