



849 NW State Road 45
Newberry, FL 32669 USA
Ph: 888.472.2424 or 352.472.5500
Fax: 352.472.2030
Email: info@timcoengr.com
Website: www.timcoengr.com

**FCC PART 15.247 AND IC RSS-210
TEST REPORT
DIGITAL SPREAD SPECTRUM**

Applicant	RM ACQUISITION LLC
Address	9855 WOODS DRIVE SKOKIE IL 60077
FCC ID	A4C01001A
IC	10199A-01001A
Model Number	TND 760
Product Description	802.11b, g module
Date Sample Received	1/4/2012
Date Tested	February 19 th , 2012
Tested By	John Day
Approved By	Mario R de Aranzeta
Report Number	24AUT12TestReport.doc
Test Results	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Testing Certificate #0955-01

TABLE OF CONTENT

GENERAL REMARKS..... 3
GENERAL INFORMATION 4
EMC EQUIPMENT LIST..... 5
TEST PROCEDURES..... 6
RADIATION INTERFERENCE 7
POWER LINE CONDUCTED INTERFERENCE 10
OCCUPIED BANDWIDTH 11
POWER OUTPUT 12
RADIATED SPURIOUS EMISSIONS INTO ADJACENT RESTRICTED BAND 13
POWER SPECTRAL DENSITY..... 19

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results relate only to the items tested.

Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
- not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, Fl 32669

Authorized Signatory Name:



Mario de Aranzeta C.E.T.
Compliance Engineer/ Lab. Supervisor

Date: April 4, 2012

GENERAL INFORMATION

DUT Specification

Applicable Standard	Part 15.247, RSS-210		
DUT Description	802.11b, g module		
FCC ID	A4C01001A		
IC	10199A-01001A		
Operating Frequency	TX: 2412 to 2462		
Number of channels	11		
	802.11b, g		
DUT Power Source	<input type="checkbox"/> 110-120Vac/50- 60Hz		
	<input checked="" type="checkbox"/> DC Power		
	<input type="checkbox"/> Battery Operated Exclusively		
Test Item	<input type="checkbox"/> Prototype	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Production
Type of Equipment	<input checked="" type="checkbox"/> Fixed	<input type="checkbox"/> Mobile	<input type="checkbox"/> Portable
Antenna Connector	integral		
Antenna	2 dBi		
Test Facility	Timco Engineering Inc. located at 849 NW State Road 45 Newberry, FL 32669 USA.		
Test Conditions	Temperature: 26°C Relative humidity: 50%		
Test Exercise	The DUT was placed in continuous transmit mode of operation.		

Test Supporting Equipment

Supporting Device	Manufacturer	Model / FCC ID	Serial Number
N/A			

EMC EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	Listed 5/10/10	5/10/12
AC Voltmeter	HP	400FL	2213A14499	CAL 6/12/11	6/12/13
Antenna: Active Loop	ETS-Lindgren	6502	00062529	CAL 9/23/10	9/23/12
Frequency Counter	HP	5385A	2730A03025	CAL 8/17/11	8/17/13
Hygro-Thermometer	Extech	445703	0602	CAL 6/15/11	6/15/13
Modulation Analyzer	HP	8901A	3435A06868	CAL 7/18/11	7/18/13
Digital Multimeter	Fluke	FLUKE-77	35053830	CAL 9/9/11	9/9/13
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 10/28/11	10/28/13
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 10/28/11	10/28/13
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 10/28/11	10/28/13
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 10/28/11	10/28/13
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 4/25/10	4/25/12
Antenna	ETS	3117	41534	9/22/2010	9/22/2012
Antenna	Electro metrics	LPA-25	1122	5/04/2011	5/04/2013
Antenna	Electro metrics	BIA-25	1096	5/04/2011	5/04/2013

APPLICANT: RM ACQUISITION LLC

FCC ID: A4C01001A, IC: 10199A-01001A

REPORT: R\RM ACQUISITION\24AUT12\24AUT12TestReport.doc

TEST PROCEDURES

Radiation Interference: ANSI C63.4-2003 using a spectrum analyzer, a preselector, a quasi-peak adapter, and an appropriate antenna. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz with an appropriate sweep speed and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3 MHz above 1 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental.

Formula Of Conversion Factors: The field strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBμV) to the antenna correction factor supplied by the antenna manufacturer plus the coax loss. The antenna correction factors are stated in terms of dB. The gain of the preselector was accounted for in the spectrum analyzer meter reading.

Example:

Freq (MHz)	Meter Reading	+ ACF	+ CL = FS
33	20 dBμV	+ 10.36 dB	+ 0.5 = 30.86 dBμV/m @ 3m

Power Line Conducted Interference: The procedure used was ANSI C63.4-2003 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed. The spectrum was scanned from 0.15 to 30 MHz.

Occupied Bandwidth: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to -10 dBm per division.

Bandwidth 6.0dB: The measurements were made with the spectrum analyzer's resolution bandwidth (RBW)=1 MHz and the video bandwidth (VBW) =3 MHz and the span set as shown on plot.

Power Output: The RF power output was measured at the antenna feed point using a peak power meter.

Antenna Conducted Emissions: The RBW=100 kHz, VBW=300 kHz and the span set to 10 MHz and the spectrum was scanned from 30 MHz to the 10th Harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

ANSI C63.4-2003 10.1 Measurement Procedures: The DUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The DUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. Emissions attenuated more than 20 dB below the permissible value are not reported.

APPLICANT: RM ACQUISITION LLC

FCC ID: A4C01001A, IC: 10199A-01001A

REPORT: R\RM ACQUISITION\24AUT12\24AUT12TestReport.doc

RADIATION INTERFERENCE

Rules Part No.: 15.247, 15.209, RSS-210

Requirements:

Frequency	Limits
Part 15.209	
9 to 490 kHz	2400/F (kHz) μ V/m @ 300 meters
490 to 1705 kHz	24000/F (kHz) μ V/m @ 30 meters
1705 kHz to 30 MHz	29.54 dB μ V/m @ 30 meters
30 – 88	40.0 dB μ V/m @ 3 meters
80 – 216	43.5 dB μ V/m @ 3 meters
216 – 960	46.0 dB μ V/m @ 3 meters
Above 960	54.0 dB μ V/m @ 3 meters
Part 15.247	
Fundamental 902 – 928 MHz	127.37 dB μ V/m @ 3 meters
Fundamental 2.4 – 2.4835 MHz	127.37 dB μ V/m @ 3 meters
Harmonics	54.0 dB μ V/m @ 3 meters

Any emissions that fall in the restricted bands (15.205) must be less than or equal to 54 dB μ V/m. Spurious emissions not in a restricted band must be 20 dBc. Harmonics were checked through the 10th harmonic.

Test Data: All values are peak unless noted.
Items mark with an * designate a frequency in a restricted band.

802.11g

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB μ V	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dB μ V/m	Margin dB
2,412.0	2,412.00	67.8	H	3.19	32.42	103.41	23.97
2,412.0A	4,824.00	7.6	H	4.91	34.39	46.90	7.10
2,412.0P	4,824.00	22.2	H	4.91	34.39	61.50	12.50
2,437.0	2,437.00	64.1	V	3.21	32.47	99.78	27.60
2,437.0	2,437.00	65.9	H	3.21	32.47	101.58	25.80
2,437.0A	4,874.00	3.7	H	4.94	34.42	43.06	10.94
2,437.0P	4,874.00	18.6	H	4.94	34.42	57.96	16.04
2,462.0	2,462.00	62.0	V	3.22	32.52	97.74	29.64
2,462.0	2,462.00	65.3	H	3.22	32.52	101.04	26.34
2,462.0A	4,920.00	1.9	V	4.96	34.45	41.31	12.69
2,462.0P	4,920.00	15.6	V	4.96	34.45	55.01	18.99
2,462.0A	4,924.00	5.2	H	4.96	34.45	44.61	9.39
2,462.0P	4,924.00	20.0	H	4.96	34.45	59.41	14.59

APPLICANT: RM ACQUISITION LLC
 FCC ID: A4C01001A, IC: 10199A-01001A
 REPORT: R\RM ACQUISITION\24AUT12\24AUT12TestReport.doc

802.11b

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBμV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dBμV/m	Margin dB
2,412.0	2,412.00	68.3	H	3.19	32.42	103.91	23.47
2,412.0	2,412.00	68.8	V	3.19	32.42	104.41	22.97
2,412.0	4,824.00	9.8	V	4.91	34.39	49.10	4.90
2,437.0	2,437.00	68.5	H	3.21	32.47	104.18	23.20
2,437.0	2,437.00	68.9	V	3.21	32.47	104.58	22.80
2,437.0	4,874.00	9.7	V	4.94	34.42	49.06	4.94
2,462.0	2,462.00	66.6	H	3.22	32.52	102.34	25.04
2,462.0	2,462.00	70.5	V	3.22	32.52	106.24	21.14
2,462.0	4,924.00	9.0	V	4.96	34.45	48.41	5.59

Digital emissions common to all TX frequencies.

Emission Frequency MHz	Meter Reading dBμV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dBμV/m	Margin dB
39.56	9.6	H	0.45	10.85	20.90	19.10
39.56	20.8	V	0.45	10.85	32.10	7.90
60.08	13.3	H	0.53	10.88	24.71	15.29
60.08	18.9	V	0.53	10.88	30.31	9.69
115.30	21.5	H	0.67	14.52	36.69	6.81
115.30	27.0	V	0.67	14.52	42.19	1.31
126.01	26.2	H	0.68	12.90	39.78	3.72
126.01	26.4	V	0.68	12.90	39.98	3.52
240.04	13.4	V	0.98	12.20	26.58	19.42
240.04	20.9	H	0.98	12.20	34.08	11.92
288.08	11.9	V	1.08	15.16	28.14	17.86
288.08	17.9	H	1.08	15.16	34.14	11.86
312.00	18.8	V	1.11	14.38	34.29	11.71
312.00	19.9	H	1.11	14.38	35.39	10.61
335.96	18.9	H	1.14	14.80	34.84	11.16
335.96	18.9	V	1.14	14.80	34.84	11.16
360.04	18.5	V	1.16	15.10	34.76	11.24
360.04	25.4	H	1.16	15.10	41.66	4.34
984.04	7.1	H	2.08	24.78	33.96	12.04
984.04	10.5	V	2.08	24.78	37.36	8.64


APPLICANT: RM ACQUISITION LLC

FCC ID: A4C01001A, IC: 10199A-01001A

REPORT: R\RM ACQUISITION\24AUT12\24AUT12TestReport.doc

Method of Measuring Radiated Spurious Emissions

Antenna is Calibrated
and appropriate one.
Raised from 1 to 4 M.



METHOD OF MEASUREMENT: The procedure used was ANSI C63.4-2003 & the FCC/OET Guidance on Measurements for Spread Spectrum Systems – KDB 558074 dated January 18, 2012.

POWER LINE CONDUCTED INTERFERENCE

Rules Part No.: Part 15.207

Requirements:

Frequency (MHz)	Quasi Peak Limits (dBμV)	Average Limits (dBμV)
0.15 – 0.5	66 – 56 *	56 – 46 *
0.5 – 5.0	56	46
5.0 – 30	60	50
* Decrease with logarithm of frequency		



Test Data: Not applicable. Device is DC or vehicle powered exclusively.

OCCUPIED BANDWIDTH

Rules Part No.: 15.247(a)(2), RSS-210, RSS-GEN

Requirements: The 6 dB bandwidth must be greater than 500 kHz.

Test Data: mode g 20 dB BW is 21. MHz
mode g 6 dB BW is 16.9 MHz



Three places in the band were measured and the worst case reported.

APPLICANT: RM ACQUISITION LLC


FCC ID: A4C01001A, IC: 10199A-01001A

REPORT: R\RM ACQUISITION\24AUT12\24AUT12TestReport.doc

POWER OUTPUT

Rules Part #: 15.247(b) 1 Watt conducted, 4W ERP, RSS-210

TEST SET UP:



Test Results:

mode g

Frequency MHz	Po dBm	Po Watts
2412	19.3	0.85
2437	20	0.100
2462	20	0.100

mode b


Frequency MHz	Po dBm	Po Watts
2412	19	0.079
2437	19.4	0.087
2462	19.7	0.093

RADIATED SPURIOUS EMISSIONS INTO ADJACENT RESTRICTED BAND


Requirements: Emissions that fall in the restricted bands (15.205). These emissions must be less than or equal to 500 $\mu\text{V}/\text{m}$ (54 $\text{dB}\mu\text{V}/\text{m}$).

Test Procedure: An in band field strength measurement of the fundamental Emission using the RBW and detector function required by C63.4-2000 and FCC Rules. The procedure was repeated with an average detector and a plot made. The calculated field strength in the adjacent restricted band is presented below.

Mode g




ch 2412-Lower restricted band peak




ch 2412-Lower restricted band Average

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBμV	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Field Strength dBμV/m	Margin dB
2,412.0	2,400.00	16.0	H	3.18	32.40	51.58	2.42
2,412.0	2,400.00	26.1	H	3.18	32.40	61.68	12.32

Mode g



Upper bandedge peak



Upper bandedge average


Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBμV	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Field Strength dBμV/m	Margin dB
2,462.0	2,483.50	3.9	V	3.24	32.57	39.71	14.29
2,462.0	2,483.50	19.4	V	3.24	32.57	55.21	18.79

APPLICANT: RM ACQUISITION LLC

FCC ID: A4C01001A, IC: 10199A-01001A

REPORT: R\RM ACQUISITION\24AUT12\24AUT12TestReport.doc


Mode b



ch 2412-Lower adjacent restricted band peak


Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBµV	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Field Strength dBµV/m	Margin dB
2,412.0	2,386.00	16.4	V	3.17	32.37	51.94	2.06

Mode b



ch 2412-Lower bandedge Peak (meets 20 dBc)

Mode b



Upper bandedge peak

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB μ V	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Field Strength dB μ V/m	Margin dB
2,462.0	2,487.0	15.1	V	3.24	32.57	50.91	3.09

POWER SPECTRAL DENSITY

Rules Part No.: 15.247(d)


Requirements: The peak level measured must be less than +8.0 dBm.

Test Procedure: kdb 558074

Test Data: SEE THE FOLLOWING PLOTS

Mode	Channel	dBm/100 kHz	dBm/3 kHz
B	6	-13.3	-28.5
G	11	-19.6	-34.8

Mode b



Three places in the band were measured and the worst case reported.

mode g

