

1. RF Exposure Requirements

1.1 General Information

Client Information

Applicant: eMoMo Technology Co., Ltd
Address of applicant: 4th, Floor, Yong He Building ,Tai Wan Industrial Park ,Shi Yan Town ,Bao'an District ,Shen Zhen, 518108, Guangdong, China

Manufacturer: eMoMo Technology Co., Ltd
Address of manufacturer: 4th, Floor, Yong He Building ,Tai Wan Industrial Park ,Shi Yan Town ,Bao'an District ,Shen Zhen, 518108, Guangdong, China

General Description of EUT:

Product Name: Smart sofa control panel
Trade Name: iTable
Model No.: iTable40624TRHLWA
Adding Model(s): iTable406RRWG, iTable406TRWF, iTable406
Rated Voltage: AC120V/60Hz
Battery Capacity: /
FCC ID: A4E-ITABLE406A
Equipment Type: Mobile device

Technical Characteristics of EUT:

Bluetooth

Bluetooth Version:	V5.0 (BLE mode)	V5.0 (BR/EDR mode)
Frequency Range:	2402-2480MHz	2402-2480MHz
RF Output Power:	-0.23dBm (Conducted)	4.65dBm (Conducted)
Data Rate:	1Mbps	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK	GFSK, $\pi/4$ DQPSK, 8DPSK
Quantity of Channels:	40	79
Channel Separation:	2MHz	1MHz
Type of Antenna:	PCB Antenna	PCB Antenna
Antenna Gain:	3.38dBi	3.38dBi

1.2 RF Exposure Exemption

Option A: FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

Option B: FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option C: FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$
1.34-30	$3,450 R^2/f^2$
30-300	$3.83 R^2$
300-1,500	$0.0128 R^2 f$
1,500-100,000	$19.2 R^2$

For Multiple RF sources: FCC Rule Part 1.1307(b)(3)(ii):

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).

(B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

1.3 Calculated Result

Radio Access Technology	Min. Frequency	Max. Output Power	Max. Tune-Up Output Power	Antenna Gain	Duty Cycle	Tune-Up EIRP
	(MHz)	(dBm)	(dBm)	(dBi)	(%)	(dBm)
Bluetooth	2402	4.65	5.00	3.38	--	8.38

Frequency (MHz)	Option	Min. Distance	Tune-Up ERP		Exposure Limit	Ratio	Result
		(cm)	(dBm)	(mW)	(mW)		Pass/Fail
2402	C	20.00	6.23	4.20	768.00	0.01	Pass

Note: 1. $ERP = EIRP - 2.15dB$; $EIRP = Output Power + Antenna gain$

2. Option A, B and C refers as clause 1.2.

3. For option B, $P_{th}(mW)$ convert to Exposure Limit(mW); For option C, $ERP(W)$ convert to Exposure Limit(mW).

4. $Ratio = Tune-Up ERP(mW) / Exposure Limit (mW)$

Mode for Simultaneous Multi-band Transmission:

Radio Access Technology	Ratio 1	Ratio 2	Simultaneous Ratio	Limit	Result
					Pass/Fail
--	--	--	--	--	--

Result: Pass