

FCC PART 15B
MEASUREMENT AND TEST REPORT
FOR

American Fone Company Ltd
1461 First Avenue, #360 New York, NY 10075-2201 USA

FCC ID: A4FFONE-1

Report Concerns: Original Report	Equipment Type: Mobile Phone
Model: <u>FONE-1</u>	
Report No.: <u>STR11118139I-3</u>	
Test Date: <u>2011-11-16 to 2011-12-19</u>	
Issue Date: <u>2011-12-27</u>	
Tested By: <u>Silin Chen / Engineer</u> <i>Silin chen</i>	
Reviewed By: <u>Lahm Peng / EMC Manager</u> <i>Lahm peng</i>	
Approved & Authorized By: <u>Jandy so / PSQ Manager</u> <i>Jandy so</i>	
Prepared By: SEM.Test Compliance Service Co., Ltd 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C. (518101) Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn	

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	3
1.3 TEST METHODOLOGY.....	3
1.4 TEST FACILITY	4
1.5 EUT EXERCISE SOFTWARE	4
1.6 ACCESSORIES EQUIPMENT LIST AND DETAILS	4
1.7 EUT CABLE LIST AND DETAILS	4
2. SUMMARY OF TEST RESULTS	5
3. §15.107 (A)- CONDUCTED EMISSION	6
3.1 MEASUREMENT UNCERTAINTY	6
3.2 TEST EQUIPMENT LIST AND DETAILS	6
3.3 TEST PROCEDURE.....	6
3.4 BASIC TEST SETUP BLOCK DIAGRAM.....	6
3.5 ENVIRONMENTAL CONDITIONS	7
3.6 TEST RECEIVER SETUP	7
3.7 SUMMARY OF TEST RESULTS/PLOTS	7
3.8 CONDUCTED EMISSIONS TEST DATA.....	7
4. §15.109(A)- RADIATED EMISSION	10
4.1 MEASUREMENT UNCERTAINTY	10
4.2 TEST EQUIPMENT LIST AND DETAILS	10
4.3 TEST PROCEDURE.....	10
4.4 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	11
4.5 ENVIRONMENTAL CONDITIONS	11
4.6 SUMMARY OF TEST RESULTS/PLOTS	11

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant:

American Fone Company Ltd

Address of applicant:

1461 First Avenue, #360 New York, NY 10075-2201 USA

Manufacturer:

Shenzhen Punud Electronics Co., Ltd

Address of manufacturer:

4F, Block B, Jinkaijin Technical Park, Minying Industrial District, Shuitian, Shiyan Town, Baoan District, Shenzhen, 518108, Guangdong Province, China

General Description of E.U.T

Items	Description
EUT Description:	Mobile Phone
Trade Name:	FONE
Model No.:	FONE-1
Rated Voltage:	Battery DC 3.7V
Rated Current:	1500mA
Battery:	M/N: PF-4L; DC 3.7V/1500mAh
Power Adapter:	M/N: FONE; Input: 100-240V ~ 50/60Hz, 0.2A

For more information refer to the circuit diagram form and the user's manual.

The test data is gathered from a production sample, provided by the manufacturer.

1.2 Test Standards

The following report is prepared on behalf of the American Fone Company Ltd in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15.107, and 15.109 rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible susceptibility against the tested phenomena. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

- **FCC – Registration No.: 994117**

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

- **Industry Canada (IC) Registration No.: 7673A**

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Exercise Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the system components. The test software, provided by the customer, is started while the EUT is on to simulate the normal work.

1.6 Accessories Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	ASUS	X50R	74N0AS297138

1.7 EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	1.1	Unshielded	Without Core
Earpluq Cable	0.9	Unshielded	Without Core

2. SUMMARY OF TEST RESULTS

Description of Test	Result
§15.107 (a) Conducted Emission	Compliant
§15.109(a) Radiated Emission	Compliant

3. §15.107 (a)- CONDUCTED EMISSION

3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

3.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2010-12-20	2011-12-19
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2010-12-20	2011-12-19
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2010-12-20	2011-12-19

3.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.107 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

3.4 Basic Test Setup Block Diagram



3.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

3.6 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:


Start Frequency 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal


3.7 Summary of Test Results/Plots

According to the data in section 3.8, the EUT complied with the FCC Part 15B Conducted margin for a Class B device, with the *worst* margin reading of:

-6.39 dB μ V at 24.642 MHz in the Neutral, Average detector, 0.15-30MHz

3.8 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data*Conducted Disturbance**EUT: Mobile Phone**M/N: FONE-1**Operating Condition: Charging**Test Specification: N**Comment: 120V/60Hz*

Plot of Conducted Emissions Test Data*Conducted Disturbance**EUT: Mobile Phone**M/N: FONE-1**Operating Condition: Charging**Test Specification: L**Comment: 120V/60Hz*

4. §15.109(a)- RADIATED EMISSION

4.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any radiation emissions measurement is ± 5.10 dB.

4.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2010-12-20	2011-12-19
EMI Test Receiver	R&S	ESVB	825471/005	2010-12-20	2011-12-19
Positioning Controller	C&C	CC-C-1F	N/A	2010-12-20	2011-12-19
RF Switch	EM	EMSW18	SW060023	2010-12-20	2011-12-19
Pre-amplifier	Agilent	8447F	3113A06717	2010-12-20	2011-12-19
Pre-amplifier	Compliance Direction	PAP-0118	24002	2010-12-20	2011-12-19
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2011-01-09	2012-01-08
Horn Antenna	ETS	3117	00086197	2011-01-09	2012-01-08

4.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 and FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



4.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15B Limit}$$

4.5 Environmental Conditions


Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

4.6 Summary of Test Results/Plots

According to the data, the EUT complied with the FCC Part 15B Class B standards, and had the worst margin of:


-5.740 dB μ V at 43.5057 MHz in the Vertical polarization, Charging mode, 9 kHz to 1 GHz, 3Meters

Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


Plot of Radiation Emissions Test Data*Radiated Disturbance**EUT: Mobile Phone**M/N: FONE-1**Operating Condition: Downloading**Test Specification: Horizontal & Vertical**Comment: AC 120V/60Hz**Horizontal*

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	200.6881	25.41	6.60	32.01	43.50	-11.49	360	100	peak
2	229.2931	26.15	7.82	33.97	46.00	-12.03	360	100	peak
3	299.3158	24.09	9.77	33.86	46.00	-12.14	360	100	peak
4	670.4893	20.00	17.26	37.26	46.00	-8.74	360	100	peak
5	1000.0000	16.61	22.74	39.35	54.00	-14.65	360	100	peak

Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	31.2893	20.92	6.77	27.69	40.00	-12.31	360	100	peak
2	123.6985	25.28	5.44	30.72	43.50	-12.78	360	100	peak
3	275.1570	25.63	9.38	35.01	46.00	-10.99	360	100	peak
4	341.9787	25.50	10.47	35.97	46.00	-10.03	360	100	peak
5	410.3825	25.71	11.39	37.10	46.00	-8.90	360	100	peak
6	755.3873	20.20	18.34	38.54	46.00	-7.46	360	100	peak

*Radiated Disturbance**EUT: Mobile Phone**M/N: FONE-1**Operating Condition: Charging**Test Specification: Horizontal & Vertical**Comment: AC 120V/60Hz**Horizontal*

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	33.0950	22.66	6.77	29.43	40.00	-10.57	360	100	peak
2	67.6751	24.54	4.53	29.07	40.00	-10.93	360	100	peak
3	72.0843	25.68	3.30	28.98	40.00	-11.02	360	100	peak
4	247.6819	20.97	8.63	29.60	46.00	-16.40	360	100	peak

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	33.0950	23.60	6.77	30.37	40.00	-9.63	360	100	peak
2	43.5057	26.06	8.20	34.26	40.00	-5.74	360	100	peak
3	67.6751	26.52	4.53	31.05	40.00	-8.95	360	100	peak

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5th Harmonics is close to the noise base even antenna close up to 1meter distance according the measurement of ANSI C63.4.

The measurements greater than 20dB below the limit from 9kHz to 30MHz..

***** END OF REPORT *****