Key Functions

The new designed ORACLE Customer Faced Display (CFD in short) is with new outlook and USB C powered. It perfectly works with new and old generation Workstation with USB C output.

The CFD is with touch LCD, provide platform for customer to view the purchasing information, to make choice, signature on the touch panel.





Specification

Model	7 Inch CFD
Overall Dimension (not including mounting fixture)	185 x 115 x 10mm
Weight	0.45kg
LCD size	7.0 inch
Module size	163.8 x 97 x 2.6mm
Backlight	LED Backlight
Power in	DC 5V from Oracle Workstation
Rating	DC 5V, 2A
Max. Operating Temperature	50°C
Storage Temperature	-20-70°C
RFID Function	125k or 13.56MHz

Installation



7 Inch CFD mounted on the Low-Profile Stand, and work with MICROS Workstation 8



7 Inch CFD mounted on the Vertical Stand, and work with MICROS Workstation 8



7 Inch CFD stand alone, work as Pole customer display

FCC Class A Notice

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- 1. This device may not cause harmful interference.
- 2. This device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy, and if it is not installed and used in accordance with the instruction manual, it may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference, in which case the user will be required to correct the interference at his own expense.

Modifications: Any modifications made to this device that are not approved by Oracle may void the authority granted to the user by the FCC to operate this equipment.

To satisfy FCC/IC RF exposure requirements, a separate distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.

To ensure compliance, operation at closer than this distance is not recommended.

Les antennes installées doivent être situées de facon à ce que la population ne puisse y être exposée à une distance de moin de 20 cm. Installer les antennes de facon à ce

que le personnel ne puisse approcher à 20 cm ou moins de la position centrale de l'

antenne.

La FCC des éltats-unis stipule que cet appareil doit être en tout temps éloigné d'au

moins 20 cm des personnes pendant son functionnement.

This device complies with Industry Canada's licence-exempt RSSs. Operation is subject to the following two conditions:

(1) This device may not cause interference; and

(2) This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.