



FCC RADIO TEST REPORT

FCC ID : A4R-H2E
Equipment : Interactive internet streaming device
Model Name : H2E
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, California, 94043 USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Jun. 06, 2019 and testing was started from Jul. 05, 2019 and completed on Sep. 11, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	5
1.3 Modification of EUT	6
1.4 Testing Location	6
1.5 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	16
3.3 Power Spectral Density Measurement	17
3.4 Conducted Band Edges and Spurious Emission Measurement	22
3.5 Radiated Band Edges and Spurious Emission Measurement	27
3.6 AC Conducted Emission Measurement.....	31
3.7 Antenna Requirements.....	33
4 List of Measuring Equipment	34
5 Uncertainty of Evaluation.....	36
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Peak Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 1.94 dB at 2483.520 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 12.12 dB at 0.602 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang**Report Producer: Ann Lee**



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Interactive internet streaming device
Model Name	H2E
FCC ID	A4R-H2E
EUT supports Radios application	WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE 802.15.4
HW version	EVT 1.0
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

EUT Information List	
No.	S/N
#1	96190EXBSZZ2RI
#2	96190EXBSZZ2SU
#3	96180EXBSZZ2Y2

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2405 MHz ~ 2475 MHz
Number of Channels	15
Carrier Frequency of Each Channel	5 MHz
Maximum Output Power to Antenna	19.90 dBm (0.0977 W)
99% Occupied Bandwidth	2.258 MHz
Antenna Type / Gain	Dipole Antenna type with gain 5.18 dBi
Type of Modulation	O-QPSK



1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory		
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		
	TH05-HY	CO05-HY	03CH07-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2405-2475 MHz	11	2405	19	2445
	12	2410	20	2450
	13	2415	21	2455
	14	2420	22	2460
	15	2425	23	2465
	16	2430	24	2470
	17	2435	25	2475
	18	2440	-	-



2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	802.15.4 Tx
Conducted Test Cases	Mode 1: 802.15.4 Tx CH11_2405 MHz Mode 2: 802.15.4 Tx CH18_2440 MHz Mode 3: 802.15.4 Tx CH25_2475 MHz
Radiated Test Cases	Mode 1: 802.15.4 Tx CH11_2405 MHz Mode 2: 802.15.4 Tx CH18_2440 MHz Mode 3: 802.15.4 Tx CH25_2475 MHz
AC Conducted Emission	Mode 1: 802.15.4 Link + AC Adapter Mode 2: 802.15.4 Link + WLAN (5GHz) TX + AC Adapter
Remark: The worst case of conducted emission is mode 2; only the test data of it was reported.	

2.3 Connection Diagram of Test System

<802.15.4 Tx Mode>



<AC Conducted Emission Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Spectrum Analyzer	Agilent	N9030A	N/A	N/A	Unshielded, 1.8m
2.	NOTE BOOK	Dell	P20G	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT4_ 4.0.00064” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


6 dB Bandwidth Plot on Channel 11



Date: 12.JUL.2019 17:20:07




6 dB Bandwidth Plot on Channel 18



Date: 12.JUL.2019 17:05:25

6 dB Bandwidth Plot on Channel 25




Date: 12.JUL.2019 16:59:58



3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


99% Bandwidth Plot on Channel 11



Date: 12.JUL.2019 17:21:43




99% Occupied Bandwidth Plot on Channel 18



Date: 12.JUL.2019 17:13:25

99% Occupied Bandwidth Plot on Channel 25



Date: 12.JUL.2019 17:02:28

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGP-M-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup




3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.




3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 11



Date: 12.JUL.2019 17:20:35


PSD 100kHz Plot on Channel 18



Date: 12.JUL.2019 17:08:02



PSD 100kHz Plot on Channel 25




Date: 12.JUL.2019 17:01:24




3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 11



Date: 12.JUL.2019 17:20:20


PSD 3kHz Plot on Channel 18



Date: 12.JUL.2019 17:06:18



PSD 3kHz Plot on Channel 25



Date: 12.JUL.2019 17:00:19

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 11



Date: 12.JUL.2019 17:20:49

High Band Edge Plot on Channel 25




Date: 12.JUL.2019 17:01:47




3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on 802.15.4 Channel 11



Date: 12.JUL.2019 17:21:12


Conducted Spurious Emission Plot on 802.15.4 Channel 11



Date: 12.JUL.2019 17:21:27




Conducted Spurious Emission Plot on 802.15.4 Channel 18



Date: 12.JUL.2019 17:16:46


Conducted Spurious Emission Plot on 802.15.4 Channel 18



Date: 12.JUL.2019 17:17:07




Conducted Spurious Emission Plot on 802.15.4 Channel 25



Date: 12.JUL.2019 17:02:01

Conducted Spurious Emission Plot on 802.15.4 Channel 25



Date: 12.JUL.2019 17:02:16



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.




3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Sensor	DARE	RPR3006W	13I00030SN O32	9kHz~6GHz	Dec. 03, 2018	Jul. 12, 2019~ Jul. 13, 2019	Dec. 02, 2019	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 13, 2018	Jul. 12, 2019~ Jul. 13, 2019	Nov. 12, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1208382	N/A	Mar. 27, 2019	Jul. 12, 2019~ Jul. 13, 2019	Mar. 26, 2020	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 26, 2019 ~ Sep. 11, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	Jul. 26, 2019 ~ Sep. 11, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Jul. 26, 2019 ~ Sep. 11, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Jul. 26, 2019 ~ Sep. 11, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 26, 2019 ~ Sep. 11, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Jul. 26, 2019 ~ Sep. 11, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Jul. 26, 2019 ~ Sep. 11, 2019	Dec. 30, 2019	Conduction (CO05-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	35419 & 03	30MHz~1GHz	Apr. 30, 2019	Jul. 05, 2019 ~ Aug. 05, 2019	Apr. 29, 2020	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Dec. 02, 2018	Jul. 05, 2019 ~ Aug. 05, 2019	Dec. 03, 2019	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz~26.5GHz	Jan. 23, 2019	Jul. 05, 2019 ~ Aug. 05, 2019	Jan. 22, 2020	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jan. 11, 2019	Jul. 05, 2019 ~ Aug. 05, 2019	Jan. 10, 2020	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz~18GHz	Apr. 24, 2019	Jul. 05, 2019 ~ Aug. 05, 2019	Apr. 23, 2020	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	May 20, 2019	Jul. 05, 2019 ~ Aug. 05, 2019	May 19, 2020	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~26.5GHz	Nov. 02, 2018	Jul. 05, 2019 ~ Aug. 05, 2019	Nov. 01, 2019	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4, MY28655/4	9kHz~30MHz	Feb. 26, 2019	Jul. 05, 2019 ~ Aug. 05, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4, MY24971/4, MY15682/4	30MHz~1GHz	Feb. 26, 2019	Jul. 05, 2019 ~ Aug. 05, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4, MY24971/4, MY15682/4	1GHz~18GHz	Feb. 26, 2019	Jul. 05, 2019 ~ Aug. 05, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2858/2	18GHz~40GHz	Feb. 26, 2019	Jul. 05, 2019 ~ Aug. 05, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Jul. 05, 2019 ~ Aug. 05, 2019	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Jul. 05, 2019 ~ Aug. 05, 2019	N/A	Radiation (03CH07-HY)
Preamplifier	MITEQ	TTA1840-35-H G	1871923	18GHz~40GHz, VSWR : 2.5:1 max	N/A	Jul. 05, 2019 ~ Aug. 05, 2019	N/A	Radiation (03CH07-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz~44GHz	Nov. 02, 2018	Jul. 05, 2019 ~ Aug. 05, 2019	Nov. 01, 2019	Radiation (03CH07-HY)
Software	Audix	E3 6.2009-8-24	8050400465 6H	N/A	N/A	Jul. 05, 2019 ~ Aug. 05, 2019	N/A	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	18GHz~40GHz	Nov. 20, 2018	Jul. 05, 2019 ~ Aug. 05, 2019	Nov. 19, 2019	Radiation (03CH07-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.2
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.5
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Derek Hsu	Temperature:	21~25	°C
Test Date:	2019/7/12~2019/07/13	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
802.15.4	250K	1	11	2405	2.253	1.464	0.50	Pass
802.15.4	250K	1	17	2435	2.258	1.558	0.50	Pass
802.15.4	250K	1	25	2475	2.253	1.429	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
802.15.4	250K	1	11	2405	19.90	30.00	5.18	25.08	36.00	Pass
802.15.4	250K	1	17	2435	19.80	30.00	5.18	24.98	36.00	Pass
802.15.4	250K	1	25	2475	17.20	30.00	5.18	22.38	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
802.15.4	250K	1	11	2405	16.23	6.67	5.18	8.00	Pass
802.15.4	250K	1	17	2435	16.29	6.65	5.18	8.00	Pass
802.15.4	250K	1	25	2475	13.80	4.19	5.18	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.



Appendix B. AC Conducted Emission Test Results


Test Engineer :	Jimmy Chang	Temperature :	25.5~26.4°C
		Relative Humidity :	55~58%

EUT Information

Report NO : 960638

Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	30.17	55.40	25.23	L1	OFF	19.4
0.161250	42.22	---	65.40	23.18	L1	OFF	19.4
0.228750	---	26.46	52.50	26.04	L1	OFF	19.4
0.228750	35.67	---	62.50	26.83	L1	OFF	19.4
0.602250	---	33.88	46.00	12.12	L1	OFF	19.4
0.602250	38.31	---	56.00	17.69	L1	OFF	19.4
2.442750	---	23.63	46.00	22.37	L1	OFF	19.5
2.442750	25.09	---	56.00	30.91	L1	OFF	19.5
8.927250	---	25.01	50.00	24.99	L1	OFF	19.8
8.927250	26.02	---	60.00	33.98	L1	OFF	19.8
22.107750	---	24.66	50.00	25.34	L1	OFF	20.2
22.107750	25.78	---	60.00	34.22	L1	OFF	20.2

EUT Information

Report NO : 960638

Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	30.33	55.40	25.07	N	OFF	19.5
0.161250	43.11	---	65.40	22.29	N	OFF	19.5
0.591000	---	27.69	46.00	18.31	N	OFF	19.5
0.591000	35.48	---	56.00	20.52	N	OFF	19.5
2.091750	---	23.70	46.00	22.30	N	OFF	19.6
2.091750	25.38	---	56.00	30.62	N	OFF	19.6
5.016750	---	24.73	50.00	25.27	N	OFF	19.7
5.016750	25.77	---	60.00	34.23	N	OFF	19.7
11.305500	---	24.86	50.00	25.14	N	OFF	19.9
11.305500	25.86	---	60.00	34.14	N	OFF	19.9
20.422500	---	24.47	50.00	25.53	N	OFF	20.3
20.422500	25.52	---	60.00	34.48	N	OFF	20.3



Appendix C. Radiated Spurious Emission

Test Engineer :	Jesse Wang, Stan Hsieh and Ken Wu	Temperature :	24~26°C
		Relative Humidity :	52~60%

2.4GHz 2400~2483.5MHz
802.15.4 (Band Edge @ 3m)

802.15.4	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
802.15.4 CH 11 2405MHz		2388.645	61.67	-12.33	74	46.87	32	17.74	34.94	258	171	P	H	
		2390	47.77	-6.23	54	32.98	32	17.74	34.95	258	171	A	H	
	*	2405	117.28	-	-	102.42	32.07	17.74	34.95	258	171	P	H	
	*	2405	115.61	-	-	100.75	32.07	17.74	34.95	258	171	A	H	
													H	
														H
			2388.855	61.21	-12.79	74	46.41	32	17.74	34.94	396	313	P	V
			2389.485	46.61	-7.39	54	31.81	32	17.74	34.94	396	313	A	V
	*		2405	114.78	-	-	99.92	32.07	17.74	34.95	396	313	P	V
	*		2405	112.96	-	-	98.1	32.07	17.74	34.95	396	313	A	V
														V
														V
802.15.4 CH 18 2440MHz		2366.14	55.81	-18.19	74	41.21	31.87	17.67	34.94	242	166	P	H	
		2386.72	45.27	-8.73	54	30.47	32	17.74	34.94	242	166	A	H	
	*	2440	117.83	-	-	102.8	32.2	17.79	34.96	242	166	P	H	
	*	2440	116.23	-	-	101.2	32.2	17.79	34.96	242	166	A	H	
			2485.16	56.23	-17.77	74	41.16	32.2	17.84	34.97	242	166	P	H
			2484.39	47.18	-6.82	54	32.11	32.2	17.84	34.97	242	166	A	H
			2342.62	55.55	-18.45	74	41.03	31.8	17.66	34.94	358	287	P	V
			2383.64	45.07	-8.93	54	30.34	31.93	17.74	34.94	358	287	A	V
	*		2440	114.81	-	-	99.78	32.2	17.79	34.96	358	287	P	V
	*		2440	113.09	-	-	98.06	32.2	17.79	34.96	358	287	A	V
			2492.65	55.44	-18.56	74	40.38	32.2	17.84	34.98	358	287	P	V
			2484.53	45.76	-8.24	54	30.69	32.2	17.84	34.97	358	287	A	V



802.15.4 CH 25 2475MHz	*	2475	114.78	-	-	99.71	32.2	17.84	34.97	271	164	P	H
	*	2475	112.74	-	-	97.67	32.2	17.84	34.97	271	164	A	H
		2485.76	61.03	-12.97	74	45.96	32.2	17.84	34.97	271	164	P	H
		2483.52	52.06	-1.94	54	36.99	32.2	17.84	34.97	271	164	A	H
													H
													H
	*	2475	111.08	-	-	96.01	32.2	17.84	34.97	400	287	P	V
	*	2475	109.4	-	-	94.33	32.2	17.84	34.97	400	287	A	V
		2483.76	57.81	-16.19	74	42.74	32.2	17.84	34.97	400	287	P	V
		2483.52	49.15	-4.85	54	34.08	32.2	17.84	34.97	400	287	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
802.15.4 (Harmonic @ 3m)

802.15.4	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.15.4 CH 11 2405MHz		4810	43.4	-30.6	74	57.1	34	11.36	59.06	100	0	P	H
													H
													H
													H
		4810	43.26	-30.74	74	56.96	34	11.36	59.06	100	0	P	V
													V
													V
802.15.4 CH 18 2440MHz		4880	43.83	-30.17	74	57.2	34.13	11.42	58.92	100	0	P	H
		7320	45.51	-28.49	74	54.22	35.63	13.97	58.31	100	0	P	H
													H
													H
		4880	43.83	-30.17	74	57.2	34.13	11.42	58.92	100	0	P	V
		7320	46.75	-27.25	74	55.46	35.63	13.97	58.31	100	0	P	V
													V
802.15.4 CH 25 2475MHz		4950	43.16	-30.84	74	56.26	34.2	11.48	58.78	100	0	P	H
		7425	45.46	-28.54	74	54.24	35.5	14.09	58.37	100	0	P	H
													H
													H
		4950	43.3	-30.7	74	56.4	34.2	11.48	58.78	100	0	P	V
		7425	44.65	-29.35	74	53.43	35.5	14.09	58.37	100	0	P	V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz 802.15.4 (LF)

802.15.4	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
2.4GHz 802.15.4 LF		30.27	22.76	-17.24	40	26.95	24.6	1.19	29.98	-	-	P	H	
		51.06	19.1	-20.9	40	34.04	13.86	1.19	29.99	-	-	P	H	
		170.4	27.35	-16.15	43.5	39.66	15.51	2.07	29.89	-	-	P	H	
		394.5	35.9	-10.1	46	41.13	21.49	3.07	29.79	100	0	P	H	
		863.5	33.22	-12.78	46	28.64	29.01	4.63	29.06	-	-	P	H	
		953.1	34.26	-11.74	46	27.52	30.54	4.74	28.54	-	-	P	H	
														H
														H
														H
														H
														H
														H
			30	32.94	-7.06	40	37.13	24.6	1.19	29.98	100	0	P	V
			36.21	27.58	-12.42	40	34.86	21.51	1.19	29.98	-	-	P	V
			50.79	25.32	-14.68	40	39.87	14.25	1.19	29.99	-	-	P	V
			376.3	33.7	-12.3	46	39.74	20.88	2.86	29.78	-	-	P	V
			848.1	32.75	-13.25	46	28.67	28.71	4.48	29.11	-	-	P	V
			952.4	34.19	-11.81	46	27.51	30.49	4.74	28.55	-	-	P	V
														V
														V
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
					(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 00		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H
2402MHz													

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots





Test Engineer :	Jesse Wang, Stan Hsieh and Ken Wu	Temperature :	24~26°C
		Relative Humidity :	52~60%

Note symbol





-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz
802.15.4 (Band Edge @ 3m)

802.15.4	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
802.15.4 CH11 2405MHz		
	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Peak : Peak Project : 960638 Mode : 9 v320</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Peak : Peak Project : 960638 Mode : 9 v320</p>
<p>Avg.</p>	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Peak : Peak Project : 960638 Mode : 9 v320</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Peak : Peak Project : 960638 Mode : 9 v320</p>





802.15.4	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
802.15.4 CH11 2405MHz		
	Vertical	Fundamental
<p>Peak</p>	 <p>Date: 2019-07-05</p> <pre> Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 960638 Mode : v320 </pre>	 <p>Date: 2019-07-05</p> <pre> Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 960638 Mode : v320 </pre>
<p>Avg</p>	 <p>Date: 2019-07-05</p> <pre> Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 960638 Mode : v320 </pre>	 <p>Date: 2019-07-05</p> <pre> Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 960638 Mode : v320 </pre>



802.15.4	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
802.15.4 CH18 2440MHz - L		
	Horizontal	Fundamental
<p>Peak</p>	 <p>Level (dBm/3m) vs Frequency (MHz) plot showing a peak at 2440 MHz. The y-axis ranges from 8.8 to 140 dBm/3m, and the x-axis ranges from 2310 to 2450 MHz. A red vertical line marks the peak at 2440 MHz.</p> <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 960638 Mode : v320</p>	 <p>Level (dBm/3m) vs Frequency (MHz) plot showing a peak at 2440 MHz. The y-axis ranges from 8.8 to 140 dBm/3m, and the x-axis ranges from 1000 to 3000 MHz. A red horizontal line labeled 'PEAK_74' is at approximately 78 dBm/3m.</p> <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 960638 Mode : v320</p>
<p>Avg.</p>	 <p>Level (dBm/3m) vs Frequency (MHz) plot showing the average spectrum. The y-axis ranges from 8.8 to 140 dBm/3m, and the x-axis ranges from 2310 to 2450 MHz. A red vertical line marks the peak at 2440 MHz.</p> <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 960638 Mode : v320</p>	 <p>Level (dBm/3m) vs Frequency (MHz) plot showing the average spectrum. The y-axis ranges from 8.8 to 140 dBm/3m, and the x-axis ranges from 1000 to 3000 MHz. A red horizontal line labeled 'AVG_54' is at approximately 61 dBm/3m.</p> <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 960638 Mode : v320</p>





802.15.4	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
802.15.4 CH18 2440MHz - R		
	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 960638 Mode : v320</p>	Left blank
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 960638 Mode : v320</p>	Left blank







802.15.4	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
802.15.4 CH18 2440MHz - L		
	Vertical	Fundamental
<p>Peak</p>	<p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_0007596Z VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 10 : v320</p>	<p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_0007596Z VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 10 : v320</p>
<p>Avg.</p>	<p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : AVG_BE_S4 3m HF_ANT_0007596Z VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 10 : v320</p>	<p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : AVG_S4 3m HF_ANT_0007596Z VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 10 : v320</p>




802.15.4	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
802.15.4 CH18 2440MHz - R		
	Vertical	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_0007596Z VERTICAL Detector : Peak Project : 960638 Mode : v320</p>	Left blank
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_S4 3m HF_ANT_0007596Z VERTICAL Detector : Peak Project : 960638 Mode : v320</p>	Left blank



802.15.4	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
802.15.4 CH25 2475MHz		
	Horizontal	Fundamental
<p>Peak</p>	 <p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 11 : v180</p>	 <p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 11 : v180</p>
<p>Avg.</p>	 <p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : AVG_BE_S4 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 11 : v180</p>	 <p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : AVG_S4 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 11 : v180</p>





802.15.4	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
802.15.4 CH25 2475MHz		
	Vertical	Fundamental
<p>Peak</p>	 <p>Level (dBm/1m) vs Frequency (MHz) plot showing a peak at 2475 MHz. The y-axis ranges from 8.8 to 140 dBm/1m, and the x-axis ranges from 2460 to 2500 MHz. A red horizontal line indicates the peak level at approximately 70 dBm/1m.</p> <p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_0007596Z VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 11 : v180</p>	 <p>Level (dBm/1m) vs Frequency (MHz) plot showing a sharp peak at 2475 MHz. The y-axis ranges from 8.8 to 140 dBm/1m, and the x-axis ranges from 2400 to 3000 MHz. A red horizontal line indicates the peak level at approximately 70 dBm/1m.</p> <p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_0007596Z VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 11 : v180</p>
<p>Avg.</p>	 <p>Level (dBm/1m) vs Frequency (MHz) plot showing the average spectrum. The y-axis ranges from 8.8 to 140 dBm/1m, and the x-axis ranges from 2460 to 2500 MHz. A red horizontal line indicates the average level at approximately 43 dBm/1m.</p> <p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : AVG_BE_S4 3m HF_ANT_0007596Z VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 11 : v180</p>	 <p>Level (dBm/1m) vs Frequency (MHz) plot showing the average spectrum. The y-axis ranges from 8.8 to 140 dBm/1m, and the x-axis ranges from 2400 to 3000 MHz. A red horizontal line indicates the average level at approximately 43 dBm/1m.</p> <p>Date: 2019-07-05</p> <p>Site : 03CH07-HY Condition : AVG_S4 3m HF_ANT_0007596Z VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Detector : Peak Project : 960638 Mode : 11 : v180</p>





2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

802.15.4	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
802.15.4 CH11 2405MHz		
Horizontal		Vertical
Peak Avg.	 <p>Site : 03CHO7-HY Condition : PEAK_T4 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 960638 Mode : 9 v320</p>	 <p>Site : 03CHO7-HY Condition : PEAK_T4 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 960638 Mode : 9 v320</p>





802.15.4	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
802.15.4 CH18 2440MHz		
	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 960638 Mode : 10 : v320</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 960638 Mode : 10 : v320</p>



802.15.4	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
802.15.4 CH25 2475MHz		
	Horizontal	Vertical
Peak	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 960638 Mode : 11 v180</p>	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 960638 Mode : 11 v180</p>



Emission below 1GHz
2.4GHz 802.15.4 (LF)


802.15.4	2.4GHz 2400~2483.5MHz	
802.15.4 LF		
Horizontal		Vertical
QP / Peak	 <p data-bbox="443 828 654 884">Site : 03CH07-HY Condition : QP 3m LF-ANT-35419(6) HORIZONTAL Detector : Peak Project : 960638 Mode : 12</p>	 <p data-bbox="919 828 1129 884">Site : 03CH07-HY Condition : QP 3m LF-ANT-35419(6) VERTICAL Detector : Peak Project : 960638 Mode : 12</p>



Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
802.15.4	14.04	2245	0.45	1kHz	8.53

802.15.4



Date: 12.JUL.2019 16:33:52

—————THE END—————