

RF Exposure Report

Report No.: SA180604C04 R1

FCC ID: (1) A4R-WT3

(2) A4R-WT4

Test Model: WT3

Received Date: Jun. 04, 2018

Date of Evaluation: Jul. 13, 2018

Issued Date: Sep. 03, 2018

Applicant: Google LLC

Address: 1600 Amphitheatre Parkway, Mountain View, California, United States
94043

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan,
R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City
33383, Taiwan (R.O.C)

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specifically mentioned, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula.....	5
2.3 Classification.....	5
2.4 Antenna Gain	5
2.5 Calculation Result Of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA180604C04	Original Release	Jul. 23, 2018
SA180604C04 R1	Add FCC ID	Sep. 03, 2018

1 Certificate of Conformity

Product: Study Hub

Brand: Verily

Test Model: WT3

Sample Status: Production Unit

Applicant: Google LLC

Date of Evaluation: Jul. 13, 2018


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :




Date:

Sep. 03, 2018

Rona Chen / Specialist

Approved by :



Date:

Sep. 03, 2018

Dylan Chiou / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

WWAN Antenna											
Antenna Type	Fixed Internal										
Band	WCDMA			LTE							
	II	VI	V	2	4	5	12	17	30	38	66
Gain	3.81	2.51	1.53	3.81	2.51	1.53	2.63	2.35	3.68	1.87	2.51

BT/WLAN Antenna						
Antenna Type	PIFA					
Frequency	BT		WLAN			
	2.4 GHz	2.4 GHz	5.15~5.25 GHz	5.25~5.35 GHz	5.47~5.725 GHz	5.725~5.825 GHz
Gain	1.72	2.42	3.61	3.48	3.08	3.35

2.5 Calculation Result of Maximum Conducted Power

Band	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA II	1850-1910	23.62	3.81	20	0.110	1.00
WCDMA IV	1710-1755	23.77	2.51	20	0.084	1.00
WCDMA V	824-849	23.76	1.53	20	0.067	0.55
LTE 2	1850-1910	22.75	3.81	20	0.090	1.00
LTE 4	1710-1755	23.27	2.51	20	0.075	1.00
LTE 5	824-849	22.72	1.53	20	0.053	0.55
LTE 12	699-716	22.88	2.63	20	0.071	0.47
LTE 17	704-716	23.00	2.35	20	0.068	0.47
LTE 30	2305-2315	23.03	3.68	20	0.093	1.00
LTE 38	2570-2620	22.96	1.87	20	0.060	1.00
LTE 66	1710-1780	23.25	2.51	20	0.075	1.00
WLAN	2412-2462	19.42	5.43	20	0.061	1.00
	5180-5240	18.10	6.62	20	0.059	1.00
	5260-5320	18.50	6.62	20	0.065	1.00
	5500-5700	18.76	6.62	20	0.069	1.00
	5745-5825	18.45	6.62	20	0.064	1.00
BT	2402-2480	9.55	1.72	20	0.003	1.00

NOTE:

1. Max power used is already max. tune up power for RF exposure evaluation
2. 2.4GHz: Directional gain = 2.42 dBi + 10log(2) = 5.43dBi
3. 5.0GHz: Directional gain = 3.61 dBi + 10log(2) = 6.62dBi

Conclusion:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$WWAN + WLAN + BT = 0.071 / 0.47 + 0.069 / 1.00 + 0.003 / 1.00 = 0.223$$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---