



RF EXPOSURE EVALUATION REPORT

FCC ID : A4RG022A
Equipment : Wireless Device
Model Name : G022A
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA 94043
Standard : 47 CFR Part 2.1093
FCC KDB 447498 D01 v06

We, SPORTON INTERNATIONAL INC has been evaluated in accordance with 47 CFR Part 2.1093 for the device and pass the limit.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

- 1. General Information 3
- 1.1 Description of Device Under Test (DUT) 3
- 2. Maximum Average RF output power among production units..... 3
- 3. RF Exposure Evaluation 4

History of this test report

Report No.	Version	Description	Issued Date
FA8D2820	Rev. 01	Initial issue of report	Apr. 30, 2019
FA8D2820	Rev. 02	Updated Average RF output power	May 10, 2019



1. General Information

1.1 Description of Device Under Test (DUT)

Product Feature & Specification	
DUT Type	Wireless Device
Model Name	G022A
FCC ID	A4RG022A
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	Bluetooth LE

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Reviewed by: Jason Wang

Report Producer: Wan Liu

2. Maximum Average RF output power among production units

Mode / Band	Average RF output power(dBm)
	LE
	(GFSK)
2.4GHz Bluetooth	1.5



3. RF Exposure Evaluation

Bluetooth Max Power (dBm)	mW	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
1.5	1.41	5	2.48	0.44

Note:

1. Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Conclusion: Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.44 which is ≤ 3, SAR testing is not required.