





DFT-s-OFDM Module B

NR Band n261 QPSK (18-40GHz)


Lowest Channel / 200MHz




Lowest Channel / 300MHz




Middle Channel / 200MHz




Middle Channel / 300MHz



Highest Channel / 200MHz



Highest Channel / 300MHz




Remark: In band and out of band frequencies are omitted.



DFT-s-OFDM Module B


NR Band n261 QPSK (18-40GHz)

Lowest Channel / 400MHz




intentionally blank

Middle Channel / 400MHz



intentionally blank

Highest Channel / 400MHz



intentionally blank


Remark: In band and out of band frequencies are omitted.




CP-OFDM Module B

NR Band n261 QPSK (18-40GHz)


Lowest Channel / 50MHz




Lowest Channel / 100MHz



Middle Channel / 50MHz




Middle Channel / 100MHz



Highest Channel / 50MHz



Highest Channel / 100MHz




Remark: In band and out of band frequencies are omitted.




CP-OFDM Module B

NR Band n261 QPSK (18-40GHz)


Lowest Channel / 200MHz




Lowest Channel / 300MHz




Middle Channel / 200MHz




Middle Channel / 300MHz



Highest Channel / 200MHz



Highest Channel / 300MHz




Remark: In band and out of band frequencies are omitted.



CP-OFDM Module B


NR Band n261 QPSK (18-40GHz)

Lowest Channel / 400MHz




intentionally blank

Middle Channel / 400MHz



intentionally blank

Highest Channel / 400MHz




intentionally blank

Remark: In band and out of band frequencies are omitted.



There is no significant spurious emission signal found for frequency started from 40GHz up to 200GHz.
Only the noise floor is reported.




$$\text{Offset} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} + 107 + 20\log(D) - 104.8$$
$$= 43 + 0.43 + 107 + 20\log(1) - 104.8 = 45.63(\text{dB})$$



NR Band n261

(60GHz-90GHz)




$$\text{Offset} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} + 107 + 20\log(D) - 104.8$$
$$= 46.9 + 0.43 + 107 + 20\log(1) - 104.8 = 49.53 \text{ (dB)}$$



NR Band n261

(90GHz-100GHz)



$$\begin{aligned} \text{Offset} &= \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} + 107 + 20\log(D) - 104.8 \\ &= 47.92 + 0.43 + 107 + 20\log(0.5) - 104.8 = 44.53 \text{ (dB)} \end{aligned}$$



Frequency Stability

Test Conditions		NR Band n261 / Middle Channel			Limit
Temperature (°C)	Voltage (Volt)	CW tone			Note 2.
		Frequency (GHz)	Deviation (kHz)	Deviation (ppm)	Result
50	Normal Voltage	27.924966	16.000	0.573	Pass
40	Normal Voltage	27.924986	-4.000	0.143	
30	Normal Voltage	27.92497	12.000	0.430	
20(Ref.)	Normal Voltage	27.924982	0.000	0.000	
10	Normal Voltage	27.924976	6.000	0.215	
0	Normal Voltage	27.924986	-4.000	0.143	
-10	Normal Voltage	27.925008	-26.000	0.931	
-20	Normal Voltage	27.925038	-56.000	2.005	
-30	Normal Voltage	27.925044	-62.000	2.220	
20	Maximum Voltage	27.924976	6.000	0.215	
20	Normal Voltage	27.924978	4.000	0.143	
20	Battery End Point	27.924976	6.000	0.215	

Note:

1. Normal Voltage = 3.89 V. ; Battery End Point (BEP) = 3.6 V. ; Maximum Voltage = 4.4 V.
2. The frequency fundamental emissions stay within the operation band.



Appendix B. R&S Mixer and Horn Antenna Calibration Reports



CALIBRATION CERTIFICATE



Kalibrierschein

Certificate Number
Zertifikatsnummer

0001A300718726

General Data	
Item Gegenstand	FS-Z60 HARMONIC MIXER 40-60GHZ
Manufacturer Hersteller	ROHDE & SCHWARZ
Type Typ	FS-Z60
Material Number Materialnummer	1048.0171.02
Serial Number Seriennummer	100986
Order Number Bestellnummer	Q786007
Asset Number Inventarnummer	
Customer Auftraggeber	Sporton International Inc. 6F., Sec. 1, Hsin Tai Wu Rd 106 221 New Taipei City TW
Performance	
Place and Date of Calibration Ort und Datum der Kalibrierung	87700 Memmingen, Rohde-und-Schwarz-Str. 1 2023-10-31
Statement of Compliance (Incoming) Konformitätsaussage (Anlieferung)	All measured values are within the data sheet specifications.
Statement of Compliance (Outgoing) Konformitätsaussage (Auslieferung)	All measured values are within the data sheet specifications.
Customers due Interval Kalibrierintervall des Kunden	
Extent of Calibration Document Umfang des Kalibrierdokuments	3 Pages Certificate 6 Pages Outgoing Results 6 Pages Incoming Results
Date of Issue Ausstellungsdatum	Approval of the certificate by Freigabe des Kalibrierscheins durch
2023-11-08	Dr. Gerhard Rösel Johannes Negele
	 
	Laboratory management Labormanagement Person responsible Bearbeiter

Calibration Mark
Kalibrierzeichen

300718726
D-K- 15195-01-00
2023-10

Member of Deutscher Kalibrierdienst
Mitglied im Deutschen Kalibrierdienst



This calibration certificate documents the metrological traceability to national standards, which realize the units of measurement according to the International System of Units (SI). The DAkkS is signatory to the multilateral agreements of the European co-operation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates. The user is obliged to have the object recalibrated at appropriate intervals. This calibration certificate may not be reproduced other than in full except with the permission of the issuing laboratory. Calibration certificates with the full name of the approval responsible person are valid without signature.

Dieser Kalibrierschein dokumentiert die metrologische Rückführbarkeit auf nationale Normale zur Darstellung der Einheiten in Übereinstimmung mit dem Internationalen Einheitensystem (SI). Die DAkkS ist Unterzeichner der multilateralen Übereinkommen der European cooperation for Accreditation (EA) und der International Laboratory Accreditation Cooperation (ILAC) zur gegenseitigen Anerkennung der Kalibrierscheine. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich. Dieser Kalibrierschein darf nur vollständig weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung des ausstellenden Kalibrierlaboratoriums. Kalibrierscheine sind bei Nennung des für die Freigabe Verantwortlichen in Klarschrift auch ohne Unterschrift gültig.



Material No 1048.0171.02 **Serial No** 100986 **Certificate** 0001A300718726
Page 2/3 **Number**

Calibration Procedure

The measuring object is an RF harmonic mixer, which converts an RF signal at one frequency into a signal at another frequency (here: IF). The conversion loss was measured using a vector network analyzer. The RF output power as well as the IF input power of the corresponding ports of the VNA were traced back to a power sensor. The conversion loss is defined as the ratio of the power at the IF frequency to the power at the RF frequency with a given LO power. (IF: Intermediate frequency; LO: Local Oscillator)
The traceability is represented in the table Working Standards used.

Working Standards used

Item	Type	Serial Number	Calibration Certificate Number	Cal. Due
Therm.Power Sensor DC-40GHz	NRP-Z55	130179	0001A300682928	2025-01-31
Thermal Power Sensor	NRP67T	100977	0001A300658977	2025-07-31
Vector Network Analyzer 4 Port	ZVA67	101100	0001A300698540	2024-05-31

Remarks



Material No 1048.0171.02 **Serial No** 100986 **Certificate** 0001A300718726
Page 3/3 **Number**

Environmental Conditions			
Ambient Temperature	(23 ± 1) °C	Relative Humidity	20%-70%

Comments on Measurement Results
<p>The reported results apply only to those items specifically listed on this calibration certificate and have been tested for compliance with the specifications. The associated uncertainty of measurement has been taken into account if not otherwise stated.</p> <p>The non-binary decision rule with guard band is used according to ILAC G8:09/2019 'Guidelines on Decision Rules and Statements of Conformity'. Pass is normally not marked. Conditional Pass is marked with UGB1, Conditional Fail with UGB2 and Fail with Fail.</p> <p>The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k such that the coverage probability corresponds to approximately 95 %. It is consistent with the EA-4/02 M:2022.</p> <p>In addition to the calibration results, the calibration certificate includes functional measurements that might have an influence on the measurement uncertainty of the calibration results.</p> <p>The functional measurement results are marked and are not intended to be used to support the further dissemination of metrological traceability. They are intended to verify the requirements on the measurement object according to manufacturer specifications and technical standards.</p>

Outgoing Results

Designation: HARMONIC MIXER
Type: FS-Z60
Material No.: 1048.0171.02
Serial No.: 100986
Certificate No.: 0001A300718726
Referring to Test Documentation: 5038.8581.01-PB-02.00

Test Department: 3MM-P
Name: see certificate
Date: 2023-10-31



Table of contents


Software used for measurement	3
1. Conversion Loss (4. Harmonic)	4
1.1 Conversion Loss (IF = 404.4 MHz)	4
1.2 Conversion Loss (IF = 729 MHz)	5
1.3 Conversion Loss (IF = 1330 MHz)	6
1.4 Continuity response within 1 GHz	6

Software used for measurement			
Item	Type	Version	Remark
Suite	Setup	V12.37.04	Test Management Software G5
Test Program (7012.8706.00_)	Component	V01.05	

1. Conversion Loss (4. Harmonic)

1.1 Conversion Loss (IF = 404.4 MHz)

IF = 404.4 MHz, 4. Harmonic




Conversion Loss (IF = 404.4 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
40.0	10.0	±1.3
41.0	10.4	±1.3
42.0	11.9	±1.3
43.0	13.0	±1.3
44.0	13.3	±1.3
45.0	14.0	±1.3
46.0	15.1	±1.3
47.0	14.3	±1.3
48.0	14.9	±1.3
49.0	14.7	±1.3
50.0	12.5	±1.3
51.0	11.2	±1.3
52.0	11.1	±1.3
53.0	10.1	±1.3
54.0	10.0	±1.3
55.0	10.0	±1.3
56.0	10.7	±1.3
57.0	11.2	±1.3
58.0	11.7	±1.3
59.0	12.5	±1.3
60.0	14.0	±1.3

1.2 Conversion Loss (IF = 729 MHz)

IF = 729 MHz, 4. Harmonic




Conversion Loss (IF = 729 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
40.0	9.9	±1.3
41.0	10.2	±1.3
42.0	11.6	±1.3
43.0	12.6	±1.3
44.0	12.9	±1.3
45.0	13.4	±1.3
46.0	15.1	±1.3
47.0	13.9	±1.3
48.0	15.0	±1.3
49.0	14.7	±1.3
50.0	12.9	±1.3
51.0	11.4	±1.3
52.0	11.2	±1.3
53.0	10.0	±1.3
54.0	10.0	±1.3
55.0	10.0	±1.3
56.0	10.7	±1.3
57.0	11.2	±1.3
58.0	11.6	±1.3
59.0	12.6	±1.3
60.0	13.9	±1.3

1.3 Conversion Loss (IF = 1330 MHz)

IF = 1330 MHz, 4. Harmonic



Conversion Loss (IF = 1330 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
40.0	10.3	±1.3
41.0	10.5	±1.3
42.0	11.9	±1.3
43.0	13.2	±1.3
44.0	13.1	±1.3
45.0	13.4	±1.3
46.0	14.8	±1.3
47.0	14.1	±1.3
48.0	15.0	±1.3
49.0	16.1	±1.3
50.0	13.9	±1.3
51.0	12.8	±1.3
52.0	11.8	±1.3
53.0	10.5	±1.3
54.0	10.5	±1.3
55.0	10.4	±1.3
56.0	11.1	±1.3
57.0	11.4	±1.3
58.0	12.2	±1.3
59.0	13.0	±1.3
60.0	14.6	±1.3

1.4 Continuity response within 1 GHz

Continuity response within any 1 GHz Band, 4. Harmonic

	DUL /dB	Continuity /dB
max. at IF = 404.4 MHz:	6.0	2.37
max. at IF = 729 MHz:	6.0	2.19
max. at IF = 1330 MHz:	6.0	2.19

Incoming Results

Designation: HARMONIC MIXER
Type: FS-Z60
Material No.: 1048.0171.02
Serial No.: 100986
Certificate No.: 0001A300718726
Referring to Test Documentation: 5038.8581.01-PB-02.00

Test Department: 3MM-P
Name: see certificate
Date: 2023-10-31



Table of contents

Software used for measurement	3
1. Conversion Loss (4. Harmonic)	4
1.1 Conversion Loss (IF = 404.4 MHz)	4
1.2 Conversion Loss (IF = 729 MHz)	5
1.3 Conversion Loss (IF = 1330 MHz)	6
1.4 Continuity response within 1 GHz	6


Incoming Results

Software used for measurement			
Item	Type	Version	Remark
Suite	Setup	V12.37.04	Test Management Software G5
Test Program (7012.8706.00_)	Component	V01.05	

1. Conversion Loss (4. Harmonic)

1.1 Conversion Loss (IF = 404.4 MHz)

IF = 404.4 MHz, 4. Harmonic




Conversion Loss (IF = 404.4 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
40.0	10.2	±1.3
41.0	10.6	±1.3
42.0	12.0	±1.3
43.0	13.1	±1.3
44.0	13.5	±1.3
45.0	14.2	±1.3
46.0	15.3	±1.3
47.0	14.4	±1.3
48.0	15.1	±1.3
49.0	14.8	±1.3
50.0	12.7	±1.3
51.0	11.4	±1.3
52.0	11.3	±1.3
53.0	10.3	±1.3
54.0	10.2	±1.3
55.0	10.2	±1.3
56.0	10.9	±1.3
57.0	11.3	±1.3
58.0	11.9	±1.3
59.0	12.6	±1.3
60.0	14.2	±1.3

Incoming Results

1.2 Conversion Loss (IF = 729 MHz)

IF = 729 MHz, 4. Harmonic




Conversion Loss (IF = 729 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
40.0	10.1	±1.3
41.0	10.4	±1.3
42.0	11.8	±1.3
43.0	12.9	±1.3
44.0	13.1	±1.3
45.0	13.6	±1.3
46.0	15.4	±1.3
47.0	14.1	±1.3
48.0	15.2	±1.3
49.0	14.9	±1.3
50.0	13.1	±1.3
51.0	11.6	±1.3
52.0	11.4	±1.3
53.0	10.2	±1.3
54.0	10.1	±1.3
55.0	10.1	±1.3
56.0	10.8	±1.3
57.0	11.4	±1.3
58.0	11.8	±1.3
59.0	12.7	±1.3
60.0	14.0	±1.3

Incoming Results

1.3 Conversion Loss (IF = 1330 MHz)

IF = 1330 MHz, 4. Harmonic



Conversion Loss (IF = 1330 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
40.0	10.5	±1.3
41.0	10.6	±1.3
42.0	12.1	±1.3
43.0	13.3	±1.3
44.0	13.2	±1.3
45.0	13.5	±1.3
46.0	15.0	±1.3
47.0	14.2	±1.3
48.0	15.1	±1.3
49.0	16.2	±1.3
50.0	14.0	±1.3
51.0	12.9	±1.3
52.0	11.8	±1.3
53.0	10.6	±1.3
54.0	10.6	±1.3
55.0	10.5	±1.3
56.0	11.2	±1.3
57.0	11.4	±1.3
58.0	12.3	±1.3
59.0	13.0	±1.3
60.0	14.7	±1.3

1.4 Continuity response within 1 GHz

Continuity response within any 1 GHz Band, 4. Harmonic

	DUL /dB	Continuity /dB
max. at IF = 404.4 MHz:	6.0	2.35
max. at IF = 729 MHz:	6.0	2.18
max. at IF = 1330 MHz:	6.0	2.22

Incoming Results





CALIBRATION CERTIFICATE



Kalibrierschein

Certificate Number
Zertifikatsnummer

0001A300718729

General Data	
Item Gegenstand	FS-Z90 HARMONIC MIXER 60-90GHZ
Manufacturer Hersteller	ROHDE & SCHWARZ
Type Typ	FS-Z90
Material Number Materialnummer	1048.0371.02
Serial Number Seriennummer	101811
Order Number Bestellnummer	Q786007
Asset Number Inventarnummer	
Customer Auftraggeber	Sporton International Inc. 6F., Sec. 1, Hsin Tai Wu Rd 106 221 New Taipei City TW
Performance	
Place and Date of Calibration Ort und Datum der Kalibrierung	87700 Memmingen, Rohde-und-Schwarz-Str. 1 2023-10-31
Statement of Compliance (Incoming) Konformitätsaussage (Anlieferung)	All measured values are within the data sheet specifications.
Statement of Compliance (Outgoing) Konformitätsaussage (Auslieferung)	All measured values are within the data sheet specifications.
Customers due Interval Kalibrierintervall des Kunden	
Extent of Calibration Document Umfang des Kalibrierdokuments	3 Pages Certificate 7 Pages Outgoing Results 7 Pages Incoming Results
Date of Issue Ausstellungsdatum	Approval of the certificate by Freigabe des Kalibrierscheins durch
2023-11-08	Dr. Gerhard Rösel Johannes Negele
	 
	Laboratory management Labormanagement Person responsible Bearbeiter

Calibration Mark
Kalibrierzeichen

300718729
D-K- 15195-01-00
2023-10

Member of Deutscher Kalibrierdienst
Mitglied im Deutschen Kalibrierdienst



This calibration certificate documents the metrological traceability to national standards, which realize the units of measurement according to the International System of Units (SI). The DAkkS is signatory to the multilateral agreements of the European co-operation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates. The user is obliged to have the object recalibrated at appropriate intervals. This calibration certificate may not be reproduced other than in full except with the permission of the issuing laboratory. Calibration certificates with the full name of the approval responsible person are valid without signature.

Dieser Kalibrierschein dokumentiert die metrologische Rückführbarkeit auf nationale Normale zur Darstellung der Einheiten in Übereinstimmung mit dem Internationalen Einheitensystem (SI). Die DAkkS ist Unterzeichner der multilateralen Übereinkommen der European cooperation for Accreditation (EA) und der International Laboratory Accreditation Cooperation (ILAC) zur gegenseitigen Anerkennung der Kalibrierscheine. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich. Dieser Kalibrierschein darf nur vollständig weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung des ausstellenden Kalibrierlaboratoriums. Kalibrierscheine sind bei Nennung des für die Freigabe Verantwortlichen in Klarschrift auch ohne Unterschrift gültig.



Material No 1048.0371.02 **Serial No** 101811 **Certificate** 0001A300718729
Page 2/3 **Number**

Calibration Procedure

The measuring object is an RF harmonic mixer, which converts an RF signal at one frequency into a signal at another frequency (here: IF). The conversion loss was measured using a vector network analyzer. The RF output power as well as the IF input power of the corresponding ports of the VNA were traced back to a power sensor. The conversion loss is defined as the ratio of the power at the IF frequency to the power at the RF frequency with a given LO power. (IF: Intermediate frequency; LO: Local Oscillator)
The traceability is represented in the table Working Standards used.

Working Standards used

Item	Type	Serial Number	Calibration Certificate Number	Cal. Due
Therm.Power Sensor DC-40GHz	NRP-Z55	130179	0001A300682928	2025-01-31
Thermal Waveguide Power Sensor	NRP90TWG	910001	20A1129129	2026-04-30
Vector Network Analyzer 4 Port	ZVA67	101100	0001A300698540	2024-05-31

Remarks



Material No 1048.0371.02 **Serial No** 101811 **Certificate** 0001A300718729
Page 3/3 **Number**

Environmental Conditions			
Ambient Temperature	(23 ± 1) °C	Relative Humidity	20%-70%

Comments on Measurement Results
<p>The reported results apply only to those items specifically listed on this calibration certificate and have been tested for compliance with the specifications. The associated uncertainty of measurement has been taken into account if not otherwise stated.</p> <p>The non-binary decision rule with guard band is used according to ILAC G8:09/2019 'Guidelines on Decision Rules and Statements of Conformity'. Pass is normally not marked. Conditional Pass is marked with UGB1, Conditional Fail with UGB2 and Fail with Fail.</p> <p>The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k such that the coverage probability corresponds to approximately 95 %. It is consistent with the EA-4/02 M:2022.</p> <p>In addition to the calibration results, the calibration certificate includes functional measurements that might have an influence on the measurement uncertainty of the calibration results.</p> <p>The functional measurement results are marked and are not intended to be used to support the further dissemination of metrological traceability. They are intended to verify the requirements on the measurement object according to manufacturer specifications and technical standards.</p>

Outgoing Results

Designation: HARMONIC MIXER
Type: FS-Z90
Material No.: 1048.0371.02
Serial No.: 101811
Certificate No.: 0001A300718729
Referring to Test Documentation: 5038.8323.01-PB-02.00

Test Department: 3MM-P
Name: see certificate
Date: 2023-10-31



The following abbreviations may be used in this document

- {a} No measurement uncertainty stated because the errors always add together. So it is sure that a measurement result evaluated as "PASS" is pass.
 - {b} The measurement uncertainty depends on the measurement result. The stated measurement uncertainty is valid for the close area around the specification. Measurement results outside the close area have a higher measurement uncertainty but are within the specification.
 - {c} Functional test, therefore no measurement uncertainty is stated.
 - {d} Typical value, refer to performance test.
 - {e} The measurement uncertainty is taken into account when setting the measuring system.
 - {g} Verification of specified requirements, non-accredited measurements. Technical operations that consist of the determination of one or more characteristics to a specified procedure (formerly {f}).
- DL or DT Data Limit for symmetrical tolerance limits
 - DLL Datasheet Lower Limit
 - DUL Datasheet Upper Limit
 - MU Symmetrical Measurement Uncertainty
 - MLL or MLV Measurement Uncertainty Lower Value
 - MUL or MUV Measurement Uncertainty Upper Value
 - Nom. Nominal Value
 - Dev. Deviation
 - Act. Actual Value
 - UGB Uncertainty Guard Band: Measuring uncertainty violates the data (spec.) limit.
 - UGB1 A compliance statement may be possible where a confidence level of less than 95 % is acceptable.
 - UGB2 A non-compliance statement may be possible where a confidence level of less than 95 % is acceptable.
 - DU Datasheet Uncertainty

Explanation of charts




Table of contents


Software used for measurement	4
1. Conversion Loss (6. Harmonic)	5
1.1 Conversion Loss (IF = 404.4 MHz)	5
1.2 Conversion Loss (IF = 729 MHz)	6
1.3 Conversion Loss (IF = 1330 MHz)	7
1.4 Continuity response within 1 GHz	7

Software used for measurement			
Item	Type	Version	Remark
Suite	Setup	V12.37.04	Test Management Software G5
Test Program (7012.8706.00_)	Component	V01.05	

1. Conversion Loss (6. Harmonic)

1.1 Conversion Loss (IF = 404.4 MHz)

IF = 404.4 MHz, 6. Harmonic




Conversion Loss (IF = 404.4 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
60.0	24.9	±1.3
61.0	21.5	±1.3
62.0	20.4	±1.3
63.0	19.4	±1.3
64.0	16.9	±1.3
65.0	18.3	±1.3
66.0	19.9	±1.3
67.0	18.9	±1.3
68.0	18.0	±1.3
69.0	19.1	±1.3
70.0	19.3	±1.3
71.0	18.7	±1.3
72.0	18.0	±1.3
73.0	18.1	±1.3
74.0	17.6	±1.3
75.0	17.4	±1.3
76.0	16.9	±1.3
77.0	15.5	±1.3
78.0	14.7	±1.3
79.0	14.5	±1.3
80.0	14.1	±1.3
81.0	14.0	±1.3
82.0	14.1	±1.3
83.0	14.2	±1.3
84.0	14.6	±1.3
85.0	15.5	±1.3
86.0	16.5	±1.3
87.0	17.9	±1.3
88.0	19.8	±1.3
89.0	21.0	±1.3
90.0	21.1	±1.3

1.2 Conversion Loss (IF = 729 MHz)

IF = 729 MHz, 6. Harmonic




Conversion Loss (IF = 729 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
60.0	26.2	±1.3
61.0	22.4	±1.3
62.0	21.1	±1.3
63.0	20.1	±1.3
64.0	17.4	±1.3
65.0	18.5	±1.3
66.0	20.3	±1.3
67.0	19.0	±1.3
68.0	18.0	±1.3
69.0	19.0	±1.3
70.0	19.2	±1.3
71.0	18.6	±1.3
72.0	18.1	±1.3
73.0	18.1	±1.3
74.0	17.3	±1.3
75.0	17.2	±1.3
76.0	17.0	±1.3
77.0	15.9	±1.3
78.0	14.8	±1.3
79.0	14.5	±1.3
80.0	14.3	±1.3
81.0	14.0	±1.3
82.0	14.3	±1.3
83.0	14.3	±1.3
84.0	14.5	±1.3
85.0	15.5	±1.3
86.0	16.5	±1.3
87.0	17.7	±1.3
88.0	20.0	±1.3
89.0	21.0	±1.3
90.0	21.0	±1.3

1.3 Conversion Loss (IF = 1330 MHz)

IF = 1330 MHz, 6. Harmonic



Conversion Loss (IF = 1330 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
60.0	25.7	±1.3
61.0	25.0	±1.3
62.0	24.0	±1.3
63.0	22.8	±1.3
64.0	19.4	±1.3
65.0	19.5	±1.3
66.0	20.9	±1.3
67.0	19.8	±1.3
68.0	18.4	±1.3
69.0	19.3	±1.3
70.0	19.7	±1.3
71.0	19.0	±1.3
72.0	18.5	±1.3
73.0	18.5	±1.3
74.0	17.5	±1.3
75.0	17.5	±1.3
76.0	17.5	±1.3
77.0	17.0	±1.3
78.0	15.6	±1.3
79.0	15.1	±1.3
80.0	15.1	±1.3
81.0	14.7	±1.3
82.0	15.0	±1.3
83.0	15.1	±1.3
84.0	14.7	±1.3
85.0	15.9	±1.3
86.0	17.0	±1.3
87.0	18.3	±1.3
88.0	20.5	±1.3
89.0	21.5	±1.3
90.0	21.4	±1.3

1.4 Continuity response within 1 GHz

Continuity response within any 1 GHz Band, 6. Harmonic

	DUL /dB	Continuity /dB
max. at IF = 404.4 MHz:	6.0	3.42
max. at IF = 729 MHz:	6.0	3.82
max. at IF = 1330 MHz:	6.0	3.35

Incoming Results

Designation: HARMONIC MIXER
Type: FS-Z90
Material No.: 1048.0371.02
Serial No.: 101811
Certificate No.: 0001A300718729
Referring to Test Documentation: 5038.8323.01-PB-02.00

Test Department: 3MM-P
Name: see certificate
Date: 2023-10-31



The following abbreviations may be used in this document

- {a} No measurement uncertainty stated because the errors always add together. So it is sure that a measurement result evaluated as "PASS" is pass.
 - {b} The measurement uncertainty depends on the measurement result. The stated measurement uncertainty is valid for the close area around the specification. Measurement results outside the close area have a higher measurement uncertainty but are within the specification.
 - {c} Functional test, therefore no measurement uncertainty is stated.
 - {d} Typical value, refer to performance test.
 - {e} The measurement uncertainty is taken into account when setting the measuring system.
 - {g} Verification of specified requirements, non-accredited measurements. Technical operations that consist of the determination of one or more characteristics to a specified procedure (formerly {f}).
- DL or DT Data Limit for symmetrical tolerance limits
 - DLL Datasheet Lower Limit
 - DUL Datasheet Upper Limit
 - MU Symmetrical Measurement Uncertainty
 - MLL or MLV Measurement Uncertainty Lower Value
 - MUL or MUV Measurement Uncertainty Upper Value
 - Nom. Nominal Value
 - Dev. Deviation
 - Act. Actual Value
 - UGB Uncertainty Guard Band: Measuring uncertainty violates the data (spec.) limit.
 - UGB1 A compliance statement may be possible where a confidence level of less than 95 % is acceptable.
 - UGB2 A non-compliance statement may be possible where a confidence level of less than 95 % is acceptable.
 - DU Datasheet Uncertainty

Explanation of charts




Table of contents

Software used for measurement	4
1. Conversion Loss (6. Harmonic)	5
1.1 Conversion Loss (IF = 404.4 MHz)	5
1.2 Conversion Loss (IF = 729 MHz)	6
1.3 Conversion Loss (IF = 1330 MHz)	7
1.4 Continuity response within 1 GHz	7


Incoming Results

Software used for measurement			
Item	Type	Version	Remark
Suite	Setup	V12.37.04	Test Management Software G5
Test Program (7012.8706.00_)	Component	V01.05	

1. Conversion Loss (6. Harmonic)

1.1 Conversion Loss (IF = 404.4 MHz)

IF = 404.4 MHz, 6. Harmonic




Conversion Loss (IF = 404.4 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
60.0	24.9	±1.3
61.0	21.5	±1.3
62.0	20.4	±1.3
63.0	19.3	±1.3
64.0	16.9	±1.3
65.0	18.2	±1.3
66.0	19.9	±1.3
67.0	18.8	±1.3
68.0	18.0	±1.3
69.0	19.0	±1.3
70.0	19.2	±1.3
71.0	18.7	±1.3
72.0	18.0	±1.3
73.0	18.1	±1.3
74.0	17.5	±1.3
75.0	17.3	±1.3
76.0	16.9	±1.3
77.0	15.4	±1.3
78.0	14.7	±1.3
79.0	14.4	±1.3
80.0	14.1	±1.3
81.0	14.0	±1.3
82.0	14.0	±1.3
83.0	14.2	±1.3
84.0	14.6	±1.3
85.0	15.5	±1.3
86.0	16.4	±1.3
87.0	17.8	±1.3
88.0	19.7	±1.3
89.0	20.9	±1.3
90.0	21.1	±1.3

Incoming Results

1.2 Conversion Loss (IF = 729 MHz)

IF = 729 MHz, 6. Harmonic




Conversion Loss (IF = 729 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
60.0	26.2	±1.3
61.0	22.5	±1.3
62.0	21.1	±1.3
63.0	20.1	±1.3
64.0	17.4	±1.3
65.0	18.4	±1.3
66.0	20.3	±1.3
67.0	19.0	±1.3
68.0	18.1	±1.3
69.0	19.1	±1.3
70.0	19.3	±1.3
71.0	18.7	±1.3
72.0	18.2	±1.3
73.0	18.2	±1.3
74.0	17.3	±1.3
75.0	17.3	±1.3
76.0	17.0	±1.3
77.0	16.0	±1.3
78.0	14.8	±1.3
79.0	14.5	±1.3
80.0	14.4	±1.3
81.0	14.0	±1.3
82.0	14.3	±1.3
83.0	14.3	±1.3
84.0	14.5	±1.3
85.0	15.6	±1.3
86.0	16.5	±1.3
87.0	17.7	±1.3
88.0	20.0	±1.3
89.0	21.0	±1.3
90.0	21.1	±1.3

Incoming Results

1.3 Conversion Loss (IF = 1330 MHz)

IF = 1330 MHz, 6. Harmonic



Conversion Loss (IF = 1330 MHz)

Frequency /GHz	Conversion Loss /dB	Uncertainty /dB
60.0	26.2	±1.3
61.0	25.5	±1.3
62.0	24.5	±1.3
63.0	23.2	±1.3
64.0	19.9	±1.3
65.0	19.9	±1.3
66.0	21.3	±1.3
67.0	20.3	±1.3
68.0	18.8	±1.3
69.0	19.7	±1.3
70.0	20.1	±1.3
71.0	19.5	±1.3
72.0	18.9	±1.3
73.0	19.0	±1.3
74.0	17.9	±1.3
75.0	17.9	±1.3
76.0	18.0	±1.3
77.0	17.5	±1.3
78.0	16.0	±1.3
79.0	15.5	±1.3
80.0	15.6	±1.3
81.0	15.1	±1.3
82.0	15.4	±1.3
83.0	15.5	±1.3
84.0	15.2	±1.3
85.0	16.3	±1.3
86.0	17.4	±1.3
87.0	18.8	±1.3
88.0	20.9	±1.3
89.0	22.0	±1.3
90.0	21.8	±1.3

1.4 Continuity response within 1 GHz

Continuity response within any 1 GHz Band, 6. Harmonic

	DUL /dB	Continuity /dB
max. at IF = 404.4 MHz:	6.0	3.46
max. at IF = 729 MHz:	6.0	3.75
max. at IF = 1330 MHz:	6.0	3.34

Incoming Results



Calibration Certificate

Certificate Number **24-0140-101128-03**

Kalibrierschein

Zertifikatsnummer

Unit Data

Item
Gegenstand **Harmonic Mixer, 90 GHz to 140 GHz**

Manufacturer
Hersteller **RPG Radiometer physics GmbH**

Type
Typ **RPG FS-Z140**

Material Number
Materialnummer **3622.0708.02** Serial Number
Seriennummer **101128**

Asset Number
Inventarnummer

This calibration certificate documents, that the named item is tested and measured against defined specifications. Measurement results are located usually in the corresponding interval with a probability of approx. 95% (coverage factor $k = 2$). Calibration is performed with test equipment and standards directly or indirectly traceable by means of approved calibration techniques to the PTB/DKD or other national/international standards, which realize the physical units of measurement according to the International System of Units (SI). In all cases where no standards are available, measurements are referenced to standards of the R&S laboratories. Principles and methods of calibration correspond with EN ISO/IEC 17025. This calibration certificate may not be reproduced other than in full. Calibration certificates without signatures are not valid. The user is obliged to have the object recalibrated at appropriate intervals.

Order Data

Customer
Auftraggeber **Sporton International Inc.**
6F., Sec. 1, Hsin Tai Wu Rd 106
Xizhi Dist.
221 New Taipei City
Taiwan

Order Number
Bestellnummer **8800047909**

Date of Receipt
Eingangdatum **2023-10-27**

Dieser Kalibrierschein dokumentiert, dass der genannte Gegenstand nach festgelegten Vorgaben geprüft und gemessen wurde. Die Messwerte lagen im Regelfall mit einer Wahrscheinlichkeit von annähernd 95% im zugeordneten Wertintervall (Erweiterte Messunsicherheit mit $k = 2$). Die Kalibrierung erfolgte mit Messmitteln und Normalen, die direkt oder indirekt durch Ableitung mittels anerkannter Kalibriertechniken rückgeführt sind auf Normale der PTB/DKD oder anderer nationaler/internationaler Standards zur Darstellung der physikalischen Einheiten in Übereinstimmung mit dem internationalen Einheitensystem (SI). Wenn keine Normale existieren, erfolgt die Rückführung auf Bezugsnormale der R&S-Laboratorien. Grundsätze und Verfahren der Kalibrierung beziehen sich auf EN ISO/IEC 17025. Dieser Kalibrierschein darf nur vollständig und unverändert weiterverbreitet werden. Kalibrierscheine ohne Unterschriften sind ungültig. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich.

Performance

Place and Date of Calibration
Ort und Datum der Kalibrierung **Meckenheim, 2023-11-03**

Scope of Calibration
Umfang der Kalibrierung **Standard Calibration**

Statement of Compliance
(Incoming)
Konformitätsaussage
(Anlieferung) **All measured values are within the data sheet specifications.**

Statement of Compliance
(Outgoing)
Konformitätsaussage
(Auslieferung) **All measured values are within the data sheet specifications.**

Extend of Calibration Documents
Umfang des Kalibrierdokuments **2 pages Calibration Certificate**
4 pages Outgoing Results
3 pages Incoming Results

RPG Radiometer physics GmbH; Meckenheim


Date of Issue
Ausstellungsdatum

2023-11-06

Head of Laboratory
Laborleitung


Emons

Person Responsible
Bearbeiter


Gottbehüt

Page (Seite) 1/2
Vers2010-05-05/
RPG2014-02-28

Calibration Method
Kalibrieranweisung

RPG-PAQA-TN-2014-002

Relative Humidity 20 % - 80 %
Relative Luftfeuchte

Ambient Temperature
Umgebungstemperatur

(23 ⁺⁷/_{.3}) °C

Working standards used (having a significant effect on the accuracy) Verwendete Gebrauchsnormale (mit signifikantem Einfluss auf die Genauigkeit)				
Item Gegenstand	Type Typ	Serial Number Seriennummer	Calibration Certificate Number Kalibrierscheinnummer	Cal. Due Kalibr. bis
Vector Network Analyzer	R&S® ZVA40	100103	0001A300715526	2026-10-04
Powersensor	R&S® NRP-Z55	140093	0001-300700427	2025-06-06

UGB1 A compliance statement may be possible where a confidence level of less than 95 % is acceptable.
Die Bestätigung der Konformität ist möglich, sofern ein Grad des Vertrauens von weniger als 95 % akzeptabel ist.

UGB2 A non-compliance statement may be possible where a confidence level of less than 95 % is acceptable.
Die Bestätigung der Nicht-Konformität ist möglich, sofern ein Grad des Vertrauens von weniger als 95 % akzeptabel ist.

Ref.: ILAC-G8:03/2009 'Guidelines on the Reporting of Compliance with Specification'.

Notes
Anmerkungen


If the new product is stored under the climate conditions as specified in the data sheet upon delivery, the product's accuracy is not significantly affected within 12 month after its calibration in our factory. In this case, the recommended calibration interval starts on the date when the product is actually put into operation.

Outgoing Results

The following abbreviations may be used in this document

{a}	No measurement uncertainty stated because the errors always add together. So it is sure that a measurement result evaluated as "PASS" is pass.
{b}	The measurement uncertainty depends on the measurement result. The stated measurement uncertainty is valid for the close area around the specification. Measurement results outside the close area have a higher measurement uncertainty but are within the specification.
{c}	Functional test, therefore no measurement uncertainty is stated.
{d}	Typical value, refer to performance test.
{e}	The measurement uncertainty is taken into account when setting the measuring system.
DL or DT	Data Limit for symmetrical tolerance limits
DLL	Datasheet Lower Limit
DUL	Datasheet Upper Limit
MU	Measurement Uncertainty
MLL or MLV	Measurement Uncertainty Lower Value
MUL or MUV	Measurement Uncertainty Upper Value
Nom.	Nominal Value
Dev.	Deviation
MErr.	Measurement Error
Act.	Actual Value
UGB	Uncertainty Guard Band: Measuring uncertainty violates the data (spec.) limit.
UGB1	Measurement results marked as UGB1 show conformity with a probability of >50 % and <95 %.
UGB2	Measurement results marked as UGB2 show non-conformity with a probability of >50 % and <95 %.
DU	Datasheet Uncertainty

Explanation of charts



Software used for measurement

Item Type

Measurement Studio Professional Edition
MixerCertification

Version


2013
7_15

Remark

1.1 Conversion loss

LO level +14 dBm nominal
Bias 0 A

Measurement uncertainty: 3.5 dB



Note: Numeric calibration data can be found attached to the PDF file of the calibration certificate. Click the “paper clip” symbol to display the file.

The file has been renamed for safety reasons.
When downloading the file onto your PC, please delete the “.file” extension and unzip the data.

1.2 Frequency response within 1 GHz


	DUL	Actual (worst case)	Evaluation
IF = 404.4 MHz, 10th harmonic	6 dB	2.49 dB	PASS
IF = 729 MHz, 10th harmonic	6 dB	2.09 dB	PASS
IF = 1330 MHz, 10th harmonic	6 dB	2.24 dB	PASS

1 Incoming Results

The following abbreviations may be used in this document

- {a) No measurement uncertainty stated because the errors always add together.
So it is sure that a measurement result evaluated as "PASS" is pass.
- {b) The measurement uncertainty depends on the measurement result. The stated measurement uncertainty is valid for the close area around the specification. Measurement results outside the close area have a higher measurement uncertainty but are within the specification.
- {c) Functional test, therefore no measurement uncertainty is stated.
- {d) Typical value, refer to performance test.
- {e) The measurement uncertainty is taken into account when setting the measuring system.
- DL or DT Data Limit for symmetrical tolerance limits
- DLL Datasheet Lower Limit
- DUL Datasheet Upper Limit
- MU Measurement Uncertainty
- MLL or MLV Measurement Uncertainty Lower Value
- MUL or MUV Measurement Uncertainty Upper Value
- Nom. Nominal Value
- Dev. Deviation
- MErr. Measurement Error
- Act. Actual Value
- UGB Uncertainty Guard Band: Measuring uncertainty violates the data (spec.) limit.
- UGB1 Measurement results marked as UGB1 show conformity with a probability of >50 %and <95 %.
- UGB2 Measurement results marked as UGB2 show non-conformity with a probability of >50 %and <95 %.
- DU Datasheet Uncertainty

Explanation of charts



Material Number 3622.0708.02

Serial Number 101128

Certificate Number 24-0140-101128-03

(Incoming)

Software used for measurement

Item Type

Measurement Studio Professional Edition
MixerCertification


Version

2013
7_15

Remark

Incoming Report

1.1 Deviation between actual and previous conversion loss



Incoming Report



Calibration Certificate

Certificate Number **24-0220-101014-03**

Kalibrierschein

Zertifikatsnummer

Unit Data

Item
Gegenstand **Harmonic Mixer, 140 GHz to 220 GHz**

Manufacturer
Hersteller **RPG Radiometer physics GmbH**

Type
Typ **RPG FS-Z220**

Material Number **3593.3250.02** **Serial Number** **101014**
Materialnummer Seriennummer

Asset Number
Inventarnummer

This calibration certificate documents, that the named item is tested and measured against defined specifications. Measurement results are located usually in the corresponding interval with a probability of approx. 95% (coverage factor $k = 2$). Calibration is performed with test equipment and standards directly or indirectly traceable by means of approved calibration techniques to the PTB/DKD or other national/international standards, which realize the physical units of measurement according to the International System of Units (SI). In all cases where no standards are available, measurements are referenced to standards of the R&S laboratories. Principles and methods of calibration correspond with EN ISO/IEC 17025. This calibration certificate may not be reproduced other than in full. Calibration certificates without signatures are not valid. The user is obliged to have the object recalibrated at appropriate intervals.

Order Data

Customer
Auftraggeber **Sporton International Inc.**
6F., Sec. 1, Hsin Tai Wu Rd 106
Xizhi Dist.
221 New Taipei City
Taiwan

Order Number **8800047911**
Bestellnummer

Date of Receipt **2023-10-27**
Eingangdatum

Dieser Kalibrierschein dokumentiert, dass der genannte Gegenstand nach festgelegten Vorgaben geprüft und gemessen wurde. Die Messwerte lagen im Regelfall mit einer Wahrscheinlichkeit von annähernd 95% im zugeordneten Wertebereich (Erweiterte Messunsicherheit mit $k = 2$). Die Kalibrierung erfolgte mit Messmitteln und Normalen, die direkt oder indirekt durch Ableitung mittels anerkannter Kalibriertechniken rückgeführt sind auf Normale der PTB/DKD oder anderer nationaler/internationaler Standards zur Darstellung der physikalischen Einheiten in Übereinstimmung mit dem Internationalen Einheitensystem (SI). Wenn keine Normale existieren, erfolgt die Rückführung auf Bezugsnormale der R&S-Laboratorien. Grundsätze und Verfahren der Kalibrierung beziehen sich auf EN ISO/IEC 17025. Dieser Kalibrierschein darf nur vollständig und unverändert weiterverbreitet werden. Kalibrierscheine ohne Unterschriften sind ungültig. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich.

Performance

Place and Date of Calibration
Ort und Datum der Kalibrierung

Meckenheim, 2023-11-06

Scope of Calibration
Umfang der Kalibrierung

Standard Calibration

Statement of Compliance (Incoming)
Konformitätsaussage (Anlieferung)

All measured values are within the data sheet specifications.

Statement of Compliance (Outgoing)
Konformitätsaussage (Auslieferung)

All measured values are within the data sheet specifications.

Extend of Calibration Documents
Umfang des Kalibrierdokuments

2 pages Calibration Certificate
4 pages Outgoing Results
3 pages Incoming Results

RPG Radiometer physics GmbH; Meckenheim

Date of Issue
Ausstellungsdatum

2023-11-06

Head of Laboratory
Laborleitung


Emons

Person Responsible
Bearbeiter


Gottbehüt

Page (Seite) 1/2
Vers2010-05-05/
RPG2014-02-28

Calibration Method
Kalibrieranweisung

RPG-PAQA-TN-2014-002

Relative Humidity 20 % - 80 %
Relative LuftfeuchteAmbient Temperature
Umgebungstemperatur(23 ⁺⁷₋₃) °C

Working standards used (having a significant effect on the accuracy) Verwendete Gebrauchsnormale (mit signifikantem Einfluss auf die Genauigkeit)				
Item Gegenstand	Type Typ	Serial Number Seriennummer	Calibration Certificate Number Kalibrierscheinnummer	Cal. Due Kalibr. bis
Vector Network Analyzer	R&S® ZVA40	100103	0001A300715526	2026-10-04
Powersensor	R&S® NRP-Z55	140093	0001-300700427	2025-06-06

UGB1	A compliance statement may be possible where a confidence level of less than 95 % is acceptable. Die Bestätigung der Konformität ist möglich, sofern ein Grad des Vertrauens von weniger als 95 % akzeptabel ist.
UGB2	A non-compliance statement may be possible where a confidence level of less than 95 % is acceptable. Die Bestätigung der Nicht-Konformität ist möglich, sofern ein Grad des Vertrauens von weniger als 95 % akzeptabel ist.
Ref.: ILAC-G8:03/2009 'Guidelines on the Reporting of Compliance with Specification'.	

Notes
Anmerkungen


If the new product is stored under the climate conditions as specified in the data sheet upon delivery, the product's accuracy is not significantly affected within 12 month after its calibration in our factory. In this case, the recommended calibration interval starts on the date when the product is actually put into operation.

Outgoing Results

The following abbreviations may be used in this document

{a}	No measurement uncertainty stated because the errors always add together. So it is sure that a measurement result evaluated as "PASS" is pass.
{b}	The measurement uncertainty depends on the measurement result. The stated measurement uncertainty is valid for the close area around the specification. Measurement results outside the close area have a higher measurement uncertainty but are within the specification.
{c}	Functional test, therefore no measurement uncertainty is stated.
{d}	Typical value, refer to performance test.
{e}	The measurement uncertainty is taken into account when setting the measuring system.
DL or DT	Data Limit for symmetrical tolerance limits
DLL	Datasheet Lower Limit
DUL	Datasheet Upper Limit
MU	Measurement Uncertainty
MLL or MLV	Measurement Uncertainty Lower Value
MUL or MUJ	Measurement Uncertainty Upper Value
Nom.	Nominal Value
Dev.	Deviation
MErr.	Measurement Error
Act.	Actual Value
UGB	Uncertainty Guard Band: Measuring uncertainty violates the data (spec.) limit.
UGB1	Measurement results marked as UGB1 show conformity with a probability of >50 % and <95 %.
UGB2	Measurement results marked as UGB2 show non-conformity with a probability of >50 % and <95 %.
DU	Datasheet Uncertainty

Explanation of charts




Software used for measurement

Item Type	Version	Remark
Measurement Studio Professional Edition	2013	
MixerCertification	7_15	

1.1 Conversion loss

LO level +13 dBm nominal
Bias 0 A

Measurement uncertainty: 4 dB



Note: Numeric calibration data can be found attached to the PDF file of the calibration certificate. Click the “paper clip” symbol to display the file.

The file has been renamed for safety reasons.

When downloading the file onto your PC, please delete the “.file” extension and unzip the data.

1.2 Frequency response within 1 GHz


	DUL	Actual (worst case)	Evaluation
IF = 404.4 MHz, 16th harmonic	6 dB	2.61 dB	PASS
IF = 729 MHz, 16th harmonic	6 dB	2.54 dB	PASS
IF = 1330 MHz, 14th harmonic	6 dB	2.39 dB	PASS

1 Incoming Results

The following abbreviations may be used in this document

{a}	No measurement uncertainty stated because the errors always add together. So it is sure that a measurement result evaluated as "PASS" is pass.
{b}	The measurement uncertainty depends on the measurement result. The stated measurement uncertainty is valid for the close area around the specification. Measurement results outside the close area have a higher measurement uncertainty but are within the specification.
{c}	Functional test, therefore no measurement uncertainty is stated.
{d}	Typical value, refer to performance test.
{e}	The measurement uncertainty is taken into account when setting the measuring system.
DL or DT	Data Limit for symmetrical tolerance limits
DLL	Datasheet Lower Limit
DUL	Datasheet Upper Limit
MU	Measurement Uncertainty
MLL or MLV	Measurement Uncertainty Lower Value
MUL or MUV	Measurement Uncertainty Upper Value
Nom.	Nominal Value
Dev.	Deviation
MErr.	Measurement Error
Act.	Actual Value
UGB	Uncertainty Guard Band: Measuring uncertainty violates the data (spec.) limit.
UGB1	Measurement results marked as UGB1 show conformity with a probability of >50 %and <95 %.
UGB2	Measurement results marked as UGB2 show non-conformity with a probability of >50 %and <95 %.
DU	Datasheet Uncertainty

Explanation of charts



Material Number 3593.3250.02

Serial Number 101014

Certificate Number 24-0220-101014-03

(Incoming)

Software used for measurement

Item Type

Measurement Studio Professional Edition

MixerCertification

Version


2013

7_15

Remark

Incoming Report

1.1 Deviation between actual and previous conversion loss



Incoming Report

Calibration Laboratory of Microwave Measuring Equipment
of MWMLab



Calibration certificate

ISO 17025
ACCREDITED LABORATORY



Accreditation certificate No. № BY/112 5.0065 of 09.01.2015

Certificate number 36-21 Date when calibrated 06.07.2021 Page 1 of 2

Item calibrated Antenna QWH-UPRR00 # 1410300003

Customer Sporton International Inc.

Method of calibration GOST 20271.1, MK KL 8.2-16

All measurements are traceable to the SI units which are realized by national measurement standards of NMI and state standards of RF. Gain measurements above 178 GHz are to confirm operation functionality and traceable only to MWMLab standards and OML. This certificate shall not be reproduced, except in full. Any publication extracts from the calibration certificate requires written permission of the issuing calibration laboratory of microwave measuring equipment.

Authorising
signature



/ Technical manager Date of issue 06.07.2021

Calibration Certificate

Certificate number **36-21**

Page 2 of 2

Calibration is performed by using

Model	Model Description	Equipment ID	Cal Due Date	Certificate Number	Trace Value
M1-11	Calibrator of power with wattmeter M3-22A	841202/ 037410	08 December 2021	3882-43	RF Power
M 568	Reference power meter	164	24 March 2022	1/111-175-20	RF Power
G4-161	Signal generator	3	12 October 2021	20-20	RF Power
MG3694C	Signal generator	133805	11 September 2021	2726-43	RF Power Frequency
V7-34	Universal voltmeter	0067787	23 September 2021	2742-42	DC Voltage
RCH3-72	Frequency meter	931200	18 September 2021	2822-43	Frequency
P6-133	Horn antenna	15005	23 September 2021	2374-43	Gain
P6-11B	Measuring horn antenna	08051	23 September 2021	2370-43	Gain

Calibration conditions

Temperature: 23.8 °C.
Humidity: 43.2 %.
Pressure: 100.1 kPa.

Calibration results are given in the measurement report # 36-21

#	Parameter	Specifications required	Specifications tested and measured
1	Frequency range	40 – 60 GHz	Corresponds
2	Antenna Gain	22.5* dBi	Corresponds (Table 1)
3	Antenna Factor	42 dB/m	Corresponds (Table 1)

* – Expanded uncertainty of measurements 2.0 dB.

The uncertainty evaluation has been performed in accordance with ISO/IEC Guide 98-3:2008 (GUM). The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k such that the coverage probability corresponds to approximately 95 %. This probability corresponds to a coverage factor of $k=2$ for a normal distribution.

Signature of the person who has performed calibration

 / Engineer