

# RF Exposure Evaluation Report

FCC ID : A4RG3MP5  
Equipment : Wireless Device  
Model Name : G3MP5  
Applicant : Google LLC  
1600 Amphitheatre Parkway,  
Mountain View, California, 94043 USA  
Standard : 47 CFR Part 2.1093

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part 2.1093 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager



**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



**Table of Contents**

- 1. General Information ..... 3
- 1.1 Description of Device Under Test (DUT) ..... 3
- 2. Maximum RF output power among production units ..... 3
- 3. RF Exposure Evaluation ..... 3

**Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA322116	Rev. 01	Initial issue of report	Apr. 19, 2023



### 1. General Information

#### 1.1 Description of Device Under Test (DUT)

Product Feature & Specification	
Equipment	Wireless Device
Model Name	G3MP5
FCC ID	A4RG3MP5
Wireless Technology and Frequency Range	Bluetooth: 2400 MHz ~ 2483.5 MHz
Mode	Bluetooth LE
Antenna Type	Slot Antenna

### 2. Maximum RF output power among production units

Mode	Maximum Output Power (dBm)
Bluetooth LE	7.5

### 3. RF Exposure Evaluation

Bluetooth Max Power (dBm)	mW	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
7.5	6	5	2.48	1.9

**Note:**

- Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for}$$

1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

**Conclusion:** Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 1.9 which is ≤ 3, SAR testing is not required.