




Spurious emission between 18GHz to 40GHz worst case plot is reported as following.


DFT-s-OFDM Module B

NR Band n261 QPSK (18-40GHz)


Lowest Channel / 50MHz




Lowest Channel / 100MHz




Middle Channel / 50MHz




Middle Channel / 100MHz



Highest Channel / 50MHz



Highest Channel / 100MHz




Remark: In band and out of band frequencies are omitted.




DFT-s-OFDM Module B

NR Band n261 QPSK (18-40GHz)


Lowest Channel / 200MHz




Lowest Channel / 300MHz




Middle Channel / 200MHz




Middle Channel / 300MHz



Highest Channel / 200MHz



Highest Channel / 300MHz




Remark: In band and out of band frequencies are omitted.



DFT-s-OFDM Module B


NR Band n261 QPSK (18-40GHz)

Lowest Channel / 400MHz




intentionally blank

Middle Channel / 400MHz



intentionally blank

Highest Channel / 400MHz



intentionally blank


Remark: In band and out of band frequencies are omitted.




CP-OFDM Module B

NR Band n261 QPSK (18-40GHz)


Lowest Channel / 50MHz




Lowest Channel / 100MHz




Middle Channel / 50MHz




Middle Channel / 100MHz



Highest Channel / 50MHz



Highest Channel / 100MHz




Remark: In band and out of band frequencies are omitted.




CP-OFDM Module B

NR Band n261 QPSK (18-40GHz)


Lowest Channel / 200MHz




Lowest Channel / 300MHz




Middle Channel / 200MHz




Middle Channel / 300MHz



Highest Channel / 200MHz



Highest Channel / 300MHz




Remark: In band and out of band frequencies are omitted.



CP-OFDM Module B


NR Band n261 QPSK (18-40GHz)

Lowest Channel / 400MHz




intentionally blank

Middle Channel / 400MHz



intentionally blank

Highest Channel / 400MHz




intentionally blank

Remark: In band and out of band frequencies are omitted.



There is no significant spurious emission signal found for frequency started from 40GHz up to 200GHz. Only the noise floor is reported.




$$\text{Offset} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} + 107 + 20\log(D) - 104.8 + \text{Duty Factor}$$

$$= 43 + 0.43 + 107 + 20\log(1) - 104.8 = 45.63(\text{dB})$$



NR Band n261


(60GHz-90GHz)



20:58:45 07.08.2023

$$\text{Offset} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} + 107 + 20\log(D) - 104.8 + \text{Duty Factor}$$
$$= 46.9 + 0.43 + 107 + 20\log(1) - 104.8 = 49.53 \text{ (dB)}$$





$$\text{Offset} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} + 107 + 20\log(D) - 104.8 + \text{Duty Factor}$$
$$= 47.92 + 0.43 + 107 + 20\log(0.5) - 104.8 = 44.53 \text{ (dB)}$$



**Frequency Stability**

Test Conditions		NR Band n261 / Middle Channel			Limit
Temperature (°C)	Voltage (Volt)	CW tone			Note 2.
		Frequency (GHz)	Deviation (kHz)	Deviation (ppm)	Result
50	Normal Voltage	27.924946	104.000	3.724	Pass
40	Normal Voltage	27.924964	86.000	3.080	
30	Normal Voltage	27.924979	71.000	2.543	
20(Ref.)	Normal Voltage	27.92505	0.000	0.000	
10	Normal Voltage	27.925042	8.000	0.286	
0	Normal Voltage	27.92511	-60.000	2.149	
-10	Normal Voltage	27.925142	-92.000	3.295	
-20	Normal Voltage	27.925133	-83.000	2.972	
-30	Normal Voltage	27.925098	-48.000	1.719	
20	Maximum Voltage	27.925027	23.000	0.824	
20	Normal Voltage	27.925031	19.000	0.680	
20	Battery End Point	27.925025	25.000	0.895	

**Note:**

1. Normal Voltage = 3.87 V. ; Battery End Point (BEP) = 3.6 V. ; Maximum Voltage = 4.48 V.
2. The frequency fundamental emissions stay within the operation band.



## **Appendix B. R&S Mixer and Horn Antenna Calibration Reports**

akkreditiert durch die / *accredited by the*

**Deutsche Akkreditierungsstelle GmbH**

als Kalibrierlaboratorium im / *as calibration laboratory in the*



Deutsche  
Akkreditierungsstelle  
D-K-15195-01-00

**Deutschen Kalibrierdienst**



Kalibrierschein

*Calibration certificate*

Kalibrierzeichen

*Calibration mark*

593876

D-K-  
15195-01-00

2021-04

Gegenstand  
*Object* **FS-Z60 HARMONIC MIXER 40-60GHZ**

Hersteller  
*Manufacturer* **ROHDE & SCHWARZ**

Typ  
*Type* **FS-Z60**

Fabrikat/Serien-Nr.  
*Serial number* **100986**

Auftraggeber  
*Customer* **Sporton International Inc.**

**6F., Sec. 1, Hsin Tai Wu Rd., No. 106  
221 New Taipei City  
TW**

Auftragsnummer  
*Order No.* **311002157**

Anzahl der Seiten des Kalibrierscheines  
*Number of pages of the certificate* **3 Certificate  
5 Outgoing Results  
5 Incoming Results**

Datum der Kalibrierung  
*Date of calibration* **2021-04-09**

Dieser Kalibrierschein dokumentiert die Rückführung auf nationale Normale zur Darstellung der Einheiten in Übereinstimmung mit dem Internationalen Einheitensystem (SI).

Die DAkkS ist Unterzeichner der multilateralen Übereinkommen der European co-operation for Accreditation (EA) und der International Laboratory Accreditation Cooperation (ILAC) zur gegenseitigen Anerkennung der Kalibrierscheine.

Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich.

*This calibration certificate documents the traceability to national standards, which realize the units of measurement according to the International System of Units (SI).*

*The DAkkS is signatory to the multilateral agreements of the European co-operation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates.*

*The user is obliged to have the object recalibrated at appropriate intervals.*

Dieser Kalibrierschein darf nur vollständig und unverändert weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung des ausstellenden Kalibrierlaboratoriums. Kalibrierscheine sind bei Nennung des für die Freigabe Verantwortlichen in Klarschrift auch ohne Unterschrift gültig.

*This calibration certificate may not be reproduced other than in full except with the permission of the issuing laboratory. Calibration certificates with the full name of the approval responsible person are valid without signature.*

Datum der Ausstellung  
*Date of issue*

2021-04-09

Freigabe des Kalibrierscheins durch  
*Approval of the calibration certificate by*



Dr. Gerhard Rösel  
Leiter des Kalibrierlaboratoriums  
*Head of the calibration laboratory*



Johannes Negele  
Bearbeiter  
*Person in charge*

**Object** FS-Z60 HARMONIC MIXER 40-60GHZ  
**Type** FS-Z60 **Serial No.** 100986  
**Date** 2021-04-09 **Material No.** 1048.0171.02  
**Page** 2 / 3

593876
D-K- 15195-01-00
2021-04



**Place of Calibration**

87700 Memmingen, Rohde-und-Schwarz-Str. 1

**Calibration Procedure**

The measuring object is an RF harmonic mixer, which converts an RF signal at one frequency into a signal at another frequency (here: IF). The conversion loss was measured using a vector network analyzer. The RF output power as well as the IF input power of the corresponding ports of the VNA were traced back to a power sensor. The conversion loss is defined as the ratio of the power at the IF frequency to the power at the RF frequency with a given LO power. (IF: Intermediate frequency; LO: Local Oscillator)

The traceability is represented in the table Working Standards used.

**Calibration Method**                      **See first page of Outgoing Results**

**Statement of Compliance**

Incoming: All measured values are within the data sheet specifications.  
 Outgoing: All measured values are within the data sheet specifications.

**Working Standards used**

Item	Type	Serial Number	Calibration Certificate Number	Cal. Due
Therm.Power Sensor DC-40GHz	NRP-Z55	130179	585760 D-K-15195-01-00 2021-01	2023-01-31
Thermal Power Sensor	NRP67T	100977	515392 D-K-15195-01-01 2019-07	2022-07-31
Vect. Netw. Analyzer 4PORT	ZVA67	101175	0023 D-K-15195-01-00 2021-03	2022-03-31

**Object** FS-Z60 HARMONIC MIXER 40-60GHZ  
**Type** FS-Z60 **Serial No.** 100986  
**Date** 2021-04-09 **Material No.** 1048.0171.02  
**Page** 3 / 3

593876
D-K- 15195-01-00
2021-04



### Measurement Uncertainty

The expanded measurement uncertainty corresponds to the measurement results from the standard measurement uncertainty multiplied by the coverage factor  $k = 2$ .  
It was determined in accordance with EA-4/02 M:2013. The true value is located in the corresponding interval with a probability of 95 %.

### Environmental Conditions

Ambient Temperature (23 ± 1) °C      Relative Humidity 20%-60%

### Ancillary Functional Measurements

In addition to the calibration results, the calibration certificate includes functional measurements that might have an influence on the measurement uncertainty of the calibration results. The functional measurement results are marked and are not intended to be used to support the further dissemination of metrological traceability. They are intended to verify the requirements on the measurement object according to manufacturer specifications and technical standards.

### Comments on Measurement Results

The measurement results in the test report stated below have been tested for compliance with the given specifications and marked if necessary. The associated uncertainty of measurement has been taken into account. Measurement results that are not covered by the DAkkS accreditation are marked with <sup>1</sup>.

Ref.: ILAC G8:09/2019 'Guidelines on Decision Rules and Statements of Conformity'.

# Outgoing Results

**Designation:** HARMONIC MIXER  
**Type:** FS-Z60  
**Material No.:** 1048.0171.02  
**Serial No.:** 100986  
**Certificate No.:** 593876 D-K-15195-01-00 2021-04  
**Referring to Test Documentation:** 5038.8581.01-PB-02.00

**Test Department:** 3MME3  
**Name:** Johannes Negele  
**Date:** 2021-04-09



# Table of contents

- Software used for measurement ..... 3
- 1. Conversion Loss (4. Harmonic) ..... 4
  - 1.1 Conversion Loss (IF = 404.4 MHz) ..... 4
  - 1.2 Conversion Loss (IF = 729 MHz) ..... 4
  - 1.3 Conversion Loss (IF = 1330 MHz) ..... 5
  - 1.4 Continuity response within 1 GHz ..... 5




<b>Software used for measurement</b>			
<b>Item</b>	<b>Type</b>	<b>Version</b>	<b>Remark</b>
Suite	Setup	V12.10.02	Test Management Software G5
Test Program (7012.8706.00_)	Component	V01.05	

# 1. Conversion Loss (4. Harmonic)


## 1.1 Conversion Loss (IF = 404.4 MHz)

IF = 404.4 MHz, 4. Harmonic




## 1.2 Conversion Loss (IF = 729 MHz)

IF = 729 MHz, 4. Harmonic



**1.3 Conversion Loss (IF = 1330 MHz)**

IF = 1330 MHz, 4. Harmonic



**1.4 Continuity response within 1 GHz**

Continuity response within any 1 GHz Band, 4. Harmonic

	DUL /dB	Continuity /dB
max. at IF = 404.4 MHz:	6.0	2.80
max. at IF = 729 MHz:	6.0	2.47
max. at IF = 1330 MHz:	6.0	2.22

# Incoming Results

**Designation:** HARMONIC MIXER  
**Type:** FS-Z60  
**Material No.:** 1048.0171.02  
**Serial No.:** 100986  
**Certificate No.:** 593876 D-K-15195-01-00 2021-04  
**Referring to Test Documentation:** 5038.8581.01-PB-02.00

**Test Department:** 3MME3  
**Name:** Johannes Negele  
**Date:** 2021-04-09

Incoming Results



# Table of contents

Software used for measurement ..... 3

1. Conversion Loss (4. Harmonic) ..... 4

    1.1 Conversion Loss (IF = 404.4 MHz) ..... 4

    1.2 Conversion Loss (IF = 729 MHz) ..... 4

    1.3 Conversion Loss (IF = 1330 MHz) ..... 5

    1.4 Continuity response within 1 GHz ..... 5


Incoming Results

Software used for measurement			
Item	Type	Version	Remark
Suite	Setup	V12.10.02	Test Management Software G5
Test Program (7012.8706.00_)	Component	V01.05	

## 1. Conversion Loss (4. Harmonic)


### 1.1 Conversion Loss (IF = 404.4 MHz)

IF = 404.4 MHz, 4. Harmonic



### 1.2 Conversion Loss (IF = 729 MHz)


IF = 729 MHz, 4. Harmonic



Incoming Results

**1.3 Conversion Loss (IF = 1330 MHz)**

IF = 1330 MHz, 4. Harmonic



**1.4 Continuity response within 1 GHz**

Continuity response within any 1 GHz Band, 4. Harmonic

	DUL /dB	Continuity /dB
max. at IF = 404.4 MHz:	6.0	2.81
max. at IF = 729 MHz:	6.0	2.48
max. at IF = 1330 MHz:	6.0	2.24

Incoming Results





# CALIBRATION CERTIFICATE



## Kalibrierschein

Certificate Number  
Zertifikatsnummer

0001A300623436

General Data			
<b>Item</b> Gegenstand	FS-Z90 HARMONIC MIXER 60-90GHZ		
<b>Manufacturer</b> Hersteller	ROHDE & SCHWARZ		
<b>Type</b> Typ	FS-Z90		
<b>Material Number</b> Materialnummer	1048.0371.02	<b>Serial Number</b> Seriennummer	101811
<b>Order Number</b> Bestellnummer	8800012961 10, 516816.0	<b>Asset Number</b> Inventarnummer	
<b>Customer</b> Auftraggeber	Sporton International Inc.  6F., Sec. 1, Hsin Tai Wu Rd., No. 106 221 New Taipei City TW		
Performance			
<b>Place and Date of Calibration</b> Ort und Datum der Kalibrierung	87700 Memmingen, Rohde-und-Schwarz-Str. 1 2021-11-16		
<b>Statement of Compliance (Incoming)</b> Konformitätsaussage (Anlieferung)	All measured values are within the data sheet specifications.		
<b>Statement of Compliance (Outgoing)</b> Konformitätsaussage (Auslieferung)	All measured values are within the data sheet specifications.		
<b>Customers due Interval</b> Kalibrierintervall des Kunden			
<b>Extent of Calibration Document</b> Umfang des Kalibrierdokuments	3 Certificate 6 Outgoing Results 6 Incoming Results		
<b>Date of Issue</b> Ausstellungsdatum	<b>Approval of the certificate by</b> Freigabe des Kalibrierscheins durch		
2021-11-16	Dr. Gerhard Rösel	Johannes Negele	
	Laboratory management Labormanagement	Person responsible Bearbeiter	

## Calibration Mark Kalibrierzeichen

300623436
D-K- 15195-01-00
2021-11

Member of Deutscher Kalibrierdienst  
Mitglied im Deutschen Kalibrierdienst



This calibration certificate documents the metrological traceability to national standards, which realize the units of measurement according to the International System of Units (SI). The DAkKS is signatory to the multilateral agreements of the European co-operation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates. The user is obliged to have the object recalibrated at appropriate intervals. This calibration certificate may not be reproduced other than in full except with the permission of the issuing laboratory. Calibration certificates with the full name of the approval responsible person are valid without signature.

Dieser Kalibrierschein dokumentiert die metrologische Rückführbarkeit auf nationale Normale zur Darstellung der Einheiten in Übereinstimmung mit dem Internationalen Einheitensystem (SI). Die DAkKS ist Unterzeichner der multilateralen Übereinkommen der European cooperation for Accreditation (EA) und der International Laboratory Accreditation Cooperation (ILAC) zur gegenseitigen Anerkennung der Kalibrierscheine. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich. Dieser Kalibrierschein darf nur vollständig weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung des ausstellenden Kalibrierlaboratoriums. Kalibrierscheine sind bei Nennung des für die Freigabe Verantwortlichen in Klarschrift auch ohne Unterschrift gültig.