



# FCC RADIO TEST REPORT

**FCC ID** : A4RG9S9B  
**Equipment** : Phone  
**Model Name** : G9S9B  
**Applicant** : Google LLC  
1600 Amphitheatre Parkway,  
Mountain View, California, 94043 USA  
**Standard** : FCC Part 15 Subpart C §15.247

The product was received on Jun. 08, 2021 and testing was started from Jun. 09, 2021 and completed on Jul. 28, 2021. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

*Louis Wu*

Approved by: Louis Wu

**Sporton International Inc. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description.....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	5
1.3 Modification of EUT .....	6
1.4 Testing Location .....	6
1.5 Applicable Standards.....	6
<b>2 Test Configuration of Equipment Under Test.....</b>	<b>7</b>
2.1 Carrier Frequency Channel .....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system .....	10
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example.....	10
<b>3 Test Result.....</b>	<b>11</b>
3.1 6dB and 99% Bandwidth Measurement .....	11
3.2 Output Power Measurement.....	20
3.3 Power Spectral Density Measurement .....	21
3.4 Conducted Band Edges and Spurious Emission Measurement .....	30
3.5 Radiated Band Edges and Spurious Emission Measurement .....	41
3.6 AC Conducted Emission Measurement.....	45
3.7 Antenna Requirements.....	47
<b>4 List of Measuring Equipment .....</b>	<b>48</b>
<b>5 Uncertainty of Evaluation.....</b>	<b>50</b>
<b>Appendix A. Conducted Test Results</b>	
<b>Appendix B. AC Conducted Emission Test Result</b>	
<b>Appendix C. Radiated Spurious Emission</b>	
<b>Appendix D. Radiated Spurious Emission Plots</b>	
<b>Appendix E. Duty Cycle Plots</b>	



### History of this test report

Report No.	Version	Description	Issued Date
FR0D2942-04B	01	Initial issue of report	Jul. 30, 2021
FR0D2942-04B	02	Adding Data for Bluetooth - LE Antenna 3	Aug. 05, 2021



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 6.94 dB at 18000.000 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 10.83 dB at 0.501 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: William Chen**

**Report Producer: Vivian Hsu**



# 1 General Description

## 1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Phone
Model Name	G9S9B
FCC ID	A4RG9S9B
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/5G NR/NFC/ GNSS/WPC/WPT WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE

**Remark:** The above EUT's information was declared by manufacturer.

EUT Information List	
S/N	Performed Test Item
15211FDF60007M	RF Conducted Measurement
15201FDF60005H	Radiated Spurious Emission
15201FDF60009S	Conducted Emission

## 1.2 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel (37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	<Ant. 4> Bluetooth – LE (1Mbps): 19.05 dBm / 0.0804 W Bluetooth – LE (2Mbps): 19.15 dBm / 0.0822 W <Ant. 3> Bluetooth – LE (1Mbps): 19.45 dBm / 0.0881 W Bluetooth – LE (2Mbps): 19.55 dBm / 0.0902 W
99% Occupied Bandwidth	<Ant. 4> Bluetooth – LE (1Mbps): 1.039MHz Bluetooth – LE (2Mbps): 2.054MHz <Ant. 3> Bluetooth – LE (1Mbps): 1.037MHz Bluetooth – LE (2Mbps): 2.050MHz
Antenna Type / Gain	<Ant. 4>ILA Antenna with gain -1.2 dBi <Ant. 3>IFA Antenna with gain -1.1 dBi
Type of Modulation	Bluetooth LE : GFSK

**Remark:** The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.



### 1.3 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.4 Testing Location

<b>Test Site</b>	Sporton International Inc. EMC & Wireless Communications Laboratory
<b>Test Site Location</b>	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
<b>Test Site No.</b>	<b>Sporton Site No.</b> TH02-HY, CO05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

<b>Test Site</b>	Sporton International Inc. Wensan Laboratory
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
<b>Test Site No.</b>	<b>Sporton Site No.</b> 03CH13-HY (TAF Code: 3786)
<b>Remark</b>	The Radiated Spurious Emissions test item subcontracted to Sporton International Inc. Wensan Laboratory.

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

### 1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
20	2442	-	-	



## 2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). The measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find X plane with Notebook as worst plane.
- b. AC power line Conducted Emission was tested under maximum output power.


The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
<b>Conducted Test Cases</b>	<b>Bluetooth – LE / GFSK</b>
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
<b>Radiated Test Cases</b>	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
<b>AC Conducted Emission</b>	Mode 1 WLAN (2.4GHz) Link + Bluetooth Link + USB Cable 1 (Charging from AC Adapter 2)
<b>Remark:</b>	
1. For Radiated Test Cases, the tests were performed with Adapter 2 and USB Cable 1.	
2. During the preliminary test, both charging modes (Adapter mode and WPC Charging mode) were verified. It is determined that the adaptor mode is the worst case for official test.	




## 2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth-LE Tx Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Google	G1013	N/A	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	Dell	Latitude E3480	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m

## 2.5 EUT Operation Test Setup

The RF test items, utility “adb command V\_1.0.36” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW)  $\geq 3 * RBW$ .
6. Measure and record the results in the test report.

##### 3.1.4 Test Setup






### 3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


<Ant. 4>

<1Mbps>






<2Mbps>






<Ant. 3>

<1Mbps>





<2Mbps>






### 3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<Ant. 4>

<1Mbps>




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.





<2Mbps>




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<Ant. 3>


<1Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<2Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Power Spectral Density


Please refer to Appendix A.



### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)


<Ant. 4>

<1Mbps>






<2Mbps>





<Ant. 3>


<1Mbps>







<2Mbps>






### 3.3.7 Test Result of Power Spectral Density Plots (3kHz)


<Ant. 4>

<1Mbps>






<2Mbps>






<Ant. 3>

<1Mbps>





<2Mbps>



## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


### 3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.4.4 Test Setup







### 3.4.5 Test Result of Conducted Band Edges Plots

<Ant. 4>

<1Mbps>




<2Mbps>






<Ant. 3>

<1Mbps>



<2Mbps>









### 3.4.6 Test Result of Conducted Spurious Emission Plots

<Ant. 4>


<1Mbps>








<2Mbps>









<Ant. 3>


<1Mbps>








<2Mbps>









### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

See list of measuring equipment of this test report.




### 3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1 GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and be reported.
7. For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and be reported.
8. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW = 100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW = 3 MHz for  $f \geq 1$  GHz for peak measurement.  
For average measurement:
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

### 3.5.7 Duty Cycle

Please refer to Appendix E.

### 3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 04, 2021	Jun. 09, 2021~ Jul. 28, 2021	Jan. 03, 2022	Radiation (03CH13-HY)
Amplifier	Sonoma-Instrument	310 N	187282	9KHz~1GHz	Dec. 16, 2020	Jun. 09, 2021~ Jul. 28, 2021	Dec. 15, 2021	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Jul. 15, 2020	Jun. 09, 2021~ Jul. 13, 2021	Jul. 14, 2021	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Jul. 13, 2021	Jul. 13, 2021~ Jul. 28, 2021	Jul. 12, 2022	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-001 01800-30-10 P	1590074	1GHz~18GHz	May 18, 2021	Jun. 09, 2021~ Jul. 28, 2021	May 17, 2022	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY53270147	1GHz~26.5GHz	Oct. 28, 2020	Jun. 09, 2021~ Jul. 28, 2021	Oct. 27, 2021	Radiation (03CH13-HY)
Signal Generator	Anritsu	MG3694C	163401	0.1Hz~40GHz	Jan. 31, 2021	Jun. 09, 2021~ Jul. 28, 2021	Jan. 30, 2022	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Mar. 18, 2021	Jun. 09, 2021~ Jul. 28, 2021	Mar. 17, 2022	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jun. 09, 2021~ Jul. 28, 2021	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500 -B	N/A	1m~4m	N/A	Jun. 09, 2021~ Jul. 28, 2021	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jun. 09, 2021~ Jul. 28, 2021	N/A	Radiation (03CH13-HY)
Software	Audix	E3 6.2009-8-24	RK-000992	N/A	N/A	Jun. 09, 2021~ Jul. 28, 2021	N/A	Radiation (03CH13-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 11, 2020	Jun. 09, 2021~ Jul. 28, 2021	Dec. 10, 2021	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30M-18G	Feb. 10, 2021	Jun. 09, 2021~ Jul. 28, 2021	Feb. 09, 2022	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	804793/4	30M-18G	Feb. 10, 2021	Jun. 09, 2021~ Jul. 28, 2021	Feb. 09, 2022	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30M~40GHz	Feb. 22, 2021	Jun. 09, 2021~ Jul. 28, 2021	Feb. 21, 2022	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz~40GHz	Mar. 11, 2021	Jun. 09, 2021~ Jul. 28, 2021	Mar. 10, 2022	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30M-18G	Feb. 10, 2021	Jun. 09, 2021~ Jul. 28, 2021	Feb. 09, 2022	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz~30MHz	Mar. 11, 2021	Jun. 09, 2021~ Jul. 28, 2021	Mar. 10, 2022	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA91705 84	18GHz- 40GHz	Dec. 11, 2020	Jun. 09, 2021~ Jul. 28, 2021	Dec. 10, 2021	Radiation (03CH13-HY)
Hygrometer	TECPEL	DTM-303B	TP200879	N/A	Oct. 22, 2020	Jun. 09, 2021~ Jul. 28, 2021	Oct. 21, 2021	Radiation (03CH13-HY)
Filter	Wainwright	WHKX8-587 2.5-6750-180 00-40ST	Sn5	6.75GHz High Pass Filter	Mar. 11, 2021	Jun. 09, 2021~ Jul. 28, 2021	Mar. 10, 2022	Radiation (03CH13-HY)
Filter	Wainwright	WHKX12-27 00-3000-180 00-60SS	SN2	3GHz High Pass Filter	May 17, 2021	Jun. 09, 2021~ Jul. 28, 2021	May 16, 2022	Radiation (03CH13-HY)





Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 02, 2021	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 30, 2020	Jul. 02, 2021	Nov. 29, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 18, 2020	Jul. 02, 2021	Nov. 17, 2021	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 16, 2020	Jul. 02, 2021	Nov. 15, 2021	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 02, 2021	N/A	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Feb. 25, 2021	Jul. 02, 2021	Feb. 24, 2022	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 31, 2020	Jul. 02, 2021	Dec. 30, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2021	Jun. 20, 2021~ Jun. 24, 2021	Mar. 01, 2022	Conducted (TH02-HY)
Power Sensor	DARE	RPR3006W	RPR6W-210 1001	10MHz~8GHz	Feb. 03, 2021	Jun. 20, 2021~ Jun. 24, 2021	Feb. 02, 2022	Conducted (TH02-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz ~ 40GHz	Jul. 22, 2020	Jun. 20, 2021~ Jun. 24, 2021	Jul. 21, 2021	Conducted (TH02-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2021	Jun. 20, 2021~ Jun. 24, 2021	Mar. 16, 2022	Conducted (TH02-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3 dB
---	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.3 dB
---	--------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.8 dB
---	--------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.6 dB
---	--------

**Appendix A. Test Result of Conducted Test Items**

Test Engineer:	Shiming Liu	Temperature:	23.5~24.4	°C
Test Date:	2021/6/20~2021/6/24	Relative Humidity:	46.5~56.6	%

&lt;Ant. 4&gt;

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.037	0.712	0.50	Pass
BLE	1Mbps	1	19	2440	1.039	0.716	0.50	Pass
BLE	1Mbps	1	39	2480	1.037	0.714	0.50	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	18.95	30.00	-1.20	17.75	36.00	Pass
BLE	1Mbps	1	19	2440	19.05	30.00	-1.20	17.85	36.00	Pass
BLE	1Mbps	1	39	2480	18.85	30.00	-1.20	17.65	36.00	Pass

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	18.41	3.69	-1.20	8.00	Pass
BLE	1Mbps	1	19	2440	19.17	4.50	-1.20	8.00	Pass
BLE	1Mbps	1	39	2480	18.94	4.28	-1.20	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.050	1.179	0.50	Pass
BLE	2Mbps	1	19	2440	2.054	1.239	0.50	Pass
BLE	2Mbps	1	39	2480	2.050	1.239	0.50	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	19.05	30.00	-1.20	17.85	36.00	Pass
BLE	2Mbps	1	19	2440	19.15	30.00	-1.20	17.95	36.00	Pass
BLE	2Mbps	1	39	2480	18.95	30.00	-1.20	17.75	36.00	Pass

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	18.97	0.72	-1.20	8.00	Pass
BLE	2Mbps	1	19	2440	19.01	0.83	-1.20	8.00	Pass
BLE	2Mbps	1	39	2480	18.68	0.46	-1.20	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<Ant. 3>

<b>TEST RESULTS DATA</b> <b>6dB and 99% Occupied Bandwidth</b>								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.037	0.708	0.50	Pass
BLE	1Mbps	1	19	2440	1.037	0.716	0.50	Pass
BLE	1Mbps	1	39	2480	1.037	0.714	0.50	Pass

<b>TEST RESULTS DATA</b> <b>Average Power Table</b>										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	18.95	30.00	-1.10	17.85	36.00	Pass
BLE	1Mbps	1	19	2440	19.45	30.00	-1.10	18.35	36.00	Pass
BLE	1Mbps	1	39	2480	18.95	30.00	-1.10	17.85	36.00	Pass

<b>TEST RESULTS DATA</b> <b>Peak Power Density</b>									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	18.57	3.88	-1.10	8.00	Pass
BLE	1Mbps	1	19	2440	19.10	4.45	-1.10	8.00	Pass
BLE	1Mbps	1	39	2480	18.73	4.09	-1.10	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.046	1.183	0.50	Pass
BLE	2Mbps	1	19	2440	2.050	1.243	0.50	Pass
BLE	2Mbps	1	39	2480	2.046	1.235	0.50	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	19.05	30.00	-1.10	17.95	36.00	Pass
BLE	2Mbps	1	19	2440	19.55	30.00	-1.10	18.45	36.00	Pass
BLE	2Mbps	1	39	2480	18.75	30.00	-1.10	17.65	36.00	Pass

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	19.14	0.87	-1.10	8.00	Pass
BLE	2Mbps	1	19	2440	19.01	0.78	-1.10	8.00	Pass
BLE	2Mbps	1	39	2480	18.56	0.36	-1.10	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




## Appendix B. AC Conducted Emission Test Results

Test Engineer :	Howard Huang	Temperature :	23~26°C
		Relative Humidity :	40~50%

# EUT Information

Report NO : 0D2942-04  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum



## Final\_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	30.13	55.40	25.27	L1	OFF	19.5
0.161250	39.90	---	65.40	25.50	L1	OFF	19.5
0.233250	---	34.54	52.33	17.79	L1	OFF	19.5
0.233250	36.85	---	62.33	25.48	L1	OFF	19.5
0.501000	---	35.17	46.00	10.83	L1	OFF	19.7
0.501000	37.76	---	56.00	18.24	L1	OFF	19.7
0.568500	---	32.49	46.00	13.51	L1	OFF	19.7
0.568500	36.76	---	56.00	19.24	L1	OFF	19.7
0.854250	---	25.02	46.00	20.98	L1	OFF	20.0
0.854250	30.82	---	56.00	25.18	L1	OFF	20.0
1.446000	---	26.86	46.00	19.14	L1	OFF	20.0
1.446000	38.16	---	56.00	17.84	L1	OFF	20.0
1.923000	---	25.67	46.00	20.33	L1	OFF	20.0
1.923000	34.66	---	56.00	21.34	L1	OFF	20.0
6.450000	---	25.67	50.00	24.33	L1	OFF	19.9
6.450000	26.96	---	60.00	33.04	L1	OFF	19.9



# EUT Information

Report NO : 0D2942-04  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	29.59	55.40	25.81	N	OFF	19.5
0.161250	38.15	---	65.40	27.25	N	OFF	19.5
0.235500	---	34.22	52.25	18.03	N	OFF	19.5
0.235500	36.21	---	62.25	26.04	N	OFF	19.5
0.503250	---	34.30	46.00	11.70	N	OFF	19.7
0.503250	37.38	---	56.00	18.62	N	OFF	19.7
0.568500	---	32.65	46.00	13.35	N	OFF	19.8
0.568500	37.13	---	56.00	18.87	N	OFF	19.8
1.374000	---	27.13	46.00	18.87	N	OFF	20.0
1.374000	37.61	---	56.00	18.39	N	OFF	20.0
1.446000	---	28.22	46.00	17.78	N	OFF	20.0
1.446000	39.79	---	56.00	16.21	N	OFF	20.0
1.500000	---	27.77	46.00	18.23	N	OFF	20.0
1.500000	38.84	---	56.00	17.16	N	OFF	20.0
1.686750	---	27.49	46.00	18.51	N	OFF	20.0
1.686750	35.40	---	56.00	20.60	N	OFF	20.0
10.749750	---	25.41	50.00	24.59	N	OFF	20.1
10.749750	26.71	---	60.00	33.29	N	OFF	20.1



### Appendix C. Radiated Spurious Emission

Test Engineer :	Daniel Lee, Jacky Hong and Wilson Wu	Temperature :	20~25°C
		Relative Humidity :	40~60%

<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE Ant.	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
BLE CH 00 2402MHz		2314.2	55.52	-18.48	74	41.57	27.77	14.04	27.86	122	294	P	H	
		2318.4	45.41	-8.59	54	31.46	27.76	14.05	27.86	122	294	A	H	
	*	2402	112.4	-	-	98.51	27.6	14.13	27.84	122	294	P	H	
	*	2402	111.88	-	-	97.99	27.6	14.13	27.84	122	294	A	H	
													H	
			2371.635	54.39	-19.61	74	40.48	27.66	14.1	27.85	400	354	P	V
			2373.735	45.5	-8.5	54	31.6	27.65	14.1	27.85	400	354	A	V
	*		2402	108.3	-	-	94.41	27.6	14.13	27.84	400	354	P	V
	*		2402	107.66	-	-	93.77	27.6	14.13	27.84	400	354	A	V
														V
BLE CH 19 2440MHz		2347.1	54.28	-19.72	74	40.34	27.71	14.08	27.85	114	292	P	H	
		2320.92	45.49	-8.51	54	31.54	27.76	14.05	27.86	114	292	A	H	
	*	2440	114.12	-	-	100.27	27.52	14.16	27.83	114	292	P	H	
	*	2440	113.47	-	-	99.62	27.52	14.16	27.83	114	292	A	H	
			2499.3	54.62	-19.38	74	40.73	27.5	14.21	27.82	114	292	P	H
			2493.84	45.19	-8.81	54	31.3	27.5	14.21	27.82	114	292	A	H
			2313.36	54.88	-19.12	74	40.93	27.77	14.04	27.86	396	17	P	V
			2313.36	45.07	-8.93	54	31.12	27.77	14.04	27.86	396	17	A	V
	*		2440	110.85	-	-	97	27.52	14.16	27.83	396	17	P	V
	*		2440	110.28	-	-	96.43	27.52	14.16	27.83	396	17	A	V
			2483.83	54.66	-19.34	74	40.78	27.5	14.2	27.82	396	17	P	V
			2486.07	45.19	-8.81	54	31.31	27.5	14.2	27.82	396	17	A	V



<b>BLE CH 39 2480MHz</b>	*	2480	113.18	-	-	99.31	27.5	14.19	27.82	113	292	P	H
	*	2480	112.59	-	-	98.72	27.5	14.19	27.82	113	292	A	H
		2492.52	54.27	-19.73	74	40.39	27.5	14.2	27.82	113	292	P	H
		2484.68	45.83	-8.17	54	31.95	27.5	14.2	27.82	113	292	A	H
													H
													H
	*	2480	108.89	-	-	95.02	27.5	14.19	27.82	332	9	P	V
	*	2480	108.24	-	-	94.37	27.5	14.19	27.82	332	9	A	V
		2498.72	54.24	-19.76	74	40.35	27.5	14.21	27.82	332	9	P	V
		2491.92	45.09	-8.91	54	31.21	27.5	14.2	27.82	332	9	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz  
BLE (Harmonic @ 3m)

BLE Ant. 4	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	38.06	-35.94	74	57.53	31.11	6.51	57.09	100	0	P	H
		18000	57.16	-16.84	74	52.6	48.1	13.18	56.72	264	198	P	H
		18000	46.96	-7.04	54	42.4	48.1	13.18	56.72	264	198	A	H
													H
		4804	38.67	-35.33	74	58.14	31.11	6.51	57.09	100	0	P	V
		18000	56.46	-17.54	74	51.9	48.1	13.18	56.72	320	209	P	V
		18000	46.76	-7.24	54	42.2	48.1	13.18	56.72	320	209	A	V
BLE CH 19 2440MHz		4880	37.6	-36.4	74	56.53	31.2	6.83	56.96	100	0	P	H
		7320	44.97	-29.03	74	56.4	36.76	8.73	56.92	100	0	P	H
		18000	56.66	-17.34	74	52.1	48.1	13.18	56.72	254	188	P	H
		18000	46.76	-7.24	54	42.2	48.1	13.18	56.72	254	188	A	H
		4880	37.44	-36.56	74	56.37	31.2	6.83	56.96	100	0	P	V
		7320	44.47	-29.53	74	55.9	36.76	8.73	56.92	100	0	P	V
		17955	56.17	-17.83	74	52.9	46.84	13.15	56.72	285	206	P	V
		17955	45.57	-8.43	54	42.3	46.84	13.15	56.72	285	206	A	V
BLE CH 39 2480MHz		4960	38.58	-35.42	74	56.8	31.42	7.17	56.81	100	0	P	H
		7440	45.74	-28.26	74	57.39	36.82	8.7	57.17	100	0	P	H
		18000	56.76	-17.24	74	52.2	48.1	13.18	56.72	249	305	P	H
		18000	46.86	-7.14	54	42.3	48.1	13.18	56.72	249	305	A	H
		4960	39.74	-34.26	74	57.96	31.42	7.17	56.81	100	0	P	V
		7440	45.2	-28.8	74	56.85	36.82	8.7	57.17	100	0	P	V
		17985	56.33	-17.67	74	52.2	47.68	13.17	56.72	320	207	P	V
		17985	46.53	-7.47	54	42.4	47.68	13.17	56.72	320	207	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
3		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)	
BLE CH 00 2402MHz		2315.88	54.51	-19.49	74	40.55	27.77	14.05	27.86	100	303	P	H	
		2351.895	45.23	-8.77	54	31.3	27.7	14.08	27.85	100	303	A	H	
	*	2402	114.06	-	-	100.17	27.6	14.13	27.84	100	303	P	H	
	*	2402	113.34	-	-	99.45	27.6	14.13	27.84	100	303	A	H	
													H	
														H
			2378.88	54.24	-19.76	74	40.33	27.64	14.11	27.84	312	102	P	V
			2362.395	45.52	-8.48	54	31.6	27.68	14.09	27.85	312	102	A	V
	*		2402	111.22	-	-	97.33	27.6	14.13	27.84	312	102	P	V
	*		2402	110.47	-	-	96.58	27.6	14.13	27.84	312	102	A	V
														V
														V
BLE CH 19 2440MHz		2363.34	54.65	-19.35	74	40.74	27.67	14.09	27.85	100	303	P	H	
		2350.46	45.42	-8.58	54	31.49	27.7	14.08	27.85	100	303	A	H	
	*	2440	113.44	-	-	99.59	27.52	14.16	27.83	100	303	P	H	
	*	2440	112.84	-	-	98.99	27.52	14.16	27.83	100	303	A	H	
			2485.37	55.48	-18.52	74	41.6	27.5	14.2	27.82	100	303	P	H
			2496.08	45.34	-8.66	54	31.45	27.5	14.21	27.82	100	303	A	H
			2326.94	54.8	-19.2	74	40.84	27.75	14.06	27.85	302	103	P	V
			2388.26	45.45	-8.55	54	31.55	27.62	14.12	27.84	302	103	A	V
	*		2440	109.85	-	-	96	27.52	14.16	27.83	302	103	P	V
	*		2440	109.2	-	-	95.35	27.52	14.16	27.83	302	103	A	V
			2494.61	54.54	-19.46	74	40.65	27.5	14.21	27.82	302	103	P	V
			2494.05	45.39	-8.61	54	31.5	27.5	14.21	27.82	302	103	A	V



<b>BLE CH 39 2480MHz</b>	*	2480	112.33	-	-	98.46	27.5	14.19	27.82	106	306	P	H
	*	2480	111.74	-	-	97.87	27.5	14.19	27.82	106	306	A	H
		2484.28	54.55	-19.45	74	40.67	27.5	14.2	27.82	106	306	P	H
		2484.2	45.87	-8.13	54	31.99	27.5	14.2	27.82	106	306	A	H
													H
													H
	*	2480	106.74	-	-	92.87	27.5	14.19	27.82	291	101	P	V
	*	2480	106.19	-	-	92.32	27.5	14.19	27.82	291	101	A	V
		2485.96	54.81	-19.19	74	40.93	27.5	14.2	27.82	291	101	P	V
		2486.8	45.32	-8.68	54	31.44	27.5	14.2	27.82	291	101	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz  
BLE (Harmonic @ 3m)

BLE Ant. 3	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BLE CH 00 2402MHz		4804	38.84	-35.16	74	58.31	31.11	6.51	57.09	100	0	P	H
		17985	56.63	-17.37	74	52.5	47.68	13.17	56.72	254	220	P	H
		17985	46.33	-7.67	54	42.2	47.68	13.17	56.72	254	220	A	H
													H
		4804	40.1	-33.9	74	59.57	31.11	6.51	57.09	100	0	P	V
		18000	56.96	-17.04	74	52.4	48.1	13.18	56.72	296	302	P	V
		18000	46.86	-7.14	54	42.3	48.1	13.18	56.72	296	302	A	V
BLE CH 19 2440MHz		4880	40.31	-33.69	74	59.24	31.2	6.83	56.96	100	0	P	H
		7320	45.71	-28.29	74	57.14	36.76	8.73	56.92	100	0	P	H
		17985	56.33	-17.67	74	52.2	47.68	13.17	56.72	220	209	P	H
		17985	46.43	-7.57	54	42.3	47.68	13.17	56.72	220	209	A	H
		4880	39.55	-34.45	74	58.48	31.2	6.83	56.96	100	0	P	V
		7320	44.93	-29.07	74	56.36	36.76	8.73	56.92	100	0	P	V
		17985	57.13	-16.87	74	53	47.68	13.17	56.72	285	224	P	V
		17985	46.63	-7.37	54	42.5	47.68	13.17	56.72	285	224	A	V
BLE CH 39 2480MHz		4960	39.54	-34.46	74	57.76	31.42	7.17	56.81	100	0	P	H
		7440	44.69	-29.31	74	56.34	36.82	8.7	57.17	100	0	P	H
		17985	56.63	-17.37	74	52.5	47.68	13.17	56.72	232	211	P	H
		17985	46.43	-7.57	54	42.3	47.68	13.17	56.72	232	211	A	H
		4960	40.69	-33.31	74	58.91	31.42	7.17	56.81	100	0	P	V
		7440	45.13	-28.87	74	56.78	36.82	8.7	57.17	100	0	P	V
		17985	57.43	-16.57	74	53.3	47.68	13.17	56.72	255	185	P	V
		17985	46.73	-7.27	54	42.6	47.68	13.17	56.72	255	185	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.	
4		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
BLE CH 00 2402MHz		2351.16	55.7	-18.3	74	41.77	27.7	14.08	27.85	144	288	P	H	
		2382.45	44.26	-9.74	54	30.35	27.64	14.11	27.84	144	288	A	H	
	*	2402	113.05	-	-	99.16	27.6	14.13	27.84	144	288	P	H	
	*	2402	111.47	-	-	97.58	27.6	14.13	27.84	144	288	A	H	
													H	
														H
			2315.775	54.07	-19.93	74	40.11	27.77	14.05	27.86	362	12	P	V
			2366.49	44.25	-9.75	54	30.33	27.67	14.1	27.85	362	12	A	V
	*		2402	110.48	-	-	96.59	27.6	14.13	27.84	362	12	P	V
	*		2402	108.85	-	-	94.96	27.6	14.13	27.84	362	12	A	V
														V
														V
BLE CH 19 2440MHz		2345	54.69	-19.31	74	40.76	27.71	14.07	27.85	113	300	P	H	
		2365.02	44.27	-9.73	54	30.35	27.67	14.1	27.85	113	300	A	H	
	*	2440	113.98	-	-	100.13	27.52	14.16	27.83	113	300	P	H	
	*	2440	112.37	-	-	98.52	27.52	14.16	27.83	113	300	A	H	
			2495.45	54.21	-19.79	74	40.32	27.5	14.21	27.82	113	300	P	H
			2496.71	44.42	-9.58	54	30.53	27.5	14.21	27.82	113	300	A	H
			2331	54.19	-19.81	74	40.24	27.74	14.06	27.85	393	16	P	V
			2324.14	44.23	-9.77	54	30.29	27.75	14.05	27.86	393	16	A	V
	*		2440	110.31	-	-	96.46	27.52	14.16	27.83	393	16	P	V
	*		2440	108.78	-	-	94.93	27.52	14.16	27.83	393	16	A	V
			2486.63	55.35	-18.65	74	41.47	27.5	14.2	27.82	393	16	P	V
			2484.25	44.47	-9.53	54	30.59	27.5	14.2	27.82	393	16	A	V





<b>BLE CH 39 2480MHz</b>	*	2480	113.54	-	-	99.67	27.5	14.19	27.82	111	302	P	H
	*	2480	112.04	-	-	98.17	27.5	14.19	27.82	111	302	A	H
		2483.64	55.15	-18.85	74	41.27	27.5	14.2	27.82	111	302	P	H
		2483.52	46.57	-7.43	54	32.69	27.5	14.2	27.82	111	302	A	H
													H
													H
	*	2480	108.91	-	-	95.04	27.5	14.19	27.82	332	10	P	V
	*	2480	107.42	-	-	93.55	27.5	14.19	27.82	332	10	A	V
		2490	54.49	-19.51	74	40.61	27.5	14.2	27.82	332	10	P	V
		2483.52	45.27	-8.73	54	31.39	27.5	14.2	27.82	332	10	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz  
BLE (Harmonic @ 3m)

BLE Ant. 4	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BLE CH 00 2402MHz		4804	37.42	-36.58	74	56.89	31.11	6.51	57.09	100	0	P	H
		18000	57.06	-16.94	74	52.5	48.1	13.18	56.72	269	302	P	H
		18000	46.86	-7.14	54	42.3	48.1	13.18	56.72	269	302	A	H
													H
		4804	38.52	-35.48	74	57.99	31.11	6.51	57.09	100	0	P	V
		17985	56.53	-17.47	74	52.4	47.68	13.17	56.72	352	208	P	V
		17985	46.53	-7.47	54	42.4	47.68	13.17	56.72	352	208	A	V
BLE CH 19 2440MHz		4880	37.88	-36.12	74	56.81	31.2	6.83	56.96	100	0	P	H
		7320	44.69	-29.31	74	56.12	36.76	8.73	56.92	100	0	P	H
		18000	56.56	-17.44	74	52	48.1	13.18	56.72	285	204	P	H
		18000	46.86	-7.14	54	42.3	48.1	13.18	56.72	285	204	A	H
		4880	37.63	-36.37	74	56.56	31.2	6.83	56.96	100	0	P	V
		7320	44.28	-29.72	74	55.71	36.76	8.73	56.92	100	0	P	V
		18000	57.06	-16.94	74	52.5	48.1	13.18	56.72	320	185	P	V
		18000	46.96	-7.04	54	42.4	48.1	13.18	56.72	320	185	A	V
BLE CH 39 2480MHz		4960	38.83	-35.17	74	57.05	31.42	7.17	56.81	100	0	P	H
		7440	44.68	-29.32	74	56.33	36.82	8.7	57.17	100	0	P	H
		17985	56.73	-17.27	74	52.6	47.68	13.17	56.72	255	203	P	H
		17985	46.33	-7.67	54	42.2	47.68	13.17	56.72	255	203	A	H
		4960	38.93	-35.07	74	57.15	31.42	7.17	56.81	100	0	P	V
		7440	44.5	-29.5	74	56.15	36.82	8.7	57.17	100	0	P	V
		17970	56.5	-17.5	74	52.8	47.26	13.16	56.72	298	227	P	V
		17970	46.3	-7.7	54	42.6	47.26	13.16	56.72	298	227	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission above 18GHz

2.4GHz BLE (SHF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
4		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz BLE SHF		24094	39.46	-34.54	74	57.34	38.7	-2.86	53.72	150	0	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			24842	39.22	-34.78	74	56.01	39.21	-2.81	53.19	150	0	P
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
4		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
2.4GHz BLE LF		30	21.43	-18.57	40	28.57	24.57	0.51	32.22	-	-	P	H	
		167.74	24.46	-19.04	43.5	39.72	15.78	1.22	32.26	-	-	P	H	
		271.53	22.92	-23.08	46	34.45	18.94	1.51	31.98	-	-	P	H	
		551.86	28.9	-17.1	46	34.11	24.98	2.09	32.28	-	-	P	H	
		846.74	31.61	-14.39	46	31.56	28.61	2.63	31.19	-	-	P	H	
		944.71	32.63	-13.37	46	30.78	29.88	2.79	30.82	100	0	P	H	
														H
														H
														H
														H
														H
														H
			30	32.78	-7.22	40	39.92	24.57	0.51	32.22	100	0	P	V
			96.93	33.82	-9.68	43.5	49.56	15.57	0.92	32.23	-	-	P	V
			167.74	25.92	-17.58	43.5	41.18	15.78	1.22	32.26	-	-	P	V
			271.53	24.14	-21.86	46	35.67	18.94	1.51	31.98	-	-	P	V
			551.86	26.79	-19.21	46	32	24.98	2.09	32.28	-	-	P	V
			901.06	33.92	-12.08	46	33.64	28.61	2.71	31.04	-	-	P	V
														V
														V
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
3		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)	
BLE CH 00 2402MHz		2375.415	55.23	-18.77	74	41.31	27.65	14.11	27.84	100	301	P	H	
		2349.06	44.49	-9.51	54	30.56	27.7	14.08	27.85	100	301	A	H	
	*	2402	114.1	-	-	100.21	27.6	14.13	27.84	100	301	P	H	
	*	2402	112.5	-	-	98.61	27.6	14.13	27.84	100	301	A	H	
													H	
														H
			2363.13	54.54	-19.46	74	40.63	27.67	14.09	27.85	312	103	P	V
			2317.56	44.49	-9.51	54	30.54	27.76	14.05	27.86	312	103	A	V
	*		2402	111.27	-	-	97.38	27.6	14.13	27.84	312	103	P	V
	*		2402	109.73	-	-	95.84	27.6	14.13	27.84	312	103	A	V
														V
														V
BLE CH 19 2440MHz		2341.08	55.28	-18.72	74	41.34	27.72	14.07	27.85	115	303	P	H	
		2367.82	44.45	-9.55	54	30.54	27.66	14.1	27.85	115	303	A	H	
	*	2440	113.64	-	-	99.79	27.52	14.16	27.83	115	303	P	H	
	*	2440	111.98	-	-	98.13	27.52	14.16	27.83	115	303	A	H	
			2493.35	54.25	-19.75	74	40.37	27.5	14.2	27.82	115	303	P	H
			2494.68	44.54	-9.46	54	30.65	27.5	14.21	27.82	115	303	A	H
			2346.82	54.31	-19.69	74	40.37	27.71	14.08	27.85	344	90	P	V
			2383.92	44.41	-9.59	54	30.51	27.63	14.11	27.84	344	90	A	V
	*		2440	110.54	-	-	96.69	27.52	14.16	27.83	344	90	P	V
	*		2440	108.95	-	-	95.1	27.52	14.16	27.83	344	90	A	V
			2494.61	54.24	-19.76	74	40.35	27.5	14.21	27.82	344	90	P	V
			2497.76	44.56	-9.44	54	30.67	27.5	14.21	27.82	344	90	A	V



<b>BLE CH 39 2480MHz</b>	*	2480	112.84	-	-	98.97	27.5	14.19	27.82	107	306	P	H
	*	2480	111.27	-	-	97.4	27.5	14.19	27.82	107	306	A	H
		2483.56	54.9	-19.1	74	41.02	27.5	14.2	27.82	107	306	P	H
		2483.52	46.72	-7.28	54	32.84	27.5	14.2	27.82	107	306	A	H
													H
													H
	*	2480	107.59	-	-	93.72	27.5	14.19	27.82	290	102	P	V
	*	2480	106.13	-	-	92.26	27.5	14.19	27.82	290	102	A	V
		2494.2	53.92	-20.08	74	40.03	27.5	14.21	27.82	290	102	P	V
		2483.52	45.07	-8.93	54	31.19	27.5	14.2	27.82	290	102	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz  
BLE (Harmonic @ 3m)

BLE Ant. 3	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BLE CH 00 2402MHz		4804	38.85	-35.15	74	58.32	31.11	6.51	57.09	100	0	P	H
		17985	56.73	-17.27	74	52.6	47.68	13.17	56.72	212	168	P	H
		17985	46.63	-7.37	54	42.5	47.68	13.17	56.72	212	168	A	H
													H
		4804	38.53	-35.47	74	58	31.11	6.51	57.09	100	0	P	V
		17985	56.53	-17.47	74	52.4	47.68	13.17	56.72	330	189	P	V
		17985	46.53	-7.47	54	42.4	47.68	13.17	56.72	330	189	A	V
BLE CH 19 2440MHz		4880	39.17	-34.83	74	58.1	31.2	6.83	56.96	100	0	P	H
		7320	44.43	-29.57	74	55.86	36.76	8.73	56.92	100	0	P	H
		17985	56.63	-17.37	74	52.5	47.68	13.17	56.72	233	201	P	H
		17985	46.53	-7.47	54	42.4	47.68	13.17	56.72	233	201	A	H
		4880	38.99	-35.01	74	57.92	31.2	6.83	56.96	100	0	P	V
		7320	44.53	-29.47	74	55.96	36.76	8.73	56.92	100	0	P	V
		18000	56.76	-17.24	74	52.2	48.1	13.18	56.72	320	209	P	V
		18000	47.06	-6.94	54	42.5	48.1	13.18	56.72	320	209	A	V
BLE CH 39 2480MHz		4960	40.17	-33.83	74	58.39	31.42	7.17	56.81	100	0	P	H
		7440	44.66	-29.34	74	56.31	36.82	8.7	57.17	100	0	P	H
		17985	56.63	-17.37	74	52.5	47.68	13.17	56.72	288	225	P	H
		17985	46.53	-7.47	54	42.4	47.68	13.17	56.72	288	225	A	H
		4960	39.7	-34.3	74	57.92	31.42	7.17	56.81	100	0	P	V
		7440	44.46	-29.54	74	56.11	36.82	8.7	57.17	100	0	P	V
		18000	57.16	-16.84	74	52.6	48.1	13.18	56.72	311	201	P	V
		18000	46.86	-7.14	54	42.3	48.1	13.18	56.72	311	201	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
3		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)	
2.4GHz BLE LF		30	21.43	-18.57	40	28.57	24.57	0.51	32.22	-	-	P	H	
		167.74	24.46	-19.04	43.5	39.72	15.78	1.22	32.26	-	-	P	H	
		271.53	22.92	-23.08	46	34.45	18.94	1.51	31.98	-	-	P	H	
		551.86	28.9	-17.1	46	34.11	24.98	2.09	32.28	-	-	P	H	
		846.74	31.61	-14.39	46	31.56	28.61	2.63	31.19	-	-	P	H	
		944.71	32.63	-13.37	46	30.78	29.88	2.79	30.82	100	0	P	H	
														H
														H
														H
														H
														H
														H
			30	32.78	-7.22	40	39.92	24.57	0.51	32.22	100	0	P	V
			96.93	33.82	-9.68	43.5	49.56	15.57	0.92	32.23	-	-	P	V
			167.74	25.92	-17.58	43.5	41.18	15.78	1.22	32.26	-	-	P	V
			271.53	24.14	-21.86	46	35.67	18.94	1.51	31.98	-	-	P	V
			551.86	26.79	-19.21	46	32	24.98	2.09	32.28	-	-	P	V
			901.06	33.92	-12.08	46	33.64	28.61	2.71	31.04	-	-	P	V
														V
														V
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													





**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.