


RF Exposure Evaluation

(Mobile Condition)

FCC ID : A4RGB7N6
Equipment : Phone
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, California, 94043 USA
Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated in accordance with 47 CFR Part 2.1091 for the device and pass the limit.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager



SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2. MAXIMUM TUNE-UP LIMIT	5
3. RF EXPOSURE LIMIT INTRODUCTION	14
4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	15
4.1. Standalone Power Density Calculation	15



History of this test report

Report No.	Version	Description	Issued Date
FA0D2942-19A	Rev. 01	Initial issue of report	Nov. 18, 2022



1. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Phone
FCC ID	A4RGB7N6
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 14: 788 MHz ~ 798 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 25: 1850 MHz ~ 1915 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 30: 2305 MHz ~ 2315 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 48: 3550 MHz ~ 3700 MHz LTE Band 66: 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz 5G NR n2 : 1850 MHz ~ 1910 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n7 : 2500 MHz ~ 2570 MHz 5G NR n12 : 699 MHz ~ 716 MHz 5G NR n25 : 1850 MHz ~ 1915 MHz 5G NR n30 : 2305 MHz ~ 2315 MHz 5G NR n38 : 2570 MHz ~ 2620 MHz 5G NR n41 : 2496 MHz ~ 2690 MHz 5G NR n66 : 1710 MHz ~ 1780 MHz 5G NR n71 : 663 MHz ~ 698 MHz 5G NR n77: 3700 MHz ~ 3980 MHz, 3450 MHz ~ 3550 MHz WLAN 2.4 GHz Band: 2400 MHz ~ 2483.5 MHz WLAN 5.2 GHz Band: 5150 MHz ~ 5250 MHz WLAN 5.3 GHz Band: 5250 MHz ~ 5350 MHz WLAN 5.6 GHz Band: 5470 MHz ~ 5725 MHz WLAN 5.8 GHz Band: 5725 MHz ~ 5850 MHz WLAN 5.8G UNII4 Band: 5850 MHz ~ 5895 MHz WLAN 6E: 5925 MHz ~ 6425 MHz, 6425 MHz ~ 6525 MHz, 6525 MHz ~ 6875 MHz, 6875 MHz ~ 7125 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz NFC : 13.56 MHz WPT: 110KHz ~ 148.5KHz
Mode	GSM/GPRS/EGPRS RMC/AMR 12.2Kbps HSDPA HSUPA LTE: QPSK, 16QAM, 64QAM, 256QAM 5G NR: DFT-s-OFDM/CP-OFDM, Pi/2 BPSK/QPSK/16QAM/64QAM/256QAM WLAN: 802.11a/b/g/n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE NFC:ASK WPT: ASK
Remark:	1. Enable SP mode for UNII-5 and UNII-7.

Reviewed by: Jason Wang

Report Producer: Paula Chen



2. Maximum Tune-up Limit

General Note:

1. For each cellular band, the device has 5 antennas, the antenna selection is based on the connection quality condition, and only one antenna will transmit at a time.
2. The maximum power of the WWAN antenna will be selected to evaluate the power density
3. For MPE calculation is using the highest output among 2Tx switching antennas for each frequency band.

<WWAN Maximum Power>

Band	TX	Antenna	Default
			Index 1
GSM850 GPRS 1TX	TX0	0	33.5
GSM850 GPRS 2TX	TX0	0	32.5
GSM850 GPRS 3TX	TX0	0	31.5
GSM850 GPRS 4TX	TX0	0	30.5
GSM850 EDGE 1TX	TX0	0	28
GSM850 EDGE 2TX	TX0	0	27.5
GSM850 EDGE 3TX	TX0	0	27.5
GSM850 EDGE 4TX	TX0	0	25.5
GSM1900 GPRS 1TX	TX0	2	31.0
GSM1900 GPRS 2TX	TX0	2	29.5
GSM1900 GPRS 3TX	TX0	2	29.0
GSM1900 GPRS 4TX	TX0	2	28.0
GSM1900 EDGE 1TX	TX0	2	26
GSM1900 EDGE 2TX	TX0	2	25
GSM1900 EDGE 3TX	TX0	2	25
GSM1900 EDGE 4TX	TX0	2	24
WCDMA B2	TX0	2	25.0
WCDMA B4	TX0	2	25.0
WCDMA B5	TX0	0	25.0
LTE B7	TX0	2	24.6
LTE B12/17	TX0	0	25.0
LTE B13	TX0	0	25.0
LTE B14	TX0	0	25.0
LTE B25/2	TX0	2	25.0
LTE B26/5	TX0	0	25.0
LTE B30	TX0	2	25.0
LTE B41/B38 PC3	TX0	2	23.8
LTE B41/B38 PC2	TX0	2	26.8
LTE B48	TX0	6	24.0
LTE B66/4	TX0	2	25.0
LTE B71	TX0	0	25.0
FR1 n5	TX0	0	25.0
FR1 n7	TX0	2	24.6
FR1 n12	TX0	0	25.0
FR1 n25/2	TX0	2	25.0
FR1 n30	TX0	2	25.0
FR1 n66	TX0	2	25.0
FR1 n71	TX0	0	25.0
FR1 n41/38 PC3	TX0	5	24.8
FR1 n41 PC2	TX0	5	26.8
FR1 n77 PC3	TX0	6	25.0
FR1 n77 PC2	TX0	6	27.0



Band	TX	Antenna	Default
			Index 1
GSM850 GPRS 1TX	TX1	1	33.9
GSM850 GPRS 2TX	TX1	1	32.4
GSM850 GPRS 3TX	TX1	1	31.4
GSM850 GPRS 4TX	TX1	1	30.4
GSM850 EDGE 1TX	TX1	1	27.9
GSM850 EDGE 2TX	TX1	1	27.4
GSM850 EDGE 3TX	TX1	1	27.4
GSM850 EDGE 4TX	TX1	1	25.4
GSM1900 GPRS 1TX	TX1	0	30.7
GSM1900 GPRS 2TX	TX1	0	29.2
GSM1900 GPRS 3TX	TX1	0	28.7
GSM1900 GPRS 4TX	TX1	0	27.7
GSM1900 EDGE 1TX	TX1	0	25.7
GSM1900 EDGE 2TX	TX1	0	24.7
GSM1900 EDGE 3TX	TX1	0	24.7
GSM1900 EDGE 4TX	TX1	0	23.7
WCDMA B2	TX1	0	24.7
WCDMA B4	TX1	0	24.7
WCDMA B5	TX1	1	24.9
LTE B4	TX1	0	24.7
LTE B7	TX1	0	24.0
LTE B12/17	TX1	1	24.9
LTE B13	TX1	1	24.9
LTE B14	TX1	1	24.9
LTE B25/2	TX1	0	24.7
LTE B26/5	TX1	1	24.9
LTE B30	TX1	0	24.4
LTE B38 PC3	TX1	0	23.2
LTE B38 PC2	TX1	0	26.2
LTE B41 PC3	TX1	0	23.2
LTE B41 PC2	TX1	0	26.5
LTE B48	TX1	2	24.5
LTE B66	TX1	0	24.7
LTE B71	TX1	1	24.9
FR1 n5	TX1	1	24.9
FR1 n7	TX1	0	24.0
FR1 n12	TX1	1	24.9
FR1 n25/2	TX1	0	24.7
FR1 n30	TX1	0	24.4
FR1 n66	TX1	0	24.7
FR1 n71	TX1	1	24.9
FR1 n38	TX1	1	25.2
FR1 n41 PC3	TX1	1	25.4
FR1 n41 PC2	TX1	1	27.4
FR1 n77 PC3	TX1	2	25.0
FR1 n77 PC2	TX1	2	27.0



<WLAN Maximum Power>

<2.4GHz WLAN>

	Transmit Antenna			MIMO		
	Mode	Channel	Frequency (MHz)	Ant 4+3(4) Tune-Up Limit	Ant 4+3(3) Tune-Up Limit	Ant 4+3 Tune-Up Limit
2.4GHz WLAN	802.11b 1Mbps	1	2412	23.00	23.00	26.0
		6	2437	23.00	23.00	26.0
		11	2462	23.00	23.00	26.0
		12	2467	23.00	23.00	26.0
		13	2472	20.50	20.50	23.5
	802.11g 6Mbps	1	2412	21.50	21.50	24.5
		6	2437	21.50	21.50	24.5
		11	2462	21.00	21.00	24.0
		12	2467	19.50	19.50	22.5
		13	2472	17.50	17.50	20.5
	802.11n-HT20 MCS0	1	2412	21.00	21.00	24.0
		6	2437	21.50	21.50	24.5
		11	2462	20.00	20.00	23.0
		12	2467	19.00	19.00	22.0
		13	2472	16.50	16.50	19.5
	802.11ac-VHT20 MCS0	1	2412	21.00	21.00	24.0
		6	2437	21.50	21.50	24.5
		11	2462	20.00	20.00	23.0
		12	2467	19.00	19.00	22.0
		13	2472	16.50	16.50	19.5
802.11ax-HE20 MCS0	1	2412	21.00	21.00	24.0	
	6	2437	21.50	21.50	24.5	
	11	2462	20.00	20.00	23.0	
	12	2467	19.00	19.00	22.0	
	13	2472	16.50	16.50	19.5	



<5GHz WLAN>

	Transmit Antenna			MIMO		
	Mode	Channel	Frequency (MHz)	Ant 4+3(4) Tune-Up Limit	Ant 4+3(3) Tune-Up Limit	Ant 4+3 Tune-Up Limit
5.2GHz WLAN	802.11a 6Mbps	36	5180	18.50	18.50	21.5
		40	5200	18.50	18.50	21.5
		44	5220	18.50	18.50	21.5
		48	5240	18.50	18.50	21.5
	802.11n-HT20 MCS0	36	5180	18.50	18.50	21.5
		40	5200	18.50	18.50	21.5
		44	5220	18.50	18.50	21.5
		48	5240	19.00	19.00	22.0
	802.11n-HT40 MCS0	38	5190	17.50	17.50	20.5
		46	5230	20.00	20.00	23.0
	802.11ac-VHT20 MCS0	36	5180	18.50	18.50	21.5
		40	5200	18.50	18.50	21.5
		44	5220	18.50	18.50	21.5
		48	5240	19.00	19.00	22.0
	802.11ac-VHT40 MCS0	38	5190	17.50	17.50	20.5
		46	5230	20.00	20.00	23.0
	802.11ac-VHT80 MCS0	42	5210	17.00	17.00	20.0
	802.11ax-HE20 MCS0	36	5180	18.50	18.50	21.5
		40	5200	18.50	18.50	21.5
		44	5220	18.50	18.50	21.5
48		5240	19.00	19.00	22.0	
802.11ax-HE40 MCS0	38	5190	17.50	17.50	20.5	
	46	5230	20.00	20.00	23.0	
802.11ax-HE80 MCS0	42	5210	17.00	17.00	20.0	



Transmit Antenna				MIMO		
5.3GHz WLAN	Mode	Channel	Frequency (MHz)	Ant 4+3(4) Tune-Up Limit	Ant 4+3(3) Tune-Up Limit	Ant 4+3 Tune-Up Limit
	802.11a 6Mbps		52	5260	19.00	19.00
56			5280	19.00	19.00	22.0
60			5300	19.00	19.00	22.0
64			5320	19.00	19.00	22.0
802.11n-HT20 MCS0		52	5260	19.00	19.00	22.0
		56	5280	19.00	19.00	22.0
		60	5300	19.00	19.00	22.0
		64	5320	17.50	17.50	20.5
802.11n-HT40 MCS0		54	5270	20.00	20.00	23.0
		62	5310	17.00	17.00	20.0
802.11ac-VHT20 MCS0		52	5260	19.00	19.00	22.0
		56	5280	19.00	19.00	22.0
		60	5300	19.00	19.00	22.0
		64	5320	17.50	17.50	20.5
802.11ac-VHT40 MCS0		54	5270	20.00	20.00	23.0
		62	5310	17.00	17.00	20.0
802.11ac-VHT80 MCS0		58	5290	16.00	16.00	19.0
802.11ac-VHT160 MCS0		50	5250	15.00	15.00	18.0
802.11ax-HE20 MCS0		52	5260	19.00	19.00	22.0
		56	5280	19.00	19.00	22.0
		60	5300	19.00	19.00	22.0
		64	5320	17.50	17.50	20.5
802.11ax-HE40 MCS0		54	5270	20.00	20.00	23.0
		62	5310	17.00	17.00	20.0
802.11ax-HE80 MCS0		58	5290	16.00	16.00	19.0
802.11ax-HE160 MCS0		50	5250	15.00	15.00	18.0



	Transmit Antenna			MIMO		
	Mode	Channel	Frequency (MHz)	Ant 4+3(4) Tune-Up Limit	Ant 4+3(3) Tune-Up Limit	Ant 4+3 Tune-Up Limit
5.5GHz WLAN	802.11a 6Mbps	100	5500	17.00	17.00	20.0
		116	5580	19.00	19.00	22.0
		124	5620	19.00	19.00	22.0
		132	5660	19.00	19.00	22.0
		140	5700	17.00	17.00	20.0
		144	5720	19.00	19.00	22.0
	802.11n-HT20 MCS0	100	5500	17.00	17.00	20.0
		116	5580	19.50	19.50	22.5
		124	5620	19.50	19.50	22.5
		132	5660	19.50	19.50	22.5
		140	5700	17.50	17.50	20.5
		144	5720	19.50	19.50	22.5
	802.11n-HT40 MCS0	102	5510	17.50	17.50	20.5
		110	5550	20.00	20.00	23.0
		126	5630	20.00	20.00	23.0
		134	5670	20.00	20.00	23.0
		142	5710	20.00	20.00	23.0
		100	5500	17.00	17.00	20.0
	802.11ac-VHT20 MCS0	116	5580	19.50	19.50	22.5
		124	5620	19.50	19.50	22.5
		132	5660	19.50	19.50	22.5
		140	5700	17.50	17.50	20.5
		144	5720	19.50	19.50	22.5
		102	5510	17.50	17.50	20.5
	802.11ac-VHT40 MCS0	110	5550	20.00	20.00	23.0
		126	5630	20.00	20.00	23.0
		134	5670	20.00	20.00	23.0
		142	5710	20.00	20.00	23.0
		106	5530	18.00	18.00	21.0
		122	5610	20.00	20.00	23.0
	802.11ac-VHT80 MCS0	138	5690	20.00	20.00	23.0
		114	5570	17.00	17.00	20.0
	802.11ac-VHT160 MCS0	100	5500	17.00	17.00	20.0
	802.11ax-HE20 MCS0	116	5580	19.50	19.50	22.5
		124	5620	19.50	19.50	22.5
		132	5660	19.50	19.50	22.5
		140	5700	17.50	17.50	20.5
		144	5720	19.50	19.50	22.5
		102	5510	17.50	17.50	20.5
	802.11ax-HE40 MCS0	110	5550	20.00	20.00	23.0
126		5630	20.00	20.00	23.0	
134		5670	20.00	20.00	23.0	
142		5710	20.00	20.00	23.0	
106		5530	18.00	18.00	21.0	
122		5610	20.00	20.00	23.0	
802.11ax-HE80 MCS0	138	5690	20.00	20.00	23.0	
	114	5570	17.00	17.00	20.0	
802.11ax-HE160 MCS0	100	5500	17.00	17.00	20.0	



Transmit Antenna				MIMO		
5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Ant 4+3(4) Tune-Up Limit	Ant 4+3(3) Tune-Up Limit	Ant 4+3 Tune-Up Limit
	802.11a 6Mbps	149	5745	21.00	21.00	24.0
		157	5785	21.00	21.00	24.0
		165	5825	21.00	21.00	24.0
	802.11n-HT20 MCS0	149	5745	21.00	21.00	24.0
		157	5785	21.00	21.00	24.0
		165	5825	21.00	21.00	24.0
	802.11n-HT40 MCS0	151	5755	20.50	20.50	23.5
		159	5795	20.50	20.50	23.5
	802.11ac-VHT20 MCS0	149	5745	21.00	21.00	24.0
		157	5785	21.00	21.00	24.0
		165	5825	21.00	21.00	24.0
	802.11ac-VHT40 MCS0	151	5755	20.50	20.50	23.5
		159	5795	20.50	20.50	23.5
802.11ac-VHT80 MCS0	155	5775	20.50	20.50	23.5	
802.11ax-HE20 MCS0	149	5745	21.00	21.00	24.0	
	157	5785	21.00	21.00	24.0	
	165	5825	21.00	21.00	24.0	
802.11ax-HE40 MCS0	151	5755	20.50	20.50	23.5	
	159	5795	20.50	20.50	23.5	
802.11ax-HE80 MCS0	155	5775	20.50	20.50	23.5	

Transmit Antenna				MIMO		
5.8GHz WLAN UNII4	Mode	Channel	Frequency (MHz)	Ant 4+3(4) Tune-Up Limit	Ant 4+3(3) Tune-Up Limit	Ant 4+3 Tune-Up Limit
	802.11a 6Mbps	169	5845	21.0	21.0	24.0
		173	5865	21.0	21.0	24.0
		177	5885	21.0	21.0	24.0
	802.11n-HT20 MCS0	169	5845	21.0	21.0	24.0
		173	5865	21.0	21.0	24.0
		177	5885	21.0	21.0	24.0
	802.11n-HT40 MCS0	167	5835	20.0	20.0	23.0
		175	5875	20.0	20.0	23.0
	802.11ac-VHT20 MCS0	169	5845	21.0	21.0	24.0
		173	5865	21.0	21.0	24.0
		177	5885	21.0	21.0	24.0
	802.11ac-VHT40 MCS0	167	5835	20.0	20.0	23.0
		175	5875	20.0	20.0	23.0
802.11ac-VHT80 MCS0	171	5855	20.5	20.5	23.5	
802.11ax-HE20 MCS0	169	5845	21.0	21.0	24.0	
	173	5865	21.0	21.0	24.0	
	177	5885	21.0	21.0	24.0	
802.11ax-HE40 MCS0	167	5835	20.0	20.0	23.0	
	175	5875	20.0	20.0	23.0	
802.11ax-HE80 MCS0	171	5855	20.5	20.5	23.5	



<6E WLAN>

	Transmit Antenna			MIMO		
	Mode	Channel	Frequency (MHz)	Ant 4+3(4) Tune-Up Limit	Ant 4+3(3) Tune-Up Limit	Ant 4+3 Tune-Up Limit
WiFi 6E	802.11a 6Mbps	1	5955	20.5	20.5	23.5
		49	6195	20.5	20.5	23.5
		93	6415	20	20	23
		117	6535	20.5	20.5	23.5
		149	6695	20	20	23
		181	6855	20	20	23
	802.11ax-HE20 MCS0	1	5955	20	20	23
		49	6195	20.5	20.5	23.5
		93	6415	20.5	20.5	23.5
		117	6535	21	21	24
		149	6695	21	21	24
		181	6855	20.5	20.5	23.5
	802.11ax-HE40 MCS0	3	5965	20	20	23
		51	6205	20	20	23
		91	6405	19.5	19.5	22.5
		123	6565	20	20	23
		147	6685	20	20	23
		179	6845	19.5	19.5	22.5
	802.11ax-HE80 MCS0	7	5985	19.5	19.5	22.5
		55	6225	20	20	23
		87	6385	19.5	19.5	22.5
		135	6625	19.5	19.5	22.5
		151	6705	19	19	22
		167	6785	19.5	19.5	22.5
	802.11ax-HE160 MCS0	15	6025	19.5	19.5	22.5
		47	6185	19.5	19.5	22.5
		79	6345	20	20	23
		143	6665	19	19	22



<Bluetooth Maximum Power>

Mode	Burst Average Power (dBm)				
	Ant 4			Ant 4	
	BR / EDR			LE	
	1Mbps	2Mbps	3Mbps	1Mbps	2Mbps
Tune-up Limit	20	18.5	17.5	20	20

Mode	Average power (dBm)				
	Ant 3			Ant 3	
	BR / EDR			LE	
	1Mbps	2Mbps	3Mbps	1Mbps	2Mbps
Tune-up Limit	20	18.5	17.5	20	20

Mode	BR / EDR	Burst Average Power (dBm)								
		1Mbps			2Mbps			3Mbps		
		Ant 4+3(4)	Ant 4+3(3)	Ant 4+3	Ant 4+3(4)	Ant 4+3(3)	Ant 4+3	Ant 4+3(4)	Ant 4+3(3)	Ant 4+3
Tune-up Limit		17	17	20	15	15	18	15	15	18



3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



4. Radio Frequency Radiation Exposure Evaluation

4.1. Standalone Power Density Calculation

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
GSM/GPRS 850 (1 Tx slot)	-3.50	33.90	30.4	1.10	138.04	0.027	0.549	0.050
GPRS 850 (2 Tx slots)	-3.50	32.50	29.0	0.79	198.58	0.040	0.549	0.072
GPRS 850 (3 Tx slots)	-3.50	31.50	28.0	0.63	236.59	0.047	0.549	0.086
GPRS 850 (4 Tx slots)	-3.50	30.50	27.0	0.50	251.19	0.050	0.549	0.091
EGPRS 850 (1 Tx slot)	-3.50	28.00	24.5	0.28	35.48	0.007	0.549	0.013
EGPRS 850 (2 Tx slots)	-3.50	27.50	24.0	0.25	62.80	0.012	0.549	0.023
EGPRS 850 (3 Tx slots)	-3.50	27.50	24.0	0.25	94.20	0.019	0.549	0.034
EGPRS 850 (4 Tx slots)	-3.50	25.50	22.0	0.16	79.24	0.016	0.549	0.029
GSM/GPRS 1900 (1 Tx slot)	0.80	31.00	31.8	1.51	190.55	0.038	1.000	0.038
GPRS 1900 (2 Tx slots)	0.80	29.50	30.3	1.07	267.88	0.053	1.000	0.053
GPRS 1900 (3 Tx slots)	0.80	29.00	29.8	0.95	358.10	0.071	1.000	0.071
GPRS 1900 (4 Tx slots)	0.80	28.00	28.8	0.76	380.19	0.076	1.000	0.076
EGPRS 1900 (1 Tx slot)	0.80	26.00	26.8	0.48	60.26	0.012	1.000	0.012
EGPRS 1900 (2 Tx slots)	0.80	25.00	25.8	0.38	95.05	0.019	1.000	0.019
EGPRS 1900 (3 Tx slots)	0.80	25.00	25.8	0.38	142.57	0.028	1.000	0.028
EGPRS 1900 (4 Tx slots)	0.80	24.00	24.8	0.30	151.00	0.030	1.000	0.030
WCDMA Band 2	0.80	25.00	25.8	0.38	380.19	0.076	1.000	0.076
WCDMA Band 4	-0.30	25.00	24.7	0.30	295.12	0.059	1.000	0.059
WCDMA Band 5	-3.50	25.00	21.5	0.14	141.25	0.028	0.549	0.051
LTE Band 2	0.80	25.00	25.8	0.38	380.19	0.076	1.000	0.076
LTE Band 4	-0.30	25.00	24.7	0.30	295.12	0.059	1.000	0.059
LTE Band 5	-3.50	25.00	21.5	0.14	141.25	0.028	0.549	0.051
LTE Band 7	0.50	24.60	25.1	0.32	323.59	0.064	1.000	0.064
LTE Band 12	-1.80	25.00	23.2	0.21	208.93	0.042	0.466	0.089
LTE Band 13	-2.10	25.00	22.9	0.19	194.98	0.039	0.518	0.075
LTE Band 14	-2.30	25.00	22.7	0.19	186.21	0.037	0.525	0.071
LTE Band 17	-1.70	25.00	23.3	0.21	213.80	0.043	0.469	0.091
LTE Band 25	0.50	25.00	25.5	0.35	354.81	0.071	1.000	0.071
LTE Band 26	-3.30	25.00	21.7	0.15	147.91	0.029	0.543	0.054
LTE Band 30	-1.40	25.00	23.6	0.23	229.09	0.046	1.000	0.046
LTE Band 38	-0.70	23.80	23.1	0.20	204.17	0.041	1.000	0.041
LTE Band 38 HPUE	-0.70	26.80	26.1	0.41	407.38	0.081	1.000	0.081
LTE Band 41	-0.30	23.80	23.5	0.22	223.87	0.045	1.000	0.045
LTE Band 41 HPUE	-0.30	26.80	26.5	0.45	446.68	0.089	1.000	0.089
LTE Band 48	-0.30	24.50	24.2	0.26	263.03	0.052	1.000	0.052
LTE Band 66	0.00	25.00	25.0	0.32	316.23	0.063	1.000	0.063
LTE Band 71	-3.20	25.00	21.8	0.15	151.36	0.030	0.442	0.068
5G NR n2	0.80	25.00	25.8	0.38	380.19	0.076	1.000	0.076
5G NR n5	-3.50	25.00	21.5	0.14	141.25	0.028	0.549	0.051
5G NR n7	0.50	24.60	25.1	0.32	323.59	0.064	1.000	0.064
5G NR n12	-1.80	25.00	23.2	0.21	208.93	0.042	0.466	0.089
5G NR n25	0.50	25.00	25.5	0.35	354.81	0.071	1.000	0.071
5G NR n30	-1.40	25.00	23.6	0.23	229.09	0.046	1.000	0.046
5G NR n38	-0.70	25.20	24.5	0.28	281.84	0.056	1.000	0.056
5G NR n41	-0.30	25.40	25.1	0.32	323.59	0.064	1.000	0.064
5G NR n41 HPUE	-0.30	27.40	27.1	0.51	512.86	0.102	1.000	0.102
5G NR n66	0.00	25.00	25.0	0.32	316.23	0.063	1.000	0.063
5G NR n71	-3.20	25.00	21.8	0.15	151.36	0.030	0.442	0.068
5G NR n77	0.40	25.00	25.4	0.35	346.74	0.069	1.000	0.069
5G NR n77 HPUE	0.40	27.00	27.4	0.55	549.54	0.109	1.000	0.109
5G NR n77	0.50	25.00	25.5	0.35	354.81	0.071	1.000	0.071
WLAN2.4GHz Band	-1.1	26.0	24.9	0.31	309.03	0.062	1.000	0.062
WLAN5GHz/6GHz Band	1.6	24.0	25.6	0.36	363.08	0.072	1.000	0.072
Bluetooth	-1.1	20.0	18.9	0.08	77.62	0.015	1.000	0.015



WWAN Power Density / Limit	2.4GHz WLAN Power Density / Limit	5GHz/6GHz WLAN Power Density / Limit	WPT	Σ (Power Density / Limit)
0.109	0.062	0.072	0.011	0.254
WWAN Power Density / Limit	5GHz/6GHz WLAN Power Density / Limit	Bluetooth Power Density / Limit	WPT	Σ (Power Density / Limit)
0.109	0.072	0.015	0.011	0.207

Note:

1. WPT ratio is, from Sporton WPT evaluation report (FCC ID: A4RGB7N6, Report No.: FA0D2942-05B), $0.011 = 0.0184 / 1.63$ for calculation.
2. For collocation analysis, the highest (power density/limit) among all WWAN wireless modes is chosen for summation.
3. Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WWAN + 2.4GHz WLAN + 5GHz WLAN + WPT transmitter or WWAN + 5GHz WLAN + Bluetooth + WPT transmitter.
4. Considering the all the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 4 collocated transmitters is compliant

Conclusion:

According to 47 CFR §1.1307, the RF exposure analysis concludes that the RF Exposure is FCC compliant.