

#44_LTE Band 66 Ant 0_20M_QPSK_1_0_Bottom Side_10mm_Ch132572


Communication System: LTE-FDD ; Frequency: 1770.000 MHz; Duty Cycle: 1:1
Medium: HSL_1750_230516 Medium parameters used: $f=1770.000$ MHz; $\sigma=1.38$ S/m; $\epsilon_r=39.9$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.92, 8.92, 8.92); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (64.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 0.735 W/kg; SAR (10g) = 0.387 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.00 dB
SAR (1g) = 0.759 W/kg; SAR (8g) = 0.444 W/kg; SAR (10g) = 0.410 W/kg
Smallest distance from peaks to all points 3 dB below = 9.6 mm
Ratio of SAR at M2 to SAR at M1 = 82.3 %



#45_LTE Band 71 Ant 0_20M_QPSK_1_0_Left Side_10mm_Ch133297


Communication System: LTE-FDD ; Frequency: 680.500 MHz; Duty Cycle: 1:1
Medium: HSL_750_230512 Medium parameters used: $f= 680.500$ MHz; $\sigma= 0.863$ S/m; $\epsilon_r = 43.5$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.36, 10.36, 10.36); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (48.0 mm x 210.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 0.440 W/kg; SAR (10g) = 0.305 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.16 dB
SAR (1g) = 0.417 W/kg; SAR (8g) = 0.308 W/kg; SAR (10g) = 0.295 W/kg
Smallest distance from peaks to all points 3 dB below = > 15.0 mm
Ratio of SAR at M2 to SAR at M1 = 86.7 %



#46_FR1 n2 Ant 5_20M_QPSK_1_1_Right Side_10mm_Ch372000


Communication System: FR1; Frequency: 1860.000 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230502 Medium parameters used: $f = 1860.000$ MHz; $\sigma = 1.39$ S/m; $\epsilon_r = 39.5$
Ambient Temperature: 23.4°C; Liquid Temperature: 22.4°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.92, 7.92, 7.92); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10931-AAC

Area Scan (60.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.776 W/kg; SAR (10g) = 0.383 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.18 dB
SAR (1g) = 0.785 W/kg; SAR (8g) = 0.416 W/kg; SAR (10g) = 0.379 W/kg
Smallest distance from peaks to all points 3 dB below = 8.4 mm
Ratio of SAR at M2 to SAR at M1 = 76.1 %



#47_FR1 n5 Ant 0_20M_QPSK_1_1_Bottom Side_10mm_Ch167300


Communication System: FR1; Frequency: 836.500 MHz; Duty Cycle: 1:1
Medium: HSL_850_230505 Medium parameters used: $f = 836.500$ MHz; $\sigma = 0.934$ S/m; $\epsilon_r = 43.3$
Ambient Temperature: 23.3°C; Liquid Temperature: 22.3°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(9.84, 9.84, 9.84); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10931-AAC

Area Scan (60.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.472 W/kg; SAR (10g) = 0.264 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.10 dB
SAR (1g) = 0.463 W/kg; SAR (8g) = 0.259 W/kg; SAR (10g) = 0.238 W/kg
Smallest distance from peaks to all points 3 dB below = 9.6 mm
Ratio of SAR at M2 to SAR at M1 = 78.5 %



#48_FR1 n7 Ant 0_50M_QPSK_1_1_Bottom Side_10mm_Ch507000


Communication System: FR1 ; Frequency: 2535.000 MHz; Duty Cycle: 1:1
Medium: HSL_2600_230507 Medium parameters used: $f= 2535.000$ MHz; $\sigma= 1.90$ S/m; $\epsilon_r = 39.7$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.32, 7.32, 7.32); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10935-AAD

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 0.591 W/kg; SAR (10g) = 0.282 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.17 dB
SAR (1g) = 0.572 W/kg; SAR (8g) = 0.302 W/kg; SAR (10g) = 0.275 W/kg
Smallest distance from peaks to all points 3 dB below = 10.1 mm
Ratio of SAR at M2 to SAR at M1 = 78.1 %



#49_FR1 n12 Ant 0_15M_QPSK_1_1_Left Side_10mm_Ch141500


Communication System: FR1 ; Frequency: 707.500 MHz; Duty Cycle: 1:1
Medium: HSL_750_230508 Medium parameters used: $f = 707.500$ MHz; $\sigma = 0.888$ S/m; $\epsilon_r = 43.8$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(10.06, 10.06, 10.06); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10930-AAC

Area Scan (64.0 mm x 210.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 0.424 W/kg; SAR (10g) = 0.293 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.01 dB
SAR (1g) = 0.405 W/kg; SAR (8g) = 0.304 W/kg; SAR (10g) = 0.290 W/kg
Smallest distance from peaks to all points 3 dB below = > 15.0 mm
Ratio of SAR at M2 to SAR at M1 = 85.0 %



#50_FR1 n25 Ant 0_40M_QPSK_1_1_Bottom Side_10mm_Ch376500


Communication System: FR1; Frequency: 1882.500 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230504 Medium parameters used: $f=1882.500$ MHz; $\sigma=1.41$ S/m; $\epsilon_r=39.1$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.92, 7.92, 7.92); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10934-AAC

Area Scan (60.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.669 W/kg; SAR (10g) = 0.342 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.12 dB
SAR (1g) = 0.705 W/kg; SAR (8g) = 0.391 W/kg; SAR (10g) = 0.358 W/kg
Smallest distance from peaks to all points 3 dB below = 9.6 mm
Ratio of SAR at M2 to SAR at M1 = 80.4 %



#51_FR1 n30 Ant 0_10M_QPSK_1_1_Bottom Side_10mm_Ch462000


Communication System: FR1; Frequency: 2310.000 MHz; Duty Cycle: 1:1
Medium: HSL_2300_230510 Medium parameters used: $f=2310.000$ MHz; $\sigma=1.65$ S/m; $\epsilon_r=40.5$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.66, 7.66, 7.66); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10929-AAD

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 0.794 W/kg; SAR (10g) = 0.396 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.04 dB
SAR (1g) = 0.792 W/kg; SAR (8g) = 0.429 W/kg; SAR (10g) = 0.391 W/kg
Smallest distance from peaks to all points 3 dB below = 9.9 mm
Ratio of SAR at M2 to SAR at M1 = 79.6 %



#52_FR1 n41 Ant 0_100M_QPSK_1_1_Bottom Side_10mm_Ch518598


Communication System: FR1; Frequency: 2592.990 MHz; Duty Cycle: 1:1
Medium: HSL_2600_230516 Medium parameters used: $f = 2592.990$ MHz; $\sigma = 1.97$ S/m; $\epsilon_r = 39.6$
Ambient Temperature: 23.7°C; Liquid Temperature: 22.7°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.32, 7.32, 7.32); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 TDD, 10866-AAF

Area Scan (60.0 mm x 120.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.697 W/kg; SAR (10g) = 0.330 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.16 dB
SAR (1g) = 0.691 W/kg; SAR (8g) = 0.364 W/kg; SAR (10g) = 0.330 W/kg
Smallest distance from peaks to all points 3 dB below = 10.8 mm
Ratio of SAR at M2 to SAR at M1 = 77.8 %



#53_FR1 n66 Ant 0_40M_QPSK_1_1_Bottom Side_10mm_Ch349000


Communication System: FR1; Frequency: 1745.000 MHz; Duty Cycle: 1:1
Medium: HSL_1750_230524 Medium parameters used: $f=1745.000$ MHz; $\sigma=1.36$ S/m; $\epsilon_r=40.7$
Ambient Temperature: 23.4°C; Liquid Temperature: 22.4°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(8.25, 8.25, 8.25); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10934-AAC

Area Scan (64.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 0.673 W/kg; SAR (10g) = 0.357 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.04 dB
SAR (1g) = 0.686 W/kg; SAR (8g) = 0.389 W/kg; SAR (10g) = 0.357 W/kg
Smallest distance from peaks to all points 3 dB below = 9.6 mm
Ratio of SAR at M2 to SAR at M1 = 81.3 %



#54_FR1 n71 Ant 0_20M_QPSK_1_1_Left Side_10mm_Ch136100


Communication System: FR1; Frequency: 680.500 MHz; Duty Cycle: 1:1
Medium: HSL_750_230528 Medium parameters used: $f = 680.500$ MHz; $\sigma = 0.880$ S/m; $\epsilon_r = 44.2$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(10.06, 10.06, 10.06); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10931-AAC

Area Scan (60.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.383 W/kg; SAR (10g) = 0.264 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.10 dB
SAR (1g) = 0.392 W/kg; SAR (8g) = 0.281 W/kg; SAR (10g) = 0.268 W/kg
Smallest distance from peaks to all points 3 dB below = > 15.0 mm
Ratio of SAR at M2 to SAR at M1 = 84.2 %



#55_FR1 n77 Ant 7_100M_QPSK_1_1_Right Side_10mm_Ch633332


Communication System: FR1; Frequency: 3499.980 MHz; Duty Cycle: 1:1
Medium: HSL_3500_230530 Medium parameters used: $f=3499.980$ MHz; $\sigma=2.96$ S/m; $\epsilon_r=38.1$
Ambient Temperature: 23.8°C; Liquid Temperature: 22.8°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3642; ConvF(6.66, 6.66, 6.66); Calibrated: 2023-04-26
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1694; Calibrated: 2022-11-18
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2055; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 TDD, 10866-AAF

Area Scan (64.0 mm x 200.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 0.581 W/kg; SAR (10g) = 0.246 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 28.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = -0.01 dB
SAR (1g) = 0.585 W/kg; SAR (8g) = 0.272 W/kg; SAR (10g) = 0.244 W/kg
Smallest distance from peaks to all points 3 dB below = 9.0 mm
Ratio of SAR at M2 to SAR at M1 = 75.6 %



#56_GSM850 Ant 0_GPRS (4 Tx slots)_Back_10mm_Ch128


Communication System: GPRS-FDD ; Frequency: 824.200 MHz; Duty Cycle: 1:2.08
Medium: HSL_835_230515 Medium parameters used: $f = 824.200$ MHz; $\sigma = 0.912$ S/m; $\epsilon_r = 42.9$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.29, 10.29, 10.29); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: GSM, 10028-DAC

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.594 W/kg; SAR (10g) = 0.393 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.08 dB
SAR (1g) = 0.570 W/kg; SAR (8g) = 0.373 W/kg; SAR (10g) = 0.347 W/kg
Smallest distance from peaks to all points 3 dB below = 10.9 mm
Ratio of SAR at M2 to SAR at M1 = 81.4 %



#57_GSM1900 Ant 0_GPRS (4 Tx slots)_Front_10mm_Ch661


Communication System: GPRS-FDD ; Frequency: 1880.000 MHz; Duty Cycle: 1:2.08
Medium: HSL_1900_230513 Medium parameters used: $f=1880.000$ MHz; $\sigma=1.40$ S/m; $\epsilon_r=40.0$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.6, 8.6, 8.6); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: GSM, 10028-DAC

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.323 W/kg; SAR (10g) = 0.181 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.15 dB
SAR (1g) = 0.381 W/kg; SAR (8g) = 0.220 W/kg; SAR (10g) = 0.202 W/kg
Smallest distance from peaks to all points 3 dB below = 9.6 mm
Ratio of SAR at M2 to SAR at M1 = 82.4 %



#58_WCDMA II Ant 0_RMC 12.2Kbps_Front_10mm_Ch9400


Communication System: WCDMA; Frequency: 1880.000 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230513 Medium parameters used: $f=1880.000$ MHz; $\sigma=1.40$ S/m; $\epsilon_r=40.0$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.6, 8.6, 8.6); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: WCDMA, 10011-CAC

Area Scan (120.0 mm x 90.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.488 W/kg; SAR (10g) = 0.260 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.03 dB
SAR (1g) = 0.545 W/kg; SAR (8g) = 0.311 W/kg; SAR (10g) = 0.287 W/kg
Smallest distance from peaks to all points 3 dB below = 9.6 mm
Ratio of SAR at M2 to SAR at M1 = 81.1 %



#59_WCDMA IV Ant 0_RMC 12.2Kbps_Front_10mm_Ch1513


Communication System: WCDMA; Frequency: 1752.600 MHz; Duty Cycle: 1:1
Medium: HSL_1750_230516 Medium parameters used: $f=1752.600$ MHz; $\sigma=1.36$ S/m; $\epsilon_r=40.1$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.92, 8.92, 8.92); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: WCDMA, 10011-CAC

Area Scan (120.0 mm x 90.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.434 W/kg; SAR (10g) = 0.236 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.11 dB
SAR (1g) = 0.478 W/kg; SAR (8g) = 0.283 W/kg; SAR (10g) = 0.261 W/kg
Smallest distance from peaks to all points 3 dB below = 9.6 mm
Ratio of SAR at M2 to SAR at M1 = 82.2 %



#60_WCDMA Ant 0_RMC 12.2Kbps_Back_10mm_Ch4233


Communication System: UMTS-FDD ; Frequency: 846.6 MHz; Duty Cycle: 1:1
Medium: HSL_850_230515 Medium parameters used: $f= 846.6$ MHz; $\sigma= 0.923$ S/m; $\epsilon_r = 42.6$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.29, 10.29, 10.29); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: WCDMA, 10011-CAC

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.524 W/kg; SAR (10g) = 0.339 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.02 dB
SAR (1g) = 0.478 W/kg; SAR (8g) = 0.297 W/kg; SAR (10g) = 0.278 W/kg
Smallest distance from peaks to all points 3 dB below = 11.9 mm
Ratio of SAR at M2 to SAR at M1 = 80.1 %



#61_LTE Band 2 Ant 5_20M_QPSK_1_0_Back_10mm_Ch19100


Communication System: LTE-FDD ; Frequency: 1900.000 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230513 Medium parameters used: $f=1900.000$ MHz; $\sigma=1.43$ S/m; $\epsilon_r=40.0$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.6, 8.6, 8.6); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (120.0 mm x 150.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.266 W/kg; SAR (10g) = 0.141 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.08 dB
SAR (1g) = 0.277 W/kg; SAR (8g) = 0.158 W/kg; SAR (10g) = 0.146 W/kg
Smallest distance from peaks to all points 3 dB below = 8.5 mm
Ratio of SAR at M2 to SAR at M1 = 81.4 %



#62_LTE Band 7 Ant 0_20M_QPSK_1_0_Back_10mm_Ch21100


Communication System: LTE-FDD ; Frequency: 2535.0 MHz; Duty Cycle: 1:1
Medium: HSL_2600_230514 Medium parameters used: $f = 2535.0$ MHz; $\sigma = 1.94$ S/m; $\epsilon_r = 38.0$
Ambient Temperature: 23.7°C; Liquid Temperature: 22.7°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(7.78, 7.78, 7.78); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.637 W/kg; SAR (10g) = 0.325 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.19 dB
SAR (1g) = 0.644 W/kg; SAR (8g) = 0.371 W/kg; SAR (10g) = 0.341 W/kg
Smallest distance from peaks to all points 3 dB below = 12.3 mm
Ratio of SAR at M2 to SAR at M1 = 81.4 %



#63_LTE Band 12 Ant 0_10M_QPSK_1_0_Back_10mm_Ch23095


Communication System: LTE-FDD ; Frequency: 707.500 MHz; Duty Cycle: 1:1
Medium: HSL_750_230512 Medium parameters used: $f=707.500$ MHz; $\sigma=0.876$ S/m; $\epsilon_r=43.4$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.36, 10.36, 10.36); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10175-CAH

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.320 W/kg; SAR (10g) = 0.220 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.02 dB
SAR (1g) = 0.306 W/kg; SAR (8g) = 0.212 W/kg; SAR (10g) = 0.199 W/kg
Smallest distance from peaks to all points 3 dB below = 14.4 mm
Ratio of SAR at M2 to SAR at M1 = 81.8 %



#64_LTE Band 13 Ant 0_10M_QPSK_1_0_Back_10mm_Ch23230


Communication System: LTE-FDD ; Frequency: 782.000 MHz; Duty Cycle: 1:1
Medium: HSL_750_230512 Medium parameters used: $f=782.000$ MHz; $\sigma=0.903$ S/m; $\epsilon_r=42.9$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.36, 10.36, 10.36); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10175-CAH

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.351 W/kg; SAR (10g) = 0.237 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.01 dB
SAR (1g) = 0.369 W/kg; SAR (8g) = 0.231 W/kg; SAR (10g) = 0.216 W/kg
Smallest distance from peaks to all points 3 dB below = 12.3 mm
Ratio of SAR at M2 to SAR at M1 = 82.4 %



#65_LTE Band 14 Ant 0_10M_QPSK_1_0_Back_10mm_Ch23330


Communication System: LTE-FDD ; Frequency: 793.000 MHz; Duty Cycle: 1:1
Medium: HSL_750_230512 Medium parameters used: $f=793.000$ MHz; $\sigma=0.905$ S/m; $\epsilon_r=43.0$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.36, 10.36, 10.36); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10175-CAH

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.387 W/kg; SAR (10g) = 0.259 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.00 dB
SAR (1g) = 0.404 W/kg; SAR (8g) = 0.253 W/kg; SAR (10g) = 0.236 W/kg
Smallest distance from peaks to all points 3 dB below = 12.3 mm
Ratio of SAR at M2 to SAR at M1 = 81.5 %



#66_LTE Band 25 Ant 0_20M_QPSK_1_0_Front_10mm_Ch26590


Communication System: LTE-FDD ; Frequency: 1905.000 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230513 Medium parameters used: $f=1905.000$ MHz; $\sigma=1.44$ S/m; $\epsilon_r=39.9$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.6, 8.6, 8.6); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.493 W/kg; SAR (10g) = 0.257 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.07 dB
SAR (1g) = 0.494 W/kg; SAR (8g) = 0.304 W/kg; SAR (10g) = 0.280 W/kg
Smallest distance from peaks to all points 3 dB below = 10.8 mm
Ratio of SAR at M2 to SAR at M1 = 82.7 %



#67_LTE Band 26 Ant 0_15M_QPSK_1_0_Back_10mm_Ch26865


Communication System: LTE-FDD ; Frequency: 831.5 MHz; Duty Cycle: 1:1
Medium: HSL_850_230515 Medium parameters used: $f= 831.5$ MHz; $\sigma= 0.918$ S/m; $\epsilon_r = 42.8$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.29, 10.29, 10.29); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10181-CAF

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.506 W/kg; SAR (10g) = 0.327 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.09 dB
SAR (1g) = 0.512 W/kg; SAR (8g) = 0.316 W/kg; SAR (10g) = 0.294 W/kg
Smallest distance from peaks to all points 3 dB below = 10.9 mm
Ratio of SAR at M2 to SAR at M1 = 80.1 %



#68_LTE Band 30 Ant 0_10M_QPSK_1_0_Front_10mm_Ch27710


Communication System: LTE-FDD ; Frequency: 2310.000 MHz; Duty Cycle: 1:1
Medium: HSL_2300_230514 Medium parameters used: $f= 2310.000$ MHz; $\sigma= 1.62$ S/m; $\epsilon_r = 39.4$
Ambient Temperature: 23.7°C; Liquid Temperature: 22.7°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.34, 8.34, 8.34); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10175-CAH

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.719 W/kg; SAR (10g) = 0.364 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.11 dB
SAR (1g) = 0.748 W/kg; SAR (8g) = 0.420 W/kg; SAR (10g) = 0.385 W/kg
Smallest distance from peaks to all points 3 dB below = 11.0 mm
Ratio of SAR at M2 to SAR at M1 = 80.3 %



#69_LTE Band 41 Ant 0_20M_QPSK_1_0_Front_10mm_Ch39750


Communication System: LTE-TDD ; Frequency: 2506.000 MHz; Duty Cycle: 1:1.59
Medium: HSL_2600_230514 Medium parameters used: $f= 2506.000$ MHz; $\sigma= 1.85$ S/m; $\epsilon_r = 38.3$
Ambient Temperature: 23.7°C; Liquid Temperature: 22.7°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(7.78, 7.78, 7.78); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-TDD, 10172-CAH

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.485 W/kg; SAR (10g) = 0.247 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.01 dB
SAR (1g) = 0.500 W/kg; SAR (8g) = 0.280 W/kg; SAR (10g) = 0.257 W/kg
Smallest distance from peaks to all points 3 dB below = 11.5 mm
Ratio of SAR at M2 to SAR at M1 = 80.8 %



#70_LTE Band 48 Ant 7_20M_QPSK_1_0_Back_10mm_Ch55830


Communication System: LTE-TDD ; Frequency: 3609.000 MHz; Duty Cycle: 1:1.59
Medium: HSL_3700_230514 Medium parameters used: $f= 3609.000$ MHz; $\sigma= 3.02$ S/m; $\epsilon_r = 37.8$
Ambient Temperature: 23.7°C; Liquid Temperature: 22.7°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(6.91, 6.91, 6.91); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-TDD, 10172-CAH

Area Scan (140.0 mm x 140.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.384 W/kg; SAR (10g) = 0.173 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 28.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = -0.07 dB
SAR (1g) = 0.388 W/kg; SAR (8g) = 0.192 W/kg; SAR (10g) = 0.175 W/kg
Smallest distance from peaks to all points 3 dB below = 10.3 mm
Ratio of SAR at M2 to SAR at M1 = 73.6 %



#71_LTE Band 66 Ant 0_20M_QPSK_1_0_Front_10mm_Ch132322


Communication System: LTE-FDD ; Frequency: 1745.000 MHz; Duty Cycle: 1:1
Medium: HSL_1750_230516 Medium parameters used: $f=$ 1745.000 MHz; $\sigma=$ 1.36 S/m; $\epsilon_r=$ 40.2
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.92, 8.92, 8.92); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.437 W/kg; SAR (10g) = 0.232 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.09 dB
SAR (1g) = 0.466 W/kg; SAR (8g) = 0.279 W/kg; SAR (10g) = 0.258 W/kg
Smallest distance from peaks to all points 3 dB below = 10.8 mm
Ratio of SAR at M2 to SAR at M1 = 83.2 %



#72_LTE Band 71 Ant 0_20M_QPSK_1_0_Back_10mm_Ch133297


Communication System: LTE-FDD ; Frequency: 680.5 MHz; Duty Cycle: 1:1
Medium: HSL_750_230512 Medium parameters used: $f=680.5$ MHz; $\sigma=0.863$ S/m; $\epsilon_r=43.5$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.36, 10.36, 10.36); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.267 W/kg; SAR (10g) = 0.180 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.04 dB
SAR (1g) = 0.245 W/kg; SAR (8g) = 0.157 W/kg; SAR (10g) = 0.148 W/kg
Smallest distance from peaks to all points 3 dB below = 14.9 mm
Ratio of SAR at M2 to SAR at M1 = 80.7 %



#73_FR1 n2 Ant 5_20M_QPSK_1_1_Back_10mm_Ch372000


Communication System: FR1; Frequency: 1860.000 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230502 Medium parameters used: $f=1860.000$ MHz; $\sigma=1.39$ S/m; $\epsilon_r=39.5$
Ambient Temperature: 23.4°C; Liquid Temperature: 22.4°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.92, 7.92, 7.92); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2448
- UID: 5G NR FR1 FDD, 10931-AAC

Area Scan (120.0 mm x 150.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.367 W/kg; SAR (10g) = 0.197 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.16 dB
SAR (1g) = 0.373 W/kg; SAR (8g) = 0.205 W/kg; SAR (10g) = 0.188 W/kg
Smallest distance from peaks to all points 3 dB below = 8.1 mm
Ratio of SAR at M2 to SAR at M1 = 81.0 %



#74_FR1 n5 Ant 0_20M_QPSK_1_1_Back_10mm_Ch167300


Communication System: FR1; Frequency: 836.500 MHz; Duty Cycle: 1:1
Medium: HSL_850_230505 Medium parameters used: $f = 836.500$ MHz; $\sigma = 0.934$ S/m; $\epsilon_r = 43.3$
Ambient Temperature: 23.3°C; Liquid Temperature: 22.3°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(9.84, 9.84, 9.84); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10931-AAC

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.427 W/kg; SAR (10g) = 0.280 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.13 dB
SAR (1g) = 0.445 W/kg; SAR (8g) = 0.274 W/kg; SAR (10g) = 0.255 W/kg
Smallest distance from peaks to all points 3 dB below = 11.9 mm
Ratio of SAR at M2 to SAR at M1 = 82.0 %



#75_FR1 n7 Ant 0_50M_QPSK_1_1_Front_10mm_Ch507000


Communication System: FR1; Frequency: 2535.000 MHz; Duty Cycle: 1:1
Medium: HSL_2600_230507 Medium parameters used: $f= 2535.000$ MHz; $\sigma= 1.90$ S/m; $\epsilon_r = 39.7$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.32, 7.32, 7.32); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10935-AAD

Area Scan (120.0 mm x 100.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.600 W/kg; SAR (10g) = 0.308 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.14 dB
SAR (1g) = 0.605 W/kg; SAR (8g) = 0.334 W/kg; SAR (10g) = 0.307 W/kg
Smallest distance from peaks to all points 3 dB below = 12.0 mm
Ratio of SAR at M2 to SAR at M1 = 78.9 %



#76_FR1 n12 Ant 0_15M_QPSK_1_1_Back_10mm_Ch141500


Communication System: FR1; Frequency: 707.500 MHz; Duty Cycle: 1:1
Medium: HSL_750_230508 Medium parameters used: $f = 707.500$ MHz; $\sigma = 0.888$ S/m; $\epsilon_r = 43.8$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(10.06, 10.06, 10.06); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10930-AAC

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.280 W/kg; SAR (10g) = 0.193 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.18 dB
SAR (1g) = 0.301 W/kg; SAR (8g) = 0.186 W/kg; SAR (10g) = 0.174 W/kg
Smallest distance from peaks to all points 3 dB below = 14.4 mm
Ratio of SAR at M2 to SAR at M1 = 78.7 %



#77_FR1 n25 Ant 0_40M_QPSK_1_1_Front_10mm_Ch376500


Communication System: FR1; Frequency: 1882.500 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230504 Medium parameters used: $f = 1882.500$ MHz; $\sigma = 1.41$ S/m; $\epsilon_r = 39.1$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.92, 7.92, 7.92); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10934-AAC

Area Scan (120.0 mm x 90.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.282 W/kg; SAR (10g) = 0.159 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.13 dB
SAR (1g) = 0.328 W/kg; SAR (8g) = 0.189 W/kg; SAR (10g) = 0.174 W/kg
Smallest distance from peaks to all points 3 dB below = 10.8 mm
Ratio of SAR at M2 to SAR at M1 = 81.2 %



#78_FR1 n30 Ant 0_10M_QPSK_1_1_Back_10mm_Ch462000


Communication System: FR1; Frequency: 2310.000 MHz; Duty Cycle: 1:1
Medium: HSL_2300_230510 Medium parameters used: $f=2310.000$ MHz; $\sigma=1.65$ S/m; $\epsilon_r=40.5$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.66, 7.66, 7.66); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10929-AAD

Area Scan (120.0 mm x 100.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.669 W/kg; SAR (10g) = 0.350 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.00 dB
SAR (1g) = 0.673 W/kg; SAR (8g) = 0.382 W/kg; SAR (10g) = 0.351 W/kg
Smallest distance from peaks to all points 3 dB below = 11.4 mm
Ratio of SAR at M2 to SAR at M1 = 81.9 %



#79_FR1 n41 Ant 0_100M_QPSK_1_1_Front_10mm_Ch518598


Communication System: FR1; Frequency: 2592.990 MHz; Duty Cycle: 1:1
Medium: HSL_2600_230516 Medium parameters used: $f=2592.990$ MHz; $\sigma=1.97$ S/m; $\epsilon_r=39.6$
Ambient Temperature: 23.7°C; Liquid Temperature: 22.7°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.32, 7.32, 7.32); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 TDD, 10866-AAF

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.780 W/kg; SAR (10g) = 0.402 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.02 dB
SAR (1g) = 0.783 W/kg; SAR (8g) = 0.433 W/kg; SAR (10g) = 0.398 W/kg
Smallest distance from peaks to all points 3 dB below = 12.0 mm
Ratio of SAR at M2 to SAR at M1 = 78.8 %



#80_FR1 n66 Ant 2_40M_QPSK_1_1_Back_10mm_Ch349000


Communication System: FR1; Frequency: 1745.000 MHz; Duty Cycle: 1:1
Medium: HSL_1750_230523 Medium parameters used: $f=1745.000$ MHz; $\sigma=1.38$ S/m; $\epsilon_r=40.7$
Ambient Temperature: 23.3°C; Liquid Temperature: 22.3°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(8.25, 8.25, 8.25); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10934-AAC

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.354 W/kg; SAR (10g) = 0.212 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.13 dB
SAR (1g) = 0.398 W/kg; SAR (8g) = 0.225 W/kg; SAR (10g) = 0.208 W/kg
Smallest distance from peaks to all points 3 dB below = 11.9 mm
Ratio of SAR at M2 to SAR at M1 = 79.8 %



#81_FR1 n71 Ant 0_20M_QPSK_1_1_Back_10mm_Ch136100


Communication System: FR1; Frequency: 680.500 MHz; Duty Cycle: 1:1
Medium: HSL_750_230528 Medium parameters used: $f = 680.500$ MHz; $\sigma = 0.880$ S/m; $\epsilon_r = 44.2$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(10.06, 10.06, 10.06); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10931-AAC

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.218 W/kg; SAR (10g) = 0.147 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.15 dB
SAR (1g) = 0.230 W/kg; SAR (8g) = 0.141 W/kg; SAR (10g) = 0.132 W/kg
Smallest distance from peaks to all points 3 dB below = 12.0 mm
Ratio of SAR at M2 to SAR at M1 = 79.3 %



#82_FR1 n77 Ant 7_100M_QPSK_1_1_Back_10mm_Ch656000


Communication System: FR1; Frequency: 3840.000 MHz; Duty Cycle: 1:1
Medium: HSL_3900_230530 Medium parameters used: $f = 3840.000$ MHz; $\sigma = 3.26$ S/m; $\epsilon_r = 37.5$
Ambient Temperature: 23.8°C; Liquid Temperature: 22.8°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3642; ConvF(6.22, 6.22, 6.22); Calibrated: 2023-04-26
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1694; Calibrated: 2022-11-18
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2055; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 TDD, 10866-AAF

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.380 W/kg; SAR (10g) = 0.166 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 28.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = -0.02 dB
SAR (1g) = 0.382 W/kg; SAR (8g) = 0.181 W/kg; SAR (10g) = 0.163 W/kg
Smallest distance from peaks to all points 3 dB below = 10.2 mm
Ratio of SAR at M2 to SAR at M1 = 72.8 %



#83_WCDMA II Ant 0_RMC 12.2Kbps_Bottom Side_0mm_Ch9400


Communication System: UMTS-FDD ; Frequency: 1880.000 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230513 Medium parameters used: $f = 1880.000$ MHz; $\sigma = 1.40$ S/m; $\epsilon_r = 40.0$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.6, 8.6, 8.6); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: WCDMA, 10011-CAC

Area Scan (64.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 4.48 W/kg; SAR (10g) = 2.07 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.01 dB
SAR (1g) = 4.33 W/kg; SAR (8g) = 2.16 W/kg; SAR (10g) = 1.96 W/kg
Smallest distance from peaks to all points 3 dB below = 6.5 mm
Ratio of SAR at M2 to SAR at M1 = 68.6 %



#84_LTE Band 7 Ant 0_20M_QPSK_1_0_Bottom Side_0mm_Ch20850


Communication System: LTE-FDD ; Frequency: 2510.000 MHz; Duty Cycle: 1:1
Medium: HSL_2600_230514 Medium parameters used: $f = 2510.000$ MHz; $\sigma = 1.86$ S/m; $\epsilon_r = 38.7$
Ambient Temperature: 23.7°C; Liquid Temperature: 22.7°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(7.78, 7.78, 7.78); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (64.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 2.93 W/kg; SAR (10g) = 1.32 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = 0.03 dB
SAR (1g) = 2.97 W/kg; SAR (8g) = 1.44 W/kg; SAR (10g) = 1.30 W/kg
Smallest distance from peaks to all points 3 dB below = 4.0 mm
Ratio of SAR at M2 to SAR at M1 = 57.9 %



#85_LTE Band 25 Ant 0_20M_QPSK_1_0_Bottom Side_0mm_Ch26340


Communication System: LTE-FDD ; Frequency: 1880.000 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230513 Medium parameters used: $f=$ 1880.000 MHz; $\sigma=$ 1.40 S/m; $\epsilon_r=$ 40.0
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.6, 8.6, 8.6); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (64.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 4.46 W/kg; SAR (10g) = 2.02 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.03 dB
SAR (1g) = 4.34 W/kg; SAR (8g) = 2.01 W/kg; SAR (10g) = 1.78 W/kg
Smallest distance from peaks to all points 3 dB below = 4.8 mm
Ratio of SAR at M2 to SAR at M1 = 55.0 %



#86_LTE Band 30 Ant 0_10M_QPSK_1_0_Bottom Side_0mm_Ch27710


Communication System: LTE-FDD ; Frequency: 2310.000 MHz; Duty Cycle: 1:1
Medium: HSL_2300_230514 Medium parameters used: $f= 2310.000$ MHz; $\sigma= 1.62$ S/m; $\epsilon_r = 39.4$
Ambient Temperature: 23.7°C; Liquid Temperature: 22.7°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.34, 8.34, 8.34); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10175-CAH

Area Scan (64.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 4.51 W/kg; SAR (10g) = 1.96 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.00 dB
SAR (1g) = 4.54 W/kg; SAR (8g) = 2.16 W/kg; SAR (10g) = 1.94 W/kg
Smallest distance from peaks to all points 3 dB below = 6.0 mm
Ratio of SAR at M2 to SAR at M1 = 68.3 %



#87_LTE Band 66_Ant 0_20M_QPSK_1_0_Bottom Side_0mm_Ch132572


Communication System: LTE-FDD ; Frequency: 1770.000 MHz; Duty Cycle: 1:1
Medium: HSL_1750_230516 Medium parameters used: $f=$ 1770.000 MHz; $\sigma=$ 1.38 S/m; $\epsilon_r =$ 39.9
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.92, 8.92, 8.92); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (64.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 4.37 W/kg; SAR (10g) = 2.02 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.02 dB
SAR (1g) = 4.37 W/kg; SAR (8g) = 2.16 W/kg; SAR (10g) = 1.95 W/kg
Smallest distance from peaks to all points 3 dB below = 7.0 mm
Ratio of SAR at M2 to SAR at M1 = 68.9 %



#88_FR1 n7 Ant 0_50M_QPSK_1_1_Bottom Side_0mm_Ch507000


Communication System: FR1; Frequency: 2535.000 MHz; Duty Cycle: 1:1
Medium: HSL_2600_230507 Medium parameters used: $f = 2535.000$ MHz; $\sigma = 1.90$ S/m; $\epsilon_r = 39.7$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.32, 7.32, 7.32); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10935-AAD

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 2.88 W/kg; SAR (10g) = 1.29 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.09 dB
SAR (1g) = 2.84 W/kg; SAR (8g) = 1.34 W/kg; SAR (10g) = 1.20 W/kg
Smallest distance from peaks to all points 3 dB below = 3.0 mm
Ratio of SAR at M2 to SAR at M1 = 53.6 %



#89_FR1 n25 Ant 0_40M_QPSK_1_1_Bottom Side_0mm_Ch376500


Communication System: FR1; Frequency: 1882.500 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230504 Medium parameters used: $f=1882.500$ MHz; $\sigma=1.41$ S/m; $\epsilon_r=39.1$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.92, 7.92, 7.92); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10934-AAC

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 3.80 W/kg; SAR (10g) = 1.74 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.03 dB
SAR (1g) = 3.87 W/kg; SAR (8g) = 1.78 W/kg; SAR (10g) = 1.57 W/kg
Smallest distance from peaks to all points 3 dB below = 6.0 mm
Ratio of SAR at M2 to SAR at M1 = 70.7 %



#90_FR1 n30 Ant 0_10M_QPSK_1_1_Bottom Side_0mm_Ch462000


Communication System: FR1; Frequency: 2310.000 MHz; Duty Cycle: 1:1
Medium: HSL_2300_230510 Medium parameters used: $f=2310.000$ MHz; $\sigma=1.65$ S/m; $\epsilon_r=40.5$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.66, 7.66, 7.66); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10929-AAD

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 3.53 W/kg; SAR (10g) = 1.54 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = 0.03 dB
SAR (1g) = 3.56 W/kg; SAR (8g) = 1.64 W/kg; SAR (10g) = 1.47 W/kg
Smallest distance from peaks to all points 3 dB below = 4.0 mm
Ratio of SAR at M2 to SAR at M1 = 57.1 %



#91_FR1 n66 Ant 0_40M_QPSK_1_1_Bottom Side_0mm_Ch349000


Communication System: FR1; Frequency: 1745.000 MHz; Duty Cycle: 1:1
Medium: HSL_1750_230524 Medium parameters used: $f=1745.000$ MHz; $\sigma=1.36$ S/m; $\epsilon_r=40.7$
Ambient Temperature: 23.4°C; Liquid Temperature: 22.4°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(8.25, 8.25, 8.25); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10934-AAC

Area Scan (64.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 3.73 W/kg; SAR (10g) = 1.76 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.02 dB
SAR (1g) = 3.71 W/kg; SAR (8g) = 1.82 W/kg; SAR (10g) = 1.65 W/kg
Smallest distance from peaks to all points 3 dB below = 7.0 mm
Ratio of SAR at M2 to SAR at M1 = 70.5 %



#92_NFC_Back_0mm_13.56MHz


Communication System: CW; Frequency: 14.0 MHz; Duty Cycle: 1:1
Medium: HSL_13M_230418 Medium parameters used: $f = 14.0$ MHz; $\sigma = 0.748$ S/m; $\epsilon_r = 53.6$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7306; ConvF(16.39, 16.39, 16.39); Calibrated: 2022-07-28
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1694; Calibrated: 2022-11-18
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2156; Section: Flat
- Measurement Software: 16.2.4.1816
- UID: CW, 0--

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.260 W/kg; SAR (10g) = 0.164 W/kg;

Zoom Scan (30.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 5.9 mm x 5.9 mm x 1.5 mm
Power Drift = -0.03 dB
SAR (1g) = 0.217 W/kg; SAR (8g) = 0.100 W/kg; SAR (10g) = 0.090 W/kg
Smallest distance from peaks to all points 3 dB below = 7.1 mm
Ratio of SAR at M2 to SAR at M1 = 64.6 %



#93_GSM850 Ant 1_GPRS (4 Tx slots)_Right Cheek_0mm_Ch128


Communication System: GPRS-FDD; Frequency: 824.200 MHz; Duty Cycle: 1:2.08
Medium: HSL_835_230515 Medium parameters used: $f = 824.200$ MHz; $\sigma = 0.912$ S/m; $\epsilon_r = 42.9$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.29, 10.29, 10.29); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: GSM, 10028-DAC

Area Scan (120.0 mm x 120.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.580 W/kg; SAR (10g) = 0.382 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.15 dB
SAR (1g) = 0.586 W/kg; SAR (8g) = 0.421 W/kg; SAR (10g) = 0.398 W/kg
Smallest distance from peaks to all points 3 dB below = 7.8 mm
Ratio of SAR at M2 to SAR at M1 = 71.6 %



#94_WCDMA V Ant 1_RMC 12.2Kbps_Right Cheek_0mm_Ch4233


Communication System: UMTS-FDD; Frequency: 846.600 MHz; Duty Cycle: 1:1
Medium: HSL_835_230515 Medium parameters used: $f= 846.600$ MHz; $\sigma= 0.923$ S/m; $\epsilon_r = 42.6$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.29, 10.29, 10.29); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: WCDMA, 10457-AAB

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.511 W/kg; SAR (10g) = 0.336 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.02 dB
SAR (1g) = 0.469 W/kg; SAR (8g) = 0.287 W/kg; SAR (10g) = 0.272 W/kg
Smallest distance from peaks to all points 3 dB below = 7.3 mm
Ratio of SAR at M2 to SAR at M1 = 72.0 %



#95_LTE Band 2 Ant 1_20M_QPSK_1_0_Right Tilted_0mm_Ch18900


Communication System: LTE-FDD ; Frequency: 1880.000 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230513 Medium parameters used: $f= 1880.000$ MHz; $\sigma= 1.40$ S/m; $\epsilon_r = 39.9$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.6, 8.6, 8.6); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.465 W/kg; SAR (10g) = 0.233 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.03 dB
SAR (1g) = 0.542 W/kg; SAR (8g) = 0.274 W/kg; SAR (10g) = 0.245 W/kg
Smallest distance from peaks to all points 3 dB below = 7.1 mm
Ratio of SAR at M2 to SAR at M1 = 81.3 %



#96_LTE Band 12 Ant 1_10M_QPSK_1_0_Right Cheek_0mm_Ch23095


Communication System: LTE-FDD; Frequency: 707.500 MHz; Duty Cycle: 1:1
Medium: HSL_750_230512 Medium parameters used: $f=707.500$ MHz; $\sigma=0.876$ S/m; $\epsilon_r=43.4$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.36, 10.36, 10.36); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10175-CAH

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.271 W/kg; SAR (10g) = 0.189 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.01 dB
SAR (1g) = 0.278 W/kg; SAR (8g) = 0.206 W/kg; SAR (10g) = 0.184 W/kg
Smallest distance from peaks to all points 3 dB below = 8.6 mm
Ratio of SAR at M2 to SAR at M1 = 71.3 %



#97_LTE Band 13 Ant 1_10M_QPSK_1_0_Right Cheek_0mm_Ch23230


Communication System: LTE-FDD; Frequency: 782.000 MHz; Duty Cycle: 1:1
Medium: HSL_750_230512 Medium parameters used: $f=782.000$ MHz; $\sigma=0.903$ S/m; $\epsilon_r=42.9$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.36, 10.36, 10.36); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10175-CAH

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.706 W/kg; SAR (10g) = 0.460 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.03 dB
SAR (1g) = 0.576 W/kg; SAR (8g) = 0.353 W/kg; SAR (10g) = 0.334 W/kg
Smallest distance from peaks to all points 3 dB below = 9.2 mm
Ratio of SAR at M2 to SAR at M1 = 71.6 %



#98_LTE Band 14 Ant 1_10M_QPSK_1_0_Right Cheek_0mm_Ch23330


Communication System: LTE-FDD; Frequency: 793.000 MHz; Duty Cycle: 1:1
Medium: HSL_750_230512 Medium parameters used: $f=793.000$ MHz; $\sigma=0.905$ S/m; $\epsilon_r=43.0$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.36, 10.36, 10.36); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10175-CAH

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.545 W/kg; SAR (10g) = 0.355 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.02 dB
SAR (1g) = 0.534 W/kg; SAR (8g) = 0.326 W/kg; SAR (10g) = 0.308 W/kg
Smallest distance from peaks to all points 3 dB below = 9.2 mm
Ratio of SAR at M2 to SAR at M1 = 71.5 %



#99_LTE Band 26 Ant 1_15M_QPSK_1_0_Right Cheek_0mm_Ch26865


Communication System: LTE-FDD; Frequency: 831.500 MHz; Duty Cycle: 1:1
Medium: HSL_835_230515 Medium parameters used: $f=831.500$ MHz; $\sigma=0.918$ S/m; $\epsilon_r=42.8$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.29, 10.29, 10.29); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10181-CAF

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.388 W/kg; SAR (10g) = 0.254 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.00 dB
SAR (1g) = 0.375 W/kg; SAR (8g) = 0.230 W/kg; SAR (10g) = 0.217 W/kg
Smallest distance from peaks to all points 3 dB below = 8.5 mm
Ratio of SAR at M2 to SAR at M1 = 71.2 %



#100_LTE Band 66 Ant 1_20M_QPSK_1_0_Right Tilted_0mm_Ch132322


Communication System: LTE-FDD; Frequency: 1745.000 MHz; Duty Cycle: 1:1
Medium: HSL_1750_230516 Medium parameters used: $f=1745.000$ MHz; $\sigma=1.36$ S/m; $\epsilon_r=40.2$
Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(8.92, 8.92, 8.92); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.435 W/kg; SAR (10g) = 0.237 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.04 dB
SAR (1g) = 0.610 W/kg; SAR (8g) = 0.308 W/kg; SAR (10g) = 0.278 W/kg
Smallest distance from peaks to all points 3 dB below = 7.3 mm
Ratio of SAR at M2 to SAR at M1 = 81.6 %



#101_LTE Band 71 Ant 1_20M_QPSK_1_0_Right Cheek_0mm_Ch133297


Communication System: LTE-FDD; Frequency: 680.500 MHz; Duty Cycle: 1:1
Medium: HSL_750_230512 Medium parameters used: $f=680.500$ MHz; $\sigma=0.863$ S/m; $\epsilon_r=43.5$
Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(10.36, 10.36, 10.36); Calibrated: 2023-04-25
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn853; Calibrated: 2022-07-20
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1719; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: LTE-FDD, 10169-CAF

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.729 W/kg; SAR (10g) = 0.468 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.03 dB
SAR (1g) = 0.696 W/kg; SAR (8g) = 0.422 W/kg; SAR (10g) = 0.399 W/kg
Smallest distance from peaks to all points 3 dB below = 8.6 mm
Ratio of SAR at M2 to SAR at M1 = 68.4 %



#102_FR1 n2 Ant 1_20M_QPSK_1_1_Right Tilted_0mm_Ch380000


Communication System: FR1; Frequency: 1900.000 MHz; Duty Cycle: 1:1
Medium: HSL_1900_230501 Medium parameters used: $f = 1900.000$ MHz; $\sigma = 1.43$ S/m; $\epsilon_r = 39.3$
Ambient Temperature: 23.2°C; Liquid Temperature: 22.2°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.92, 7.92, 7.92); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10931-AAC

Area Scan (120.0 mm x 180.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.739 W/kg; SAR (10g) = 0.311 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.16 dB
SAR (1g) = 0.733 W/kg; SAR (8g) = 0.336 W/kg; SAR (10g) = 0.300 W/kg
Smallest distance from peaks to all points 3 dB below = 5.0 mm
Ratio of SAR at M2 to SAR at M1 = 73.3 %



#103_FR1 n5 Ant 1_20M_QPSK_1_1_Right Tilted_0mm_Ch167300

Communication System: FR1; Frequency: 836.500 MHz; Duty Cycle: 1:1

Medium: HSL_850_230505 Medium parameters used: $f = 836.500$ MHz; $\sigma = 0.934$ S/m; $\epsilon_r = 43.3$

Ambient Temperature: 23.3°C; Liquid Temperature: 22.3°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(9.84, 9.84, 9.84); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10931-AAC

Area Scan (120.0 mm x 180.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.346 W/kg; SAR (10g) = 0.204 W/kg;


Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm

Power Drift = -0.02 dB

SAR (1g) = 0.351 W/kg; SAR (8g) = 0.191 W/kg; SAR (10g) = 0.176 W/kg

Smallest distance from peaks to all points 3 dB below = 6.1 mm

Ratio of SAR at M2 to SAR at M1 = 65.4 %



#104_FR1 n12 Ant 1_15M_QPSK_1_1_Right Tilted_0mm_Ch141500

Communication System: FR1; Frequency: 707.500 MHz; Duty Cycle: 1:1

Medium: HSL_750_230508 Medium parameters used: $f = 707.500$ MHz; $\sigma = 0.888$ S/m; $\epsilon_r = 43.8$

Ambient Temperature: 23.6°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(10.06, 10.06, 10.06); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 FDD, 10930-AAC

Area Scan (120.0 mm x 180.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.276 W/kg; SAR (10g) = 0.160 W/kg;


Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm

Power Drift = -0.15 dB

SAR (1g) = 0.267 W/kg; SAR (8g) = 0.145 W/kg; SAR (10g) = 0.134 W/kg

Smallest distance from peaks to all points 3 dB below = 7.3 mm

Ratio of SAR at M2 to SAR at M1 = 62.7 %



#105_FR1 n41 Ant 1_100M_QPSK_1_1_Right Tilted_0mm_Ch518598

Communication System: FR1; Frequency: 2592.990 MHz; Duty Cycle: 1:1

Medium: HSL_2600_230517 Medium parameters used: $f = 2592.990$ MHz; $\sigma = 1.96$ S/m; $\epsilon_r = 38.5$

Ambient Temperature: 23.1°C; Liquid Temperature: 22.1°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(7.32, 7.32, 7.32); Calibrated: 2023-02-21
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn854; Calibrated: 2022-08-24
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Serial: 1884; Section: RightHead
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 TDD, 10866-AAF

Area Scan (120.0 mm x 180.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.621 W/kg; SAR (10g) = 0.255 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.04 dB
SAR (1g) = 0.621 W/kg; SAR (8g) = 0.279 W/kg; SAR (10g) = 0.248 W/kg
Smallest distance from peaks to all points 3 dB below = 6.8 mm
Ratio of SAR at M2 to SAR at M1 = 72.9 %

