



FCC RADIO TEST REPORT

FCC ID : A4RGE2AE
Equipment : Phone
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, California, 94043 USA
Standard : FCC 47 CFR Part 2, and 90(S)

The product was received on Mar. 10, 2022 and testing was performed from Mar. 21, 2022 to May 24, 2022. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test	6
1.3 Modification of EUT	6
1.4 Testing Site.....	7
1.5 Applied Standards	8
2 Test Configuration of Equipment Under Test	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration and system	10
2.4 Measurement Results Explanation Example	10
2.5 Frequency List of Low/Middle/High Channels.....	11
3 Conducted Test Items.....	12
3.1 Measuring Instruments.....	12
3.2 Conducted Output Power Measurement and ERP Measurement	13
3.3 Peak-to-Average Ratio	14
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	15
3.5 Emissions Mask Measurement	16
3.6 Emissions Mask – Out Of Band Emissions Measurement.....	17
3.7 Frequency Stability Measurement.....	18
3.8 Field Strength of Spurious Radiation Measurement	19
4 List of Measuring Equipment.....	22
5 Uncertainty of Evaluation.....	24
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of Radiated Test	
Appendix C. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FG1O2919-05H	01	Initial issue of report	May 31, 2022
FG1O2919-05H	02	1. Revise Table of Contents and appendix B 2. Add remark description in test mode 3. Revise Frequency Stability 4. Remove Model Name	Jun. 06, 2022



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046 §90.635	Conducted Output Power and Effective Radiated Power	Pass	-
3.3	-	Peak-to-Average Ratio	Reporting only	-
3.4	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	-
3.5	§2.1051 §90.691	Emission masks – In-band emissions	Pass	-
3.6	§2.1051 §90.691	Emission masks – Out of band emissions	Pass	-
3.7	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	Pass	-
3.8	§2.1053 §90.691	Field Strength of Spurious Radiation	Pass	Under limit 28.85 dB at 2440.000 MHz for Primary Antenna Under limit 46.41 dB at 2456.000 MHz for ASDIV Antenna

Declaration of Conformity:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
- The measurement uncertainty please refer to this report "Uncertainty of Evaluation".

Comments and Explanations:

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: William Chen
Report Producer: Vivian Hsu



1 General Description

1.1 Feature of Equipment Under Test

Product Feature	
Equipment	Phone
FCC ID	A4RGE2AE
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/5G NR/ NFC/GNSS/WPC/WPT/UWB WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE

Remark: The above EUT's information was declared by manufacturer.

EUT Information List	
S/N	Performed Test Item
23071FDH300002	Conducted Measurement ERP
22271FDH30003S	Radiated Spurious Emission

1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx Frequency	814.7 ~ 823.3 MHz
Rx Frequency	859.7 ~ 868.3 MHz
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz
Maximum Output Power to Antenna	<Primary Antenna>: 24.82 dBm <ASDIV Antenna>: 24.82 dBm
Antenna Type	<Primary Antenna>: PIFA Antenna <ASDIV Antenna>: PIFA Antenna
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

<Primary Antenna>

Radio Tech	Band Number	Antenna name	Gain
LTE	B26	Ant. 0	-2.3

<ASDIV Antenna>

Radio Tech	Band Number	Antenna name	Gain
LTE	B26	Ant. 1	-4.6

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

1.3 Modification of EUT

No modifications are made to the EUT during all test items.



1.4 Testing Site

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH03-HY
Test Engineer	George Chen
Temperature (°C)	23.4~25.6
Relative Humidity (%)	52.0~59.0

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH15-HY (TAF Code: 3786)
Test Engineer	Leo Lee and Bigshow Wang
Temperature (°C)	18~25
Relative Humidity (%)	45~60
Remark	The Radiated Spurious Emission test item subcontracted to Sporton International Inc. Wensan Laboratory

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW3786



1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 90
- ♦ ANSI / TIA-603-E
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ Interim Guidance for Equipment Authorization of Devices with Channel Bandwidths Combined Across Two Contiguous Service Rule Allocations OET/Lab/EACB, June 6, 2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Test Mode


During all testing, EUT is in link mode with base station emulator at maximum power level.

For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.26 exploratory test procedures and find Z Plane with Adapter for Primary Antenna; Y Plane with Adapter for ASDIV Antenna as worst plane.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	26				v		-	v	v	v	v			v		v	
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v	v	v			v	v	v	
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v	v	v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v					v		v	v	v
Frequency Stability	26	v			v	v	-	v						v	v	v	
E.R.P.	26	v	v	v	v	v	-	v	v	v	v	Max. Power					
Radiated Spurious Emission	26	Worst Case												v	v	v	
Remark	<ol style="list-style-type: none"> The mark “v” means that this configuration is chosen for testing The mark “-” means that this bandwidth is not supported. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies. All the radiated test cases were performed with Adapter 1 and USB Cable 2. During the preliminary test, both charging modes (Adapter mode and WPT Charging mode) were verified. It is determined that the adaptor mode is the worst case for official test. One representative bandwidth is selected to perform PAR and frequency stability. 																

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
15	Channel	26765	-	-
	Frequency	821.5	-	-
10	Channel	-	26740	-
	Frequency	-	819	-
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	-	cross-rule channels	-
15	Channel	-	26790	-
	Frequency	-	824	-
10	Channel	-	26790	-
	Frequency	-	824	-
5	Channel	-	26790	-
	Frequency	-	824	-
3	Channel	-	26790	-
	Frequency	-	824	-
1.4	Channel	-	26790	-
	Frequency	-	824	-


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, Emissions Mask – Out Of Band Emissions, and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power Measurement and ERP Measurement

3.2.1 Description of the Conducted Output Power Measurement and ERP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The conducted output power of mobile transmitters must not exceed 100 Watts for LTE Band 26.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Reporting only

3.3.2 Test Procedures

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.



3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.4.2 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.



3.5 Emissions Mask Measurement

3.5.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a)

(a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \text{Log}_{10}(f/6.1)$ decibels or $50 + 10 \text{Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10\text{Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.5.2 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. Set RBW and VBW 3 times of RBW to make the measurement with the spectrum analyzer's, and according to KDB 971168 D02 Misc Rev Approve License Devices v02r01 standards, set RBW = 300 Hz to make offsets less than 37.5 kHz from a channel edge , RBW = 100 kHz to make offsets greater than 37.5 kHz, that is allowed.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.



3.6 Emissions Mask – Out Of Band Emissions Measurement

3.6.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least $43 + 10 \log (P)$ dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. For testing below 1GHz, make the measurement with the spectrum analyzer's RBW = 100 kHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. For testing above 1GHz, make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at 20±5° C and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.



3.8 Field Strength of Spurious Radiation Measurement

3.8.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log_{10}(P[\text{Watts}])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. For testing below 1GHz, make the measurement with the spectrum analyzer's RBW = 100 kHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. For testing above 1GHz, make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
12. $\text{ERP (dBm)} = \text{EIRP} - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10 \log(P)$ dB below the transmitter power P(Watts)

3.8.3 Test Setup


For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.8.4 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 07, 2021	Mar. 29, 2022~ May 24, 2022	Sep. 06, 2022	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	37059 & 01	30MHz~1GHz	Oct. 09, 2021	Mar. 29, 2022~ May 24, 2022	Oct. 08, 2022	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL6111D&00 800N1D01N- 06	35414 & AT- N0602	30MHz to 1GHz	Oct. 09, 2021	Mar. 29, 2022~ May 24, 2022	Oct. 08, 2022	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 30, 2021	Mar. 29, 2022~ May 24, 2022	Dec. 29, 2022	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-01620	1-18GHz	Oct. 25, 2021	Mar. 29, 2022~ May 24, 2022	Oct. 24, 2022	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1326	1GHz~18GHz	Oct. 25, 2021	Mar. 29, 2022~ May 24, 2022	Oct. 24, 2022	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JPA0118-55- 303	1710001800 055006	1GHz~18GHz	May 06, 2021	Mar. 29, 2022~ May 04, 2022	May 05, 2022	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JPA0118-55- 303	1710001800 055006	1GHz~18GHz	May 05, 2022	May 05, 2022~ May 24, 2022	May 04, 2023	Radiation (03CH15-HY)
Amplifier	E- INSTRUMENT TECH LTD	ERA-10M- 7000-MR	EC1900247	10MHz-7GHz	Dec. 03, 2021	Mar. 29, 2022~ May 24, 2022	Dec. 02, 2022	Radiation (03CH15-HY)
Preamplifier	EM Electronics	EM01G18G	060803	1GHz-18GHz	Dec. 16, 2021	Mar. 29, 2022~ May 24, 2022	Dec. 15, 2022	Radiation (03CH15-HY)
Spectrum Analyzer	Keysight	N9038A	MY54130085	20MHz~8.4GHz	Oct. 21, 2021	Mar. 29, 2022~ May 24, 2022	Oct. 20, 2022	Radiation (03CH15-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz~44GHz	Mar. 07, 2022	Mar. 29, 2022~ May 24, 2022	Mar. 06, 2023	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Mar. 29, 2022~ May 24, 2022	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Mar. 29, 2022~ May 24, 2022	N/A	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8- 24(k5)	RK-000451	N/A	N/A	Mar. 29, 2022~ May 24, 2022	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104, 102E	MY36980/4, MY9838/4PE ,508405/2E	30MHz~18G	Nov. 15, 2021	Mar. 29, 2022~ May 24, 2022	Nov. 14, 2022	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804 012/2	30MHz-40GHz	Jan. 04, 2022	Mar. 29, 2022~ May 24, 2022	Jan. 03, 2023	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz~30MHz	Mar. 10, 2022	Mar. 29, 2022~ May 24, 2022	Mar. 09, 2023	Radiation (03CH15-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	0.1Hz~40GHz	Dec. 08, 2021	Mar. 29, 2022~ May 24, 2022	Dec. 07, 2022	Radiation (03CH15-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Radio Communication Analyzer	Anritsu	MT8821C	6201664755	2/3/4G/LTE FDD/TDD with44)/LTE-3CC DLCA/2CC ULCA, CatM1/NB1/NB2	Jul. 21, 2021	Mar. 21, 2022~ May 23, 2022	Jul. 20, 2022	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101908	10Hz~40GHz	Oct. 01, 2021	Mar. 21, 2022~ May 23, 2022	Sep. 30, 2022	Conducted (TH03-HY)
Thermal Chamber	ESPEC	SH-641	92013720	-40°C ~90°C	Sep. 09, 2021	Mar. 21, 2022~ May 23, 2022	Sep. 08, 2022	Conducted (TH03-HY)
DC Power Supply	GW Instek	GPP-2323	GES906037	0V~64V ; 0A~6A	Jan. 06, 2022	Mar. 21, 2022~ May 23, 2022	Jan. 05, 2023	Conducted (TH03-HY)
Coupler	Warison	20dB 25W SMA Directional Coupler	#B	1-18GHz	Jan. 07, 2022	Mar. 21, 2022~ May 23, 2022	Jan. 06, 2023	Conducted (TH03-HY)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.92 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.72 dB
---	---------



Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power & ERP)

<Primary Antenna>

LTE Band 26 Maximum Average Power [dBm] (GT - LC = -2.3 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
15	1	0	QPSK	24.82	-	-	20.37	0.1089
15	1	37		24.45	-	-		
15	1	74		24.46	-	-		
15	36	0		23.63	-	-		
15	36	20		23.61	-	-		
15	36	39		23.59	-	-		
15	75	0		23.61	-	-		
15	1	0	16-QAM	23.91	-	-	19.46	0.0883
15	1	37		23.89	-	-		
15	1	74		23.86	-	-		
15	36	0		22.66	-	-		
15	36	20		22.63	-	-		
15	36	39		22.59	-	-		
15	75	0		22.60	-	-		
15	1	0	64-QAM	22.77	-	-	18.36	0.0685
15	1	37		22.81	-	-		
15	1	74		22.69	-	-		
15	36	0		21.65	-	-		
15	36	20		21.63	-	-		
15	36	39		21.57	-	-		
15	75	0		21.58	-	-		
15	1	0	256-QAM	19.66	-	-	15.23	0.0333
15	1	37		19.68	-	-		
15	1	74		19.58	-	-		
15	36	0		18.51	-	-		
15	36	20		18.51	-	-		
15	36	39		18.52	-	-		
15	75	0		18.58	-	-		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = -2.3 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
10	1	0	QPSK	-	24.62	-	20.17	0.1040
10	1	25		-	24.49	-		
10	1	49		-	24.55	-		
10	25	0		-	23.72	-		
10	25	12		-	23.68	-		
10	25	25		-	23.66	-		
10	50	0		-	23.69	-		
10	1	0	16-QAM	-	23.86	-	19.41	0.0873
10	1	25		-	23.80	-		
10	1	49		-	23.84	-		
10	25	0		-	22.72	-		
10	25	12		-	22.73	-		
10	25	25		-	22.73	-		
10	50	0		-	22.68	-		
10	1	0	64-QAM	-	22.81	-	18.42	0.0695
10	1	25		-	22.78	-		
10	1	49		-	22.87	-		
10	25	0		-	21.69	-		
10	25	12		-	21.67	-		
10	25	25		-	21.66	-		
10	50	0		-	21.68	-		
10	1	0	256-QAM	-	19.92	-	15.47	0.0352
10	1	25		-	19.69	-		
10	1	49		-	19.77	-		
10	25	0		-	19.02	-		
10	25	12		-	18.65	-		
10	25	25		-	18.65	-		
10	50	0		-	18.77	-		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = -2.3 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
5	1	0	QPSK	24.65	24.69	24.59	20.24	0.1057
5	1	12		24.62	24.69	24.62		
5	1	24		24.64	24.60	24.61		
5	12	0		23.65	23.67	23.68		
5	12	7		23.67	23.72	23.71		
5	12	13		23.64	23.67	23.64		
5	25	0		23.61	23.57	23.55		
5	1	0	16-QAM	23.81	23.81	23.88	19.57	0.0906
5	1	12		23.85	23.85	23.85		
5	1	24		23.95	24.02	24.00		
5	12	0		22.68	22.66	22.64		
5	12	7		22.76	22.77	22.79		
5	12	13		22.75	22.76	22.66		
5	25	0		22.68	22.72	22.63		
5	1	0	64-QAM	22.76	22.80	22.69	18.45	0.0700
5	1	12		22.72	22.77	22.62		
5	1	24		22.85	22.90	22.79		
5	12	0		21.70	21.68	21.70		
5	12	7		21.78	21.82	21.76		
5	12	13		21.80	21.79	21.76		
5	25	0		21.68	21.62	21.78		
5	1	0	256-QAM	19.71	19.72	19.68	15.27	0.0337
5	1	12		19.55	19.48	19.65		
5	1	24		19.67	19.57	19.65		
5	12	0		18.76	18.84	18.78		
5	12	7		18.61	18.68	18.71		
5	12	13		18.62	18.59	18.65		
5	25	0		18.68	18.77	18.63		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = -2.3 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
3	1	0	QPSK	24.69	24.62	24.64	20.26	0.1062
3	1	8		24.64	24.70	24.56		
3	1	14		24.71	24.67	24.66		
3	8	0		23.62	23.56	23.60		
3	8	4		23.60	23.51	23.70		
3	8	7		23.63	23.68	23.63		
3	15	0		23.58	23.66	23.68		
3	1	0	16-QAM	23.77	23.72	23.69	19.44	0.0879
3	1	8		23.71	23.64	23.66		
3	1	14		23.89	23.86	23.89		
3	8	0		22.63	22.59	22.65		
3	8	4		22.67	22.74	22.68		
3	8	7		22.72	22.71	22.74		
3	15	0		22.62	22.63	22.71		
3	1	0	64-QAM	22.81	22.83	22.83	18.51	0.0710
3	1	8		22.80	22.75	22.90		
3	1	14		22.88	22.96	22.87		
3	8	0		21.65	21.71	21.55		
3	8	4		21.68	21.75	21.77		
3	8	7		21.67	21.71	21.63		
3	15	0		21.62	21.58	21.56		
3	1	0	256-QAM	19.62	19.72	19.68	15.41	0.0348
3	1	8		19.64	19.66	19.56		
3	1	14		19.79	19.84	19.86		
3	8	0		18.81	18.84	18.75		
3	8	4		18.73	18.66	18.65		
3	8	7		18.76	18.66	18.72		
3	15	0		18.75	18.85	18.66		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = -2.3 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
1.4	1	0	QPSK	23.63	23.64	23.63	19.33	0.0857
1.4	1	3		23.61	23.54	23.52		
1.4	1	5		23.68	23.66	23.78		
1.4	3	0		23.55	23.64	23.53		
1.4	3	1		23.67	23.60	23.62		
1.4	3	3		23.65	23.61	23.64		
1.4	6	0		22.63	22.55	22.73		
1.4	1	0	16-QAM	22.78	22.87	22.68	18.49	0.0706
1.4	1	3		22.80	22.90	22.87		
1.4	1	5		22.94	22.94	22.89		
1.4	3	0		22.60	22.51	22.50		
1.4	3	1		22.80	22.75	22.75		
1.4	3	3		22.74	22.65	22.77		
1.4	6	0		21.67	21.67	21.68		
1.4	1	0	64-QAM	21.72	21.80	21.64	17.46	0.0557
1.4	1	3		21.75	21.67	21.65		
1.4	1	5		21.79	21.84	21.71		
1.4	3	0		21.72	21.68	21.65		
1.4	3	1		21.88	21.83	21.91		
1.4	3	3		21.78	21.68	21.83		
1.4	6	0		20.58	20.67	20.56		
1.4	1	0	256-QAM	18.58	18.49	18.66	14.46	0.0279
1.4	1	3		18.62	18.63	18.66		
1.4	1	5		18.72	18.79	18.80		
1.4	3	0		18.72	18.66	18.70		
1.4	3	1		18.77	18.86	18.79		
1.4	3	3		18.85	18.91	18.87		
1.4	6	0		17.74	17.72	17.73		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = -2.3 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
15	1	0	QPSK	-	24.77	-	20.32	0.1076
15	1	37		-	24.55	-		
15	1	74		-	24.45	-		
15	36	0		-	23.59	-		
15	36	20		-	23.65	-		
15	36	39		-	23.55	-		
15	75	0		-	23.58	-		
15	1	0	16-QAM	-	23.85	-	19.47	0.0885
15	1	37		-	23.92	-		
15	1	74		-	23.88	-		
15	36	0		-	22.66	-		
15	36	20		-	22.60	-		
15	36	39		-	22.63	-		
15	75	0		-	22.58	-		
15	1	0	64-QAM	-	22.68	-	18.37	0.0687
15	1	37		-	22.82	-		
15	1	74		-	22.59	-		
15	36	0		-	21.71	-		
15	36	20		-	21.70	-		
15	36	39		-	21.67	-		
15	75	0		-	21.53	-		
15	1	0	256-QAM	-	19.58	-	15.29	0.0338
15	1	37		-	19.74	-		
15	1	74		-	19.58	-		
15	36	0		-	18.47	-		
15	36	20		-	18.54	-		
15	36	39		-	18.53	-		
15	75	0		-	18.61	-		
Limit	Reporting only			Result			N/A	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = -2.3 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
10	1	0	QPSK	-	24.72	-	20.27	0.1064
10	1	25		-	24.45	-		
10	1	49		-	24.59	-		
10	25	0		-	23.71	-		
10	25	12		-	23.66	-		
10	25	25		-	23.72	-		
10	50	0		-	23.72	-		
10	1	0	16-QAM	-	23.75	-	19.58	0.0908
10	1	25		-	24.03	-		
10	1	49		-	23.90	-		
10	25	0		-	22.76	-		
10	25	12		-	22.82	-		
10	25	25		-	22.67	-		
10	50	0		-	22.68	-		
10	1	0	64-QAM	-	22.90	-	18.45	0.0700
10	1	25		-	22.85	-		
10	1	49		-	22.78	-		
10	25	0		-	21.71	-		
10	25	12		-	21.66	-		
10	25	25		-	21.66	-		
10	50	0		-	21.75	-		
10	1	0	256-QAM	-	19.79	-	15.34	0.0342
10	1	25		-	19.37	-		
10	1	49		-	19.62	-		
10	25	0		-	18.66	-		
10	25	12		-	18.66	-		
10	25	25		-	18.52	-		
10	50	0		-	18.75	-		
Limit	Reporting only			Result			N/A	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = -2.3 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
5	1	0	QPSK	-	24.55	-	20.27	0.1064
5	1	12		-	24.72	-		
5	1	24		-	24.72	-		
5	12	0		-	23.70	-		
5	12	7		-	23.58	-		
5	12	13		-	23.72	-		
5	25	0		-	23.69	-		
5	1	0	16-QAM	-	23.75	-	19.57	0.0906
5	1	12		-	23.77	-		
5	1	24		-	24.02	-		
5	12	0		-	22.64	-		
5	12	7		-	22.73	-		
5	12	13		-	22.70	-		
5	25	0		-	22.60	-		
5	1	0	64-QAM	-	22.73	-	18.37	0.0687
5	1	12		-	22.82	-		
5	1	24		-	22.78	-		
5	12	0		-	21.64	-		
5	12	7		-	21.78	-		
5	12	13		-	21.90	-		
5	25	0		-	21.74	-		
5	1	0	256-QAM	-	19.73	-	15.28	0.0337
5	1	12		-	19.47	-		
5	1	24		-	19.73	-		
5	12	0		-	18.80	-		
5	12	7		-	18.58	-		
5	12	13		-	18.68	-		
5	25	0		-	18.58	-		
Limit	Reporting only			Result			N/A	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = -2.3 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
3	1	0	QPSK	-	24.66	-	20.21	0.1050
3	1	8		-	24.62	-		
3	1	14		-	24.66	-		
3	8	0		-	23.71	-		
3	8	4		-	23.62	-		
3	8	7		-	23.62	-		
3	15	0		-	23.54	-		
3	1	0	16-QAM	-	23.75	-	19.45	0.0881
3	1	8		-	23.72	-		
3	1	14		-	23.90	-		
3	8	0		-	22.72	-		
3	8	4		-	22.70	-		
3	8	7		-	22.64	-		
3	15	0		-	22.53	-		
3	1	0	64-QAM	-	22.75	-	18.50	0.0708
3	1	8		-	22.82	-		
3	1	14		-	22.95	-		
3	8	0		-	21.69	-		
3	8	4		-	21.75	-		
3	8	7		-	21.65	-		
3	15	0		-	21.59	-		
3	1	0	256-QAM	-	19.52	-	15.24	0.0334
3	1	8		-	19.67	-		
3	1	14		-	19.69	-		
3	8	0		-	18.88	-		
3	8	4		-	18.70	-		
3	8	7		-	18.84	-		
3	15	0		-	18.71	-		
Limit	Reporting only			Result			N/A	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = -2.3 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
1.4	1	0	QPSK	-	23.72	-	19.33	0.0857
1.4	1	3		-	23.61	-		
1.4	1	5		-	23.78	-		
1.4	3	0		-	23.63	-		
1.4	3	1		-	23.76	-		
1.4	3	3		-	23.57	-		
1.4	6	0		-	22.73	-		
1.4	1	0	16-QAM	-	22.84	-	18.40	0.0692
1.4	1	3		-	22.84	-		
1.4	1	5		-	22.85	-		
1.4	3	0		-	22.58	-		
1.4	3	1		-	22.73	-		
1.4	3	3		-	22.78	-		
1.4	6	0		-	21.75	-		
1.4	1	0	64-QAM	-	21.81	-	17.44	0.0555
1.4	1	3		-	21.83	-		
1.4	1	5		-	21.89	-		
1.4	3	0		-	21.82	-		
1.4	3	1		-	21.87	-		
1.4	3	3		-	21.73	-		
1.4	6	0		-	20.65	-		
1.4	1	0	256-QAM	-	18.48	-	14.43	0.0277
1.4	1	3		-	18.68	-		
1.4	1	5		-	18.82	-		
1.4	3	0		-	18.73	-		
1.4	3	1		-	18.71	-		
1.4	3	3		-	18.88	-		
1.4	6	0		-	17.83	-		
Limit	Reporting only			Result			N/A	



<ASDIV Antenna>

LTE Band 26 Maximum Average Power [dBm] (GT - LC = -4.6 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
15	1	0	QPSK	24.82	-	-	18.07	0.0641
15	1	37		24.45	-	-		
15	1	74		24.46	-	-		
15	36	0		23.63	-	-		
15	36	20		23.61	-	-		
15	36	39		23.59	-	-		
15	75	0		23.61	-	-		
15	1	0	16-QAM	23.91	-	-	17.16	0.0520
15	1	37		23.89	-	-		
15	1	74		23.86	-	-		
15	36	0		22.66	-	-		
15	36	20		22.63	-	-		
15	36	39		22.59	-	-		
15	75	0		22.60	-	-		
15	1	0	64-QAM	22.77	-	-	16.06	0.0404
15	1	37		22.81	-	-		
15	1	74		22.69	-	-		
15	36	0		21.65	-	-		
15	36	20		21.63	-	-		
15	36	39		21.57	-	-		
15	75	0		21.58	-	-		
15	1	0	256-QAM	19.66	-	-	12.93	0.0196
15	1	37		19.68	-	-		
15	1	74		19.58	-	-		
15	36	0		18.51	-	-		
15	36	20		18.51	-	-		
15	36	39		18.52	-	-		
15	75	0		18.58	-	-		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = -4.6 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
10	1	0	QPSK	-	24.62	-	17.87	0.0612
10	1	25		-	24.49	-		
10	1	49		-	24.55	-		
10	25	0		-	23.72	-		
10	25	12		-	23.68	-		
10	25	25		-	23.66	-		
10	50	0		-	23.69	-		
10	1	0	16-QAM	-	23.86	-	17.11	0.0514
10	1	25		-	23.80	-		
10	1	49		-	23.84	-		
10	25	0		-	22.72	-		
10	25	12		-	22.73	-		
10	25	25		-	22.73	-		
10	50	0		-	22.68	-		
10	1	0	64-QAM	-	22.81	-	16.12	0.0409
10	1	25		-	22.78	-		
10	1	49		-	22.87	-		
10	25	0		-	21.69	-		
10	25	12		-	21.67	-		
10	25	25		-	21.66	-		
10	50	0		-	21.68	-		
10	1	0	256-QAM	-	19.92	-	13.17	0.0207
10	1	25		-	19.69	-		
10	1	49		-	19.77	-		
10	25	0		-	19.02	-		
10	25	12		-	18.65	-		
10	25	25		-	18.65	-		
10	50	0		-	18.77	-		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = -4.6 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
5	1	0	QPSK	24.65	24.70	24.66	17.95	0.0624
5	1	12		24.62	24.68	24.68		
5	1	24		24.64	24.57	24.61		
5	12	0		23.65	23.61	23.65		
5	12	7		23.67	23.74	23.75		
5	12	13		23.64	23.63	23.57		
5	25	0		23.61	23.60	23.57		
5	1	0	16-QAM	23.81	23.78	23.91	17.29	0.0536
5	1	12		23.85	23.84	23.84		
5	1	24		23.95	24.01	24.04		
5	12	0		22.68	22.61	22.62		
5	12	7		22.76	22.67	22.69		
5	12	13		22.75	22.79	22.69		
5	25	0		22.68	22.69	22.61		
5	1	0	64-QAM	22.76	22.80	22.68	16.10	0.0407
5	1	12		22.72	22.66	22.68		
5	1	24		22.85	22.79	22.80		
5	12	0		21.70	21.77	21.73		
5	12	7		21.78	21.78	21.74		
5	12	13		21.80	21.72	21.81		
5	25	0		21.68	21.73	21.74		
5	1	0	256-QAM	19.71	19.66	19.72	12.97	0.0198
5	1	12		19.55	19.49	19.52		
5	1	24		19.67	19.61	19.57		
5	12	0		18.76	18.80	18.75		
5	12	7		18.61	18.63	18.60		
5	12	13		18.62	18.66	18.61		
5	25	0		18.68	18.66	18.75		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = -4.6 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
3	1	0	QPSK	24.69	24.68	24.67	17.96	0.0625
3	1	8		24.64	24.61	24.69		
3	1	14		24.71	24.61	24.71		
3	8	0		23.62	23.63	23.66		
3	8	4		23.60	23.59	23.68		
3	8	7		23.63	23.62	23.66		
3	15	0		23.58	23.53	23.50		
3	1	0	16-QAM	23.77	23.71	23.67	17.17	0.0521
3	1	8		23.71	23.61	23.72		
3	1	14		23.89	23.92	23.91		
3	8	0		22.63	22.57	22.66		
3	8	4		22.67	22.57	22.74		
3	8	7		22.72	22.82	22.69		
3	15	0		22.62	22.72	22.52		
3	1	0	64-QAM	22.81	22.91	22.73	16.22	0.0419
3	1	8		22.80	22.84	22.80		
3	1	14		22.88	22.97	22.89		
3	8	0		21.65	21.70	21.70		
3	8	4		21.68	21.75	21.63		
3	8	7		21.67	21.59	21.62		
3	15	0		21.62	21.60	21.70		
3	1	0	256-QAM	19.62	19.64	19.67	13.12	0.0205
3	1	8		19.64	19.71	19.57		
3	1	14		19.79	19.87	19.82		
3	8	0		18.81	18.81	18.82		
3	8	4		18.73	18.63	18.72		
3	8	7		18.76	18.81	18.82		
3	15	0		18.75	18.74	18.65		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Maximum Average Power [dBm] (GT - LC = -4.6 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
1.4	1	0	QPSK	23.63	23.69	23.53	17.02	0.0504
1.4	1	3		23.61	23.71	23.63		
1.4	1	5		23.68	23.67	23.73		
1.4	3	0		23.55	23.46	23.46		
1.4	3	1		23.67	23.77	23.65		
1.4	3	3		23.65	23.65	23.55		
1.4	6	0		22.63	22.60	22.71		
1.4	1	0	16-QAM	22.78	22.74	22.68	16.20	0.0417
1.4	1	3		22.80	22.86	22.71		
1.4	1	5		22.94	22.95	22.85		
1.4	3	0		22.60	22.70	22.59		
1.4	3	1		22.80	22.85	22.82		
1.4	3	3		22.74	22.67	22.70		
1.4	6	0		21.67	21.60	21.58		
1.4	1	0	64-QAM	21.72	21.71	21.64	15.21	0.0332
1.4	1	3		21.75	21.74	21.74		
1.4	1	5		21.79	21.79	21.80		
1.4	3	0		21.72	21.75	21.70		
1.4	3	1		21.88	21.89	21.96		
1.4	3	3		21.78	21.80	21.77		
1.4	6	0		20.58	20.56	20.55		
1.4	1	0	256-QAM	18.58	18.56	18.51	12.13	0.0163
1.4	1	3		18.62	18.54	18.69		
1.4	1	5		18.72	18.64	18.75		
1.4	3	0		18.72	18.63	18.81		
1.4	3	1		18.77	18.79	18.83		
1.4	3	3		18.85	18.85	18.88		
1.4	6	0		17.74	17.68	17.72		
Limit	Power < 100W			Result			Pass	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = -4.6 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
15	1	0	QPSK	-	24.80	-	18.05	0.0638
15	1	37		-	24.46	-		
15	1	74		-	24.42	-		
15	36	0		-	23.59	-		
15	36	20		-	23.66	-		
15	36	39		-	23.58	-		
15	75	0		-	23.56	-		
15	1	0	16-QAM	-	23.84	-	17.18	0.0522
15	1	37		-	23.93	-		
15	1	74		-	23.87	-		
15	36	0		-	22.74	-		
15	36	20		-	22.60	-		
15	36	39		-	22.54	-		
15	75	0		-	22.59	-		
15	1	0	64-QAM	-	22.85	-	16.15	0.0412
15	1	37		-	22.90	-		
15	1	74		-	22.59	-		
15	36	0		-	21.64	-		
15	36	20		-	21.53	-		
15	36	39		-	21.54	-		
15	75	0		-	21.52	-		
15	1	0	256-QAM	-	19.58	-	12.88	0.0194
15	1	37		-	19.63	-		
15	1	74		-	19.57	-		
15	36	0		-	18.41	-		
15	36	20		-	18.57	-		
15	36	39		-	18.48	-		
15	75	0		-	18.52	-		
Limit	Reporting only			Result			N/A	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = -4.6 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
10	1	0	QPSK	-	24.67	-	17.92	0.0619
10	1	25		-	24.56	-		
10	1	49		-	24.49	-		
10	25	0		-	23.56	-		
10	25	12		-	23.59	-		
10	25	25		-	23.73	-		
10	50	0		-	23.69	-		
10	1	0	16-QAM	-	23.82	-	17.15	0.0519
10	1	25		-	23.90	-		
10	1	49		-	23.84	-		
10	25	0		-	22.84	-		
10	25	12		-	22.70	-		
10	25	25		-	22.69	-		
10	50	0		-	22.72	-		
10	1	0	64-QAM	-	22.81	-	16.11	0.0408
10	1	25		-	22.82	-		
10	1	49		-	22.86	-		
10	25	0		-	21.80	-		
10	25	12		-	21.81	-		
10	25	25		-	21.69	-		
10	50	0		-	21.63	-		
10	1	0	256-QAM	-	19.83	-	13.08	0.0203
10	1	25		-	19.53	-		
10	1	49		-	19.64	-		
10	25	0		-	18.62	-		
10	25	12		-	18.65	-		
10	25	25		-	18.60	-		
10	50	0		-	18.85	-		
Limit	Reporting only			Result			N/A	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = -4.6 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
5	1	0	QPSK	-	24.66	-	17.91	0.0618
5	1	12		-	24.54	-		
5	1	24		-	24.55	-		
5	12	0		-	23.60	-		
5	12	7		-	23.63	-		
5	12	13		-	23.72	-		
5	25	0		-	23.51	-		
5	1	0	16-QAM	-	23.88	-	17.17	0.0521
5	1	12		-	23.78	-		
5	1	24		-	23.92	-		
5	12	0		-	22.77	-		
5	12	7		-	22.70	-		
5	12	13		-	22.69	-		
5	25	0		-	22.65	-		
5	1	0	64-QAM	-	22.75	-	16.03	0.0401
5	1	12		-	22.78	-		
5	1	24		-	22.78	-		
5	12	0		-	21.79	-		
5	12	7		-	21.88	-		
5	12	13		-	21.70	-		
5	25	0		-	21.73	-		
5	1	0	256-QAM	-	19.81	-	13.06	0.0202
5	1	12		-	19.45	-		
5	1	24		-	19.66	-		
5	12	0		-	18.71	-		
5	12	7		-	18.59	-		
5	12	13		-	18.54	-		
5	25	0		-	18.66	-		
Limit	Reporting only			Result			N/A	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = -4.6 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
3	1	0	QPSK	-	24.64	-	17.98	0.0628
3	1	8		-	24.71	-		
3	1	14		-	24.73	-		
3	8	0		-	23.65	-		
3	8	4		-	23.63	-		
3	8	7		-	23.60	-		
3	15	0		-	23.65	-		
3	1	0	16-QAM	-	23.76	-	17.08	0.0511
3	1	8		-	23.72	-		
3	1	14		-	23.83	-		
3	8	0		-	22.60	-		
3	8	4		-	22.59	-		
3	8	7		-	22.64	-		
3	15	0		-	22.58	-		
3	1	0	64-QAM	-	22.81	-	16.10	0.0407
3	1	8		-	22.85	-		
3	1	14		-	22.78	-		
3	8	0		-	21.73	-		
3	8	4		-	21.69	-		
3	8	7		-	21.64	-		
3	15	0		-	21.71	-		
3	1	0	256-QAM	-	19.56	-	13.06	0.0202
3	1	8		-	19.60	-		
3	1	14		-	19.81	-		
3	8	0		-	18.84	-		
3	8	4		-	18.63	-		
3	8	7		-	18.77	-		
3	15	0		-	18.83	-		
Limit	Reporting only			Result			N/A	



LTE Band 26 Straddle Maximum Average Power [dBm] (GT - LC = -4.6 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
1.4	1	0	QPSK	-	23.53	-	16.98	0.0499
1.4	1	3		-	23.52	-		
1.4	1	5		-	23.73	-		
1.4	3	0		-	23.55	-		
1.4	3	1		-	23.60	-		
1.4	3	3		-	23.60	-		
1.4	6	0		-	22.70	-		
1.4	1	0	16-QAM	-	22.83	-	16.14	0.0411
1.4	1	3		-	22.73	-		
1.4	1	5		-	22.85	-		
1.4	3	0		-	22.63	-		
1.4	3	1		-	22.89	-		
1.4	3	3		-	22.80	-		
1.4	6	0		-	21.57	-		
1.4	1	0	64-QAM	-	21.66	-	15.18	0.0330
1.4	1	3		-	21.68	-		
1.4	1	5		-	21.89	-		
1.4	3	0		-	21.62	-		
1.4	3	1		-	21.93	-		
1.4	3	3		-	21.72	-		
1.4	6	0		-	20.58	-		
1.4	1	0	256-QAM	-	18.61	-	12.12	0.0163
1.4	1	3		-	18.71	-		
1.4	1	5		-	18.70	-		
1.4	3	0		-	18.76	-		
1.4	3	1		-	18.71	-		
1.4	3	3		-	18.87	-		
1.4	6	0		-	17.64	-		
Limit	Reporting only			Result			N/A	



LTE Band 26


Peak-to-Average Ratio

Mode	LTE Band 26 / 10MHz				
Mod.	QPSK	16QAM	64QAM	256QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Full RB	Result
Middle CH	5.39	5.86	6.00	6.75	PASS



LTE Band 26 / 10MHz / QPSK


Middle Channel / Full RB



Date: 29.APR.2022 10:36:03

LTE Band 26 / 10MHz / 16QAM


Middle Channel / Full RB



Date: 29.APR.2022 10:35:34

LTE Band 26 / 10MHz / 64QAM


Middle Channel / Full RB



Date: 29.APR.2022 10:36:31

LTE Band 26 / 10MHz / 256QAM

Middle Channel / Full RB



Date: 19.MAY.2022 20:07:24




26dB Bandwidth

Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Low CH	-	-	-	-	-	-	-	-	14.51	14.57	-	-
Middle CH	1.27	1.26	3.09	3.07	4.97	5.19	9.97	10.21	-	-	-	-
Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM
Low CH	-	-	-	-	-	-	-	-	14.54	14.15	-	-
Middle CH	1.28	1.30	3.13	3.07	5.13	5.05	10.17	10.09	-	-	-	-




LTE Band 26

Middle Channel / 1.4MHz / QPSK




Date: 29.APR.2022 09:18:57

Middle Channel / 1.4MHz / 16QAM




Date: 29.APR.2022 09:19:24

Middle Channel / 3MHz / QPSK




Date: 29.APR.2022 09:38:20

Middle Channel / 3MHz / 16QAM




Date: 29.APR.2022 09:38:55

Middle Channel / 5MHz / QPSK



Date: 29.APR.2022 09:57:16

Middle Channel / 5MHz / 16QAM




Date: 29.APR.2022 09:57:42




LTE Band 26

Middle Channel / 10MHz / QPSK




Date: 29.APR.2022 10:13:01

Middle Channel / 10MHz / 16QAM




Date: 29.APR.2022 10:13:28

Low Channel / 15MHz / QPSK



Date: 29.APR.2022 10:32:48

Low Channel / 15MHz / 16QAM




Date: 29.APR.2022 10:32:08




LTE Band 26

Middle Channel / 1.4MHz / 64QAM




Date: 29.APR.2022 09:16:30

Middle Channel / 3MHz / 64QAM




Date: 29.APR.2022 09:38:02

Middle Channel / 5MHz / 64QAM




Date: 29.APR.2022 09:54:49

Middle Channel / 10MHz / 64QAM



Date: 29.APR.2022 10:11:41

Low Channel / 15MHz / 64QAM




Date: 29.APR.2022 10:31:27




LTE Band 26

Middle Channel / 1.4MHz / 256QAM




Date: 29.APR.2022 10:47:58

Middle Channel / 3MHz / 256QAM




Date: 29.APR.2022 10:53:10

Middle Channel / 5MHz / 256QAM




Date: 29.APR.2022 10:58:26

Middle Channel / 10MHz / 256QAM



Date: 29.APR.2022 11:02:53

Low Channel / 5MHz / 256QAM



Date: 29.APR.2022 11:08:54




Occupied Bandwidth

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Low CH	-	-	-	-	-	-	-	-	13.40	13.40	-	-
Middle CH	1.10	1.11	2.73	2.75	4.50	4.52	9.05	9.01	-	-	-	-
Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM
Low CH	-	-	-	-	-	-	-	-	13.43	13.49	-	-
Middle CH	1.09	1.08	2.73	2.73	4.49	4.51	9.05	9.03	-	-	-	-




LTE Band 26

Middle Channel / 1.4MHz / QPSK




Date: 29.APR.2022 09:18:04

Middle Channel / 1.4MHz / 16QAM




Date: 29.APR.2022 09:18:31

Middle Channel / 3MHz / QPSK




Date: 29.APR.2022 09:37:09

Middle Channel / 3MHz / 16QAM




Date: 29.APR.2022 09:13:35

Middle Channel / 5MHz / QPSK



Date: 29.APR.2022 09:56:22

Middle Channel / 5MHz / 16QAM




Date: 29.APR.2022 09:56:49




LTE Band 26

Middle Channel / 10MHz / QPSK




Date: 29.APR.2022 10:12:08

Middle Channel / 10MHz / 16QAM




Date: 29.APR.2022 10:12:35

Low Channel / 15MHz / QPSK



Date: 29.APR.2022 10:32:34

Low Channel / 15MHz / 16QAM




Date: 29.APR.2022 10:31:54




LTE Band 26

Middle Channel / 1.4MHz / 64QAM




Date: 29, APR, 2022 09:16:16

Middle Channel / 3MHz / 64QAM




Date: 29, APR, 2022 09:16:42

Middle Channel / 5MHz / 64QAM




Date: 29, APR, 2022 09:54:35

Middle Channel / 10MHz / 64QAM



Date: 29, APR, 2022 10:11:27

Low Channel / 5MHz / 64QAM




Date: 29, APR, 2022 10:31:13




LTE Band 26

Middle Channel / 1.4MHz / 256QAM




Date: 29.APR.2022 10:47:44

Middle Channel / 3MHz / 256QAM




Date: 29.APR.2022 10:52:56

Middle Channel / 5MHz / 256QAM




Date: 29.APR.2022 10:58:12

Middle Channel / 10MHz / 256QAM



Date: 29.APR.2022 11:02:39

Low Channel / 15MHz / 256QAM




Date: 29.APR.2022 11:08:40



Emission masks – In-band emissions


LTE Band 26 / 1.4MHz / QPSK

Lowest Band Edge / 1RB




Date: 29.APR.2022 09:25:23

Highest Band Edge / 1RB




Date: 29.APR.2022 09:29:04

Lowest Band Edge / Full RB



Date: 29.APR.2022 09:27:13

Highest Band Edge / Full RB




Date: 29.APR.2022 09:30:54




LTE Band 26 / 1.4MHz / 16QAM


Lowest Band Edge / 1 RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 26 / 1.4MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 29.APR.2022 09:32:44

Highest Band Edge / 1 RB




Date: 29.APR.2022 09:34:35

Lowest Band Edge / Full RB



Date: 29.APR.2022 09:33:40

Highest Band Edge / Full RB




Date: 29.APR.2022 09:35:30




LTE Band 26 / 1.4MHz / 256QAM

Lowest Band Edge / 1 RB




Date: 29.APR.2022 10:48:53

Highest Band Edge / 1 RB




Date: 29.APR.2022 10:50:44

Lowest Band Edge / Full RB



Date: 29.APR.2022 10:49:48

Highest Band Edge / Full RB





Date: 29.APR.2022 10:51:39



LTE Band 26 / 3MHz / QPSK



Lowest Band Edge / 1RB

Highest Band Edge / 1 RB



Lowest Band Edge / Full RB


Highest Band Edge / Full RB






LTE Band 26 / 3MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 29.APR.2022 09:44:06

Highest Band Edge / 1 RB




Date: 29.APR.2022 09:47:48

Lowest Band Edge / Full RB



Date: 29.APR.2022 09:45:57

Highest Band Edge / Full RB




Date: 29.APR.2022 09:49:40



LTE Band 26 / 3MHz / 64QAM


Lowest Band Edge / 1 RB



Spectrum Emission Mask		Standard: None		RBW 30.000 kHz		
Range Low	Range Up	Tx Power	Tx Bandwidth	Power Abs	Power Rel	ALimit
-5.000 MHz	-1.538 MHz	100.000 kHz	3.000 MHz	-14.43 dBm	-35.82 dB	-1.43 dB
-1.538 MHz	-1.500 MHz	300.000 Hz		-37.27 dBm	-58.66 dB	-17.27 dB
1.500 MHz	1.538 MHz	300.000 Hz		-68.81 dBm	-90.20 dB	-48.81 dB
1.538 MHz	5.000 MHz	100.000 kHz		-42.62 dBm	-64.01 dB	-29.62 dB

Date: 29.APR.2022 09:50:35


Highest Band Edge / 1 RB



Spectrum Emission Mask		Standard: None		RBW 30.000 kHz		
Range Low	Range Up	Tx Power	Tx Bandwidth	Power Abs	Power Rel	ALimit
-5.000 MHz	-1.538 MHz	100.000 kHz	3.000 MHz	-42.59 dBm	-64.14 dB	-29.59 dB
-1.538 MHz	-1.500 MHz	300.000 Hz		-68.47 dBm	-90.02 dB	-48.47 dB
1.500 MHz	1.538 MHz	300.000 Hz		-38.34 dBm	-59.89 dB	-18.34 dB
1.538 MHz	5.000 MHz	100.000 kHz		-16.33 dBm	-37.98 dB	-3.33 dB

Date: 29.APR.2022 09:52:27


Lowest Band Edge / Full RB



Spectrum Emission Mask		Standard: None		RBW 30.000 kHz		
Range Low	Range Up	Tx Power	Tx Bandwidth	Power Abs	Power Rel	ALimit
-5.000 MHz	-1.538 MHz	100.000 kHz	3.000 MHz	-23.38 dBm	-44.05 dB	-10.38 dB
-1.538 MHz	-1.500 MHz	300.000 Hz		-46.04 dBm	-66.71 dB	-26.04 dB
1.500 MHz	1.538 MHz	300.000 Hz		-45.09 dBm	-65.76 dB	-25.09 dB
1.538 MHz	5.000 MHz	100.000 kHz		-22.09 dBm	-42.76 dB	-9.09 dB

Date: 29.APR.2022 09:51:31

Highest Band Edge / Full RB




Spectrum Emission Mask		Standard: None		RBW 30.000 kHz		
Range Low	Range Up	Tx Power	Tx Bandwidth	Power Abs	Power Rel	ALimit
-5.000 MHz	-1.538 MHz	100.000 kHz	3.000 MHz	-21.44 dBm	-42.15 dB	-8.44 dB
-1.538 MHz	-1.500 MHz	300.000 Hz		-45.49 dBm	-66.20 dB	-25.49 dB
1.500 MHz	1.538 MHz	300.000 Hz		-45.37 dBm	-66.08 dB	-25.37 dB
1.538 MHz	5.000 MHz	100.000 kHz		-22.01 dBm	-42.72 dB	-9.01 dB

Date: 29.APR.2022 09:53:22




LTE Band 26 / 3MHz / 256QAM

Lowest Band Edge / 1 RB




Date: 29.APR.2022 10:54:08

Highest Band Edge / 1 RB




Date: 29.APR.2022 10:55:59

Lowest Band Edge / Full RB



Date: 29.APR.2022 10:55:04

Highest Band Edge / Full RB




Date: 29.APR.2022 10:56:55




LTE Band 26 / 5MHz / QPSK

Lowest Band Edge / 1 RB




Date: 29.APR.2022 10:00:51

Highest Band Edge / 1 RB




Date: 29.APR.2022 10:04:32

Lowest Band Edge / Full RB



Date: 29.APR.2022 10:02:41

Highest Band Edge / Full RB





Date: 29.APR.2022 10:06:22



LTE Band 26 / 5MHz / 16QAM

Lowest Band Edge / 1RB

Highest Band Edge / 1 RB





Date: 29.APR.2022 10:01:46

Date: 29.APR.2022 10:05:27

Lowest Band Edge / Full RB

Highest Band Edge / Full RB



Date: 29.APR.2022 10:03:36

Date: 29.APR.2022 10:07:17