



Spot Check Summary Document

Applicant : GOOGLE
1600 AMPHITHEATRE PARKWAY
MOUNTAIN VIEW, CA 94043, U.S.A.

Model : NC2-6A5

FCC ID : A4RNC2-6A5B

IC : 10395A-NC26A5

EUT Description : Multimedia Device with BLE/BT, 2.4Ghz and 5GHz WLAN Radios

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C
FCC 47 CFR PART 15 SUBPART E
ISED RSS-247 ISSUE 2
ISED RSS-GEN ISSUE 4

Date Of Issue:

May 03, 2018

Prepared by:

UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888



TABLE OF CONTENTS

TABLE OF CONTENTS	3
1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION.....	5
4. CALIBRATION AND UNCERTAINTY	6
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>6</i>
4.2. <i>SAMPLE CALCULATION.....</i>	<i>6</i>
4.3. <i>MEASUREMENT UNCERTAINTY</i>	<i>6</i>
5. EQUIPMENT UNDER TEST	7
5.1. <i>EUT DESCRIPTION.....</i>	<i>7</i>
6. SCOPE OF DOCUMENT	7
7. TEST AND MEASUREMENT EQUIPMENT	8

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: GOOGLE
 1600 AMPHITHEATRE PARKWAY
 MOUNTAIN VIEW, CA 94043, U.S.A

EUT DESCRIPTION: Multimedia Device with BLE/BT, 2.4Ghz and 5GHz WLAN Radios

MODEL: NC2-6A5

SERIAL NUMBER: MLB1(Conducted)
 G1172786 (Radiated)


DATE TESTED: March 13 – April 12, 2018

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Complies
ISED RSS-247 Issue 2	Complies
ISED RSS-GEN Issue 4	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For
 UL Verification Services Inc. By:



Francisco de Anda
 CONSUMER TECHNOLOGY DIVISION
 Operations Leader
 UL Verification Services Inc.

Prepared By:



Eric Yu
 CONSUMER TECHNOLOGY DIVISION
 Test Engineer
 UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, KDB 558074 D01 v4, FCC KDB 789033 D02 v02r01, ANSI C63.10-2013, RSS-GEN Issue 4, and RSS-247 Issue 2.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
<input checked="" type="checkbox"/> Chamber A (ISED:2324B-1)	<input type="checkbox"/> Chamber D (ISED:22541-1)
<input type="checkbox"/> Chamber B (ISED:2324B-2)	<input type="checkbox"/> Chamber E (ISED:22541-2)
<input type="checkbox"/> Chamber C (ISED:2324B-3)	<input type="checkbox"/> Chamber F (ISED:22541-3)
	<input type="checkbox"/> Chamber G (ISED:22541-4)
	<input type="checkbox"/> Chamber H (ISED:22541-5)

The above test sites and facilities are covered under FCC Test Firm Registration # 208313.

Chambers A through C are covered under ISED company address code 2324B with site numbers 2324B -1 through 2324B-3, respectively. Chambers D through H are covered under ISED company address code 22541 with site numbers 22541 -1 through 22541-5, respectively.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at [NVLAP Lab Search](#).

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.84 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.65 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	3.15 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	5.36 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.32 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.45 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.24 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. EUT DESCRIPTION

The EUT is a Multimedia Device with BLE/BT, 2.4Ghz and 5GHz WLAN Radios.

6. SCOPE OF DOCUMENT

This document is intended to provide BE and RSE radiated spot test comparison data between original FCC ID: A4RNC2-6A5/IC ID: 10395A-NC26A5 and new FCC ID: A4RNC2-6A5B/IC ID: 10395A-NC26A5 for the Chromecast multimedia device. Below are the results;

Model NC2-6A5 -Original and New models spot check summary

Archer 5GHz Spot testing									
		Original			New				
		Channel	Frequency (GHz)	Corrected reading	PK Margin	Frequency (GHz)	Corrected reading	PK Margin	Delta
RSE	n20	5200	15.601	66.13	-7.87	15.603	66.8	-7.2	0.67
		5300	15.893	61.49	-12.51	15.898	62.75	-11.25	1.26
		5580	2.435	39.82	-28.38	2.434	36.13	-32.07	-3.69
		5785	2.44	39.86	-28.34	2.436	37.24	-30.96	-2.62
		Channel	Frequency (GHz)	Corrected reading	ave Margin	Frequency (GHz)	Corrected reading	ave Margin	
BE	n20	5180	5.149	51.12	-2.88	5.15	51.53	-2.47	0.41

Archer 2.4GHz wifi Spot testing

		Original archer			New Archer				
	Mode	Channel	Frequency (GHz)	Corrected reading	Ave Margin	Frequency (GHz)	Corrected reading	Ave Margin	Delta
RSE	11b	2437	4.874	52.64	-1.36	4.874	48.73	-5.27	-3.91
	11n20	2437	2.365	49.19	-4.81	2.365	38.16	-15.84	-11.03
		2437	7.309	45.1	-8.9	7.312	37.4	-16.6	-7.7
	11n40	2437	4.874	43.67	-10.33	4.954	32.99	-21.01	-10.68

		Channel	Frequency (GHz)	Corrected reading	ave Margin	Frequency (GHz)	Corrected reading	ave Margin	
BE	11b	2437	2.386	48.77	-5.23	2.386	50.27	-3.73	1.5
	11n20	2412	2.39	46.93	-7.07	2.39	45.85	-8.15	-1.08
		2462	2.484	47.23	-6.77	2.484	48.03	-5.97	0.8
	11n40	2422	2.389	45.61	-8.39	2.389	47.45	-6.55	1.84

7. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Asset	Cal Due
Amplifier, 10KHz to 1GHz, 32dB	Agilent (Keysight) Technologies	8447D	T15	08/14/2018
RF Preamplifier, 1 - 26GHz	Agilent	8449B	T404	07/23/2018
Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences Corp.	JB3	T130	06/15/2018
Antenna, Horn 1-18GHz	ETS-Lindgren	3117	T862	06/09/2018
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T1454	01/08/2019
UL AUTOMATION SOFTWARE				
Radiated Software	UL	UL EMC	Ver 9.5, Dec 01, 2016	

NOTES:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

END OF DOCUMENT