

# 1. RF Exposure Requirements

---

## 1.1 General Information

### Client Information

Applicant:	CE LINK LIMITED
Address of applicant:	22 Dongkang Road, Dalingshan Town, Dongguan City, Guangdong Province, China.
Manufacturer:	Dongguan CE LINK LIMITED
Address of manufacturer:	22 Dongkang Road, Dalingshan Town, Dongguan City, Guangdong Province, China.
Factory 1#:	ANFU CE LINK LIMITED
Address of factory:	Anfu County Industrial Zone, Ji'an city, Jiangxi Province, P.R. China.
Factory 2#:	CE LINK VIET NAM COMPANY LIMITED
Address of factory:	Part of lots CNSG-04, CNSG-06 Van Trung Industrial Zone, Van Trung Ward, Viet Yen Town, Bac Giang Province, Vietnam

### General Description of EUT:

Product Name:	Battery Camera
Trade Name:	CE-LINK
Model No.:	L3560
Adding Model(s):	IPC-13NS-YT2, L3561, IPC-13NU-YT2
Rated Voltage:	External power supply/Solar power supply: 5V Rechargeable Lithium-ion Battery:3.65V
Rated Current:	External power supply/Solar power supply: 1.0A
Battery Capacity:	5200mAh
Power Adapter:	ADS-6RA-06 05050EPG Input: AC100-240V~ 50/60Hz Max 0.3A Output:DC5.0V--1A 5.0W
Software Version:	SOC_T23_V1.0.1 WIFI_AB6441_44PC_V1.0.1 IPC-13NS-ZT2_MAIN~R1V0 20240419
Hardware Version:	IPC-13NS_PIR~R1V0 20240126 IPC-14NS_LED~R1V0 20230506
FCC ID:	A4X-L3560
Equipment Type:	Fixed device

## Technical Characteristics of EUT:

### Wi-Fi

Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20)
RF Output Power:	16.30dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Quantity of Channels:	11 for 802.11b/g/n(HT20)
Channel Separation:	5MHz
Type of Antenna:	FPC Antenna
Antenna Gain:	2dBi

## 1.2 RF Exposure Exemption

According to §1.1307(b)(3) and KDB 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

**Option A:** FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

**Option B:** FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula.  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz};$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

**Option C:** FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R <sup>2</sup>
1.34-30	3,450 R <sup>2</sup> /f <sup>2</sup>
30-300	3.83 R <sup>2</sup>
300-1,500	0.0128 R <sup>2</sup> f
1,500-100,000	19.2R <sup>2</sup>

**For Multiple RF sources:** FCC Rule Part 1.1307(b)(3)(ii):

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).
- (B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

### 1.3 Calculated Result

Radio Access Technology	Prediction Frequency (MHz)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	Tune-Up Time-Averaged Power (dBm)	ERP (dBm)
Wi-Fi	2412	16.30	2	100	17.00	16.85

Frequency (MHz)	Option	Min. Distance (cm)	Max. Power (dBm) (mW)		Exposure Limit (mW)	Ratio	Result (Pass/Fail)
2412	C	20.00	16.85	48.42	768.00	0.06	Pass

Note: 1. a. Time-Averaged Power=Output Power \* Duty Cycle;

ERP= Time-Averaged Power+ Antenna gain-2.15dB;

b. EIRP= E-104.8+20logD; Output Power=EIRP- Antenna Gain;

ERP=EIRP-2.15dB

2. Option A, B and C refers as clause 1.2.

3. For option B, Max (time-averaged power, effective radiated power (ERP)) converts to Max. Power. For option C, ERP converts to Max. Power;

4. For option B, P<sub>th</sub> (mW) converts to Exposure Limit (mW); For option C, ERP (W) converts to Exposure Limit (mW).

5. Ratio= Tune-Up ERP (mW)/ Exposure Limit (mW)

**Mode for Simultaneous Multi-band Transmission:**

Radio Access Technology	Ratio 1	Ratio 2	Simultaneous Ratio	Limit	Result
					Pass/Fail
/	/	/	/	/	/

Result: Pass