

# TEST REPORT

Reference No..... : WTX22X11241794W002  
FCC ID..... : A4X-WPC15-1LCNB  
Applicant..... : CE LINK LIMITED  
Address..... : 22 Dongkang Road, Dalingshan Town, Dongguan City, Guangdong  
Province, China.  
Manufacturer..... : DONGGUAN CE LINK LIMITED  
Address..... : 22 Dongkang Road, Dalingshan Town, Dongguan City, Guangdong  
Province, China.  
Product Name..... : Wireless Charger  
Model No..... : WPC15-1LCNB  
Standards..... : KDB 680106 D01 V03  
Date of Receipt sample.... : 2022-11-30  
Date of Test..... : 2022-11-30 to 2023-01-13  
Date of Issue..... : 2023-01-13  
Test Report Form No. .... : WTX\_KDB 680106 D01 V03W  
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

**Prepared By:**

**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China  
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

*Jack Huang*

Jack Huang

Approved by:

*Silin Chen*

Silin Chen

**TABLE OF CONTENTS**

**1. GENERAL INFORMATION.....4**  
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4  
1.2 AUXILIARY EQUIPMENT LIST AND DETAILS .....5  
1.3 TEST EQUIPMENT LIST AND DETAILS .....6

**2. RF EXPOSURE TEST REPORT .....7**  
2.1 STANDARD APPLICABLE.....7  
2.2 TEST CONDITIONS .....8  
2.3 TEST PROCEDURE.....9  
2.4 TEST RESULT.....10  
2.5 MEASUREMENT UNCERTAINTY .....13  
2.6 TEST PHOTOS .....13

**APPENDIX PHOTOGRAPHS.....14**

**Report version**

Version No.	Date of issue	Description
Rev.00	2023-01-13	Original
/	/	/

## 1. GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Factory#1: SuiChuan CE LINK LIMITED  
 Address of factory: SuiChuan county industrial park east zone, Ji'an city, Jiangxi province, China.

Factory#2: CE LINK VIET NAM COMPANY LIMITED.  
 Address of factory: Lot CNSG04&CNSG06 Van Trung Industrial Zone, Viet Yen district, Bac Giang Province, Vietnam

General Description of EUT	
Product Name:	Wireless Charger
Trade Name:	CE-LINK
Model No.:	WPC15-1LCNB
Adding Model(s):	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	112~201kHz
Modulation Type:	ASK
Antenna Type:	Coil Antenna
Antenna Gain:	0dBi
Rated Voltage:	Type-C: 5V---3A,9V/12V---2A
Rated Current:	Type-C: 2A
Rated Power:	Wireless Output: 5W, 7.5W, 10W, 15W

### 1.2 Auxiliary Equipment List and Details

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Smart phone	Apple	IPhone 12 Pro Max	/
Adapter	Lenovo	ADLX65UCGC2A	/

### 1.3 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200AC	180ZX10226	2021-05-20	2024-05-19

## 2. RF Exposure Test Report

---

### 2.1 Standard Applicable

According to §1.1310 system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30



f = frequency in MHz \* = Plane-wave equivalent power density

**2.2 Test Conditions**

<b>Test Mode</b>	<b>Description</b>	<b>Remark</b>
TM1	Wireless Charging	Connect to the adapter; AC120V/60Hz for adapter; Wireless charging: output: 5W
TM2	Wireless Charging	Connect to the adapter; AC120V/60Hz for adapter; Wireless charging: output: 10W
TM3	Wireless Charging	Connect to the adapter; AC120V/60Hz for adapter; Wireless charging: output: 15W
<b>Measurement Distance:</b>		
15 cm and 20 cm		



### 2.3 Test Procedure



- a. The measurement probe was placed at test distance(15 cm for A,B,C,D,F and 20 cm for E) which is between the edge of the charger and the geometric center of probe.
- b. The highest emission level was recorded at the measurement points(A, B, C, D, E, F).
- c. The EUT was measured according to the distance of KDB 680106 D01 V03.

## 2.4 Test Result

The EUT complies with item 5.b) of KDB 680106 D01V03

1. Power transfer frequency is less than 1 MHz  
Yes, the device operates in the frequency range from 110kHz to 205kHz.
2. Output power from each primary coil is less than or equal to 15 watts  
Yes, the maximum output power of the primary coil is less than 15W.
3. The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils  
Yes, the client device includes only single primary coils.
4. Client device is inserted in or placed directly in contact with the transmitter  
Yes, Client device is placed directly in contact with the transmitter.
5. Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).  
Yes, It is mobile exposure conditions only.
6. The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.  
Yes, The EUT field strength levels are less than 50% of the MPE limit, refer to test TM1, TM2, TM3, TM4, TM5 list, and the coils can't transmit simultaneously.

Test Mode: TM1

<b>Electric Field Emissions</b>			
<b>Test Position</b>	<b>Measure Value (V/m)</b>	<b>Limit(V/m)</b>	<b>50% Limit (V/m)</b>
Point E	0.9304	614	307
Point F	0.1974	614	307
Point A	0.3952	614	307
Point B	0.3461	614	307
Point C	0.2188	614	307
Point D	0.2035	614	307
<b>Magnetic Field Emissions</b>			
<b>Test Position</b>	<b>Measure Value (A/m)</b>	<b>Limit(A/m)</b>	<b>50% Limit (A/m)</b>
Point E	0.4916	1.63	0.815
Point F	0.4069	1.63	0.815
Point A	0.3496	1.63	0.815
Point B	0.0900	1.63	0.815
Point C	0.0907	1.63	0.815
Point D	0.0941	1.63	0.815

Test Mode: TM2

<b>Electric Field Emissions</b>			
<b>Test Position</b>	<b>Measure Value (V/m)</b>	<b>Limit(V/m)</b>	<b>50% Limit (V/m)</b>
Point E	0.9295	614	307
Point F	0.4152	614	307
Point A	0.3820	614	307
Point B	0.8781	614	307
Point C	0.5638	614	307
Point D	0.2085	614	307
<b>Magnetic Field Emissions</b>			
<b>Test Position</b>	<b>Measure Value (A/m)</b>	<b>Limit(A/m)</b>	<b>50% Limit (A/m)</b>
Point E	0.7266	1.63	0.815
Point F	0.4108	1.63	0.815
Point A	0.3655	1.63	0.815
Point B	0.1066	1.63	0.815
Point C	0.0941	1.63	0.815
Point D	0.0907	1.63	0.815

Test Mode: TM3

<b>Electric Field Emissions</b>			
<b>Test Position</b>	<b>Measure Value (V/m)</b>	<b>Limit(V/m)</b>	<b>50% Limit (V/m)</b>
Point E	0.7270	614	307
Point F	0.3280	614	307
Point A	0.3101	614	307
Point B	0.2188	614	307
Point C	0.2199	614	307
Point D	0.2085	614	307
<b>Magnetic Field Emissions</b>			
<b>Test Position</b>	<b>Measure Value (A/m)</b>	<b>Limit(A/m)</b>	<b>50% Limit (A/m)</b>
Point E	0.7266	1.63	0.815
Point F	0.3125	1.63	0.815
Point A	0.2827	1.63	0.815
Point B	0.1034	1.63	0.815
Point C	0.0812	1.63	0.815
Point D	0.0786	1.63	0.815

Note: this EUT was tested in 3 orthogonal positions and the worst case position (D point) data was reported.

## 2.5 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Electric Field Emissions	Radiated	$\pm 1.56$ (V/m)
Magnetic Field Emissions	Radiated	$\pm 0.08$ (A/m)

## 2.6 Test Photos



## APPENDIX PHOTOGRAPHS

---

Please refer to "ANNEX"

\*\*\*\* END OF REPORT \*\*\*\*