

# TEST REPORT

Reference No..... : WTX20X09066381W-1  
FCC ID ..... : A4X-WPC15-3XJNB  
Applicant ..... : CE LINK LIMITED  
Address ..... : Building M,LiCheng Technology Industrial Zone,GongHe Village,Shajing  
Town,ShenZhen City,China  
Product Name ..... : Wireless Charger  
Test Model. .... : WPC15-3XJNB  
Standards ..... : FCC Part 18  
Date of Receipt sample .... : Aug.14, 2020  
Date of Test..... : Aug.14, 2020 to Sept.30, 2020  
Date of Issue ..... : Oct.09, 2020  
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308


Fax.: +86-755-33663309

Tested by:



Jason Su / Project Engineer

Reviewed By:



Lion Cai / RF Manager

Approved & Authorized By:



Silin Chen / Manager

**TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION</b> .....	<b>4</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND OPERATION MODE.....	6
1.6 MEASUREMENT UNCERTAINTY.....	6
1.7 TEST EQUIPMENT LIST AND DETAILS.....	7
<b>2. SUMMARY OF TEST RESULTS</b> .....	<b>8</b>
<b>3. CONDUCTED EMISSIONS</b> .....	<b>9</b>
3.1 STANDARD APPLICABLE.....	9
3.2 TEST PROCEDURE.....	9
3.3 BASIC TEST SETUP BLOCK DIAGRAM.....	9
3.4 ENVIRONMENTAL CONDITIONS.....	9
3.5 TEST RECEIVER SETUP.....	10
3.6 SUMMARY OF TEST RESULTS/PLOTS.....	10
<b>4. RADIATED EMISSIONS</b> .....	<b>17</b>
4.1 TEST PROCEDURE.....	17
4.2 TEST RECEIVER SETUP.....	19
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	19
4.4 ENVIRONMENTAL CONDITIONS.....	19
4.5 SUMMARY OF TEST RESULTS/PLOTS.....	19

**Report version**

Version No.	Date of issue	Description
Rev.00	Oct.09, 2020	Original
/	/	/

## 1. GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: CE LINK LIMITED  
 Address of applicant: Building M,LiCheng Technology Industrial Zone,  
 GongHe Village,ShaJing Town,ShenZhen City,China

Manufacturer: CE LINK LIMITED  
 Address of manufacturer: Building M,LiCheng Technology Industrial Zone,  
 GongHe Village,ShaJing Town,ShenZhen City,China

Factory#1: SuiChuan CE LINK LIMITED  
 Address of factory: SuiChuan county industrial park east zone, Ji'an  
 city, Jiangxi Province, China.

Factory#2: CE LINK VIETNAM LIMITED  
 Address of factory: Lo FJ-25, Song Khe-Noi Hoang Industrial Zone, Noi  
 HoangVillage, Yen Dung Town, Bac Giang Province,  
 Vietnam.

General Description of EUT	
Product Name:	Wireless Charger
Trade Name:	CE-LINK
Model No.:	WPC15-3XJNB
Adding Model(s):	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	112~205kHz
Antenna Type:	Coil Antenna
Rated Voltage:	DC5V / DC9V /DC12V
Rated Current:	Input :2A, output : 1A, 1.1A, 1.25A
Rated Power:	Wireless output: 5W/7.5W, 10W, 15W

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Part 18 Subpart C**: Industrial, Scientific, and medical medical equipment.

**ANSI C63.4-2014**: American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

*Maintenance of compliance* is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

## 1.4 Test Facility

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

### **FCC – Registration No.: 125990**

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

## 1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List:

Test Mode	Description	Remark	Power Supply Mode
TM1	Wireless Charging	/	Input DC5V/2A; Output:DC5V/1A
TM2	Wireless Charging	/	Input DC9V/2A; Output:DC9V/1.1A
TM3	Wireless Charging		Input DC12V/2; Output:DC12V/1.25A

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Power Port Speed	ANKER	A2025	/

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	1.0	Shielded	Without Ferrite

## 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Conducted Emissions	Conducted	9-150kHz $\pm 3.74$ dB
		0.15-30MHz $\pm 3.34$ dB
Radiated Emissions	Radiated	30-200MHz $\pm 4.52$ dB
		0.2-1GHz $\pm 5.56$ dB
		1-6GHz $\pm 3.84$ dB
		6-18GHz $\pm 3.92$ dB

### 1.7 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
Spectrum Analyzer	Agilent	E4407B	MY41440400	2020-04-28	2021-04-27
Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2020-04-28	2021-04-27
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28	2021-04-27
Amplifier	Agilent	8447F	3113A06717	2020-04-28	2021-04-27
Amplifier	C&D	PAP-1G18	2002	2020-04-28	2021-04-27
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2020-04-28	2021-04-27
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2020-04-28	2021-04-27
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2020-04-28	2021-04-27

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

\*Remark: indicates software version used in the compliance certification testing

## 2. SUMMARY OF TEST RESULTS

---

FCC RULES	DESCRIPTION OF TEST	RESULT
§ 18.307 (b)	Conducted Emission	Compliant
§ 18.305 (b)	Radiated Emission	Compliant



### 3. Conducted Emissions

#### 3.1 Standard Applicable

According to FCC 18.307(b), the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies shall not exceed the limits in the following tables:


Frequency (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

#### 3.2 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 18.307 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

#### 3.3 Basic Test Setup Block Diagram



#### 3.4 Environmental Conditions

Temperature:	23.5° C
Relative Humidity:	55%
ATM Pressure:	1016 mbar


**3.5 Test Receiver Setup**

During the conducted emission test, the test receiver was set with the following configurations:

- Start Frequency ..... 150 kHz
- Stop Frequency..... 30 MHz
- Sweep Speed ..... Auto
- IF Bandwidth..... 10 kHz
- Quasi-Peak Adapter Bandwidth ..... 9 kHz
- Quasi-Peak Adapter Mode ..... Normal


**3.6 Summary of Test Results/Plots**

Test mode:	TM1	Polarity:	Line
------------	-----	-----------	------




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1620	32.51	10.26	42.77	55.36	-12.59	AVG
2*	0.1660	50.71	10.26	60.97	65.15	-4.18	QP
3	0.2060	47.84	10.27	58.11	63.36	-5.25	QP
4	0.2100	28.61	10.27	38.88	53.20	-14.32	AVG
5	0.3379	41.31	10.26	51.57	59.25	-7.68	QP
6	0.3820	22.31	10.23	32.54	48.23	-15.69	AVG

Test mode:	TM1	Polarity:	Neutral
------------	-----	-----------	---------




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1580	48.98	10.25	59.23	65.56	-6.33	QP
2	0.1620	34.27	10.26	44.53	55.36	-10.83	AVG
3	0.8940	35.22	10.22	45.44	56.00	-10.56	QP
4*	0.8940	33.29	10.22	43.51	46.00	-2.49	AVG
5	9.5860	28.34	10.28	38.62	50.00	-11.38	AVG
6	9.8420	29.90	10.28	40.18	60.00	-19.82	QP

Test mode:	TM2	Polarity:	Line
------------	-----	-----------	------




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1780	48.68	10.26	58.94	64.57	-5.63	QP
2	0.1780	30.53	10.26	40.79	54.57	-13.78	AVG
3	0.6860	35.40	10.17	45.57	56.00	-10.43	QP
4	0.6860	33.83	10.17	44.00	46.00	-2.00	AVG
5	0.9580	36.35	10.21	46.56	56.00	-9.44	QP
6*	0.9580	34.42	10.21	44.63	46.00	-1.37	AVG

Test mode:	TM2	Polarity:	Neutral
------------	-----	-----------	---------




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1860	47.18	10.26	57.44	64.21	-6.77	QP
2	0.1860	29.30	10.26	39.56	54.21	-14.65	AVG
3	0.6860	34.94	10.17	45.11	56.00	-10.89	QP
4	0.6860	33.10	10.17	43.27	46.00	-2.73	AVG
5	0.9580	35.71	10.21	45.92	56.00	-10.08	QP
6*	0.9580	34.25	10.21	44.46	46.00	-1.54	AVG

Test mode:	TM3	Polarity:	Line
------------	-----	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1500	52.89	10.25	63.14	65.99	-2.85	QP
2	0.1539	40.19	10.25	50.44	55.78	-5.34	AVG
3	0.1940	45.83	10.27	56.10	63.86	-7.76	QP
4	0.2020	29.91	10.27	40.18	53.52	-13.34	AVG
5	0.2460	40.39	10.26	50.65	61.89	-11.24	QP
6	0.2500	26.15	10.26	36.41	51.75	-15.34	AVG

Test mode:	TM3	Polarity:	Neutral
------------	-----	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1539	53.22	10.25	63.47	65.78	-2.31	QP
2	0.1580	39.70	10.25	49.95	55.56	-5.61	AVG
3	0.2060	44.53	10.27	54.80	63.36	-8.56	QP
4	0.2060	31.65	10.27	41.92	53.36	-11.44	AVG
5	0.2540	41.13	10.26	51.39	61.62	-10.23	QP
6	0.2540	27.34	10.26	37.60	51.62	-14.02	AVG



## 4. Radiated Emissions

---


### 4.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 18.305 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.


The test setup for emission measurement below 30MHz..



The test setup for emission measurement from 30 MHz to 1 GHz..



The test setup for emission measurement above 1 GHz..



## 4.2 Test Receiver Setup

Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

## 4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit for Any non-ISM frequency device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 18.305 Limit}$$


## 4.4 Environmental Conditions

Temperature:	23.5 °C
Relative Humidity:	55 %
ATM Pressure:	1011 mbar

## 4.5 Summary of Test Results/Plots


**Plot of Radiated Emissions Test Data (Below 30MHz)**

Test mode:	TM1	Polarity:	Vertical
------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	0.0091	75.69	-6.29	69.40	103.50	-34.10	-	-	peak
2	0.0250	73.93	-6.49	67.44	103.50	-36.06	-	-	peak
3	0.0335	68.40	-5.88	62.52	103.50	-40.98	-	-	peak
4	0.1281	80.52	-5.14	75.38	103.50	-28.12	-	-	peak
5	3.5843	66.69	-5.19	61.50	103.50	-42.00	-	-	peak
6	4.4777	58.24	-4.69	53.55	103.50	-49.95	-	-	peak
7	7.8102	53.60	-3.61	49.99	103.50	-53.51	-	-	peak

Test mode:	TM2	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	0.0105	76.47	-6.36	70.11	103.50	-33.39	-	-	peak
2	0.0250	73.34	-6.49	66.85	103.50	-36.65	-	-	peak
3	0.0338	67.89	-5.86	62.03	103.50	-41.47	-	-	peak
4	0.1340	83.58	-5.15	78.43	103.50	-25.07	-	-	peak
5	0.3997	53.75	-7.81	45.94	103.50	-57.56	-	-	peak
6	3.5843	67.76	-5.19	62.57	103.50	-40.93	-	-	peak
7	8.1916	54.63	-3.51	51.12	103.50	-52.38	-	-	peak
8	16.0545	51.58	-2.00	49.58	103.50	-53.92	-	-	peak


Test mode:	TM3	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	0.0093	78.19	-6.30	71.89	103.50	-31.61	-	-	peak
2	0.0249	72.88	-6.49	66.39	103.50	-37.11	-	-	peak
3	0.1281	83.94	-5.14	78.80	103.50	-24.70	-	-	peak
4	3.5843	62.53	-5.19	57.34	103.50	-46.16	-	-	peak
5	7.7278	57.12	-3.64	53.48	103.50	-50.02	-	-	peak
6	12.7837	48.81	-2.17	46.64	103.50	-56.86	-	-	peak


**Plot of Radiated Emissions Test Data ( Above 30MHz)**

Test mode:	TM1	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	41.8596	28.73	-11.31	17.42	63.50	-46.08	-	-	QP
2	66.9668	35.66	-13.43	22.23	63.50	-41.27	-	-	QP
3	89.2762	42.41	-14.55	27.86	63.50	-35.64	-	-	QP
4	190.4050	50.17	-12.04	38.13	63.50	-25.37	-	-	QP
5	306.7536	41.27	-7.28	33.99	63.50	-29.51	-	-	QP
6	475.4990	33.61	-4.85	28.76	63.50	-34.74	-	-	QP


Test mode:	TM1	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	37.0248	44.84	-12.27	32.57	63.50	-30.93	-	-	QP
2	51.8430	41.74	-10.59	31.15	63.50	-32.35	-	-	QP
3	86.8068	52.67	-14.47	38.20	63.50	-25.30	-	-	QP
4	195.1365	52.23	-11.66	40.57	63.50	-22.93	-	-	QP
5	305.6800	35.93	-7.27	28.66	63.50	-34.84	-	-	QP
6	570.6100	31.82	-2.76	29.06	63.50	-34.44	-	-	QP




Test mode:	TM2	Polarity:	Horizontal
------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	50.5860	30.48	-10.32	20.16	63.50	-43.34	-	-	QP
2	89.5899	41.14	-14.54	26.60	63.50	-36.90	-	-	QP
3	196.5098	50.73	-11.56	39.17	63.50	-24.33	-	-	QP
4	324.4561	48.00	-7.40	40.60	63.50	-22.90	-	-	QP
5	392.0951	43.51	-5.79	37.72	63.50	-25.78	-	-	QP
6	752.7432	30.48	-0.85	29.63	63.50	-33.87	-	-	QP

Test mode:	TM2	Polarity:	Vertical
------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	37.0249	46.52	-12.27	34.25	63.50	-29.25	-	-	QP
2	51.1209	45.44	-10.43	35.01	63.50	-28.49	-	-	QP
3	85.2981	52.42	-14.43	37.99	63.50	-25.51	-	-	QP
4	197.2001	47.37	-11.52	35.85	63.50	-27.65	-	-	QP
5	378.5843	43.46	-5.68	37.78	63.50	-25.72	-	-	QP
6	609.9217	31.08	-2.33	28.75	63.50	-34.75	-	-	QP

Test mode:	TM3	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	52.0251	33.16	-10.63	22.53	63.50	-40.97	-	-	QP
2	91.4949	43.29	-14.21	29.08	63.50	-34.42	-	-	QP
3	197.2001	50.63	-11.52	39.11	63.50	-24.39	-	-	QP
4	305.6800	47.03	-7.27	39.76	63.50	-23.74	-	-	QP
5	420.5803	38.29	-4.51	33.78	63.50	-29.72	-	-	QP
6	656.5300	29.64	-2.49	27.15	63.50	-36.35	-	-	QP

Test mode:	TM3	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	52.0251	47.78	-10.63	37.15	63.50	-26.35	-	-	QP
2	88.0329	53.58	-14.50	39.08	63.50	-24.42	-	-	QP
3	191.0738	47.77	-11.98	35.79	63.50	-27.71	-	-	QP
4	305.6800	36.33	-7.27	29.06	63.50	-34.44	-	-	QP
5	477.1694	34.74	-4.81	29.93	63.50	-33.57	-	-	QP
6	890.7278	32.57	1.39	33.96	63.50	-29.54	-	-	QP

Remark: ‘-’Means’ the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

\*\*\*\*\* END OF REPORT \*\*\*\*\*