

TEST REPORT

Reference No...... : WTX20X08054794W-2
FCC ID : A4X-WPC30-2XCNA
Applicant : CE LINK LIMITED
Address : Building M,LiCheng Technology Industrial Zone,GongHe Village,Shajing
Town,ShenZhen City,China
Product Name : Wireless charger Dual Pad 15W
Test Model. : WPC30-2XCNA
Standards : KDB 680106 D01 V03
Date of Receipt sample : Aug.11, 2020
Date of Test..... : Aug.11, 2020 to Aug.19, 2020
Date of Issue : Aug.19, 2020
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:


Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308


Fax.: +86-755-33663309

Tested by:



Jason Su / Project Engineer

Reviewed By:



Lion Cai / RF Manager

Approved & Authorized By:



Silin Chen / Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION.....4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4
1.2 TEST EQUIPMENT LIST AND DETAILS5

2. RF EXPOSURE TEST REPORT6
2.1 STANDARD APPLICABLE.....6
2.2 TEST CONDITIONS6
2.3 TEST PROCEDURE.....7
2.4 TEST RESULT.....7

Report version

Version No.	Date of issue	Description
Rev.00	Aug.19, 2020	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: CE LINK LIMITED
 Address of applicant: Building M,LiCheng Technology Industrial Zone,
 GongHe Village,ShaJing Town,ShenZhen City,China

Manufacturer: CE LINK LIMITED
 Address of manufacturer: Building M,LiCheng Technology Industrial Zone,
 GongHe Village,ShaJing Town,ShenZhen City,China

General Description of EUT	
Product Name:	Wireless charger Dual Pad 15W
Trade Name:	CE-LINK
Model No.:	WPC30-2XCNA
Adding Model(s):	/
Power adapter:	K48V150300U Input: AC100-240V, 50/60Hz, 1.2A, Output: DC15.0V, 3.0A
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	110~205kHz
Modulation Type:	ASK
Antenna Type:	Coil Antenna
Rated Voltage:	Input: DC15V 3A Wireless output :DC5V 1A/ DC9V 1.1A/DC12V 1.25A
Rated Power:	Wireless output: 5W / 10W / 15W

1.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
MPE Measuring Instrument	Narda	ELT-400	M-0155/M-0170	2020-07-15	2021-07-14
Broadband Field Meter	Narda	NBM-520	D-1699	2020-06-21	2021-06-20

2. RF Exposure Test Report

2.1 Standard Applicable

According to § 1.1310 system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)


Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

2.2 Test Conditions

Test Mode	Description	Remark
TM1	Wireless Charging	Input DC15V/3A; Output:DC5V/1A
TM2	Wireless Charging	Input DC15V/3A; Output:DC9V/1.1A
TM3	Wireless Charging	Input DC15V/3A; Output:DC12V/1.25A
Measurement Distance:		
		15 cm

2.3 Test Procedure



- The measurement probe was placed at test distance (15 cm for A, B, C, D, F and 20 cm for E) which is between the edge of the charger and the geometric center of probe.
- The highest emission level was recorded at the measurement points (A, B, C, D, E, F).
- The EUT was measured according to the distance of KDB 680106 D01 V03.

2.4 Test Result

The EUT dose comply with item 5.2 of KDB 680106 D01V03

- Power transfer frequency is less than 1 MHz
Yes, the device operate in the frequency range from 110kHz to 205kHz.
- Output power from each primary coil is less than or equal to 15 watts
Yes, the maximum output power of the primary coil is equal to 15W.
- The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils
Yes, the client device includes only single primary coils.
- Client device is inserted in or placed directly in contact with the transmitter
Yes, Client device is placed directly in contact with the transmitter.
- Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

Yes, It is mobile exposure conditions only.

6. The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Yes, The EUT field strength levels are less than 50% of the MPE limit, refer to test TM1, TM2 list, and the coils can't transmitted simultaneous.

Test Mode: TM1

Electric Field Emissions			
Test Position	Measure Value (V/m)	Limit(V/m)	50% Limit (V/m)
Top	46	614	307
Bottom	51	614	307
Side 1	49	614	307
Side 2	52	614	307
Side 3	46	614	307
Side 4	43	614	307
Magnetic Field Emissions			
Test Position	Measure Value (A/m)	Limit(A/m)	50% Limit (A/m)
Top	0.28	1.63	0.815
Bottom	0.29	1.63	0.815
Side 1	0.32	1.63	0.815
Side 2	0.29	1.63	0.815
Side 3	0.29	1.63	0.815
Side 4	0.28	1.63	0.815

Test Mode: TM2

Electric Field Emissions			
Test Position	Measure Value (V/m)	Limit(V/m)	50% Limit (V/m)
Top	45	614	307
Bottom	43	614	307
Side 1	46	614	307
Side 2	48	614	307
Side 3	43	614	307
Side 4	48	614	307
Magnetic Field Emissions			
Test Position	Measure Value (A/m)	Limit(A/m)	50% Limit (A/m)
Top	0.30	1.63	0.815
Bottom	0.31	1.63	0.815
Side 1	0.26	1.63	0.815

Side 2	0.27	1.63	0.815
Side 3	0.28	1.63	0.815
Side 4	0.27	1.63	0.815

Test Mode: TM3

Electric Field Emissions			
Test Position	Measure Value (V/m)	Limit(V/m)	50% Limit (V/m)
Top	39	614	307
Bottom	35	614	307
Side 1	41	614	307
Side 2	40	614	307
Side 3	41	614	307
Side 4	40	614	307
Magnetic Field Emissions			
Test Position	Measure Value (A/m)	Limit(A/m)	50% Limit (A/m)
Top	0.36	1.63	0.815
Bottom	0.43	1.63	0.815
Side 1	0.38	1.63	0.815
Side 2	0.37	1.63	0.815
Side 3	0.38	1.63	0.815
Side 4	0.37	1.63	0.815

***** END OF REPORT *****