

FCC Part 15C

Measurement and Test Report

For

CE LINK LIMITED

Building G, LiCheng Technology Industrial Zone, GongHe Village, ShaJing
Town, ShenZhen City, China

FCC ID: A4XCEBLUE002

Report Concerns: Original Report	Equipment Type: Bluetooth Audio Redeiver
Model:	<u>CEBLUE002</u>
Report No.:	<u>STR11128034I</u>
Test Date:	<u>2011-12-04 to 2011-12-10</u>
Issue Date:	<u>2011-12-15</u>
Tested By:	<u>Jason Chen / Engineer</u> <i>Jason chen</i>
Reviewed By:	<u>Lahm Peng / EMC Manager</u> <i>Lahm peng</i>
Approved & Authorized By:	<u>Jandy so / PSQ Manager</u> <i>Jandyso</i>
Prepared By:	SEM.Test Compliance Service Co., Ltd. 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C. (518101) Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....4

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4

1.2 TEST STANDARDS.....4

1.3 TEST METHODOLOGY4

1.4 TEST FACILITY5

1.5 EUT EXERCISE SOFTWARE5

1.6 ACCESSORIES EQUIPMENT LIST AND DETAILS5

1.7 EUT CABLE LIST AND DETAILS5

2. SUMMARY OF TEST RESULTS6

3. §15.203 - ANTENNA REQUIREMENT.....7

3.1 STANDARD APPLICABLE.....7

3.2 TEST RESULT.....7

4. NUMBER OF HOPPING CHANNELS AND CHANNEL SPACING8

4.1 STANDARD APPLICABLE.....8

4.2 TEST EQUIPMENT LIST AND DETAILS8

4.3 TEST PROCEDURE.....8

4.4 ENVIRONMENTAL CONDITIONS8

4.5 SUMMARY OF TEST RESULTS/PLOTS9

5. DWELL TIME OF A HOPPING CHANNEL.....11

5.1 STANDARD APPLICABLE.....11

5.2 TEST EQUIPMENT LIST AND DETAILS11

5.3 TEST PROCEDURE.....11

5.4 ENVIRONMENTAL CONDITIONS11

5.5 SUMMARY OF TEST RESULTS/PLOTS12

6. 20-DB BANDWIDTH.....14

6.1 STANDARD APPLICABLE.....14

6.2 TEST EQUIPMENT LIST AND DETAILS14

6.3 TEST PROCEDURE.....14

6.4 ENVIRONMENTAL CONDITIONS14

6.5 SUMMARY OF TEST RESULTS/PLOTS14

7. POWER OUTPUT.....17

7.1 STANDARD APPLICABLE.....17

7.2 TEST EQUIPMENT LIST AND DETAILS17

7.3 TEST PROCEDURE.....17

7.4 ENVIRONMENTAL CONDITIONS17

7.5 SUMMARY OF TEST RESULTS/PLOTS17

8. FIELD STRENGTH OF SPURIOUS EMISSIONS18

8.1 MEASUREMENT UNCERTAINTY18

8.2 STANDARD APPLICABLE.....18

8.3 TEST EQUIPMENT LIST AND DETAILS18

8.4 TEST PROCEDURE.....19

8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....19

8.6 ENVIRONMENTAL CONDITIONS19

8.7 SUMMARY OF TEST RESULTS/PLOTS20

9. OUT OF BAND EMISSIONS.....30

9.1 STANDARD APPLICABLE.....30

9.2 TEST EQUIPMENT LIST AND DETAILS30

9.3 TEST PROCEDURE.....30

9.4 ENVIRONMENTAL CONDITIONS30

9.5 SUMMARY OF TEST RESULTS/PLOTS31

10. §15.207 (A) CONDUCTED EMISSIONS33

10.1 MEASUREMENT UNCERTAINTY33

10.2 TEST EQUIPMENT LIST AND DETAILS33

10.3 TEST PROCEDURE.....33

10.4 BASIC TEST SETUP BLOCK DIAGRAM.....33
10.5 ENVIRONMENTAL CONDITIONS34
10.6 SUMMARY OF TEST RESULTS/PLOTS34
10.7 CONDUCTED EMISSIONS TEST DATA.....34

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: CE LINK LIMITED
 Address of applicant: Building G, LiCheng Technology Industrial Zone, GongHe Village, ShaJing Town, ShenZhen City, China

Manufacturer: CE LINK LIMITED
 Address of manufacturer: Building G, LiCheng Technology Industrial Zone, GongHe Village, ShaJing Town, ShenZhen City, China

General Description of E.U.T

Items	Description
EUT Description:	Bluetooth Audio Receiver
Trade Name:	/
Model No.:	CEBLUE002
Rated Voltage:	3.7V DC
Max. Output Power	1.1792mW
Frequency range:	2402-2480MHz
Number of channels:	79
Channel Separation:	1MHz
Type of Antenna:	Integral Antenna

Note: The test data is gathered from a production sample, provided by the manufacture.

1.2 Test Standards

The following report is prepared on behalf of the CE LINK LIMITED in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes

were adapted with Low Channel, Middle Channel and High Channel, accordingly in reference to the Operating Instructions.

1.4 Test Facility

- **FCC – Registration No.: 994117**

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

- **Industry Canada (IC) Registration No.: 7673A**

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Exercise Software

The EUT exercise program used during the testing was designed to exercise the system components.

1.6 Accessories Equipment List and Details

Description	Manufacturer	Model	Serial Number
/	/	/	/

1.7 EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

2. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§ 15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§ 15.247(a)(1)	Channel Separation	Compliant
§ 15.247(a)(1)(iii)	Time of Occupancy (Dwell time)	Compliant
§ 15.247(a)	20dB Bandwidth	Compliant
§ 15.247(b)(1)	Power Output	Compliant
§ 15.209(a)(f)	Radiated Emission	Compliant
§ 15.247(d)	Band edge	Compliant
§ 15.207(a)	Conducted Emission	Compliant

3. §15.203 - ANTENNA REQUIREMENT

3.1 Standard Applicable

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a permanent antenna, fulfill the requirement of this section.

4. NUMBER OF HOPPING CHANNELS AND CHANNEL SPACING

4.1 Standard Applicable

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

4.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2010-12-20	2011-12-19
Attenuator	ATTEN	ATS100-4-20	/	2010-12-20	2011-12-19

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

4.3 Test Procedure


Set the Lowest channel to the Highest Channel, observed the band of 2400MHz to 2483.5MHz, than count it out the number of channels for comparing with the FCC rules. Adjust channel spacing can be read by adjusting the Analyzer SPAN.

4.4 Environmental Conditions


Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

4.5 Summary of Test Results/Plots


No. of Channel=79




Channel Spacing (Low CH=1MHz)



Channel Spacing (Middle CH=1MHz)



Channel Spacing (High CH=1MHz)



5. DWELL TIME OF A HOPPING CHANNEL

5.1 Standard Applicable

According to 15.247(a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

5.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2010-12-20	2011-12-19
Attenuator	ATTEN	ATS100-4-20	/	2010-12-20	2011-12-19

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

5.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set center frequency of spectrum analyzer = operating frequency.
3. Set the spectrum analyzer as RBW, VBW=100KHz, Span = 0Hz.
4. Repeat above procedures until all frequency measured was complete.

5.4 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar


5.5 Summary of Test Results/Plots

The dwell time within a 31.6 second period in data mode is independent from the packet type (packet length). The calculation for a 31.6 second period is as follows:

$$\text{Dwell time} = \text{time slot length} * \text{hop rate} / \text{number of hopping channels} * 31.6\text{s}$$


Test data is corrected with the worse case, which the packet length is DH1.

CH Low:




$$\text{DH1 time slot} = 0.390 \text{ (ms)} * (1600/(79)) * 31.6 = 249.6 \text{ (ms)} < 400 \text{ (ms)}$$

CH Mid:



$$DH1 \text{ time slot} = 0.390 \text{ (ms)} * (1600/(79)) * 31.6 = 249.6 \text{ (ms)} < 400 \text{ (ms)}$$

CH High:



$$DH1 \text{ time slot} = 0.390 \text{ (ms)} * (1600/(79)) * 31.6 = 249.6 \text{ (ms)} < 400 \text{ (ms)}$$

6. 20-dB BANDWIDTH

6.1 Standard Applicable

According to 15.247(a)(1)(iii). For frequency hopping systems operating in the 2400MHz-2483.5 MHz no limit for 20dB bandwidth.

6.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2010-12-20	2011-12-19
Attenuator	ATTEN	ATS100-4-20	/	2010-12-20	2011-12-19

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

6.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set center frequency of spectrum analyzer = operating frequency.
3. The spectrum analyzer as RBW=10KHz (1 % of Bandwidth.), Sweep=auto
4. Mark the peak frequency and -20dB (upper and lower) frequency.


6.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


6.5 Summary of Test Results/Plots

Frequency MHz	20 dB Bandwidth kHz	Limit dB
2402	1115	/
2441	1122	/
2480	1122	/


CH Low:



CH Mid:



CH High:



7. POWER OUTPUT

7.1 Standard Applicable

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

7.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2010-12-20	2011-12-19
EMI Test Receiver	R&S	ESVB	825471/005	2010-12-20	2011-12-19
Positioning Controller	C&C	CC-C-1F	N/A	2010-12-20	2011-12-19
RF Switch	EM	EMSW18	SW060023	2010-12-20	2011-12-19
Pre-amplifier	Agilent	8447F	3113A06717	2010-12-20	2011-12-19
Pre-amplifier	Compliance Direction	PAP-0118	24002	2010-12-20	2011-12-19
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2011-01-09	2012-01-08
Horn Antenna	ETS	3117	00086197	2011-01-09	2012-01-08

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

7.3 Test Procedure

The device under test has an integral antenna and the power was measured on a radiated basis.

7.4 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

7.5 Summary of Test Results/Plots

2402 MHz 1.0969 mW EIRP

2441 MHz 1.1792 mW EIRP

2480 MHz 1.1140 mW EIRP

Note: The Antenna Gain is under considering.

8. FIELD STRENGTH OF SPURIOUS EMISSIONS

8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.10 dB.

8.2 Standard Applicable

According to §15.247(c), 15.205 15.209(b) & 15.35 (b), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Section 15.209:

30 - 88 MHz 40 dBuV/m @3M

88 -216 MHz 43.5 dBuV/m @3M

216 -960 MHz 46 dBuV/m @3M

Above 960 MHz 54dBuV/m @3M

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

Emissions that fall in the restricted bands (15.205) must be less than 54dBuV/m otherwise the spurious and harmonics must be attenuated by at least 20dB.

8.3 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2010-12-20	2011-12-19
EMI Test Receiver	R&S	ESVB	825471/005	2010-12-20	2011-12-19
Positioning Controller	C&C	CC-C-1F	N/A	2010-12-20	2011-12-19
RF Switch	EM	EMSW18	SW060023	2010-12-20	2011-12-19
Pre-amplifier	Agilent	8447F	3113A06717	2010-12-20	2011-12-19
Pre-amplifier	Compliance Direction	PAP-0118	24002	2010-12-20	2011-12-19
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2011-01-09	2012-01-08
Horn Antenna	ETS	3117	00086197	2011-01-09	2012-01-08
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2011-01-09	2012-01-08

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

8.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.



8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBµV means the emission is 6dBµV below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.6 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

8.7 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst margin of:

-5.84 dB μ V at 4804.0 MHz in the Horizontal polarization for Low Channel, 9 kHz to 25 GHz, 3 Meters


Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

From 30 MHz to 1 GHz

Test Mode: Charging


Comment: AC120V/60Hz; Connect to PC, USB 5V

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	112.1305	18.36	7.24	25.60	40.00	-14.40	360	100	peak
2	163.7550	23.21	4.67	27.88	40.00	-12.12	360	200	peak
3	227.6906	23.54	7.74	31.28	40.00	-8.72	0	200	peak


Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	51.1209	18.19	7.93	26.12	40.00	-13.88	360	100	peak
2	103.8055	16.09	8.11	24.20	43.50	-19.30	0	200	peak


Test Mode: Transmitting-Low channel (2402MHz)

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	112.9196	15.24	6.45	21.69	43.50	-21.81	360	100	peak
2	334.8589	14.06	9.12	23.18	46.00	-22.82	0	100	peak


Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	42.0066	14.86	7.95	22.81	40.00	-17.19	0	200	peak
2	98.1419	14.91	7.69	22.60	43.50	-20.90	0	200	peak
3	385.2805	14.72	9.96	24.68	46.00	-21.32	360	200	peak


Test Mode: Transmitting-Middle channel (2441MHz)

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	299.3158	14.89	8.65	23.54	46.00	-22.46	360	100	peak
2	215.2678	16.10	6.18	22.28	43.50	-21.22	0	100	peak
3	517.2480	16.66	12.72	29.38	46.00	-16.62	360	100	peak


Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	38.6161	16.21	7.57	23.78	40.00	-16.22	360	100	peak
2	98.1419	14.91	7.69	22.60	43.50	-20.90	0	200	peak


Test Mode: Transmitting-High channel (2480MHz)

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	61.7781	15.59	6.48	22.07	40.00	-17.93	360	100	peak
2	103.0800	14.80	7.55	22.35	43.50	-21.15	0	200	peak
3	249.4250	14.92	7.67	22.59	46.00	-23.41	0	200	peak

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	38.6161	16.21	7.57	23.78	40.00	-16.22	0	200	peak
2	98.1419	14.91	7.69	22.60	43.50	-20.90	0	200	peak
3	374.6226	15.78	9.84	25.62	46.00	-20.38	0	200	peak

Spurious Emissions Above 1GHz

Frequency MHz	Detector	Meter Reading dBuV	Direction Degree	Polar H / V	Antenna Loss dB	Cable loss dB	Amplifier dB	Correction Amplitude dBuV/m	Limit dBuV/m	Margin dB
Low Channel (2402MHz)										
4804.0	AV	41.86	57	H	34.1	5.2	33.0	48.16	54	-5.84
4804.0	AV	39.96	35	V	34.1	5.2	33.0	46.26	54	-7.74
7206.0	AV	32.31	60	H	37.4	6.1	33.5	42.31	54	-11.69
7206.0	AV	31.02	79	V	37.4	6.1	33.5	41.02	54	-12.98
2402.0	AV	81.65	45	H	29.1	3.7	34.0	80.45		(Fund.)
2402.0	AV	81.41	359	V	29.1	3.7	34	80.21		(Fund.)
4804.0	PK	46.38	65	H	34.1	5.2	33.0	52.68	74	-21.32
4804.0	PK	42.18	98	V	34.1	5.2	33.0	48.48	74	-25.52
7206.0	PK	37.32	256	H	37.4	6.1	33.5	47.32	74	-26.68
7206.0	PK	36.26	185	V	37.4	6.1	33.5	46.26	74	-27.74
2402.0	PK	85.37	78	H	29.1	3.7	34.0	84.17		(Fund.)
2402.0	PK	82.61	44	V	29.1	3.7	34.0	81.41		(Fund.)
Middle Channel (2441MHz)										
4882.0	AV	37.95	21	H	34.1	5.2	33.0	44.25	54	-9.75
4882.0	AV	39.89	34	V	34.1	5.2	33.0	46.19	54	-7.81
7323.0	AV	29.36	342	H	37.4	6.1	33.5	39.36	54	-14.64
7323.0	AV	30.21	30	V	37.4	6.1	33.5	40.21	54	-13.79
2441.0	AV	82.92	98	H	29.1	3.7	34	81.72		(Fund.)
2441.0	AV	80.54	72	V	29.1	3.7	34	79.34		(Fund.)
4882.0	PK	44.96	237	H	34.1	5.2	33.0	51.26	74	-22.74
4882.0	PK	45.97	354	V	34.1	5.2	33.0	52.27	74	-21.73
7323.0	PK	37.2	264	H	37.4	6.1	33.5	47.2	74	-26.8
7323.0	PK	39.26	187	V	37.4	6.1	33.5	49.26	74	-24.74
2441.0	PK	86.61	55	H	29.1	3.7	34	85.41		(Fund.)
2441.0	PK	81.81	49	V	29.1	3.7	34	80.61		(Fund.)

High Channel (2480MHz)										
4960.0	AV	37.88	21	H	34.1	5.2	33	44.18	54	-9.82
4960.0	AV	36.31	34	V	34.1	5.2	33	42.61	54	-11.39
7440.0	AV	36.03	355	H	37.4	6.1	33.5	46.03	54	-7.97
7440.0	AV	35.84	66	V	37.4	6.1	33.5	45.84	54	-8.16
2480.0	AV	83.82	63	H	29.1	3.7	34.0	82.62		(Fund.)
2480.0	AV	82.76	85	V	29.1	3.7	34.0	81.56		(Fund.)
4960.0	PK	41.84	237	H	34.1	5.2	33	48.14	74	-25.86
4960.0	PK	40.29	354	V	34.1	5.2	33	46.59	74	-27.41
7440.0	PK	41.95	269	H	37.4	6.1	33.5	51.95	74	-22.05
7440.0	PK	41.38	64	V	37.4	6.1	33.5	51.38	74	-22.62
2480.0	PK	88.41	85	H	29.1	3.7	34.0	87.21		(Fund.)
2480.0	PK	86.57	55	V	29.1	3.7	34.0	85.37		(Fund.)

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5th Harmonics is close to the noise base even antenna close up to 1meter distance according the measurement of ANSI C63.4.

The measurements greater than 20dB below the limit from 9kHz to 30MHz..

9. OUT OF BAND EMISSIONS

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

9.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2010-12-20	2011-12-19
EMI Test Receiver	R&S	ESVB	825471/005	2010-12-20	2011-12-19
Positioning Controller	C&C	CC-C-1F	N/A	2010-12-20	2011-12-19
RF Switch	EM	EMSW18	SW060023	2010-12-20	2011-12-19
Pre-amplifier	Agilent	8447F	3113A06717	2010-12-20	2011-12-19
Pre-amplifier	Compliance Direction	PAP-0118	24002	2010-12-20	2011-12-19
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2011-01-09	2012-01-08
Horn Antenna	ETS	3117	00086197	2011-01-09	2012-01-08

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

9.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW, VBW=100KHz, Span=100MHz, Sweep = auto
3. Set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2438.5MHz, then mark the higher-level emission for comparing with the FCC rules.

9.4 Environmental Conditions


Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.5 Summary of Test Results/Plots

Test mode	Frequency MHz	Limit dBuV /dB	Result
Lowest	2310.00	<54dBuV	Pass
	2390.00	<54dBuV	Pass
	2400.00	>20dB	Pass
Highest	2483.50	<54dBuV	Pass
	2500.00	<54dBuV	Pass


The edge emissions are below the FCC 15.209 Limits. Please refer to the test plots below.

Lowest Bandedge



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	36.35	-7.51	28.84	54.00	-25.16	Average Detector
	2310.000	48.26	-7.51	40.75	74.00	-33.25	Peak Detector
2	2390.000	36.31	-7.34	28.97	54.00	-25.03	Average Detector
	2390.000	47.61	-7.34	40.27	74.00	-33.73	Peak Detector
3	2400.000	61.25	-7.31	53.94	/	/	Average Detector
4	2402.200	87.08	-7.31	79.77	/	/	Average Detector

Highest Bandedge



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	54.44	-7.13	47.31	54.00	-6.69	Average Detector
	2483.500	61.24	-7.13	54.11	74.00	-19.89	Peak Detector
2	2500.000	36.31	-7.08	29.23	54.00	-24.77	Average Detector
	2500.000	48.61	-7.08	41.53	74.00	-32.47	Peak Detector

10. §15.207 (a) CONDUCTED EMISSIONS

10.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

10.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2010-12-20	2011-12-19
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2010-12-20	2011-12-19
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2010-12-20	2011-12-19

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

10.3 Test Procedure

Test is conducting under the description of ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

10.4 Basic Test Setup Block Diagram



10.5 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

10.6 Summary of Test Results/Plots

According to the data in section 10.7, the EUT complied with the FCC Part 15.207 Conducted margin for a Class B device, with the *worst* margin reading of:

-9.67 dBµV at 210 kHz in the Neutral mode, QP detector, 0.15-30MHz

10.7 Conducted Emissions Test Data

LINE CONDUCTED EMISSIONS				FCC PART 15.207	
Frequency	Amplitude	Detector	Phase	Limit	Margin
MHz	dBµV	QP/Ave/Pk	Line/Neutral	dBµV	dB
0.210	53.44	QP	Neutral	63.11	-9.67
0.210	42.57	Ave	Neutral	53.20	-10.63
0.174	53.30	QP	Line	64.76	-11.46
4.090	33.69	Ave	Line	45.99	-12.30
0.634	32.98	Ave	Neutral	45.99	-13.01
0.282	37.38	Ave	Line	50.75	-13.37
4.798	32.13	Ave	Neutral	46.00	-13.87
0.634	31.80	Ave	Line	46.00	-14.20
1.342	29.27	Ave	Neutral	45.99	-16.72
0.986	29.26	Ave	Line	45.99	-16.73
7.122	32.81	Ave	Line	49.99	-17.18
7.902	32.45	Ave	Neutral	49.99	-17.54
3.594	38.05	QP	Line	55.99	-17.94
4.658	37.57	QP	Neutral	55.99	-18.42
0.390	39.31	QP	Line	58.05	-18.74

Emission attenuated more than 20dB of the limit is not reported.

Plot of Conducted Emissions Test Data

Conducted Disturbance

EUT: Bluetooth Audio Receiver

M/N: CEBLUE002

Operating Condition: Charging


Test Specification: N

Comment: 120V/60Hz; USB 5V



RBW 9 kHz
MT 4 ms

Att 10 dB AUTO



Plot of Conducted Emissions Test Data

Conducted Disturbance

EUT: Bluetooth Audio Receiver

M/N: CEBLUE002

Operating Condition: Charging


Test Specification: L

Comment: 120V/60Hz; USB 5V



RBW 9 kHz
MT 4 ms

Att 10 dB AUTO



***** END OF REPORT *****