


MosArt Antenna Specifications

主要技術指標		Main technical specifications	
頻率 (MHz)	2400/2450/2500	Frequency (MHz)	2400/2450/2500
特性阻抗 (Ω)	50 ± 10	Impedance (Ω)	50 ± 10
增益 (dBi)	max 0.11	Gain (dBi)	max 0.11
輸出電壓駐波比	< 1.0	VSWR	< 1.0
最大功率	1mW	Admitted power	1mW
極化方式	垂直極化	Polarization	Linear, Vertical
方向性	全向性	Radiation	Omni-directional
連接方式	SMA	Connector Type	SMA
物理性能		Physical properties	
天線材料	PCB	Antenna base	PCB
工作溫度	-20°C ~ +60°C	Operating temp	-20°C ~ +60°C
保存溫度	-20°C ~ +70°C	Storage temp	-20°C ~ +70°C
			

Lenovo (Beijing) Limited

201-H2-6, Floor 2, Building 2, No. 6 Shangdi West Road, Haidian District, Beijing, China



Neutron Engineering Inc.

Test Result (Gain)


Frequency (MHz)	Max Gain (dBi)	
	Vertical	Horizontal
2400	-8.12	0.11
2450	-7.50	-0.49
2500	-6.89	-0.78



Neutron Engineering Inc.

Antenna Pattern-Vertical

2400 MHz 2450 MHz 2500 MHz




NEUTRON ENGINEERING INC.

No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792



Neutron Engineering Inc.

Antenna Pattern-Horizontal



NEUTRON ENGINEERING INC.

No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792