



FCC ID: A5MBT500A

According to KDB 447498 D01 General RF Exposure Guidance v06, section 4.3.1

At 100 MHz to 6 GHz and for test separation distances  $\leq 50\text{mm}$ , the SAR test exclusion threshold is determined according to the following

$$\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \times \sqrt{f(\text{GHz})} \leq 3.0$$

### 1. SAR test exclusion threshold

**Frequency: 2 480 MHz (min. separation distances = 5 mm)**

SAR test exclusion thresholds (5 mm) =  $3 \times 5 / (\sqrt{2.480}) = 9.525 \text{ mW}$

Test mode	Max. Tune-up Tolerance (mW)	SAR Test Exclusion Thresholds (5mm) (mW)
Classic BT	4.0	9.525

Calculation value:  $4.00 \text{ (mW)} / 5 \text{ (mm)} \times \sqrt{2.480} = 1.260$

So, Calculation value  $\leq 3.0$

Remark:

-For Classic BT Max. conducted power is 3.02 (mW), so 4.00 (mW) was calculated.

-When the minimum test separation distance is  $< 5 \text{ mm}$ , a distance of 5 mm is applied to determine SAR test exclusion.

**2. Conclusion: No SAR is required.**