


Prüfbericht-Nr.: <i>Test Report No.:</i>	17054571 001	Auftrags-Nr.: <i>Order No.:</i>	164049653	Seite 1 von 21 Page 1 of 21
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	381128	Auftragsdatum: <i>Order date:</i>	12.10.2015	
Auftraggeber: <i>Client:</i>	Lenovo (Beijing) Limited, No. 6, Chuang Ye Road, Shangdi Information Industry Base, Haidian District, Beijing 100085, P.R. China			
Prüfgegenstand: <i>Test item:</i>	Lenovo 300 Wireless Compact Mouse			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	L300			
Auftrags-Inhalt: <i>Order content:</i>	FCC approval			
Prüfgrundlage: <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.249 FCC KDB publication 447498 D01 v06			
Wareneingangsdatum: <i>Date of receipt:</i>	19.11.2015			
Prüfmuster-Nr.: <i>Test sample No.:</i>	A000283294-001, A000283294-002, A000283294-003			
Prüfzeitraum: <i>Testing period:</i>	24.11.2015 - 14.12.2015			
Ort der Prüfung: <i>Place of testing:</i>	Accurate Technology Co., Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von / tested by: 		kontrolliert von / reviewed by: 		
15.12.2015	Lin Lin / Project Manager	15.12.2015	Sam Lin / Technical Certifier	
Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>
				Unterschrift <i>Signature</i>
Sonstiges / Other: This report is for DXX equipment class.				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht - Nr.: 17054571 001
Test Report No.

Seite 2 von 21
Page 2 of 21

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 FIELD STRENGTH OF FUNDAMENTAL AND HARMONICS

RESULT: Pass

5.1.3 20dB BANDWIDTH AND 99% BANDWIDTH

RESULT: Pass

5.1.4 OUT-OF-BAND EMISSIONS

RESULT: Pass

CONTENTS

1.	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS	4
2.	TEST SITES	4
2.1	TEST FACILITIES	4
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	5
2.3	TRACEABILITY	6
2.4	CALIBRATION	6
2.5	MEASUREMENT UNCERTAINTY.....	6
2.6	LOCATION OF ORIGINAL DATA.....	6
2.7	STATUS OF FACILITY USED FOR TESTING.....	6
3.	GENERAL PRODUCT INFORMATION	7
3.1	PRODUCT FUNCTION AND INTENDED USE.....	7
3.2	RATINGS AND SYSTEM DETAILS	7
3.3	INDEPENDENT OPERATION MODES	8
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	9
3.5	SUBMITTED DOCUMENTS	9
4.	TEST SET-UP AND OPERATION MODES	9
4.1	PRINCIPLE OF CONFIGURATION SELECTION.....	9
4.2	TEST OPERATION AND TEST SOFTWARE	9
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	10
4.5	TEST SETUP DIAGRAM	11
5.	TEST RESULTS	13
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	13
5.1.1	Antenna Requirement	13
5.1.2	Field strength of fundamental and harmonics.....	14
5.1.3	20dB Bandwidth and 99% Bandwidth.....	15
5.1.4	Out-of-band emissions	18
6.	PHOTOGRAPHS OF THE TEST SET-UP	19
7.	LIST OF TABLES	21
8.	LIST OF PHOTOGRAPHS	21

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of 2.4 GHz Wireless mode

Appendix B: Test Results of RF Exposure - 2.4 GHz Wireless mode

2. Test Sites

2.1 Test Facilities

Accurate Technology Co., Ltd.

(FCC Registration No.: 752051 & IC Registration Number: 5077A-2)

F1, Bldg A, Changyuan New Material Port, Keyuan Rd., Science & Industry Park,
Nanshan District, Shenzhen, 518057, P.R. China

The tests at the test site have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Type	S/N	Calibrated until
Radio Spectrum Test				
Spectrum Analyzer	Rohde&Schwarz	FSV40	101495	Jan.11, 2016
Test Receiver	Rohde& Schwarz	ESR	101817	Jul. 30, 2016
Spectrum Analyzer	Rohde&Schwarz	FSP30	100220	Jan.21, 2016
Radiated emissions				
Spectrum Analyzer	Rohde&Schwarz	FSV40	101495	Jan.11, 2016
Test Receiver	Rohde& Schwarz	ESR	101817	Jul. 30, 2016
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan.15, 2016
Bilog Antenna	Schwarzbeck	VULB9163	9163-194	Jan.15, 2016
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan.15, 2016
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan.11, 2016
RF Switching Unit+PreAMP	Compliance Direction	RSU-M2	38322	Jan.11, 2016
Pre-Amplifier	Agilent	8447D	294A10619	Jan.11, 2016
Pre-Amplifier	Rohde&Schwarz	CBLU1183540-01	3791	Jan.11, 2016

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table,

Items		Extended Uncertainty
CE	Disturbance Voltage (dBuV)	U=1.94dB, k=2, σ =95%
RE (9kHz-30MHz)	Field strength (dBuV/m)	U=3.08dB, k=2, σ =95%
RE (30-1000MHz)	Field strength (dBuV/m)	U=4.42dB, k=2, σ =95%
RE (above 1000MHz)	Field strength (dBuV/m)	U=4.06dB, k=2, σ =95%

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The Accurate Technology Co., Ltd. facility located at F1, Bldg A, Changyuan New Material Port, Keyuan Rd., Science & Industry Park, Nanshan District, Shenzhen, 518057, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3. General Product Information

3.1 Product Function and Intended Use

The EUT is Lenovo 2.4 GHz wireless mouse.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

Technical Specification	Value
Kind of Equipment:	Lenovo 300 Wireless Compact Mouse
Type Designation:	L300
FCC ID:	A5ML300
IC:	5903G-L300
Type of Equipment:	Class B digital equipment
Equipment Class:	DXX
Wireless Technology:	2.4 GHz Wireless
Rated output power:	0 dBm
Operating Frequency Range:	2402-2479 MHz for 2.4 GHz Wireless
Channel Number:	78 channels for 2.4 GHz Wireless
Channel Separation:	1 MHz for 2.4 GHz Wireless
Type of Modulation:	GFSK
Operating Voltage:	DC 1.5V via AA ALKALINE battery
Operating Temperature Range:	0°C to 40°C
Antenna Type:	Printed PCB Antenna for 2.4 GHz
Smart Antenna Systems:	Not Applicable
Number of Antenna:	1
Antenna Gain:	Max. -0.28dBi

Table 3: List of Radio Frequency Channel, 2.4 GHz Wireless

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
0	2402.00	21	2423.00	42	2444.00	63	2465.00
1	2403.00	22	2424.00	43	2445.00	64	2466.00
2	2404.00	23	2425.00	44	2446.00	65	2467.00
3	2405.00	24	2426.00	45	2447.00	66	2468.00
4	2406.00	25	2427.00	46	2448.00	67	2469.00
5	2407.00	26	2428.00	47	2449.00	68	2470.00
6	2408.00	27	2429.00	48	2450.00	69	2471.00
7	2409.00	28	2430.00	49	2451.00	70	2472.00
8	2410.00	29	2431.00	50	2452.00	71	2473.00
9	2411.00	30	2432.00	51	2453.00	72	2474.00
10	2412.00	31	2433.00	52	2454.00	73	2475.00
11	2413.00	32	2434.00	53	2455.00	74	2476.00
12	2414.00	33	2435.00	54	2456.00	75	2477.00
13	2415.00	34	2436.00	55	2457.00	76	2478.00
14	2416.00	35	2437.00	56	2458.00	77	2479.00
15	2417.00	36	2438.00	57	2459.00	--	--
16	2418.00	37	2439.00	58	2460.00	--	--
17	2419.00	38	2440.00	59	2461.00	--	--
18	2420.00	39	2441.00	60	2462.00	--	--
19	2421.00	40	2442.00	61	2463.00	--	--
20	2422.00	41	2443.00	62	2464.00	--	--

3.3 Independent Operation Modes

The basic operation modes are:

- A. 2.4GHz Wireless operating
 - 1. Transmitting
 - a. Low channel
 - b. Middle channel
 - c. High channel
 - 2. Receiving
 - a. Low channel
 - b. Middle channel
 - c. High channel
- B. Standby
- C. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Bill of Material	- Circuit Diagram
- PCB Layout	- Instruction Manual
- Photo Document	- Rating Label

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5.

Table 4: List of Frequencies under Test, 2.4 GHz Wireless operation

RF channel of 2.4 GHz Wireless			
Test Channel	Channel Number	Frequency (MHz)	Remark
Low	0	2402.00	Max. output power level
Middle	37	2439.00	Max. output power level
High	77	2479.00	Max. output power level

4.3 Special Accessories and Auxiliary Equipment

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Laptop	Lenovo	ThinkPad X240	PD-01UAM3	Input: DC 20V, 3.25A
Printer	HP	HP Laserjet 1015	CNFG030424	--
2.4 GHz USB Dongle	Lenovo	RG10	--	Input: DC 5V

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test below 1 GHz




Diagram of Measurement Configuration for Radiation Test above 1 GHz




Diagram of Measurement Equipment Configuration for Conduction Measurement





Diagram of Measurement Equipment Configuration for Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Pass**

Test date : 2015-11-24 to 2015-12-04
Test standard : Part 15.203

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is -0.28 dBi for 2.4 GHz, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to compliance the provision.

Refer to EUT photo for details.

5.1.2 Field strength of fundamental and harmonics

RESULT:
Pass

Date of testing : 2015-11-24 to 2015-12-04
 Test standard : FCC part 15.249(a)
 Clause A2.9(a) of RSS-210
 Basic standard : ANSI C63.10:2013
 Limits : Refer to 15.249(a)
 Clause A2.9(a) of RSS-210
 Kind of test site : 3m Semi-Anechoic Chamber

Test setup

Test Channel : Low/ Middle/ High
 Operation mode : A.1
 Ambient temperature : 23°C
 Relative humidity : 48%
 Atmospheric pressure : 101.0 kPa

Table 6: Test result of Field strength of fundamental and harmonics, 2.4 GHz Wireless operation

2.4 GHz Wireless						
Test Channel	Frequency (MHz)	Measured Result (dBuV/m)	Limit (dBuV/m)	Detector	Polarity	Verdict
Low	2402	85.16	114	Peak	Horizontal	Pass
		72.39	94	Average		
		84.94	114	Peak	Vertical	Pass
		72.17	94	Average		
Middle	2439	84.94	114	Peak	Horizontal	Pass
		72.17	94	Average		
	4878	43.78	74	Peak		
		31.01	54	Average		
	2439	73.42	114	Peak	Vertical	Pass
		60.65	94	Average		
High	2479	82.00	114	Peak	Horizontal	Pass
		69.23	94	Average		
	4958	44.84	74	Peak		
		32.07	54	Average		
	2479	73.23	114	Peak	Vertical	Pass
		60.46	94	Average		

Note:

- The average value of fundamental = Peak value + 20*log(Duty cycle).
- Duty cycle = TX_{on}/TX_{on+off} = 0.23, hence 20*log(Duty cycle) = -12.77dB.

5.1.3 20dB Bandwidth and 99% Bandwidth

RESULT:**Pass**

Date of testing : 2015-11-24 to 2015-12-14
Test standard : FCC part 15.215
Clause 6.6 of RSS-Gen
Basic standard : ANSI C63.10:2013
Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
Operation mode : A.1
Ambient temperature : 23°C
Relative humidity : 48%
Atmospheric pressure : 101.0 kPa

Table 7: Test result of 20dB Bandwidth and 99% Bandwidth, 2.4 GHz Wireless operation

2.4 GHz Wireless				
Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)	Verdict
Low Channel	2402	1899.00	1852.39	Pass
Mid Channel	2439	1887.00	1620.84	Pass
High Channel	2479	1957.00	1655.57	Pass


Test Graph of 99% Bandwidth, 2.4 GHz Wireless mode

Low Channel



Middle Channel



High Channel


Date: 30.NOV.2015 14:21:09

5.1.4 Out-of-band emissions

RESULT:**Pass**

Date of testing	:	2015-11-24 to 2015-12-04
Test standard	:	FCC part 15.249(d) Clause A2.9(b) of RSS-210
Basic standard	:	ANSI C63.10:2013
Limits	:	Refer to 15.249(d) Clause A2.9(b) of RSS-210
Kind of test site	:	3m Semi-Anechoic Chamber & Full-Anechoic Chamber

Test setup

Test Channel	:	Low/ Middle/ High
Operation mode	:	A.1
Ambient temperature	:	23°C
Relative humidity	:	48%
Atmospheric pressure	:	101.0 kPa

Refer to attached Appendix A for details.

7. List of Tables

Table 1: List of Test and Measurement Equipment	5
Table 2: Technical Specification of EUT	7
Table 3: List of Radio Frequency Channel, 2.4 GHz Wireless	8
Table 4: List of Frequencies under Test, 2.4 GHz Wireless operation	9
Table 5: List of Accessories and Auxiliary Equipment	10
Table 6: Test result of Field strength of fundamental and harmonics, 2.4 GHz Wireless operation	14
Table 7: Test result of 20dB Bandwidth and 99% Bandwidth, 2.4 GHz Wireless operation	15

8. List of Photographs

Photograph 1: Set-up for Spurious Emissions (9kHz-30MHz)	19
Photograph 2: Set-up for Spurious Emissions (30MHz-1GHz)	19
Photograph 3: Set-up for Spurious Emissions (1GHz-18GHz)	20
Photograph 4: Set-up for Spurious Emissions (18GHz-26GHz)	20

Appendix A

Test Results of 2.4 GHz Wireless Mode

APPENDIX A.1: SPURIOUS EMISSIONS OF 2.4 GHZ WIRELESS OPERATION 2

Low Channel..... 2

Middle Channel..... 11

High Channel..... 20

APPENDIX A.2: RADIATED EMISSIONS IN RESTRICTED BANDS - 2.4 GHZ WIRELESS OPERATION 29

Low Channel..... 29

High Channel..... 31

Appendix A.1: Spurious Emissions of 2.4 GHz Wireless operation Low Channel


ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2402MHz
 Test Site: 2# Chamber
 Operator: LAN
 Test Specification: DC 1.5V
 Comment: X
 Start of Test: 2015-12-01 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2402MHz
 Test Site: 2# Chamber
 Operator: LAN
 Test Specification: DC 1.5V
 Comment: Y
 Start of Test: 2015-12-01 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70		IF	Transducer
Start	Stop	Step	Detector	Meas. Time	Bandw.	
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2402MHz
 Test Site: 2# Chamber
 Operator: LAN
 Test Specification: DC 1.5V
 Comment: Z
 Start of Test: 2015-12-01 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M





ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2027

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2402MHz

Model: L300

Manufacturer: Lenovo

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	900.1473	22.16	1.28	23.44	46.00	-22.56	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2028

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2402MHz

Model: L300

Manufacturer: Lenovo

Polarization: Vertical

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	824.5968	23.44	0.42	23.86	46.00	-22.14	QP			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2033

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2402MHz

Model: L300

Manufacturer: Lenovo

Polarization: Vertical

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	86.29	-7.45	78.84	/	/	peak			
2	2402.000	84.46	-7.45	77.01	/	/	AVG			
3	15221.824	9.16	40.66	49.82	74.00	-24.18	peak			
4	15221.824	-0.54	40.66	40.12	54.00	-13.88	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2034

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2402MHz

Model: L300

Manufacturer: Lenovo

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	92.61	-7.45	85.16	/	/	peak			
2	2402.000	90.37	-7.45	82.92	/	/	AVG			
3	16081.142	9.41	40.05	49.46	74.00	-24.54	peak			
4	16081.142	9.41	40.05	49.46	54.00	-4.54	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2043

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2402MHz

Model: L300

Manufacturer: Lenovo

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26184.163	33.48	16.50	49.98	74.00	-24.02	peak			
2	26184.163	21.87	16.50	38.37	54.00	-15.63	AVG			

Produkte
Products



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2044

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2402MHz

Model: L300

Manufacturer: Lenovo

Polarization: Vertical

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26428.351	34.03	16.50	50.53	74.00	-23.47	peak			
2	26428.351	22.10	16.50	38.60	54.00	-15.40	AVG			

Middle Channel


ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2439MHz
 Test Site: 2# Chamber
 Operator: LAN
 Test Specification: DC 1.5V
 Comment: X
 Start of Test: 2015-12-01 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2439MHz
 Test Site: 2# Chamber
 Operator: LAN
 Test Specification: DC 1.5V
 Comment: Y
 Start of Test: 2015-12-01 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2439MHz
 Test Site: 2# Chamber
 Operator: LAN
 Test Specification: DC 1.5V
 Comment: Z
 Start of Test: 2015-12-01 /

SCAN TABLE: "LFRE Fin"

Short Description:				_SUB_STD_VTERM2 1.70		IF	Transducer
Start	Stop	Step	Detector	Meas. Time	Bandw.		
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M	
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M	





ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2029

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2439MHz

Model: L300

Manufacturer: Lenovo

Polarization: Vertical

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	851.0353	23.65	0.72	24.37	46.00	-21.63	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2030

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2439MHz

Model: L300

Manufacturer: Lenovo

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	854.0247	23.40	0.74	24.14	46.00	-21.86	QP			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2037

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2439MHz

Model: L300

Manufacturer: Lenovo

Polarization: Vertical

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2439.000	80.78	-7.36	73.42	/	/	peak			
2	2439.000	78.05	-7.36	70.69	/	/	AVG			
3	14916.942	8.33	41.35	49.68	74.00	-24.32	peak			
4	14916.942	-1.46	41.35	39.89	54.00	-14.11	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2038

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2439MHz

Model: L300

Manufacturer: Lenovo

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2439.000	92.30	-7.36	84.94	/	/	peak			
2	2439.000	90.12	-7.36	82.76	/	/	AVG			
3	4878.022	43.67	0.11	43.78	74.00	-30.22	peak			
4	4878.022	35.78	0.11	35.89	54.00	-18.11	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2045

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2439MHz

Model: L300

Manufacturer: Lenovo

Polarization: Vertical

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25112.941	33.99	16.50	50.49	74.00	-23.51	peak			
2	25112.941	21.84	16.50	38.34	54.00	-15.66	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2046

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2439MHz

Model: L300

Manufacturer: Lenovo

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26133.575	33.17	16.50	49.67	74.00	-24.33	peak			
2	26133.575	21.45	16.50	37.95	54.00	-16.05	AVG			

High Channel


ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2479MHz
 Test Site: 2# Chamber
 Operator: LAN
 Test Specification: DC 1.5V
 Comment: X
 Start of Test: 2015-12-01 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2479MHz
 Test Site: 2# Chamber
 Operator: LAN
 Test Specification: DC 1.5V
 Comment: Y
 Start of Test: 2015-12-01 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2479MHz
 Test Site: 2# Chamber
 Operator: LAN
 Test Specification: DC 1.5V
 Comment: Z
 Start of Test: 2015-12-01 /

SCAN TABLE: "LFRE Fin"

Short Description:				_SUB_STD_VTERM2 1.70		
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M





ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2031

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2479MHz

Model: L300

Manufacturer: Lenovo

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	863.0561	23.67	0.96	24.63	46.00	-21.37	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2032

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2479MHz

Model: L300

Manufacturer: Lenovo

Polarization: Vertical

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	854.0247	23.75	0.74	24.49	46.00	-21.51	QP			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2039

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2479MHz

Model: L300

Manufacturer: Lenovo

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	89.37	-7.37	82.00	/	/	peak			
2	2479.000	87.86	-7.37	80.49	/	/	AVG			
3	4958.027	44.33	0.51	44.84	74.00	-29.16	peak			
4	4958.027	34.51	0.51	35.02	54.00	-18.98	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2040

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2479MHz

Model: L300

Manufacturer: Lenovo

Polarization: Vertical

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	80.60	-7.37	73.23	/	/	peak			
2	2479.000	78.05	-7.37	70.68	/	/	AVG			
3	16891.045	8.61	41.39	50.00	74.00	-24.00	peak			
4	16891.045	-1.87	41.39	39.52	54.00	-14.48	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2047

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2479MHz

Model: L300

Manufacturer: Lenovo

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26002.504	33.85	16.50	50.35	74.00	-23.65	peak			
2	26002.504	22.31	16.50	38.81	54.00	-15.19	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2048

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2479MHz

Model: L300

Manufacturer: Lenovo

Polarization: Vertical

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25151.823	32.49	16.50	48.99	74.00	-25.01	peak			
2	25151.823	21.33	16.50	37.83	54.00	-16.17	AVG			

Appendix A.2: Radiated Emissions in Restricted Bands - 2.4 GHz Wireless operation
 Low Channel
**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2035

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2402MHz

Model: L300

Manufacturer: Lenovo

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2400.000	65.82	-7.46	58.36	74.00	-15.64	peak			
2	2400.000	56.42	-7.46	48.96	54.00	-5.04	AVG			
3	2402.000	91.06	-7.45	83.61	114.00	-30.39	peak			
4	2402.000	83.78	-7.45	76.33	94.00	-17.67	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2036

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2402MHz

Model: L300

Manufacturer: Lenovo

Polarization: Vertical

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2400.000	53.59	-7.46	46.13	74.00	-27.87	peak			
2	2400.000	46.35	-7.46	38.89	54.00	-15.11	AVG			
3	2402.000	83.48	-7.45	76.03	114.00	-37.97	peak			
4	2402.000	74.97	-7.45	67.52	94.00	-26.48	AVG			

High Channel

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2041

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2479MHz

Model: L300

Manufacturer: Lenovo

Polarization: Vertical

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	76.39	-7.37	69.02	114.00	-44.98	peak			
2	2479.000	69.16	-7.37	61.79	94.00	-32.21	AVG			
3	2492.300	43.26	-7.39	35.87	74.00	-38.13	peak			
4	2492.300	32.49	-7.39	25.10	54.00	-28.90	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ian2015-2 #2042

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Lenovo 300 Wireless Compact Mouse

Mode: TX 2479MHz

Model: L300

Manufacturer: Lenovo

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2015-11-30

Time:

Engineer Signature: PEI

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	87.62	-7.37	80.25	114.00	-33.75	peak			
2	2479.000	78.57	-7.37	71.20	94.00	-22.80	AVG			
3	2491.100	44.34	-7.38	36.96	74.00	-37.04	peak			
4	2491.100	33.49	-7.38	26.11	54.00	-27.89	AVG			

Appendix B

Test Results of RF Exposure - 2.4 GHz Wireless Mode

APPENDIX B.1: RF EXPOSURE COMPLIANCE	2
--	---

Appendix B.1: RF Exposure Compliance

Radio Frequency Exposure Compliance

RESULT:

Pass

Test standard : FCC 1.1310
RSS-102 Issue 5
KDB 447498 D01 General RF Exposure Guidance v06

This device is 2.4 GHz wireless device.

Since the maximum peak output power of the transmitter is 0.60 mw, and the separation between body and antenna is 5 mm. The maximum peak output power is less than 10mW (FCC Limit) and 4mW (IC Limit), hence the EUT is excluded from SAR evaluation according to FCC KDB 447498 D01: Mobile Portable RF Exposure and RSS-102 Issue 5.