

Prüfbericht-Nr.: <i>Test Report No.:</i>	50072565 001	Auftrags-Nr.: <i>Order No.:</i>	164082609	Seite 1 von 60 <i>Page 1 of 60</i>	
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	06.01.2017		
Auftraggeber: <i>Client:</i>	Lenovo (Beijing) Limited, No.6 Chuang Ye Road, Shangdi Information Industry Base, Haidian District, Beijing, China				
Prüfgegenstand: <i>Test item:</i>	Lenovo 300 Wireless Compact Mouse				
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	L300 (Lenovo)				
Auftrags-Inhalt: <i>Order content:</i>	FCC/IC Certification				
Prüfgrundlage: <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.249 RSS-210 Issue 9 August 2016 FCC KDB Publication 447498 D01 v06		CFR47 FCC Part 15: Subpart C Section 15.209 RSS-Gen Issue 4 November 2014 RSS-102 Issue 5 March 2015		
Wareneingangsdatum: <i>Date of receipt:</i>	16.01.2017				
Prüfmuster-Nr.: <i>Test sample No.:</i>	A000476499-001, A000476499-002				
Prüfzeitraum: <i>Testing period:</i>	16.01.2017 - 16.02.2017				
Ort der Prüfung: <i>Place of testing:</i>	Accurate Technology Co., Ltd.				
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüfergebnis*: <i>Test result*:</i>	Pass				
geprüft von / tested by:		kontrolliert von / reviewed by:			
23.02.2017	Andy Yan/Project Manager	23.02.2017	Owen Tian/Technical Certifier		
Datum	Name / Stellung	Unterschrift	Datum	Name / Stellung	Unterschrift
Date	Name / Position	Signature	Date	Name / Position	Signature
Sonstiges / Other:					
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>			Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
<p>* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet</p> <p>Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested</p>					
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>					

v04

Prüfbericht - Nr.: 50072565 001
*Test Report No.***Seite 2 von 60**
Page 2 of 60

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT*RESULT: Pass***5.1.2 20DB BANDWIDTH AND 99% BANDWIDTH***RESULT: Pass***5.1.3 FUNDAMENTAL & HARMONICS RADIATED EMISSION***RESULT: Pass***5.1.4 RADIATED EMISSIONS OUTSIDE OF THE BAND***RESULT: Pass***6.1.1 ELECTROMAGNETIC FIELDS***RESULT: Pass*

Contents

1.	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS	4
2.	TEST SITES	4
2.1	TEST FACILITIES	4
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	5
2.3	TRACEABILITY	5
2.4	CALIBRATION	5
2.5	MEASUREMENT UNCERTAINTY.....	6
2.6	LOCATION OF ORIGINAL DATA.....	6
2.7	STATUS OF FACILITY USED FOR TESTING.....	6
3.	GENERAL PRODUCT INFORMATION	7
3.1	PRODUCT FUNCTION AND INTENDED USE.....	7
3.2	RATINGS AND SYSTEM DETAILS	7
3.3	INDEPENDENT OPERATION MODES	7
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	7
3.5	SUBMITTED DOCUMENTS	8
4.	TEST SET-UP AND OPERATION MODES	9
4.1	PRINCIPLE OF CONFIGURATION SELECTION.....	9
4.2	TEST OPERATION AND TEST SOFTWARE	9
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	9
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	9
4.5	TEST SETUP DIAGRAM	10
5.	TEST RESULTS	12
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	12
5.1.1	<i>Antenna Requirement.....</i>	<i>12</i>
5.1.2	<i>20dB Bandwidth and 99% Bandwidth.....</i>	<i>13</i>
5.1.3	<i>Fundamental & Harmonics Radiated Emission</i>	<i>18</i>
5.1.4	<i>Radiated emissions outside of the band.....</i>	<i>25</i>
6.	SAFETY HUMAN EXPOSURE	57
6.1	RADIO FREQUENCY EXPOSURE COMPLIANCE.....	57
6.1.1	<i>Electromagnetic Fields.....</i>	<i>57</i>
7.	PHOTOGRAPHS OF THE TEST SET-UP	58
8.	LIST OF TABLES	60
9.	LIST OF PHOTOGRAPHS	60

1. General Remarks

1.1 Complementary Materials

None.

2. Test Sites

2.1 Test Facilities

Accurate Technology Co., Ltd.

(FCC Registration No.: 752051)

(Test site Industry Canada No.: 5077A-2)

F1, Bldg. A, Changyuan New Material Port
Keyuan Rd., Science & Industry Park, Nanshan
Shenzhen, P.R. China

The tests at the test site have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Type	S/N	Calibrated until
Transmitter spurious emissions				
Spectrum Analyzer	Rohde & Schwarz	FSV40	101495	2018-01-06
Test Receiver	Rohde & Schwarz	ESCS30	100307	2018-01-06
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	2018-01-09
Loop Antenna	Schwarzbeck	FMZB1516	1516131	2018-01-09
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	2018-01-09
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	2018-01-09
RF Switching Unit+PreAMP	Compliance Direction	RSU-M2	38322	2018-01-06
Pre-Amplifier	Rohde&Schwarz	CBLU11835 40-01	3791	2018-01-06
50 Coaxial Switch	Anritsu Corp	MP59B	6200506474	2018-01-06
RF Coaxial Cable	SUHNER	N-3m	No.8	2018-01-06
RF Coaxial Cable	RESENBERGER	N-3.5m	No.9	2018-01-06
RF Coaxial Cable	SUHNER	N-6m	No.10	2018-01-06
RF Coaxial Cable	RESENBERGER	N-12m	No.11	2018-01-06
RF Coaxial Cable	RESENBERGER	N-0.5m	No.12	2018-01-06
Radio Spectrum Test				
Spectrum Analyzer	Rohde & Schwarz	FSV40	101495	2018-01-06
Vector Signal Generator	Rohde & Schwarz	SMBV100A	260434	2018-01-06
Signal Generator	Rohde & Schwarz	SMB100A	108362	2018-01-06
Open Switch and Control Unit	Rohde & Schwarz	OSP120 + OSP-B157	101244 + 100866	2018-01-06

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

Table 2: Measurement Uncertainty

Parameter	Uncertainty
Radio Spectrum	$< \pm 0.60$ dB
Radiated emission of transmitter, valid up to 26.5 GHz	$< \pm 4.42$ dB
Conducted Emission	$< \pm 2.23$ dB
Radiated Emission	$< \pm 4.42$ dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

Accurate Technology Co., Ltd. test facility located at F1, Bldg. A, Changyuan New Material Port Keyuan Rd., Science & Industry Park, Nanshan, Shenzhen, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a wireless mouse, it operates at 2.4GHz ISM band.
For details refer to the User Manual and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

Technical Specification	Value
Kind of Equipment	Lenovo 300 Wireless Compact Mouse
Type Designation	L300
FCC ID	A5ML300B
IC	5903G-L300B
Operating Frequency Band	2400MHz ~ 2483.5MHz
Operating Frequency	2403MHz ~ 2479MHz
Channel Separation	1MHz
Number of Channel	77
Extreme Temperature Range	0~+40°C
Operation Voltage	DC 1.5V (via 'AA' size battery)
Modulation	GFSK
Antenna Gain	2.15dBi

3.3 Independent Operation Modes

The basic operation modes are:

- A. On
 - 1. Transmitting
 - 2. Receiving
- B. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

Prüfbericht - Nr.: 50072565 001*Test Report No.***Seite 8 von 60***Page 8 of 60*

3.5 Submitted Documents

- Bill of Material
- PCB Layout
- Photo Document
- Circuit Diagram
- Instruction Manual
- Rating Label

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

4.3 Special Accessories and Auxiliary Equipment

None.

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test for below 1GHz




Diagram of Measurement Configuration for Radiation Test for above 1GHz





Diagram of Measurement Equipment Configuration for Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Pass**

Test standard	:	Part 15.203 RSS-Gen 8.3
Limit	:	the use of antennas with directional gains that do not exceed 6dBi

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is 2.15dBi, therefore the EUT is considered sufficient to comply with the provision.

Prüfbericht - Nr.: 50072565 001

Test Report No.

Seite 13 von 60

Page 13 of 60

5.1.2 20dB Bandwidth and 99% Bandwidth**RESULT:****Pass**

Date of testing : 2017-02-16
Test standard : FCC Part 15.215 (c)
RSS-Gen clause 6.6
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded room


Test setup

Test Channel : Low/ Middle/ High
Operation Mode : A.1
Ambient temperature : 21°C
Relative humidity : 60%
Atmospheric pressure : 101kPa


Table 4: Test result of 20dB & 99% Bandwidth

Channel	Channel Frequency (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low Channel	2403	3.321	3.394
Mid Channel	2439	3.604	3.263
High Channel	2479	2.967	2.996


For details refer to following test plot.

Test Plot of 20dB Bandwidth



Date: 16.FEB.2017 09:27:05




Date: 16.FEB.2017 09:29:32




Date: 16.FEB.2017 09:32:59

Test Plot of 99% Bandwidth


Date: 16.FEB.2017 09:10:39



Date: 16.FEB.2017 09:12:45



Date: 16.FEB.2017 09:14:29



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1523	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2403MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2403.000	93.00	-1.61	91.39	114.00	-22.61	peak			
2	2403.000	91.50	-1.61	89.89	94.00	-4.11	AVG			
3	4806.027	45.69	4.92	50.61	74.00	-23.39	peak			
4	4806.027	36.42	4.92	41.34	54.00	-12.66	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1524	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2403MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2403.000	84.46	-1.61	82.85	114.00	-31.15	peak			
2	2403.000	82.96	-1.61	81.35	94.00	-12.65	AVG			
3	4806.033	43.70	4.92	48.62	74.00	-25.38	peak			
4	4806.033	35.31	4.92	40.23	54.00	-13.77	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F 1,Bldg.A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1526	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2439MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2439.000	91.20	-1.46	89.74	114.00	-24.46	peak			
2	2439.000	90.00	-1.46	88.54	94.00	-5.46	AVG			
3	4878.028	43.83	5.57	49.40	74.00	-24.60	peak			
4	4878.028	35.90	5.57	41.47	54.00	-12.53	AVG			


ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1525	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2439MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2439.000	83.30	-1.46	81.84	114.00	-32.16	peak			
2	2439.000	82.10	-1.46	80.64	94.00	-13.36	AVG			
3	4878.029	43.09	5.57	48.66	74.00	-25.34	peak			
4	4878.029	34.64	5.57	40.21	54.00	-13.79	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1522	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2479MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	91.73	-1.40	90.33	114.00	-23.67	peak			
2	2479.000	90.43	-1.40	89.03	94.00	-4.97	AVG			
3	4958.032	43.89	6.08	49.97	74.00	-24.03	peak			
4	4958.032	35.27	6.08	41.35	54.00	-12.65	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F 1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1521	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2479MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	80.91	-1.40	79.51	114.00	-34.49	peak			
2	2479.000	79.61	-1.40	78.21	94.00	-15.79	AVG			
3	4958.027	41.07	6.08	47.15	74.00	-26.85	peak			
4	4958.027	33.16	6.08	39.24	54.00	-14.76	AVG			

Prüfbericht - Nr.: 50072565 001

Test Report No.

Seite 25 von 60

Page 25 of 60

5.1.4 Radiated emissions outside of the band**RESULT:****Pass**

Date of testing	:	2017-01-16 to 2017-02-10
Test standard	:	FCC Part 15.209(a) FCC Part 15.249(d) RSS-210 Clause B.10(b)
Basic standard	:	ANSI C63.10: 2013
Frequency range	:	0.009 – 26500MHz*
Limits	:	FCC Part 15.209(a) FCC Part 15.249(d)
Kind of test site	:	3m Semi-Anechoic Chamber & Anechoic Chamber

Test Setup

Test channel	:	Low/ Middle/ High
Operation mode	:	A.1
Ambient temperature	:	23°C
Relative humidity	:	48%
Atmospheric pressure	:	101kPa

For details refer to following test plot.

Test Plot of Radiated emissions outside band


ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2403MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 1.5V
 Comment: X
 Start of Test: 2017-2-10 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD
FCC Class B 3M Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2403MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 1.5V
 Comment: Y
 Start of Test: 2017-2-10 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD
FCC Class B 3M Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2403MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 1.5V
 Comment: Z
 Start of Test: 2017-2-10 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD
FCC Class B 3M Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2439MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 1.5V
 Comment: X
 Start of Test: 2017-2-10 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M

Short Description: _SUB STD_VTERM2 1.70




ACCURATE TECHNOLOGY CO.,LTD
FCC Class B 3M Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2439MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 1.5V
 Comment: Y
 Start of Test: 2017-2-10 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD
FCC Class B 3M Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2439MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 1.5V
 Comment: Z
 Start of Test: 2017-2-10 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD
FCC Class B 3M Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2479MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 1.5V
 Comment: X
 Start of Test: 2017-2-10 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD
FCC Class B 3M Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2479MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 1.5V
 Comment: Y
 Start of Test: 2017-2-10 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO.,LTD
FCC Class B 3M Radiated

EUT: Lenovo 300 Wireless Compact Mouse M/N:L300
 Manufacturer: Lenovo
 Operating Condition: TX 2479MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 1.5V
 Comment: Z
 Start of Test: 2017-2-10 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M





ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1558	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2403MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	31.0705	29.80	-10.03	19.77	40.00	-20.23	QP			
2	119.8555	24.64	-13.06	11.58	43.50	-31.92	QP			
3	744.8660	25.93	-0.37	25.56	46.00	-20.44	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: lenovo #1557	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2403MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	32.6340	27.80	-9.71	18.09	40.00	-21.91	QP			
2	121.1230	25.61	-13.19	12.42	43.50	-31.08	QP			
3	833.3171	26.63	1.42	28.05	46.00	-17.95	QP			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1559	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2439MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	31.1798	28.24	-10.04	18.20	40.00	-21.80	QP			
2	117.3602	25.08	-13.07	12.01	43.50	-31.49	QP			
3	684.7454	26.39	-1.30	25.09	46.00	-20.91	QP			


ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1560	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2439MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	31.0705	27.74	-9.25	18.49	40.00	-21.51	QP			
2	99.5279	25.08	-13.21	11.87	43.50	-31.63	QP			
3	906.4823	25.62	2.22	27.84	46.00	-18.16	QP			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1562	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2479MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	30.9618	29.02	-10.02	19.00	40.00	-21.00	QP			
2	99.5279	24.48	-13.21	11.27	43.50	-32.23	QP			
3	848.0562	25.93	1.54	27.47	46.00	-18.53	QP			


ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1561	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2479MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	31.0705	28.41	-9.25	19.16	40.00	-20.84	QP			
2	99.8777	25.51	-13.09	12.42	43.50	-31.08	QP			
3	860.0352	24.65	1.72	26.37	46.00	-19.63	QP			


ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1523	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2403MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2403.000	93.00	-1.61	91.39	114.00	-22.61	peak			
2	2403.000	91.50	-1.61	89.89	94.00	-4.11	AVG			
3	4806.027	45.69	4.92	50.61	74.00	-23.39	peak			
4	4806.027	36.42	4.92	41.34	54.00	-12.66	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1524	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2403MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2403.000	84.46	-1.61	82.85	114.00	-31.15	peak			
2	2403.000	82.96	-1.61	81.35	94.00	-12.65	AVG			
3	4806.033	43.70	4.92	48.62	74.00	-25.38	peak			
4	4806.033	35.31	4.92	40.23	54.00	-13.77	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1526	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2439MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2439.000	91.20	-1.46	89.74	114.00	-24.46	peak			
2	2439.000	90.00	-1.46	88.54	94.00	-5.46	AVG			
3	4878.028	43.83	5.57	49.40	74.00	-24.60	peak			
4	4878.028	35.90	5.57	41.47	54.00	-12.53	AVG			


ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1525	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2439MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2439.000	83.30	-1.46	81.84	114.00	-32.16	peak			
2	2439.000	82.10	-1.46	80.64	94.00	-13.36	AVG			
3	4878.029	43.09	5.57	48.66	74.00	-25.34	peak			
4	4878.029	34.64	5.57	40.21	54.00	-13.79	AVG			


ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1522	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2479MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	91.73	-1.40	90.33	114.00	-23.67	peak			
2	2479.000	90.43	-1.40	89.03	94.00	-4.97	AVG			
3	4958.032	43.89	6.08	49.97	74.00	-24.03	peak			
4	4958.032	35.27	6.08	41.35	54.00	-12.65	AVG			


ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1521	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2479MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	80.91	-1.40	79.51	114.00	-34.49	peak			
2	2479.000	79.61	-1.40	78.21	94.00	-15.79	AVG			
3	4958.027	41.07	6.08	47.15	74.00	-26.85	peak			
4	4958.027	33.16	6.08	39.24	54.00	-14.76	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1527	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2403MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26032.693	10.72	40.26	50.98	74.00	-23.02	peak			
2	26032.693	0.06	40.26	40.32	54.00	-13.68	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park, Nanshan Shenzhen, P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1528	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2403MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26234.849	9.59	40.95	50.54	74.00	-23.46	peak			
2	26234.849	-0.61	40.95	40.34	54.00	-13.66	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1530	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2439MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25922.172	10.78	40.21	50.99	74.00	-23.01	peak			
2	25922.172	0.03	40.21	40.24	54.00	-13.76	AVG			


ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1529	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2439MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26174.038	9.75	40.95	50.70	74.00	-23.30	peak			
2	26174.038	-0.64	40.95	40.31	54.00	-13.69	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1531	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2479MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25327.539	10.58	39.91	50.49	74.00	-23.51	peak			
2	25327.539	0.63	39.91	40.54	54.00	-13.46	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1532	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/02/06/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2479MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25882.099	9.26	41.00	50.26	74.00	-23.74	peak			
2	25882.099	-0.68	41.00	40.32	54.00	-13.68	AVG			

Prüfbericht - Nr.: 50072565 001
Test Report No.
Seite 53 von 60
Page 53 of 60


Test Plot of Frequency Band Edge


ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1517	Polarization: Horizontal
Standard: FCC (Band Edge)	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2403MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2400.000	72.32	-1.62	70.70	74.00	-3.30	peak			
2	2400.000	50.92	-1.62	49.30	54.00	-4.70	AVG			
3	2403.000	93.93	-1.61	92.32	114.00	-21.68	peak			
4	2403.000	92.43	-1.61	90.82	94.00	-3.18	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1518	Polarization: Vertical
Standard: FCC (Band Edge)	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2403MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2400.000	63.49	-1.62	61.87	74.00	-12.13	peak			
2	2400.000	42.55	-1.62	40.93	54.00	-13.07	AVG			
3	2403.000	85.50	-1.61	83.89	114.00	-30.11	peak			
4	2403.000	84.00	-1.61	82.39	94.00	-11.61	AVG			



ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: lenovo #1519	Polarization: Horizontal
Standard: FCC (Band Edge)	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2479MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	91.45	-1.40	90.05	114.00	-23.95	peak			
2	2479.000	90.15	-1.40	88.75	94.00	-5.25	AVG			
3	2483.500	61.02	-1.40	59.62	74.00	-14.38	peak			
4	2483.500	40.86	-1.40	39.46	54.00	-14.54	AVG			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: lenovo #1520	Polarization: Vertical
Standard: FCC (Band Edge)	Power Source: DC 1.5V
Test item: Radiation Test	Date: 17/01/16/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Lenovo 300 Wireless Compact Mouse	Engineer Signature: LGWADE
Mode: TX 2479MHz	Distance: 3m
Model: L300	
Manufacturer: Lenovo	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	79.09	-1.40	77.69	114.00	-36.31	peak			
2	2479.000	77.79	-1.40	76.39	94.00	-17.61	AVG			
3	2483.500	49.82	-1.40	48.42	74.00	-25.58	peak			
4	2483.500	35.98	-1.40	34.58	54.00	-19.42	AVG			

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:**Pass**


Test standard : RSS-102 Issue 5 March 2015
FCC KDB Publication 447498 D01 v06

The maximum radiated power of the transmitter is 0.235mW (-6.29dBm) only, which less than 4mW. Hence the EUT is exempted from routine evaluation limits (SAR Evaluation) according to clause 2.5.1 of RSS-102 Issue 5.


Since maximum radiated power of the transmitter is $0.235\text{mW} < 10\text{mW}$, and the distance from EUT to human is 5mm, hence the EUT is excluded from SAR evaluation according to FCC KDB publication 447498 D01 General RF Exposure Guidance v06.

7. Photographs of the Test Set-Up


Photograph 1: Set-up for Spurious Emissions below 30MHz




Photograph 2: Set-up for Spurious Emissions of 30MHz – 1GHz



Photograph 3: Set-up for Spurious Emissions of 1 – 18GHz



Photograph 4: Set-up for Spurious Emissions of 18 – 26.5GHz



8. List of Tables

Table 1: List of Test and Measurement Equipment	5
Table 2: Measurement Uncertainty	6
Table 3: Technical Specification of EUT	7
Table 4: Test result of 20dB & 99% Bandwidth.....	13
Table 5: Polarization of the measurement for the larger power level channel 2403MHz: Horizontal.....	18

9. List of Photographs

Photograph 1: Set-up for Spurious Emissions below 30MHz	58
Photograph 2: Set-up for Spurious Emissions of 30MHz – 1GHz.....	58
Photograph 3: Set-up for Spurious Emissions of 1 – 18GHz.....	59
Photograph 4: Set-up for Spurious Emissions of 18 – 26.5GHz	59