

# **RF Exposure Report**

**Report No.:** SA191122C10

FCC ID: A5UWICHI201

Test Model: WICHI201

Received Date: Nov. 22, 2019

Test Date: Dec. 06 ~ Dec. 17, 2019

**Issued Date:** Dec. 31, 2019

**Applicant:** Whirlpool Corporation

Address: 2000 N M-63 Mail Drop 3005, Benton Harbor, MI, United States, 49022

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, Taiwan

FCC Registration / 788550 / TW0003

**Designation Number:** 





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA191122C10 Page No. 1 / 5 Report Format Version: 6.1.1



# Table of Contents Release Control Record 3 1 Certificate of Conformity 4 2 RF Exposure 5 2.1 Limits for Maximum Permissible Exposure (MPE) 5 2.2 MPE Calculation Formula 5 2.3 Classification 5

3



## **Release Control Record**

Issue No.	Description	Date Issued
SA191122C10	Original release	Dec. 31, 2019



### **Certificate of Conformity**

Product: Indigo-2 WiFi Module

**Brand:** Whirlpool Corporation

Test Model: WICHI201

Sample Status: Engineering sample

**Applicant:** Whirlpool Corporation

**Test Date:** Dec. 06 ~ Dec. 17, 2019

Standards: FCC Part 2 (Section 2.1091)

References Test KDB 447498 D01 General RF Exposure Guidance v06

Guidance:

IEEE C95.3 -2002

The above equipment has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by: Pettie Chen / Senior Specialist Dec. 31, 2019



### 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
0.3-1.34	614	1.63	(100)*	30				
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30				
30-300	27.5	0.073	0.2	30				
300-1500			f/1500	30				
1500-100,000			1.0	30				

f = Frequency in MHz; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

### 3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WLAN 2412~2462	18.16	2.8	20	0.025	1
BT LE 2402~2480	5.42	2.8	20	0.001	1
BT EDR 2402~2480	5.28	2.8	20	0.001	1

Noe: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 + .....etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN + Bluetooth = 0.025 / 1 + 0.001 / 1 = 0.026

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---

Report No.: SA191122C10 Page No. 5 / 5 Report Format Version: 6.1.1