



166 South Carter, Genoa City, WI 53128

Company:  
Model Tested:  
DLS Project:

Whirlpool Corporation  
XPWG3  
7037

## FCC Code of Federal Regulations 47 Part 1.1307(b) (1)

### RF Exposure Statement of Compliance

THE FOLLOWING **MEETS** THE ABOVE TEST SPECIFICATION

Formal Name:	Wifi Gen3
Kind of Equipment:	802.11b/g/n Wi-Fi appliance module
Frequency Range:	2412-2462 MHz
Test Configuration:	DC powered transceiver module
Model Number(s):	XPWG3
Model(s) Tested:	XPWG3
Serial Number(s):	RF Conducted SN: GW95013003GG
Date of Tests:	February 27 <sup>th</sup> through April 21 <sup>st</sup> , 2015 (Original certification & Class II PC testing)
Test Conducted For:	Whirlpool Corporation 750 Monte Rd Benton Harbor, MI 49022, USA



166 South Carter, Genoa City, WI 53128

Company:  
Model Tested:  
DLS Project:

Whirlpool Corporation  
XPWG3  
7037

### Transmitter Information:

Maximum Conducted Output Power:	25.08 dBm
Maximum Effective Isotropic Radiated Power	29.28 dBm
Frequency:	2412 MHz
Antenna Type:	PIFA antenna
Antenna Gain:	4.2 dBi

### Exposure Limit:

Maximum Permissible Exposure (MPE) limit for General Population / Uncontrolled Exposure in the frequency range 1500 – 100,000 MHz (ref: 47 CFR Part 1.1310 Table 1(b))

Limit: (S) ( $\text{mW}/\text{cm}^2$ ) =  $1.0 \text{ mW}/\text{cm}^2$

### MPE Calculation:

Power Density ( $\text{mW}/\text{cm}^2$ ):

$$S = \frac{PG}{4\pi R^2}$$

S = Power Density ( $\text{mW}/\text{cm}^2$ )

P = Power Input to the antenna (mW)

G = Numeric Power Gain of the antenna

R = Distance to the center of the radiation of the antenna (cm)



Company:  
Model Tested:  
DLS Project:

Whirlpool Corporation  
XPWG3  
7037

166 South Carter, Genoa City, WI 53128

## Results:

RF Exposure Calculation								
	Input							
Frequency =	2412	MHz						
P =	25.08	dBm						
G =	4.2	dBi						
R =	20	cm						
$\pi$	3.14159							
Transmit Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Antenna Gain (dBi)	Antenna Gain (numeric)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Power Density Limit (mW/cm <sup>2</sup> )	Margin
2412	25.08	322.10688	4.2	2.63027	20	0.1686	1.0	0.831

## Summary of Results:

With a minimum separation distance of 20 centimeters as defined by FCC 2.1091(b), for a mobile device, the Whirlpool Inc. Wifi Gen3 model XPWG3 **meets** the RF exposure evaluation requirements for maximum permissible exposure to any radiating structure and the general population / uncontrolled exposure.

## Conclusion:

The Whirlpool Inc Wifi Gen3 model XPWG3 operating under FCC part 15.247 complies with the requirements of FCC Part 1.1307(b)(1) for RF Exposure Evaluation.