



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Bluetooth Module

Model: BM20L

Brand: YAMAHA

Test Report Number:

C180611Z03-RP1

Issued fo

YAMAHA CORPORATION

10-1 Nakazawa-cho, Naka-ku, Hamamatsu-shi, Shizuoka-ken, Japan

Issued by:

COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC.

No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd.,
Guan Lan Town, Baoan District, Shenzhen China

TEL: 86-755-28055000

FAX: 86-755-28055221

E-Mail: service@ccssz.com

Issued Date: July 10, 2018



Certificate Number: 2861.01

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc. This document may be altered or revised by Compliance Certification Services (Shenzhen) Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST, CNAS or any government agencies. The test result of this report relate only to the tested sample identified in this report.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	July 10, 2018	Initial Issue	ALL	Sabrina Wang



TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION..... 4

2 TEST RESULT SUMMARY 5

3 EUT DESCRIPTION 6

4 TEST METHODOLOGY 7

 4.1. DESCRIPTION OF TEST MODES 7

5 SETUP OF EQUIPMENT UNDER TEST 8

 5.1. SETUP CONFIGURATION OF EUT 8

 5.2. SUPPORT EQUIPMENT 8

 5.3. TEST INSTRUMENTS..... 9

6 FACILITIES AND ACCREDITATIONS..... 11

 6.1. FACILITIES 11

 6.2. ACCREDITATIONS..... 11

 6.3. MEASUREMENT UNCERTAINTY 11

7 FCC PART 15.247 REQUIREMENTS 12

 7.1. POWERLINE CONDUCTED EMISSIONS 12

 7.2. 20DB BANDWIDTH 18

 7.3. ANTENNA GAIN 22

 7.4. PEAK POWER..... 23

 7.5. FREQUENCY SEPARATION 25

 7.6. NUMBER OF HOPPING FREQUENCY 28

 7.7. TIME OF OCCUPANCY (DWELL TIME) 30

 7.8. BAND EDGES MEASUREMENT 32

 7.9. SPURIOUS EMISSIONS 45



1 TEST RESULT CERTIFICATION

Product	Bluetooth Module
Model	BM20L
Brand	YAMAHA
Tested	May 21~ July 10, 2018
Applicant	YAMAHA CORPORATION 10-1 Nakazawa-cho, Naka-ku, Hamamatsu-shi, Shizuoka-ken, Japan
Manufacturer	Sunitec Enterprise Co., Ltd. No. 192, Runtang Ind, Danhu community, Fucheng, Longhua District, Shenzhen, China (ZIP:518100)

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services (Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.10: 2013** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Eve Wang
Supervisor of EMC Dept.
Compliance Certification Services (Shenzhen)
Inc.

Reviewed by:

Nancy Fu
Supervisor of Report Dept.
Compliance Certification Services (Shenzhen)
Inc.



2 TEST RESULT SUMMARY

APPLICABLE STANDARDS			
Standard	Test Type	Result	Remark
15.247(a)(1)	20dB Bandwidth Measurement	Pass	Meet the requirement of limit.
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.
15.247(a)(1)	Frequency Separation	Pass	Meet the requirement of limit.
15.247(a)(1)(ii)	Number Of Hopping Frequency	Pass	Meet the requirement of limit.
15.247(a)(1)(iii)	Time Of Occupancy (Dwell Time)	Pass	Meet the requirement of limit.
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.
15.247(d)	<ul style="list-style-type: none">● Spurious Emissions● Conducted Measurement● Radiated Emissions	Pass	Meet the requirement of limit.
15.207(a)	Power line Conducted Emissions	Pass	Meet the requirement of limit.

Note:

1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.
2. The information of measurement uncertainty is available upon the customer's request.



3 EUT DESCRIPTION

Product	Bluetooth Module
Model Number	BM20L
Brand	YAMAHA
Model Discrepancy	N/A
Identify Number	C180611Z03-RP1
Received Date	June 11, 2018
Power Supply	DC3.3V supply by the PCB board
Frequency Range	2402 ~ 2480 MHz
Transmit Power	GFSK: 1.80dBm $\pi/4$ -DQPSK: 2.31dBm 8DPSK: 2.85dBm
Modulation Technique	FHSS (GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8DPSK for 3Mbps)
Number of Channels	79 Channels
Antenna Specification	PCB antenna with 1.78dBi gain (Max)
Temperature Range	-20°C ~ +70°C
Hardware Version	V0.2
Software Version	V10

Note: This submittal(s) (test report) is intended for FCC ID: A6RBM20L filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



4 TEST METHODOLOGY

4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Use “certification Tool 1.26” to control the EUT for staying in continuous transmitting and receiving mode.

Conducted emissions	
Test Mode	Description
1	Normal
The worst test results were recorded in the report.	

Radiated Emission	
Test Mode	Description
1	Continuously Transmitting
The worst test results were recorded in the report.	

Note:

1. Channel Low (2402MHz), Mid (2441MHz) and High (2480MHz) were chosen for pre-testing for GFSK, $\pi/4$ -DQPSK and 8DPSK, GFSK and 8DPSK were the worse case and print in the report.
2. Radiated band edges were tested with both fixed and hopping mode; the fixed mode was the worse case and recorded in the report.
3. For $\pi/4$ QPSK its same modulation type with 8-DPSK, and based exploratory test, there is no significant difference of that two types test result, so except output power, all other items final test were only performed with the worst case 8-DPSK and GFSK.



5 SETUP OF EQUIPMENT UNDER TEST

5.1. SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

5.2. SUPPORT EQUIPMENT

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Notebook	Thinkpad S2	SL 10K92342	N/A	Lenovo	N/A	Unshielded 1.00m (AC Cable) Unshielded 1.80m (DC Cable)

Note: Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use



5.3. TEST INSTRUMENTS

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	01/27/2018	01/26/2019
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	01/27/2018	01/26/2019
LISN	EMCO	3825/2	8901-1459	01/27/2018	01/26/2019
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	01/29/2018	01/28/2019
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			

Radiated Emission Test Site 966 (2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	01/27/2018	01/26/2019
Amplifier	EMEC	EM330	060661	01/27/2018	01/26/2019
High Noise Amplifier	Agilent	8449B	3008A01838	01/27/2018	01/26/2019
Loop Antenna	COM-POWER	AL-130	121044	01/30/2018	01/29/2019
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2018	02/20/2019
Horn Antenna	SCHWARZBECK	BBHA9120	D286	01/27/2018	01/26/2019
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	01/24/2018	01/23/2019
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	01/29/2018	01/28/2019
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

99% Bandwidth					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

20dB Bandwidth					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019



Antenna Gain					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Peak Output Power					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Power Meter	Anritsu	ML2495A	1204003	01/27/2018	01/26/2019
Power Sensor	Anritsu	MA2411B	1126150	01/27/2018	01/26/2019

Frequency Separation					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Number Of Hopping Frequency					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Time Of Occupancy (Dwell Time)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Band edges					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Antenna Conducted Spurious Emission					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.



6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at

- No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China**

The sites are constructed in conformance with the requirements of ANSI C63.10:2013, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA	A2LA
China	CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA	FCC
Japan	VCCI(C-4815, R-4320, T-2317, G-10624)
Canada	INDUSTRY CANADA

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccscsz.com>

6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.9211dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.9037dB
Radiated Emission, 1 to 8 GHz	+/-5.3516dB
Radiated Emission, 8 to 18 GHz	+/-5.3894dB
Conducted Emissions	+/-4.1742dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.



7 FCC PART 15.247 REQUIREMENTS

7.1. POWERLINE CONDUCTED EMISSIONS


7.1.1. LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

7.1.2. TEST CONFIGURATION



See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.




7.1.3. TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



7.1.4. TEST RESULTS


Model No.	BM20L	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 1
Tested by	Eve Wang	Line	L
Test Voltage	AC120V/60Hz	Test Date	July 9, 2018



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.2620	28.11	15.88	19.62	47.73	35.50	61.36	51.37	-13.63	-15.87	Pass
0.5899	27.62	14.95	19.57	47.19	34.52	56.00	46.00	-8.81	-11.48	Pass
0.8059	24.81	8.20	19.59	44.40	27.79	56.00	46.00	-11.60	-18.21	Pass
1.3420	24.57	8.58	19.60	44.17	28.18	56.00	46.00	-11.83	-17.82	Pass
1.8100	26.11	11.98	19.69	45.80	31.67	56.00	46.00	-10.20	-14.33	Pass
3.4900	24.84	9.35	19.72	44.56	29.07	56.00	46.00	-11.44	-16.93	Pass




Model No.	BM20L	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 1
Tested by	Eve Wang	Line	N
Test Voltage	AC120V/60Hz	Test Date	July 9, 2018



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.2020	25.01	12.94	19.54	44.55	32.48	63.52	53.53	-18.97	-21.05	Pass
0.5899	22.85	10.89	19.57	42.42	30.46	56.00	46.00	-13.58	-15.54	Pass
0.7820	21.47	5.97	19.59	41.06	25.56	56.00	46.00	-14.94	-20.44	Pass
1.2980	23.72	6.37	19.60	43.32	25.97	56.00	46.00	-12.68	-20.03	Pass
1.8060	25.70	10.41	19.69	45.39	30.10	56.00	46.00	-10.61	-15.90	Pass
2.2980	24.85	7.69	19.73	44.58	27.42	56.00	46.00	-11.42	-18.58	Pass




Model No.	BM20L	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 1
Tested by	Eve Wang	Line	L
Test Voltage	AC240V/50Hz	Test Date	July 9, 2018



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.5899	28.62	15.95	19.57	48.19	35.52	56.00	46.00	-7.81	-10.48	Pass
0.8059	25.81	9.20	19.59	45.40	28.79	56.00	46.00	-10.60	-17.21	Pass
1.3420	24.57	8.58	19.60	44.17	28.18	56.00	46.00	-11.83	-17.82	Pass
1.8100	26.61	12.48	19.69	46.30	32.17	56.00	46.00	-9.70	-13.83	Pass
2.3380	24.97	10.08	19.72	44.69	29.80	56.00	46.00	-11.31	-16.20	Pass
3.4900	25.34	9.85	19.72	45.06	29.57	56.00	46.00	-10.94	-16.43	Pass



Model No.	BM20L	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 1
Tested by	Eve Wang	Line	N
Test Voltage	AC240V/50Hz	Test Date	July 9, 2018




Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.2020	24.51	12.44	19.54	44.05	31.98	63.52	53.53	-19.47	-21.55	Pass
0.5899	23.85	11.89	19.57	43.42	31.46	56.00	46.00	-12.58	-14.54	Pass
0.7820	22.47	6.97	19.59	42.06	26.56	56.00	46.00	-13.94	-19.44	Pass
1.2980	24.72	7.37	19.60	44.32	26.97	56.00	46.00	-11.68	-19.03	Pass
1.8060	25.70	10.41	19.69	45.39	30.10	56.00	46.00	-10.61	-15.90	Pass
2.2980	24.35	7.19	19.73	44.08	26.92	56.00	46.00	-11.92	-19.08	Pass



7.2. 20DB BANDWIDTH

No limits

7.2.1. TEST CONFIGURATION



7.2.2. TEST PROCEDURE


- Place the EUT on the table and set it in the transmitting mode.
- Remove the antenna from the EUT, and then connect a low loss RF cable from antenna port to the spectrum analyzer.
- Set the spectrum analyzer as RBW=30 kHz, VBW=100 kHz, Span=3MHz, Sweep = auto.
- Mark the peak frequency and 20dB (upper and lower) frequency.
- Repeat until all the test channels are investigated.

7.2.3. TEST RESULTS

No non-compliance noted


Test Data

Test mode	Channel	Frequency (MHz)	20 dB Bandwidth (kHz)
GFSK	Low	2402	1041
	Mid	2441	1035
	High	2480	1039
8DPSK	Low	2402	1202
	Mid	2441	1203
	High	2480	1201






20dB Bandwidth (CH High)




8DPSK

20dB Bandwidth (CH Low)






20dB Bandwidth (CH Mid)



20dB Bandwidth (CH High)





7.3. ANTENNA GAIN

7.3.1. MEASUREMENT

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal BT devices, the GFSK mode is used.

7.3.2. MEASUREMENT PARAMETERS

Measurement parameter	
Detector	Peak
Sweep time	Auto
Resolution bandwidth	3 MHz
Video bandwidth	3 MHz
Trace-Mode	Max hold

7.3.3. LIMITS

FCC	IC
Antenna Gain	
6 dBi	

7.3.4. TEST RESULTS

GFSK				
T _{nom}	V _{nom}	Lowest channel 2402MHz	Middle channel 2441MHz	Highest channel 2480MHz
Conducted power [dBm] Measured with GFSK modulation		1.80	1.65	1.30
Radiated power [dBm] Measured with GFSK modulation		3.25	3.18	2.87
Gain [dBi] Calculated		1.45	1.53	1.57
Measurement uncertainty		± 1.5 dB (cond.) / ± 3 dB (rad.)		
8DPSK				
T _{nom}	V _{nom}	Lowest channel 2402MHz	Middle channel 2441MHz	Highest channel 2480MHz
Conducted power [dBm] Measured with GFSK modulation		2.85	2.70	2.37
Radiated power [dBm] Measured with GFSK modulation		4.27	4.25	3.76
Gain [dBi] Calculated		1.42	1.55	1.39
Measurement uncertainty		± 1.5 dB (cond.) / ± 3 dB (rad.)		




7.4. PEAK POWER

7.4.1. LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.
3. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.4.2. TEST CONFIGURATION



7.4.3. TEST PROCEDURE

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.



7.4.4. TEST RESULTS

No non-compliance noted

Test Data

GFSK

Channel	Frequency (MHz)	Reading Power (dBm)	Cable loss (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Peak /AVG	Result
Low	2402	-1.70	3.50	1.80	0.00151	0.125	peak	PASS
Mid	2441	-1.85	3.50	1.65	0.00146			PASS
High	2480	-2.20	3.50	1.30	0.00135			PASS
Low	2402	-4.39	3.50	-0.89	0.00081	0.125	AVG	PASS
Mid	2441	-4.54	3.50	-1.04	0.00079			PASS
High	2480	-4.90	3.50	-1.40	0.00072			PASS

$\pi/4$ -DQPSK

Channel	Frequency (MHz)	Reading Power (dBm)	Cable loss (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Peak /AVG	Result
Low	2402	-1.19	3.50	2.31	0.00170	0.125	peak	PASS
Mid	2441	-1.34	3.50	2.16	0.00164			PASS
High	2480	-1.70	3.50	1.80	0.00151			PASS
Low	2402	-6.49	3.50	-2.99	0.00050	0.125	AVG	PASS
Mid	2441	-6.64	3.50	-3.14	0.00049			PASS
High	2480	-6.99	3.50	-3.49	0.00045			PASS

8DPSK

Channel	Frequency (MHz)	Reading Power (dBm)	Cable loss (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Peak /AVG	Result
Low	2402	-0.65	3.50	2.85	0.00193	0.125	peak	PASS
Mid	2441	-0.80	3.50	2.70	0.00186			PASS
High	2480	-1.13	3.50	2.37	0.00173			PASS
Low	2402	-6.51	3.50	-3.01	0.00050	0.125	AVG	PASS
Mid	2441	-6.65	3.50	-3.15	0.00048			PASS
High	2480	-6.99	3.50	-3.49	0.00045			PASS




7.5. FREQUENCY SEPARATION

7.5.1. LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

7.5.2. TEST CONFIGURATION



7.5.3. TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW=30kHz, VBW=30kHz, Adjust Span to 4 MHz, Sweep = auto.
5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

7.5.4. TEST RESULTS

No non-compliance noted



Test Data

GFSK

Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	694.000	> Two-thirds of the 20 dB Bandwidth	Pass

8DPSK


Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	802.000	> Two-thirds of the 20 dB Bandwidth	Pass






8DPSK

Measurement of Channel Separation



20 dB bandwidth(CH Mid)






7.6. NUMBER OF HOPPING FREQUENCY

7.6.1. LIMIT

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

7.6.2. TEST CONFIGURATION



7.6.3. TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = 1ms.
4. Set the spectrum analyzer as RBW, VBW=300kHz,
5. Max hold, view and count how many channel in the band.

7.6.4. TEST RESULTS

No non-compliance noted

Test Data

GFSK / 8DPSK


Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS



Channel Number


GFSK

2.400 GHz – 2.4835 GHz



8DPSK

2.400 GHz – 2.4835 GHz






7.7. TIME OF OCCUPANCY (DWELL TIME)

7.7.1. LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4s multiplied by the number of hopping channels employed.

7.7.2. TEST CONFIGURATION



7.7.3. TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.

7.7.4. TEST RESULTS

No non-compliance noted




Test Data


GFSK



DH 1					
CH Mid: $0.416 * (1600/2)/79 * 31.6 = 133.12$ (ms)					
CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.416	133.12	31.60	400.00	PASS
DH 3					
CH Mid: $1.675 * (1600/4)/79 * 31.6 = 268.00$ (ms)					
CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.675	268.00	31.60	400.00	PASS
DH 5					
CH Mid: $2.924 * (1600/6)/79 * 31.6 = 311.89$ (ms)					
CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	2.924	311.89	31.60	400.00	PASS


8DPSK

3DH 1					
CH Mid: $0.429 * (1600/2)/79 * 31.6 = 137.28$ (ms)					
CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.429	137.28	31.60	400.00	PASS
3DH 3					
CH Mid: $1.680 * (1600/4)/79 * 31.6 = 268.80$ (ms)					
CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.680	268.80	31.60	400.00	PASS
3DH 5					
CH Mid: $2.936 * (1600/6)/79 * 31.6 = 313.17$ (ms)					
CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	2.936	313.17	31.60	400.00	PASS












7.8. BAND EDGES MEASUREMENT

7.8.1. LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

7.8.2. TEST CONFIGURATION




7.8.3. TEST PROCEDURE



1. The EUT is placed on a turntable, which is 1.5m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz / VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=1/T / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

7.8.4. TEST RESULTS


Refer to attach spectrum analyzer data chart.





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	53.79	-2.86	50.93	74.00	-23.07	Peak	Vertical
2.	2402.100	92.32	-2.80	89.52	---	---	Peak	Vertical
1.	2390.000	41.66	-2.86	38.80	54.00	-15.20	Average	Vertical
2.	2402.000	89.34	-2.80	86.54	---	---	Average	Vertical




No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	55.27	-2.86	52.41	74.00	-21.59	Peak	Horizontal
2.	2402.000	103.75	-2.80	100.95	---	---	Peak	Horizontal
1.	2390.000	43.46	-2.86	40.60	54.00	-13.40	Average	Horizontal
2.	2402.000	102.98	-2.80	100.18	---	---	Average	Horizontal





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2480.125	93.41	-2.37	91.04	---	---	Peak	Vertical
2.	2483.500	57.63	-2.35	55.28	74.00	-18.72	Peak	Vertical
1.	2480.050	92.83	-2.37	90.46	---	---	Average	Vertical
2.	2483.500	41.97	-2.35	39.62	54.00	-14.38	Average	Vertical





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2479.900	105.90	-2.37	103.53	---	---	Peak	Horizontal
2.	2483.500	71.25	-2.35	68.90	74.00	-5.10	Peak	Horizontal
1.	2480.025	105.37	-2.37	103.00	---	---	Average	Horizontal
2.	2483.500	45.33	-2.35	42.98	54.00	-11.02	Average	Horizontal





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
3.	2390.000	52.23	-2.86	49.37	74.00	-24.63	Peak	Vertical
4.	2402.000	90.44	-2.80	87.64	---	---	Peak	Vertical
3.	2390.000	41.47	-2.86	38.61	54.00	-15.39	Average	Vertical
4.	2402.000	85.71	-2.80	82.91	---	---	Average	Vertical



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
3.	2390.000	56.39	-2.86	53.53	74.00	-20.47	Peak	Horizontal
4.	2402.000	104.15	-2.80	101.35	---	---	Peak	Horizontal
1.	2390.000	43.49	-2.86	40.63	54.00	-13.37	Average	Horizontal
2.	2402.000	99.39	-2.80	96.59	---	---	Average	Horizontal



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2479.975	93.54	-2.37	91.17	---	---	Peak	Vertical
2.	2483.500	56.25	-2.35	53.90	74.00	-20.10	Peak	Vertical
1.	2480.025	89.97	-2.37	87.60	---	---	Average	Vertical
2.	2483.500	42.97	-2.35	40.62	54.00	-13.38	Average	Vertical



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
3.	2479.975	106.00	-2.37	103.63	---	---	Peak	Horizontal
4.	2483.500	70.03	-2.35	67.68	74.00	-6.32	Peak	Horizontal
3.	2479.975	106.00	-2.37	103.63	---	---	Average	Horizontal
4.	2483.500	70.03	-2.35	67.68	74.00	-6.32	Average	Horizontal




7.9. SPURIOUS EMISSIONS

7.9.1. CONDUCTED MEASUREMENT

7.9.1.1. LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

7.9.1.2. TEST CONFIGURATION



7.9.1.3. TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 9 kHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels, and highest channels. No emission found between lowest internal used/generated frequency to 10MHz , it is only recorded 10MHz to 26GHz.


7.9.1.4. TEST RESULTS

No non-compliance noted

Remark: *The hopping on mode and hopping off mode were chosen for pre-test and the hopping off mode was the worse case and print in the report.*




Hopping Off






CH Mid (10MHz ~26.5GHz)




CH Mid






CH High (10MHz ~26.5GHz)




CH High (2.45GHz ~2.5GHz)








8DPSK mode



CH Low (10MHz ~26.5GHz)



CH Low (2.31GHz ~2.43GHz)










Hopping On


GFSK

CH Low (2.31GHz ~2.5GHz)



8DPSK

CH Low (2.31GHz ~2.5GHz)





7.9.2. RADIATED EMISSIONS

7.9.2.1. LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54




7.9.2.2. TEST CONFIGURATION

Below 30MHz




Below 1 GHz





Above 1 GHz





7.9.2.3. MEASURING SETTING

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/T for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/T for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

7.9.2.4. TEST PROCEDURE

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Pre measurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions



Final measurement:

--- Identified emissions during the pre measurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Pre measurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:



- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Pre measurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna



polarizations.

- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

Pre measurement:

- The antenna is moved spherical over the EUT in different polarisations of the antenna.

Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.




7.9.2.5. TEST RESULTS

Below 1 GHz

Notes:

- 1. No emission found between lowest internal used/generated frequency to 30MHz.
- 2. Pre-scan all mode and recorded the worst case results in this report (TX-Low Channel(1Mbps))


Temp. & Humidity	24°C, 52%	Test By	Eve Wang
Polarization	Vertical	Test Date	2018/06/28
Test Mode	TX / GFSK / CH Low		



Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
148.3400	50.63	-21.68	28.95	43.50	-14.55	QP
288.0200	50.67	-20.45	30.22	46.00	-15.78	QP
406.3600	51.66	-15.78	35.88	46.00	-10.12	QP
489.7800	43.30	-14.36	28.94	46.00	-17.06	QP
606.1800	40.82	-12.71	28.11	46.00	-17.89	QP
879.7200	44.11	-9.98	34.13	46.00	-11.87	QP



Temp. & Humidity	24°C, 52%	Test By	Eve Wang
Polarization	Horizontal	Test Date	2018/06/28
Test Mode	TX / GFSK / CH Low		



Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
148.3400	54.32	-21.68	32.64	43.50	-10.86	QP
288.0200	49.26	-20.45	28.81	46.00	-17.19	QP
405.3900	50.01	-15.83	34.18	46.00	-11.82	QP
660.5000	38.41	-12.37	26.04	46.00	-19.96	QP
742.9500	41.06	-11.30	29.76	46.00	-16.24	QP
890.3900	37.35	-9.90	27.45	46.00	-18.55	QP



Above 1 GHz

Temp. & Humidity	24°C, 52%	Test By	Eve Wang
Polarization	Vertical / Horizontal	Test Date	2018/06/28
Test Mode	TX / GFSK / CH Low		

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1909.000	55.42	-5.58	49.84	74.00	-24.16	V	peak
2665.000	46.23	-1.96	44.27	74.00	-29.73	V	peak
3619.000	43.20	-0.02	43.18	74.00	-30.82	V	peak
4807.000	43.95	4.35	48.30	74.00	-25.70	V	peak
5644.000	40.97	5.93	46.90	74.00	-27.10	V	peak
6526.000	41.76	6.93	48.69	74.00	-25.31	V	peak
1594.000	58.27	-6.71	51.56	74.00	-22.44	H	Peak
1909.000	50.16	-5.58	44.58	74.00	-29.42	H	Peak
2656.000	45.73	-1.98	43.75	74.00	-30.25	H	Peak
3367.000	43.41	-0.74	42.67	74.00	-31.33	H	Peak
4807.000	44.96	4.35	49.31	74.00	-24.69	H	peak
5068.000	42.04	5.10	47.14	74.00	-26.86	H	peak

Temp. & Humidity	24°C, 52%	Test By	Eve Wang
Polarization	Vertical / Horizontal	Test Date	2018/06/28
Test Mode	TX / GFSK / CH Mid		

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1909.000	55.24	-5.58	49.66	74.00	-24.34	V	peak
2656.000	45.81	-1.98	43.83	74.00	-30.17	V	peak
4879.000	43.14	4.59	47.73	74.00	-26.27	V	peak
5446.000	41.76	5.77	47.53	74.00	-26.47	V	peak
6544.000	41.07	6.96	48.03	74.00	-25.97	V	peak
7327.000	43.21	8.34	51.55	74.00	-22.45	V	peak
1909.000	53.06	-5.58	47.48	74.00	-26.52	H	Peak
2665.000	45.43	-1.96	43.47	74.00	-30.53	H	Peak
3367.000	43.56	-0.74	42.82	74.00	-31.18	H	Peak
4879.000	43.59	4.59	48.18	74.00	-25.82	H	Peak
5914.000	41.61	6.04	47.65	74.00	-26.35	H	peak
7327.000	46.16	8.34	54.50	74.00	-19.50	H	peak
7327.000	40.76	8.34	49.10	54.00	-4.90	H	AVG



Temp. & Humidity	24°C, 52%	Test By	Eve Wang
Polarization	Vertical / Horizontal	Test Date	2018/06/28
Test Mode	TX / GFSK / CH High		

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2656.000	47.12	-1.98	45.14	74.00	-28.86	V	peak
4231.000	41.48	2.40	43.88	74.00	-30.12	V	peak
4960.000	43.17	4.85	48.02	74.00	-25.98	V	peak
6139.000	40.74	6.31	47.05	74.00	-26.95	V	peak
6553.000	41.30	6.98	48.28	74.00	-25.72	V	peak
7444.000	45.41	8.57	53.98	74.00	-20.02	V	peak
7444.000	42.59	8.57	51.16	54.00	-2.84	V	AVG
2674.000	45.78	-1.95	43.83	74.00	-30.17	H	Peak
4330.000	42.86	2.75	45.61	74.00	-28.39	H	Peak
5185.000	41.30	5.31	46.61	74.00	-27.39	H	Peak
5950.000	40.89	6.06	46.95	74.00	-27.05	H	Peak
6562.000	42.13	6.99	49.12	74.00	-24.88	H	peak
7444.000	45.10	8.57	53.67	74.00	-20.33	H	peak
7444.000	41.78	8.57	50.35	54.00	-3.65	H	AVG

Temp. & Humidity	24°C, 52%	Test By	Eve Wang
Polarization	Vertical / Horizontal	Test Date	2018/06/28
Test Mode	TX / 8DPSK / CH Low		

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1594.000	52.41	-6.71	45.70	74.00	-28.30	V	peak
1918.000	52.17	-5.52	46.65	74.00	-27.35	V	peak
2674.000	45.55	-1.95	43.60	74.00	-30.40	V	peak
4150.000	43.02	2.12	45.14	74.00	-28.86	V	peak
4807.000	42.88	4.35	47.23	74.00	-26.77	V	peak
6346.000	41.81	6.64	48.45	74.00	-25.55	V	peak
1909.000	50.65	-5.58	45.07	74.00	-28.93	H	Peak
2647.000	46.23	-2.00	44.23	74.00	-29.77	H	Peak
4807.000	43.79	4.35	48.14	74.00	-25.86	H	Peak
5716.000	40.76	5.96	46.72	74.00	-27.28	H	Peak
6706.000	40.80	7.22	48.02	74.00	-25.98	H	peak
7210.000	41.02	8.11	49.13	74.00	-24.87	H	peak



Temp. & Humidity	24°C, 52%	Test By	Eve Wang
Polarization	Vertical / Horizontal	Test Date	2018/06/28
Test Mode	TX / 8DPSK / CH Mid		

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1594.000	50.04	-6.71	43.33	74.00	-30.67	V	peak
2035.000	47.01	-4.81	42.20	74.00	-31.80	V	peak
2656.000	45.81	-1.98	43.83	74.00	-30.17	V	peak
4204.000	42.29	2.31	44.60	74.00	-29.40	V	peak
4879.000	42.64	4.59	47.23	74.00	-26.77	V	peak
6751.000	40.82	7.30	48.12	74.00	-25.88	V	peak
1594.000	50.11	-6.71	43.40	74.00	-30.60	H	Peak
2233.000	45.96	-3.72	42.24	74.00	-31.76	H	Peak
2665.000	44.93	-1.96	42.97	74.00	-31.03	H	Peak
4879.000	42.59	4.59	47.18	74.00	-26.82	H	Peak
5455.000	41.28	5.79	47.07	74.00	-26.93	H	peak
6382.000	41.24	6.70	47.94	74.00	-26.06	H	peak

Temp. & Humidity	24°C, 52%	Test By	Eve Wang
Polarization	Vertical / Horizontal	Test Date	2018/06/28
Test Mode	TX / 8DPSK / CH High		

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1306.000	48.97	-7.40	41.57	74.00	-32.43	V	peak
1909.000	48.07	-5.58	42.49	74.00	-31.51	V	peak
2656.000	47.12	-1.98	45.14	74.00	-28.86	V	peak
4033.000	42.11	1.71	43.82	74.00	-30.18	V	peak
4960.000	43.17	4.85	48.02	74.00	-25.98	V	peak
5464.000	41.78	5.81	47.59	74.00	-26.41	V	peak
2206.000	45.78	-3.87	41.91	74.00	-32.09	H	Peak
2674.000	45.78	-1.95	43.83	74.00	-30.17	H	Peak
3367.000	43.92	-0.74	43.18	74.00	-30.82	H	Peak
4330.000	42.86	2.75	45.61	74.00	-28.39	H	Peak
5185.000	41.30	5.31	46.61	74.00	-27.39	H	peak
6562.000	42.13	6.99	49.12	74.00	-24.88	H	peak



Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = auto.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.
5. Frequency (MHz). = Emission frequency in MHz
Reading (dB μ V/m) = Uncorrected Analyzer / Receiver Reading
Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
Limit (dB μ V/m) = Limit stated in standard
Margin (dB) = Result (dB μ V/m)- Limit (dB μ V/m)
Peak =Peak Reading
AVG. =Average Reading
Remark = Mark Peak Reading or Average Reading