Shenzhen Reflying Electronic Co., Ltd.

2018/5/21

To: Federal Communications Commission 7435 Oakland Mills Road Columbia, MD

FCC ID: A7M-K1181291

To Whom It May Concern:

This letter is to ascertain that **Shenzhen Reflying Electronic Co., Ltd.** Product Wireless Charger **A7M-K1181291**, has been the units used for conducting FCC compliance testing, and it meets 680106 D01 RF Exposure Wireless Charging App v03 Clause 5(b) all 6 conditions.

| 1 | Power transfer frequency is less that 1 MHz |
|--------|--|
| Reply: | Yes, frequency is 110 - 205 KHz |
| 2 | Output power from each primary coil is less than or equal to 15 watts. |
| Reply: | Yes, output power of the primary coil is 5W. |
| 3 | The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils. |
| Reply: | Yes, the transfer system includes only single primary and secondary coils. |
| 4 | Client device is placed directly in contact with the transmitter. |
| Reply: | Yes, client device is placed directly in contact with the transmitter. |
| 5 | Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion). |
| Reply: | Yes, the EUT is a Mobile Wireless Charger |
| 6 | The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit. |
| Reply: | Yes, the EUT field strength levels are 50% x MPE limit. |

If you have any question or concerns, pls. contact us.

Sincerely,

Client's signature:

Client's name / title : Wen Luo /manager

Contact information / address: 6 Bldg, GaoXinJian Industrial zone, HePing village, Fuyong Town,

Bao'an district, Shenzhen, Guangdong, China