

S

T

S

L

A

B



## MPE TEST REPORT

Report No:STS2207074H01

Issued for

Shenzhen Reflying Electronic Co., Ltd

6 Bldg, GaoXinJian Industrial zone, HePing village, Fuyong  
Town, Bao'an district, Shenzhen, Guangdong, China

<b>Product Name:</b>	Magnetic Wireless Car Charger
<b>Brand Name:</b>	NA
<b>Model Name:</b>	BE-MVQ3AC1B23, BE-MVQ3ACxxxxxxxx, NS- MVQ3ACxxxxxxxx, ("x"=0-9, A-Z, a-z, - or blank, for market purpose only)
<b>Series Model:</b>	N/A
<b>FCC ID:</b>	A7M-MVQ3AC1B23
<b>Test Standard:</b>	FCC CFR 47 part 1, 1.1310

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.  
A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ,  
Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China  
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com



**TEST RESULT CERTIFICATION**

Applicant's Name.....: Shenzhen Reflying Electronic Co., Ltd  
Address .....: 6 Bldg, GaoXinJian Industrial zone, HePing village, Fuyong Town, Bao'an district, Shenzhen, Guangdong, China  
Manufacturer's Name .....: Shenzhen Reflying Electronic Co., Ltd  
Address .....: 6 Bldg, GaoXinJian Industrial zone, HePing village, Fuyong Town, Bao'an district, Shenzhen, Guangdong, China

**Product Description**

Product Name.....: Magnetic Wireless Car Charger  
Brand Name .....: NA  
Model Name .....: BE-MVQ3AC1B23, BE-MVQ3ACxxxxxxxx, NS-MVQ3ACxxxxxxxx, ("x"=0-9, A-Z, a-z, - or blank, for market purpose only)  
Series Model.....: N/A  
Standards .....: FCC CFR 47 part 1, 1.1310  
Test Procedure .....: 680106 D01 RF Exposure Wireless Charging Apps v03

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the Date of Test.....:

Date of receipt of test item.....: 13 July 2022  
Date of performance of tests ...: 13 July 2022 ~ 19 July 2022  
Date of Issue .....: 19 July 2022  
Test Result .....: **Pass**

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sean She)

Authorized Signatory :

(Bovey Yang)





Table of Contents	Page
<b>1. SUMMARY OF TEST RESULTS</b>	<b>5</b>
1.1 TEST FACTORY	5
1.2 MEASUREMENT UNCERTAINTY	5
1.3 GENERAL DESCRIPTION OF THE EUT	6
1.4 EQUIPMENTS LIST FOR ALL TEST ITEMS	7
1.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	7
<b>2. MAXIMUM PERMISSIBLE EXPOSURE</b>	<b>8</b>
2.1 MAXIMUM PERMISSIBLE EXPOSURE	8
2.2 TEST PROCEDURE	9
2.3 TEST SETUP	9
2.4 TEST RESULTS	9
2.5 MAXIMUM PERMISSIBLE EXPOSURE	10



**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	19 July 2022	STS2207074H01	ALL	Initial Issue





## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC KDB 680106 D01 RF Exposure Wireless Charging Apps v03

FCC CFR 47			
Standard Section	Test Item	Judgment	Remark
FCC CFR 47 part1, 1.1310 KDB680106 D01v03	Electric Field Strength (E) (V/m)	PASS	
	Magnetic Field Strength (H) (A/m)	PASS	

### 1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainly
1	H-filed	$\pm 0.83\text{dB}$
2	E-filed	$\pm 0.91\text{dB}$

### 1.3 GENERAL DESCRIPTION OF THE EUT

Product Name	Magnetic Wireless Car Charger
Trade Name	NA
Model Name	BE-MVQ3AC1B23, BE-MVQ3ACxxxxxxx, NS-MVQ3ACxxxxxxx, ("x"=0-9, A-Z, a-z, - or blank, for market purpose only)
Series Model	N/A
Model Difference	N/A
Equipemnt Category	Non-ISM frequency
Antenna Type	Please refer to the Note 2.
Operating frequency	111-205kHz
Modulation Type	ASK
Rating	For car charger: Input: DC 12-24V Cable Output: DC 9V, 2A USB-A Output: DC 5V, 1A  For Wireless charger: Input: DC 9V, A via car charger Output: 10W maximum
Hardware version number	N/A
Software version number	N/A
Connecting I/O Port(s)	A003288382-012

Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
- Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	NOTE
1	N/A	BE-MQ231W23	Coil	NA	Antenna

The EUT antenna is Coil Antenna. No antenna other than that furnished by the responsible party shall be used with the device.



## 1.4 EQUIPMENTS LIST FOR ALL TEST ITEMS

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Electric and Magnetic field Probe - Analyzer	Narda	EHP 200A	180ZX10220	2021.08.02	2022.08.01

## 1.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

## Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
N/A	N/A	N/A	N/A	N/A	N/A

## Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
E-1	Iphone	Iphone	Iphone 8	N/A	N/A

## Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.

## 2. MAXIMUM PERMISSIBLE EXPOSURE

### 2.1 MAXIMUM PERMISSIBLE EXPOSURE

#### Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180 / f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1	30

Note 1: f = frequency in MHz ; \*Plane-wave equivalent power density

Note 2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v03

Note 3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1

of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.


Note 4: The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.



## 2.2 TEST PROCEDURE

- a. For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 20 cm(Top) and 15cm(Edge). E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 20 cm(Top) and 15cm(Edge) measured from the center of the probe(s) to the edge of the device.

## 2.3 TEST SETUP



Remark: The EHP 200A probe antenna diameter is less than 11.5cm.

## 2.4 TEST RESULTS

The EUT does comply with item 5 KDB680106 D01 v03.

- (1) Power transfer frequency is less than 1 MHz.  
(Conform)
- (2) Output power from each primary coil is less than or equal to 15 watts.  
(Conform)
- (3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.  
(Conform)
- (4) Client device is placed directly in contact with the transmitter.  
(Conform)
- (5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).  
(Conform)
- (6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.  
(Conform)



## 2.5 MAXIMUM PERMISSIBLE EXPOSURE

Maximum Permissible Exposure				
Charging	Separation	Probe from EUT Side	E-field (V/m)	H-field (A/m)
< 1% Battery	15cm	Front	0.449	0.097
< 1% Battery	15cm	Rear	0.429	0.116
< 1% Battery	15cm	Left	0.426	0.115
< 1% Battery	15cm	Right	0.449	0.109
< 1% Battery	20cm	Top	0.474	0.132
Limit			614	1.630
Margin Limit (%)			0.08%	8.10%

Maximum Permissible Exposure				
Charging	Separation	Probe from EUT Side	E-field (V/m)	H-field (A/m)
50% Battery	15cm	Front	0.455	0.125
50% Battery	15cm	Rear	0.431	0.098
50% Battery	15cm	Left	0.432	0.111
50% Battery	15cm	Right	0.441	0.114
50% Battery	20cm	Top	0.475	0.135
Limit			614	1.630
Margin Limit (%)			0.08%	8.28%

Maximum Permissible Exposure				
Charging	Separation	Probe from EUT Side	E-field (V/m)	H-field (A/m)
> 99% Battery	15cm	Front	0.455	0.115
> 99% Battery	15cm	Rear	0.428	0.103
> 99% Battery	15cm	Left	0.418	0.122
> 99% Battery	15cm	Right	0.453	0.11
> 99% Battery	20cm	Top	0.465	0.146
Limit			614	1.630
Margin Limit (%)			0.08%	8.96%

