

# FCC Co-Location Test Report

**FCC ID** : A8J-EAP1250  
**Equipment** : AC1300 Ceiling Mount Access Point  
**Model No.** : EAP1250, EWS330AP  
(Please refer to section 1.1.1 for more details)  
**Brand Name** : EnGenius  
**Applicant** : EnGenius Technologies  
**Address** : 1580 Scenic Avenue, Costa Mesa CA92626  
**Standard** : 47 CFR FCC Part 15.247  
47 CFR FCC Part 15.407  
**Received Date** : Dec. 11, 2017  
**Tested Date** : Dec. 11, 2017

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

  
\_\_\_\_\_  
Along Chen / Assistant Manager

Approved by:

  
\_\_\_\_\_  
Gary Chang / Manager



---

## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	The Equipment List .....	6
1.3	Test Standards .....	7
1.4	Measurement Uncertainty .....	7
<b>2</b>	<b>TEST CONFIGURATION .....</b>	<b>8</b>
2.1	Testing Condition .....	8
2.2	The Worst Test Modes and Channel Details .....	8
<b>3</b>	<b>TRANSMITTER TEST RESULTS.....</b>	<b>9</b>
3.1	Unwanted Emissions into Restricted Frequency Bands .....	9
<b>4</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>17</b>

---

## Release Record

Report No.	Version	Description	Issued Date
FR7D1201CO	Rev. 01	Initial issue	Jan. 29, 2018

---

## Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.247(d) 15.407(b) 15.209	Radiated Emissions	[dBuV/m at 3m]: 70.69MHz 37.42(Margin -2.58dB) - QP	Pass

# 1 General Description

## 1.1 Information

### 1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name	Description
EnGenius	EWS330AP	AC1300 Ceiling Mount Access Point	For marketing difference
	EAP1250		
† The above models, model EAP1250 was selected as a representative one for the final test and only its data was recorded in this report.			

### 1.1.2 Antenna Details

Ant. No.	Model	Type	Connector	Operating Frequency (MHz) / Gain (dBi)			Remark
				2400~2483.5	5150~5250	5725~5850	
1	Antenna 1	Dipole	UFL	4.12	---	---	---
2	Antenna 2	Dipole	UFL	4.03	---	---	---
3	Antenna 3	Dipole	UFL	---	5.11	5.11	---
4	Antenna 4	Dipole	UFL	---	5.03	5.03	---

### 1.1.3 Accessories

Accessories		
No.	Equipment	Description
1	AC adapter	Brand: DVE Model: DSA-12PFT-12 FUS 120100 Power Rating: I/P: 100-240Vac, 50/60Hz, 0.5A O/P: 12Vdc, 1A Power Line: 1.5m non-shielded without core

## 1.2 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Tested Date	Dec. 11, 2017				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101499	Dec. 16, 2016	Dec. 15, 2017
Receiver	R&S	ESR3	101658	Nov. 20, 2017	Nov. 19, 2018
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 28, 2017	Apr. 27, 2018
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 09, 2017	Feb. 08, 2018
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 23, 2017	Nov. 22, 2018
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2017	Nov. 12, 2018
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 07, 2017	Dec. 06, 2018
Preamplifier	EMC	EMC02325	980187	Sep. 04, 2017	Sep. 03, 2018
Preamplifier	Agilent	83017A	MY53270014	Aug. 21, 2017	Aug. 20, 2018
Preamplifier	EMC	EMC184045B	980192	Aug. 22, 2017	Aug. 21, 2018
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Nov. 27, 2017	Nov. 26, 2018
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY32487/4	Nov. 27, 2017	Nov. 26, 2018
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Nov. 27, 2017	Nov. 26, 2018
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Nov. 27, 2017	Nov. 26, 2018
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Nov. 27, 2017	Nov. 26, 2018
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Nov. 27, 2017	Nov. 26, 2018
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

### 1.3 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v04

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

### 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty	
Parameters	Uncertainty
Radiated emission $\leq$ 1GHz	$\pm 3.62$ dB
Radiated emission $>$ 1GHz	$\pm 5.60$ dB

## 2 Test Configuration

### 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH03-WS	23-24°C / 65-66%	Brad Wu Roger Lu

➤ FCC site registration No.: 207696

➤ IC site registration No.: 10807C-1

### 2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Radiated Emissions ≤1GHz	2.4G 11AC20 + 5G 11AC20	CH6 + CH40	MCS 0 + MCS 0	1,2
Radiated Emissions >1GHz	2.4G 11AC20 + 5G 11AC20	CH6 + CH40	MCS 0 + MCS 0	1

**NOTE:**

- The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The Y-plane result was found as the worst case and was shown in this report.
- The following antennas are used on this EUT:  
Configuration 1: POE MODE.  
Configuration 2: Adapter MODE



## 3 Transmitter Test Results

### 3.1 Unwanted Emissions into Restricted Frequency Bands

#### 3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

**Note 1:**  
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

**Note 2:**  
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

#### 3.1.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

**Note:**


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

### 3.1.3 Test Setup

#### Radiated Emissions below 1 GHz




#### Radiated Emissions above 1 GHz



### 3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

<b>Modulation</b>	2.4G 11AC20 + 5G 11AC20	<b>Test Freq. (MHz)</b>	CH6 + CH40
<b>Polarization</b>	Horizontal	<b>Test Configuration</b>	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	142.52	35.74	43.50	-7.76	44.10	-8.36	Peak	---	---
2	212.36	28.57	43.50	-14.93	39.23	-10.66	Peak	---	---
3	326.82	26.51	46.00	-19.49	33.42	-6.91	Peak	---	---
4	429.64	29.84	46.00	-16.16	34.06	-4.22	Peak	---	---
5	608.12	29.80	46.00	-16.20	30.32	-0.52	Peak	---	---
6	831.22	33.08	46.00	-12.92	30.09	2.99	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Modulation</b>	2.4G 11AC20 + 5G 11AC20	<b>Test Freq. (MHz)</b>	CH6 + CH40
<b>Polarization</b>	Vertical	<b>Test Configuration</b>	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	70.69	37.42	40.00	-2.58	47.94	-10.52	QP	100	5
2	140.58	32.55	43.50	-10.95	40.97	-8.42	Peak	---	---
3	406.36	26.45	46.00	-19.55	31.26	-4.81	Peak	---	---
4	499.48	28.54	46.00	-17.46	31.54	-3.00	Peak	---	---
5	611.03	33.64	46.00	-12.36	34.12	-0.48	Peak	---	---
6	884.57	34.38	46.00	-11.62	30.55	3.83	Peak	---	---


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Modulation</b>	2.4G 11AC20 + 5G 11AC20	<b>Test Freq. (MHz)</b>	CH6 + CH40
<b>Polarization</b>	Horizontal	<b>Test Configuration</b>	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	99.84	30.08	43.50	-13.42	43.27	-13.19	Peak	---	---
2	157.07	37.09	43.50	-6.41	45.11	-8.02	Peak	---	---
3	334.58	26.45	46.00	-19.55	33.19	-6.74	Peak	---	---
4	500.45	29.13	46.00	-16.87	32.11	-2.98	Peak	---	---
5	837.04	34.58	46.00	-11.42	31.51	3.07	Peak	---	---
6	953.44	36.97	46.00	-9.03	31.82	5.15	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Modulation</b>	2.4G 11AC20 + 5G 11AC20	<b>Test Freq. (MHz)</b>	CH6 + CH40
<b>Polarization</b>	Vertical	<b>Test Configuration</b>	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	50.37	36.98	40.00	-3.02	44.88	-7.90	QP	100	49
2	103.72	29.58	43.50	-13.92	42.10	-12.52	Peak	---	---
3	159.01	31.22	43.50	-12.28	39.21	-7.99	Peak	---	---
4	335.55	25.35	46.00	-20.65	32.07	-6.72	Peak	---	---
5	634.31	30.97	46.00	-15.03	31.15	-0.18	Peak	---	---
6	953.44	37.33	46.00	-8.67	32.18	5.15	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.1.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation	2.4G 11AC20 + 5G 11AC20	Test Freq. (MHz)	CH6 + CH40																																																											
Polarization	Horizontal	Test Configuration	1																																																											
																																																														
	<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High</th> <th>Turn Table</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2763.00</td> <td>45.99</td> <td>54.00</td> <td>-8.01</td> <td>46.02</td> <td>-0.03</td> <td>Average</td> <td>100</td> <td>15</td> </tr> <tr> <td>2</td> <td>2763.00</td> <td>59.20</td> <td>74.00</td> <td>-14.80</td> <td>59.23</td> <td>-0.03</td> <td>Peak</td> <td>100</td> <td>15</td> </tr> <tr> <td>3</td> <td>7637.00</td> <td>39.60</td> <td>54.00</td> <td>-14.40</td> <td>28.22</td> <td>11.38</td> <td>Average</td> <td>100</td> <td>24</td> </tr> <tr> <td>4</td> <td>7637.00</td> <td>52.37</td> <td>74.00</td> <td>-21.63</td> <td>40.99</td> <td>11.38</td> <td>Peak</td> <td>100</td> <td>24</td> </tr> </tbody> </table>	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	2763.00	45.99	54.00	-8.01	46.02	-0.03	Average	100	15	2	2763.00	59.20	74.00	-14.80	59.23	-0.03	Peak	100	15	3	7637.00	39.60	54.00	-14.40	28.22	11.38	Average	100	24	4	7637.00	52.37	74.00	-21.63	40.99	11.38	Peak	100	24			
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																						
1	2763.00	45.99	54.00	-8.01	46.02	-0.03	Average	100	15																																																					
2	2763.00	59.20	74.00	-14.80	59.23	-0.03	Peak	100	15																																																					
3	7637.00	39.60	54.00	-14.40	28.22	11.38	Average	100	24																																																					
4	7637.00	52.37	74.00	-21.63	40.99	11.38	Peak	100	24																																																					
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>																																																														

<b>Modulation</b>	2.4G 11AC20 + 5G 11AC20	<b>Test Freq. (MHz)</b>	CH6 + CH40
<b>Polarization</b>	Vertical	<b>Test Configuration</b>	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2763.00	45.94	54.00	-8.06	45.97	-0.03	Average	106	48
2	2763.00	59.03	74.00	-14.97	59.06	-0.03	Peak	106	48
3	7637.00	39.88	54.00	-14.12	28.50	11.38	Average	100	19
4	7637.00	53.27	74.00	-20.73	41.89	11.38	Peak	100	19

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

### **Linkou**

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin  
Kou District, New Taipei City,  
Taiwan, R.O.C.

### **Kwei Shan**

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,  
Kwei Shan District, Tao Yuan City  
333, Taiwan, R.O.C.

### **Kwei Shan Site II**

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd  
St., Kwei Shan District, Tao Yuan  
City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==