

Radio Exposure Evaluation Report

FCC ID : A8J-ECW526
Equipment : EnGenius Cloud Wi-Fi 7 2x2 Tri-Band Indoor Access Point
Brand Name : EnGenius EnGenius®
Model Name : ECW526
Applicant : EnGenius Technologies
1580 Scenic Avenue, Costa Mesa, CA92626
Manufacturer : EnGenius Networks Inc.
10F., No.209, Sec. 1, Nangang Rd., Nangang Dist., Taipei City
115018, Taiwan
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Nov. 28, 2023, and testing was started from Mar. 25, 2024 and completed on Apr. 04, 2024. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Ben Tesng

SPORTON INTERNATIONAL INC. Hsinhua Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT3

SUMMARY OF TEST RESULT4

1 GENERAL DESCRIPTION5

1.1 Information.....5

1.2 Applicable Standards8

1.3 Testing Location8

2 MAXIMUM PERMISSIBLE EXPOSURE9

2.1 Limit of Maximum Permissible Exposure9

2.2 RF Exposure Exempt Measurement10

2.3 Multiple RF Sources Exposure.....11

2.4 MPE Calculation Method12

2.5 Calculated Result and Limit.....13

Photographs of EUT V01



History of this test report

Report No.	Version	Description	Issued Date
FA422116	01	Initial issue of report	May 03, 2024
FA422116	02	Revised typo (This report is the latest version replacing for the report issued on May 03, 2024.)	May 28, 2024



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Terry Chang

Report Producer: Amber Chiu

1 General Description

1.1 Information

1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
6GHz WLAN	5925-7125	5955-7115	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)



1.1.2 Antenna Information

Ant.	Port	Brand	Model Name	Antenna Type	Connector	Support
1	1	Senao	5718A0751300	PIFA	I-Pex	2.4G
2	2	Senao	5718A0750300	PIFA	I-Pex	2.4G
3	1	Senao	5718A0753300	PIFA	I-Pex	5G
4	2	Senao	5718A0752300	PIFA	I-Pex	5G
5	1	AWAN	7102A0951000	Alford Loop	I-Pex	6G
6	2	AWAN	7102A0952000	Alford Loop	I-Pex	6G
7	3	AWAN	7102A0953000	Dipole	I-Pex	BT

Gain (dBi)									Remark
Ant.	Port	2.4G	5G				6G	BT	
			UNII-1	UNII-2A	UNII-2C	UNII-3			
1	1	2.24	-	-	-	-	-	-	Radio 1
2	2	3.12	-	-	-	-	-	-	Radio 1
3	1	-	5.55	5.98	5.87	5.49	-	-	Radio 2_5G 2*2
4	2	-	5.48	5.41	4.88	4.65	-	-	Radio 2_5G 2*2
5	1	-	-	-	-	-	5.1	-	Radio 2
6	2	-	-	-	-	-	5.6	-	Radio 2
7	3	-	-	-	-	-	-	3.2	-

Composite Gain (dBi)							
	2.4G	2.45G	2.4835G	UNII-1	UNII-2A	UNII-2C	UNII-3
DG [1SS] (dBi)	3.33	3.92	4.52	6.77	7	7.46	6.35
DG [2SS] (dBi)	2.24	2.35	3.12	5.55	5.98	5.87	5.49

Note 1: The EUT has seven antennas.

Note 2: The composite gain is derived as KDB 662911 D03 v01 which was used as directional gain. For more detail information, please refer to the Antenna Pattern Report AP421504.

For 2.4GHz function: < Radio 1 >

For IEEE 802.11b/g/n/VHT/ax/be mode (2TX/2RX)

Ant.1 (port 1), Ant.2 (port 2) could transmit/receive simultaneously.

For 5GHz function: < Radio 2 >

For IEEE 802.11a/n/ac/ax/be mode (2TX/2RX)

Ant.3 (port 1), Ant.4 (port 2) could transmit/receive simultaneously.

For 6GHz function: < Radio 2 >

For IEEE 802.11 ax/be mode (2TX/2RX)

Ant.5 (port 1), Ant.6 (port 2) could transmit/receive simultaneously.

For Bluetooth function:

For Bluetooth mode (1TX/1RX)

Only Ant.7 can be used as transmitting/receiving.



1.1.3 Accessories

Accessories				
Bracket	Brand Name	Dragonjet	Part Number	6301A6543000

Reminder: Regarding to more detail and other information, please refer to user manual.

1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 2 Subpart J, section 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

1.3 Testing Location

Test Lab. : Sporton International Inc. Hsinhua Laboratory			
☒	Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)	
		TEL: 886-3-327-3456	FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.			
☐	Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)	
		TEL: 886-3-318-0787	FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.			

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

Multiple Transmitters Condition

Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.

Co-transmitting mode: 2.4GHz WLAN + 5GHz WLAN + 6GHz WLAN + Bluetooth

2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x \rightarrow d \leq 20cm \\ ERP_{20cm} \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040 f(mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060(mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920 R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450 R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128 R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ f is in MHz; R is in m; $R > \lambda / 2\pi$

2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added. b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added. c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters. P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive). $P_{th,i}$ = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i. ERP_j = the ERP of fixed, mobile, or portable RF source j. $ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section. $Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure. $Evaluated Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.



2.4 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.
The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

2.4GHz WLAN_Non-Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	3.12	24.01	27.13	0.50	353.27	20	B	3060.000	0.11545
2.4G;D1D	3.12	23.63	26.75	0.50	323.68	20	B	3060.000	0.10578

2.4GHz WLAN_Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	4.52	23.42	27.94	0.50	425.71	20	B	3060.000	0.13912

5GHz WLAN_Non-Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	5.55	24.36	29.91	0.50	670.05	20	B	3060.000	0.21897
5.3G;D1D	5.98	23.35	29.33	0.50	586.29	20	B	3060.000	0.19160
5.6G;D1D	5.87	23.57	29.44	0.50	601.33	20	B	3060.000	0.19651
5.8G;D1D	5.49	24.08	29.57	0.50	619.60	20	B	3060.000	0.20248

5GHz WLAN_Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	6.77	24.22	30.99	0.50	859.23	20	B	3060.000	0.28079
5.3G;D1D	7.00	22.47	29.47	0.50	605.49	20	B	3060.000	0.19787
5.6G;D1D	7.46	22.03	29.49	0.50	608.29	20	B	3060.000	0.19879
5.8G;D1D	6.35	23.96	30.31	0.50	734.70	20	B	3060.000	0.24010

6GHz WLAN_Non-Beamforming

Mode	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	26.99	0.50	342.07	20	C	768.000	0.44540
6.4G;D1D	24.48	0.50	191.92	20	C	768.000	0.24989
6.7G;D1D	27.37	0.50	373.34	20	C	768.000	0.48613
7.0G;D1D	25.94	0.50	268.60	20	C	768.000	0.34974

6GHz WLAN_Beamforming

Mode	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
6.2G;D1D	26.68	0.50	318.50	20	C	768.000	0.41471
6.4G;D1D	25.51	0.50	243.28	20	C	768.000	0.31677
6.7G;D1D	26.78	0.50	325.92	20	C	768.000	0.42437
7.0G;D1D	26.25	0.50	288.48	20	C	768.000	0.37562

**Bluetooth**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;BT-LE	3.20	6.74	9.94	0.50	6.75	20	B	3060.000	0.00220

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Simultaneous Transmission Analysis Mode:**2.4GHz WLAN + 5GHz WLAN + 6GHz WLAN + Bluetooth**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	4.52	23.42	27.94	0.50	425.71	20	B	3060.000	0.13912
5.2G;D1D	6.77	24.22	30.99	0.50	859.23	20	B	3060.000	0.28079
6.7G;D1D	-	-	27.37	0.50	373.34	20	C	768.000	0.48613
2.4G;BT-LE	3.20	6.74	9.94	0.50	6.75	20	B	3060.000	0.00220
Sum Ratio	0.90824								
Ratio Limit	1.00000								

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Note 4: Refer as clause 2.3 Multiple RF Sources Exposure. Please follow below option and sum TL ration table.

Option	Sum TL Ratio_B	Option	Sum TL Ratio_C	Option	Sum TL Ratio_E
B	$\sum_{i=1}^a \frac{P_i}{P_{th,i}}$	C	$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}}$	E	$\sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k}$

Note: The above antenna gain was declared by manufacturer.

—————THE END—————