

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)
Report No.: RFBDIS-WTW-P23030040
FCC ID: A8J-ENSTATION6
Product: EnGenius Station Wi-Fi 6 2x2 5GHz Outdoor CPE
Brand: EnGenius
Model No.: EnStation6
Received Date: 2023/2/15
Test Date: 2023/2/15 ~ 2023/3/22
Issued Date: 2023/4/17

Applicant: EnGenius Technologies, Inc.
Address: 1580 Scenic Avenue, Costa Mesa, CA92626
Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories
Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kewi Shan Dist., Taoyuan City 33383, Taiwan
FCC Registration / 788550 / TW0003
Designation Number:

Approved by: Jeremy Lin, **Date:** 2023/4/17
Jeremy Lin / Project Engineer

This test report consists of 59 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Vera Huang / Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description	7
3.2 Antenna Description of EUT	8
3.3 Channel List	9
3.4 Test Mode Applicability and Tested Channel Detail	10
3.5 Duty Cycle of Test Signal	11
3.6 Test Program Used and Operation Descriptions	13
3.7 Connection Diagram of EUT and Peripheral Devices	13
3.8 Configuration of Peripheral Devices and Cable Connections	13
4 Test Instruments	14
4.1 RF Output Power	14
4.2 Power Spectral Density	14
4.3 6 dB Bandwidth	14
4.4 Conducted Out of Band Emissions	14
4.5 AC Power Conducted Emissions	14
4.6 Unwanted Emissions below 1 GHz	15
4.7 Unwanted Emissions above 1 GHz	16
5 Limits of Test Items	17
5.1 RF Output Power	17
5.2 Power Spectral Density	17
5.3 6 dB Bandwidth	17
5.4 Conducted Out of Band Emissions	17
5.5 AC Power Conducted Emissions	17
5.6 Unwanted Emissions below 1 GHz	17
5.7 Unwanted Emissions above 1 GHz	18
6 Test Arrangements	19
6.1 RF Output Power	19
6.1.1 Test Setup	19
6.1.2 Test Procedure	19
6.2 Power Spectral Density	19
6.2.1 Test Setup	19
6.2.2 Test Procedure	19
6.3 6 dB Bandwidth	20
6.3.1 Test Setup	20
6.3.2 Test Procedure	20
6.4 Conducted Out of Band Emissions	20
6.4.1 Test Setup	20
6.4.2 Test Procedure	20
6.5 AC Power Conducted Emissions	21
6.5.1 Test Setup	21
6.5.2 Test Procedure	21
6.6 Unwanted Emissions below 1 GHz	22
6.6.1 Test Setup	22
6.6.2 Test Procedure	23
6.7 Unwanted Emissions above 1 GHz	24
6.7.1 Test Setup	24
6.7.2 Test Procedure	24
7 Test Results of Test Item	25



7.1	RF Output Power.....	25
7.2	Power Spectral Density	26
7.3	6 dB Bandwidth	28
7.4	Conducted Out of Band Emissions	30
7.5	AC Power Conducted Emissions	34
7.6	Unwanted Emissions below 1 GHz	36
7.7	Unwanted Emissions above 1 GHz.....	38
8	Pictures of Test Arrangements	58
9	Information of the Testing Laboratories	59



Release Control Record

Issue No.	Description	Date Issued
RFB DYS-WTW-P23030040	Original Release	2023/4/17

1 Certificate

Product: EnGenius Station Wi-Fi 6 2x2 5GHz Outdoor CPE

Brand: EnGenius

Test Model: EnStation6

Sample Status: Engineering sample

Applicant: EnGenius Technologies, Inc.

Test Date: 2023/2/15 ~ 2023/3/22

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)

Measurement ANSI C63.10-2013

procedure: KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -20.64 dB at 0.66987 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -1.2 dB at 77.53 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -0.6 dB at 2390.00, 2483.50 MHz
15.203	Antenna Requirement	Pass	Antenna connector is ipex(MHF) not a standard connector.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.79 dB
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.99 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3 dB
	30 MHz ~ 1 GHz	2.93 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	1.76 dB
	18 GHz ~ 40 GHz	1.77 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	EnGenius Station Wi-Fi 6 2x2 5GHz Outdoor CPE
Brand	EnGenius
Test Model	EnStation6
Status of EUT	Engineering sample
Power Supply Rating	54Vdc from PoE
Modulation Type	CCK, DQPSK, DBPSK for DSSS 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM 1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDMA
Modulation Technology	DSSS, OFDM, OFDMA
Transfer Rate	802.11b:11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 150Mbps VHT: up to 200Mbps 802.11ax: up to 286.8Mbps
Operating Frequency	2.412 GHz ~ 2.462 GHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20):11 802.11n (HT40), VHT40, 802.11ax (HE40): 7
Output Power	73.282 mW (18.65 dBm)

Note:

1. The EUT uses following accessories.

POE		
Brand	Model	Specification
EnGenius	EPA5006GR	AC Input : 100-240VAC~0.8A, 50-60Hz DC Output : 54V/0.6A Power cord : Non-shielding AC (0.5M)

2. There is WLAN (2.4 GHz & 5 GHz) technology used for the EUT, it supported simultaneous transmission which was verified and compliance.
3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Antenna NO.	RF Chain NO.	Brand	Model	Antenna Net Gain(dBi)	Frequency range	Antenna Type	Connector Type
1	Chain 0	Senao	5718A0725300	14.1	5.15~5.25GHz	Patch	Ipex (MHF)
1	Chain 0	Senao	5718A0725300	14	5.725~5.85GHz	Patch	Ipex (MHF)
2	Chain 1	Senao	5718A0725300	14.7	5.15~5.25GHz	Patch	Ipex (MHF)
2	Chain 1	Senao	5718A0725300	14.1	5.725~5.85GHz	Patch	Ipex (MHF)
3	Chain 0	Senao	5718A0726300	3.9	2.4~2.4835GHz	Patch	Ipex (MHF)

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2. The EUT provides 1 completed transmitter and 1 receiver.

2.4 GHz Band		
Modulation Mode	TX & RX Configuration	
802.11b	1TX	1RX
802.11g	1TX	1RX
802.11n (HT20)	1TX	1RX
802.11n (HT40)	1TX	1RX
VHT20	1TX	1RX
VHT40	1TX	1RX
802.11ax (HE20)	1TX	1RX
802.11ax (HE40)	1TX	1RX

Note:

- The modulation and bandwidth are similar for 802.11n mode for 20 MHz (40 MHz) and VHT mode for 20 MHz (40 MHz), therefore the manufacturer will control the power for 802.11n/VHT mode is the same as the 802.11ax or more lower than it and investigated worst case to representative mode in test report.
- The EUT device modulation technique OFDMA does not support partial RUs (resource units).
- Partial RU (resource unit) and channel puncturing/bandwidth reduction mechanisms are not supported.

3.3 Channel List

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40), VHT40, 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	EUT can be used in the following ways: X-axis / Y-axis / Z-axis. Pre-scan these ways and find the worst case as a representative test condition.
Worst Case:	Y-axis

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power / Power Spectral Density	802.11b	1, 6, 11	DBPSK	1Mb/s
	802.11g	1, 6, 11	BPSK	6Mb/s
	802.11ax (HE20)	1, 6, 11	BPSK	MCS0
	802.11ax (HE40)	3, 6, 9	BPSK	MCS0
6 dB Bandwidth / Conducted Out of Band Emissions	802.11b	1, 6, 11	DBPSK	1Mb/s
	802.11g	1, 6, 11	BPSK	6Mb/s
	802.11ax (HE20)	1, 6, 11	BPSK	MCS0
	802.11ax (HE40)	3, 6, 9	BPSK	MCS0
AC Power Conducted Emissions	802.11b	1	DBPSK	1Mb/s
Unwanted Emissions below 1 GHz	802.11b	1	DBPSK	1Mb/s
Unwanted Emissions above 1 GHz	802.11b	1, 6, 11	DBPSK	1Mb/s
	802.11g	1, 6, 11	BPSK	6Mb/s
	802.11ax (HE20)	1, 6, 11	BPSK	MCS0
	802.11ax (HE40)	3, 6, 9	BPSK	MCS0

*The 802.11ax mode was the worst case for final test on RF Output Power.


3.5 Duty Cycle of Test Signal

802.11b: Duty cycle = 13.138 ms / 13.566 ms x 100% = 96.8%, duty factor = 10 * log (1/Duty cycle) = 0.14 dB


802.11g: Duty cycle = 1.986 ms / 2.104 ms x 100% = 94.4%, duty factor = 10 * log (1/Duty cycle) = 0.25 dB

802.11ax (HE20): Duty cycle = 5.446 ms / 5.934 ms x 100% = 91.8%, duty factor = 10 * log (1/Duty cycle) = 0.37 dB


802.11ax (HE40): Duty cycle = 5.46 ms / 6.38 ms x 100% = 85.6%, duty factor = 10 * log (1/Duty cycle) = 0.68 dB




802.11b



802.11g



802.11ax (HE20)




802.11ax (HE40)

3.6 Test Program Used and Operation Descriptions

Controlling software QSPR Version 5.0-00197 has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Noteboot	Lenovo	L470	N/A	N/A	Provided by Lab
B	Load	N/A	N/A	N/A	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	RJ-45 Cable	1	1.5	N/A	N/A	Provided by Lab
2	RJ-45 Cable	1	1.5	N/A	N/A	Provided by Lab
3	RJ-45 Cable	1	10	N/A	N/A	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
USB Wideband Power Sensor KEYSIGHT	U2021XA	MY55050005/MY55190004/MY55190007/MY55210005	2022/7/13	2023/7/12

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2023/3/22

4.2 Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Software BV	ADT_RF Test Software V6.6.5.4	N/A	N/A	N/A
Spectrum Analyzer R&S	FSV40	100980	2022/4/20	2023/4/19

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2023/3/22

4.3 6 dB Bandwidth

Refer to section 4.2 to get information of the instruments.

4.4 Conducted Out of Band Emissions

Refer to section 4.2 to get information of the instruments.

4.5 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
LISN R&S	ESH3-Z5	100311	2022/9/12	2023/9/11
LISN ROHDE & SCHWARZ	ENV216	101826	2022/3/14	2023/3/13
RF Coaxial Cable WOKEN	5D-FB	Cable-cond1-01	2023/1/7	2024/1/6
Software BVADT	BVADT_Cond_ V7.3.7.4	N/A	N/A	N/A
Test Receiver Rohde&Schwarz	ESCI	100613	2022/12/5	2023/12/4
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2022/8/31	2023/8/30

Notes:

1. The test was performed in HY - Conduction 1.
2. Tested Date: 2023/2/17

4.6 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower Max-Full	MFT-151SS-0.5T	N/A	N/A	N/A
Bi-log Broadband Antenna Schwarzbeck	VULB9168	9168-1213	2022/10/20	2023/10/19
Loop Antenna EMCI	EM-6879	269	2022/9/19	2023/9/18
Loop Antenna TESEQ	HLA 6121	45745	2022/7/27	2023/7/26
Pre-amplifier EMCI	EMC001340	980201	2022/9/23	2023/9/22
Pre_Amplifier EMCI	EMC330N	980782	2023/1/16	2024/1/15
RF Coaxial Cable EMCI	5D-NM-BM	140903+140902	2023/1/7	2024/1/6
	EMCCFD400-NM-NM- 500	201233	2023/1/16	2024/1/15
	EMCCFD400-NM-NM- 3000	201235	2023/1/16	2024/1/15
	EMCCFD400-NM-NM- 9000	201236(with PAD)	2023/1/16	2024/1/15
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Spectrum Analyzer R&S	FSW43	101866	2023/1/10	2024/1/9
Test Receiver R&S	ESR3+	102782	2022/12/12	2023/12/11
Turn Table Max-Full	MF-7802BS	N/A	N/A	N/A
Turn Table Controller Max-Full	MF-7802BS	MF780208674	N/A	N/A

Notes:

1. The test was performed in WM - 966 chamber 8.
2. Tested Date: 2023/2/18

4.7 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower Max-Full	MFT-151SS-0.5T	N/A	N/A	N/A
Horn Antenna RFSPIN	DRH18-E	210103A18E	2022/11/13	2023/11/12
Horn Antenna Schwarzbeck	BBHA 9170	9170-1049	2022/11/13	2023/11/12
Pre_Amplifier EMCI	EMC118A45SE	980808	2022/12/29	2023/12/28
	EMC184045SE	980788	2023/1/16	2024/1/15
RF Coaxial Cable EMCI	EMC101G-KM-KM-2000	201254	2023/1/16	2024/1/15
	EMC101G-KM-KM-3000	201257	2023/1/16	2024/1/15
	EMC101G-KM-KM-5000	201260	2023/1/16	2024/1/15
	EMC104-SM-SM-1000	210102	2023/1/16	2024/1/15
	EMC104-SM-SM-3000	201231	2023/1/16	2024/1/15
	EMC104-SM-SM-9000	201243	2023/1/16	2024/1/15
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Spectrum Analyzer R&S	FSW43	101866	2023/1/10	2024/1/9
Test Receiver R&S	ESR3+	102782	2022/12/12	2023/12/11
Turn Table Max-Full	MF-7802BS	N/A	N/A	N/A
Turn Table Controller Max-Full	MF-7802BS	MF780208674	N/A	N/A

Notes:

1. The test was performed in WM - 966 chamber 8.
2. Tested Date: 2023/2/15

5 Limits of Test Items

5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

5.2 Power Spectral Density

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

5.3 6 dB Bandwidth

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

5.4 Conducted Out of Band Emissions

Below 30 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

5.5 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.6 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.7 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3


Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup




6.1.2 Test Procedure

Average Power:

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

6.2 Power Spectral Density

6.2.1 Test Setup




6.2.2 Test Procedure

- a. Measure the duty cycle (x).
- b. Set instrument center frequency to DTS channel center frequency.
- c. Set span to at least 1.5 times the OBW.
- d. Set RBW to: 3 kHz.
- e. Set VBW $\geq 3 \times$ RBW.
- f. Detector = power averaging (RMS) or sample detector (when RMS not available).
- g. Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW.
- h. Sweep time = auto couple.
- i. Do not use sweep triggering. Allow sweep to "free run".
- j. Employ trace averaging (RMS) mode over a minimum of 100 traces.
- k. Use the peak marker function to determine the maximum amplitude level.
- l. Note: If Duty cycle < 98%, Add $10 \log (1/x)$, where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

6.3 6 dB Bandwidth

6.3.1 Test Setup




6.3.2 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Conducted Out of Band Emissions

6.4.1 Test Setup



6.4.2 Test Procedure

MEASUREMENT PROCEDURE REF


- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW ≥ 300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.5 AC Power Conducted Emissions

6.5.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.5.2 Test Procedure


- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.6 Unwanted Emissions below 1 GHz

6.6.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.7 Unwanted Emissions above 1 GHz

6.7.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Wayne Lin
--------------	----------------	---------------------------	--------------	------------	-----------

802.11b

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
1	2412	73.282	18.65	30	Pass
6	2437	67.453	18.29	30	Pass
11	2462	56.494	17.52	30	Pass

Note: The antenna gain is 3.9 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11g

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
1	2412	51.523	17.12	30	Pass
6	2437	68.707	18.37	30	Pass
11	2462	46.881	16.71	30	Pass

Note: The antenna gain is 3.9 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
1	2412	38.548	15.86	30	Pass
6	2437	59.156	17.72	30	Pass
11	2462	34.914	15.43	30	Pass

Note: The antenna gain is 3.9 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
3	2422	31.477	14.98	30	Pass
6	2437	33.729	15.28	30	Pass
9	2452	25.235	14.02	30	Pass

Note: The antenna gain is 3.9 dBi < 6 dBi, so the output power limit shall not be reduced.

7.2 Power Spectral Density

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Wayne Lin
--------------	----------------	---------------------------	--------------	------------	-----------

802.11b

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/3kHz)	Duty Factor (dB)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
1	2412	-9.76	0.14	-9.62	8	Pass
6	2437	-10.11	0.14	-9.97	8	Pass
11	2462	-10.86	0.14	-10.72	8	Pass

Note: The antenna gain is 3.9 dBi < 6 dBi, so the power density limit shall not be reduced.

802.11g

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/3kHz)	Duty Factor (dB)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
1	2412	-12.36	0.25	-12.11	8	Pass
6	2437	-11.09	0.25	-10.84	8	Pass
11	2462	-12.78	0.25	-12.53	8	Pass

Note: The antenna gain is 3.9 dBi < 6 dBi, so the power density limit shall not be reduced.

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/3kHz)	Duty Factor (dB)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
1	2412	-16.08	0.37	-15.71	8	Pass
6	2437	-14.21	0.37	-13.84	8	Pass
11	2462	-16.47	0.37	-16.10	8	Pass

Note: The antenna gain is 3.9 dBi < 6 dBi, so the power density limit shall not be reduced.


802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/3kHz)	Duty Factor (dB)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
3	2422	-18.38	0.68	-17.70	8	Pass
6	2437	-18.05	0.68	-17.37	8	Pass
9	2452	-19.36	0.68	-18.68	8	Pass

Note: The antenna gain is 3.9 dBi < 6 dBi, so the power density limit shall not be reduced.



Spectrum Plot of Maximum Value



7.3 6 dB Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Wayne Lin
--------------	----------------	---------------------------	--------------	------------	-----------

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
1	2412	8.08	0.5	Pass
6	2437	8.07	0.5	Pass
11	2462	7.61	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
1	2412	15.15	0.5	Pass
6	2437	15.13	0.5	Pass
11	2462	15.12	0.5	Pass


802.11ax (HE20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
1	2412	15.12	0.5	Pass
6	2437	15.09	0.5	Pass
11	2462	15.43	0.5	Pass


802.11ax (HE40)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
3	2422	32.56	0.5	Pass
6	2437	33.52	0.5	Pass
9	2452	33.95	0.5	Pass


Spectrum Plot of Minimum Value




802.11b : CH 11



802.11g : CH 11



802.11ax (HE20) : CH 6




802.11ax (HE40) : CH 3



7.4 Conducted Out of Band Emissions









Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Wayne Lin
--------------	----------------	---------------------------	--------------	------------	-----------

802.11b






802.11g







802.11ax (HE20)




CH 1




CH 1




CH 6




CH 6




CH 11



CH 11




CH 11 Band edge




CH 11 Band edge




802.11ax (HE40)




CH 3




CH 3




CH 6




CH 6




CH 9



CH 9



CH 3 Band edge



CH 9 Band edge


7.5 AC Power Conducted Emissions

RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 75% RH
Tested By	Greg Lin		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.21800	9.66	25.44	16.07	35.10	25.73	62.89	52.89	-27.79	-27.16
2	0.24600	9.67	24.51	15.52	34.18	25.19	61.89	51.89	-27.71	-26.70
3	0.48200	9.69	23.79	14.68	33.48	24.37	56.30	46.30	-22.82	-21.93
4	0.65400	9.70	20.59	14.66	30.29	24.36	56.00	46.00	-25.71	-21.64
5	1.10200	9.71	17.19	10.29	26.90	20.00	56.00	46.00	-29.10	-26.00
6	1.61000	9.72	18.55	11.88	28.27	21.60	56.00	46.00	-27.73	-24.40

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 75% RH
Tested By	Greg Lin		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.33000	9.68	17.26	12.87	26.94	22.55	59.45	49.45	-32.51	-26.90
2	0.49000	9.69	23.76	13.63	33.45	23.32	56.17	46.17	-22.72	-22.85
3	0.66987	9.70	22.61	15.66	32.31	25.36	56.00	46.00	-23.69	-20.64
4	1.22600	9.72	14.37	10.62	24.09	20.34	56.00	46.00	-31.91	-25.66
5	2.11000	9.74	13.14	8.46	22.88	18.20	56.00	46.00	-33.12	-27.80
6	2.82200	9.75	10.58	8.84	20.33	18.59	56.00	46.00	-35.67	-27.41

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




7.6 Unwanted Emissions below 1 GHz

RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	9 kHz ~ 1 GHz	Detector Function & Bandwidth	(QP) RB = 120kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	77.53	37.0 QP	40.0	-3.0	1.00 H	302	54.6	-17.6
2	125.06	41.6 QP	43.5	-1.9	1.25 H	267	56.5	-14.9
3	197.81	35.3 QP	43.5	-8.2	1.00 H	186	52.1	-16.8
4	250.19	36.9 QP	46.0	-9.1	1.00 H	329	51.5	-14.6
5	375.32	39.7 QP	46.0	-6.3	1.25 H	289	50.6	-10.9
6	843.83	32.0 QP	46.0	-14.0	1.00 H	271	33.9	-1.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	9 kHz ~ 1 GHz	Detector Function & Bandwidth	(QP) RB = 120kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Greg Lin		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	35.82	38.7 QP	40.0	-1.3	1.00 V	185	52.8	-14.1
2	77.53	38.8 QP	40.0	-1.2	1.50 V	312	56.4	-17.6
3	125.06	38.0 QP	43.5	-5.5	1.25 V	264	52.9	-14.9
4	198.78	33.3 QP	43.5	-10.2	1.00 V	145	50.1	-16.8
5	296.75	37.1 QP	46.0	-8.9	1.00 V	86	49.8	-12.7
6	541.19	35.0 QP	46.0	-11.0	1.50 V	169	42.2	-7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



7.7 Unwanted Emissions above 1 GHz

RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.7 PK	74.0	-13.3	1.32 H	313	28.4	32.3
2	2390.00	53.4 AV	54.0	-0.6	1.32 H	313	21.1	32.3
3	*2412.00	112.4 PK			1.35 H	303	80.1	32.3
4	*2412.00	110.2 AV			1.35 H	303	77.9	32.3
5	4824.00	49.1 PK	74.0	-24.9	1.92 H	149	45.5	3.6
6	4824.00	41.2 AV	54.0	-12.8	1.92 H	149	37.6	3.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.3 PK	74.0	-14.7	1.74 V	249	27.0	32.3
2	2390.00	51.3 AV	54.0	-2.7	1.74 V	249	19.0	32.3
3	*2412.00	109.5 PK			1.69 V	244	77.2	32.3
4	*2412.00	107.3 AV			1.69 V	244	75.0	32.3
5	4824.00	48.3 PK	74.0	-25.7	1.92 V	222	44.7	3.6
6	4824.00	38.6 AV	54.0	-15.4	1.92 V	222	35.0	3.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.



RF Mode	802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	112.0 PK			1.32 H	310	79.7	32.3
2	*2437.00	109.8 AV			1.32 H	310	77.5	32.3
3	2483.50	62.2 PK	74.0	-11.8	1.29 H	300	29.8	32.4
4	2483.50	53.1 AV	54.0	-0.9	1.29 H	300	20.7	32.4
5	4874.00	51.2 PK	74.0	-22.8	1.99 H	152	47.7	3.5
6	4874.00	41.6 AV	54.0	-12.4	1.99 H	152	38.1	3.5

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	108.3 PK			1.56 V	246	76.0	32.3
2	*2437.00	106.7 AV			1.56 V	246	74.4	32.3
3	2483.50	60.8 PK	74.0	-13.2	1.64 V	248	28.4	32.4
4	2483.50	51.8 AV	54.0	-2.2	1.64 V	248	19.4	32.4
5	4874.00	48.4 PK	74.0	-25.6	1.93 V	208	44.9	3.5
6	4874.00	38.6 AV	54.0	-15.4	1.93 V	208	35.1	3.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.



RF Mode	802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	111.7 PK			1.32 H	311	79.4	32.3
2	*2462.00	110.1 AV			1.32 H	311	77.8	32.3
3	2483.50	61.8 PK	74.0	-12.2	1.22 H	308	29.4	32.4
4	2483.50	53.4 AV	54.0	-0.6	1.22 H	308	21.0	32.4
5	4924.00	48.8 PK	74.0	-25.2	1.99 H	153	45.0	3.8
6	4924.00	40.4 AV	54.0	-13.6	1.99 H	153	36.6	3.8

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.8 PK			1.71 V	245	75.5	32.3
2	*2462.00	106.3 AV			1.71 V	245	74.0	32.3
3	2483.50	61.1 PK	74.0	-12.9	1.66 V	250	28.7	32.4
4	2483.50	51.6 AV	54.0	-2.4	1.66 V	250	19.2	32.4
5	4924.00	48.2 PK	74.0	-25.8	1.93 V	234	44.4	3.8
6	4924.00	38.6 AV	54.0	-15.4	1.93 V	234	34.8	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.



RF Mode	802.11g	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	61.7 PK	74.0	-12.3	1.16 H	310	29.4	32.3
2	2390.00	53.3 AV	54.0	-0.7	1.16 H	310	21.0	32.3
3	*2412.00	114.1 PK			1.35 H	309	81.8	32.3
4	*2412.00	107.2 AV			1.35 H	309	74.9	32.3
5	4824.00	49.0 PK	74.0	-25.0	1.89 H	162	45.4	3.6
6	4824.00	39.1 AV	54.0	-14.9	1.89 H	162	35.5	3.6

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.2 PK	74.0	-13.8	1.65 V	254	27.9	32.3
2	2390.00	50.7 AV	54.0	-3.3	1.65 V	254	18.4	32.3
3	*2412.00	110.5 PK			1.69 V	241	78.2	32.3
4	*2412.00	103.7 AV			1.69 V	241	71.4	32.3
5	4824.00	47.5 PK	74.0	-26.5	2.01 V	227	43.9	3.6
6	4824.00	38.0 AV	54.0	-16.0	2.01 V	227	34.4	3.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.



RF Mode	802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	116.0 PK			1.03 H	310	83.7	32.3
2	*2437.00	108.6 AV			1.03 H	310	76.3	32.3
3	2483.50	63.6 PK	74.0	-10.4	1.00 H	311	31.2	32.4
4	2483.50	53.4 AV	54.0	-0.6	1.00 H	311	21.0	32.4
5	4874.00	48.3 PK	74.0	-25.7	1.98 H	154	44.8	3.5
6	4874.00	38.6 AV	54.0	-15.4	1.98 H	154	35.1	3.5

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	111.1 PK			1.69 V	239	78.8	32.3
2	*2437.00	104.6 AV			1.69 V	239	72.3	32.3
3	2483.50	61.7 PK	74.0	-12.3	1.68 V	249	29.3	32.4
4	2483.50	51.6 AV	54.0	-2.4	1.68 V	249	19.2	32.4
5	4874.00	47.3 PK	74.0	-26.7	1.92 V	221	43.8	3.5
6	4874.00	37.7 AV	54.0	-16.3	1.92 V	221	34.2	3.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.



RF Mode	802.11g	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	113.8 PK			1.07 H	301	81.5	32.3
2	*2462.00	106.8 AV			1.07 H	301	74.5	32.3
3	2483.50	62.8 PK	74.0	-11.2	1.02 H	303	30.4	32.4
4	2483.50	53.0 AV	54.0	-1.0	1.02 H	303	20.6	32.4
5	4924.00	48.8 PK	74.0	-25.2	1.92 H	162	45.0	3.8
6	4924.00	39.4 AV	54.0	-14.6	1.92 H	162	35.6	3.8

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	109.9 PK			1.74 V	251	77.6	32.3
2	*2462.00	102.6 AV			1.74 V	251	70.3	32.3
3	2483.50	60.9 PK	74.0	-13.1	1.72 V	244	28.5	32.4
4	2483.50	51.4 AV	54.0	-2.6	1.72 V	244	19.0	32.4
5	4924.00	47.8 PK	74.0	-26.2	1.85 V	236	44.0	3.8
6	4924.00	38.0 AV	54.0	-16.0	1.85 V	236	34.2	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.



RF Mode	802.11ax (HE20)	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	62.8 PK	74.0	-11.2	1.00 H	306	30.5	32.3
2	2390.00	53.1 AV	54.0	-0.9	1.00 H	306	20.8	32.3
3	*2412.00	116.0 PK			1.02 H	312	83.7	32.3
4	*2412.00	105.3 AV			1.02 H	312	73.0	32.3
5	4824.00	48.4 PK	74.0	-25.6	1.93 H	231	44.8	3.6
6	4824.00	38.9 AV	54.0	-15.1	1.93 H	231	35.3	3.6

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.8 PK	74.0	-13.2	1.70 V	238	28.5	32.3
2	2390.00	50.5 AV	54.0	-3.5	1.70 V	238	18.2	32.3
3	*2412.00	113.0 PK			1.73 V	242	80.7	32.3
4	*2412.00	101.6 AV			1.73 V	242	69.3	32.3
5	4824.00	47.5 PK	74.0	-26.5	2.01 V	209	43.9	3.6
6	4824.00	37.8 AV	54.0	-16.2	2.01 V	209	34.2	3.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.



RF Mode	802.11ax (HE20)	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	118.6 PK			1.07 H	310	86.3	32.3
2	*2437.00	107.9 AV			1.07 H	310	75.6	32.3
3	2483.50	63.1 PK	74.0	-10.9	1.00 H	309	30.7	32.4
4	2483.50	52.8 AV	54.0	-1.2	1.00 H	309	20.4	32.4
5	4874.00	48.5 PK	74.0	-25.5	1.96 H	158	45.0	3.5
6	4874.00	38.9 AV	54.0	-15.1	1.96 H	158	35.4	3.5

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	114.3 PK			1.64 V	241	82.0	32.3
2	*2437.00	103.3 AV			1.64 V	241	71.0	32.3
3	2483.50	61.6 PK	74.0	-12.4	1.67 V	245	29.2	32.4
4	2483.50	51.2 AV	54.0	-2.8	1.67 V	245	18.8	32.4
5	4874.00	47.2 PK	74.0	-26.8	1.86 V	233	43.7	3.5
6	4874.00	37.7 AV	54.0	-16.3	1.86 V	233	34.2	3.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.



RF Mode	802.11ax (HE20)	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	116.1 PK			1.02 H	303	83.8	32.3
2	*2462.00	105.2 AV			1.02 H	303	72.9	32.3
3	2483.50	63.4 PK	74.0	-10.6	1.03 H	307	31.0	32.4
4	2483.50	53.4 AV	54.0	-0.6	1.03 H	307	21.0	32.4
5	4924.00	49.2 PK	74.0	-24.8	1.90 H	163	45.4	3.8
6	4924.00	39.8 AV	54.0	-14.2	1.90 H	163	36.0	3.8

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.8 PK			1.67 V	251	78.5	32.3
2	*2462.00	100.7 AV			1.67 V	251	68.4	32.3
3	2483.50	61.8 PK	74.0	-12.2	1.65 V	244	29.4	32.4
4	2483.50	51.5 AV	54.0	-2.5	1.65 V	244	19.1	32.4
5	4924.00	47.3 PK	74.0	-26.7	1.93 V	221	43.5	3.8
6	4924.00	38.4 AV	54.0	-15.6	1.93 V	221	34.6	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.



RF Mode	802.11ax (HE40)	Channel	CH 3 : 2422 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	65.0 PK	74.0	-9.0	1.00 H	307	32.7	32.3
2	2390.00	53.3 AV	54.0	-0.7	1.00 H	307	21.0	32.3
3	*2422.00	112.2 PK			1.06 H	308	79.8	32.4
4	*2422.00	102.1 AV			1.06 H	308	69.7	32.4
5	4844.00	48.3 PK	74.0	-25.7	1.93 H	161	44.7	3.6
6	4844.00	38.8 AV	54.0	-15.2	1.93 H	161	35.2	3.6

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	62.3 PK	74.0	-11.7	1.69 V	249	30.0	32.3
2	2390.00	51.3 AV	54.0	-2.7	1.69 V	249	19.0	32.3
3	*2422.00	108.2 PK			1.67 V	251	75.8	32.4
4	*2422.00	98.3 AV			1.67 V	251	65.9	32.4
5	4844.00	47.4 PK	74.0	-26.6	2.03 V	231	43.8	3.6
6	4844.00	38.1 AV	54.0	-15.9	2.03 V	231	34.5	3.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.



RF Mode	802.11ax (HE40)	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	112.1 PK			1.00 H	311	79.8	32.3
2	*2437.00	102.5 AV			1.00 H	311	70.2	32.3
3	2483.50	62.9 PK	74.0	-11.1	1.04 H	304	30.5	32.4
4	2483.50	53.1 AV	54.0	-0.9	1.04 H	304	20.7	32.4
5	4874.00	48.7 PK	74.0	-25.3	1.99 H	170	45.2	3.5
6	4874.00	38.3 AV	54.0	-15.7	1.99 H	170	34.8	3.5

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	108.3 PK			1.62 V	248	76.0	32.3
2	*2437.00	98.3 AV			1.62 V	248	66.0	32.3
3	2483.50	61.4 PK	74.0	-12.6	1.66 V	244	29.0	32.4
4	2483.50	51.6 AV	54.0	-2.4	1.66 V	244	19.2	32.4
5	4874.00	47.5 PK	74.0	-26.5	1.86 V	236	44.0	3.5
6	4874.00	38.1 AV	54.0	-15.9	1.86 V	236	34.6	3.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.



RF Mode	802.11ax (HE40)	Channel	CH 9 : 2452 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21°C, 69% RH
Tested By	Edison Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	110.7 PK			1.03 H	309	78.4	32.3
2	*2452.00	100.5 AV			1.03 H	309	68.2	32.3
3	2483.50	64.5 PK	74.0	-9.5	1.00 H	308	32.1	32.4
4	2483.50	53.3 AV	54.0	-0.7	1.00 H	308	20.9	32.4
5	4904.00	48.8 PK	74.0	-25.2	1.93 H	163	45.2	3.6
6	4904.00	39.2 AV	54.0	-14.8	1.93 H	163	35.6	3.6

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	106.5 PK			1.72 V	246	74.2	32.3
2	*2452.00	96.7 AV			1.72 V	246	64.4	32.3
3	2483.50	62.1 PK	74.0	-11.9	1.70 V	244	29.7	32.4
4	2483.50	51.4 AV	54.0	-2.6	1.70 V	244	19.0	32.4
5	4904.00	47.4 PK	74.0	-26.6	1.99 V	236	43.8	3.6
6	4904.00	37.9 AV	54.0	-16.1	1.99 V	236	34.3	3.6


Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.




Plot of Band Edge


802.11b Channel 1




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11b Channel 6




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11b Channel 11




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11g Channel 1




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11g Channel 6




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11g Channel 11




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11ax (HE20) Channel 1




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11ax (HE20) Channel 6




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11ax (HE20) Channel 11




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11ax (HE40) Channel 3




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11ax (HE40) Channel 6




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11ax (HE40) Channel 9




Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---