



# FCC TEST REPORT (15.407)

**REPORT NO.:** RF131210C07-1

**MODEL NO.:** EPG600

**FCC ID:** A8J-EPG600

**RECEIVED:** Dec. 10, 2013

**TESTED:** Dec. 14 ~ Dec. 17, 2013

**ISSUED:** Dec. 24, 2013

**APPLICANT:** EnGenius Technologies

**ADDRESS:** 1580 Scenic Avenue, Costa Mesa, CA92626

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,  
New Taipei City, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	4
1. CERTIFICATION.....	5
2. SUMMARY OF TEST RESULTS .....	6
2.1 MEASUREMENT UNCERTAINTY.....	6
3. GENERAL INFORMATION.....	7
3.1 GENERAL DESCRIPTION OF EUT .....	7
3.2 DESCRIPTION OF TEST MODES .....	8
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	9
3.3 DUTY CYCLE OF TEST SIGNAL.....	11
3.4 DESCRIPTION OF SUPPORT UNITS .....	15
3.4.1 CONFIGURATION OF SYSTEM UNDER TEST .....	16
3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	17
4. TEST TYPES AND RESULTS .....	18
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	18
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	18
4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS .....	18
4.1.3 TEST INSTRUMENTS.....	19
4.1.4 TEST PROCEDURES .....	20
4.1.5 DEVIATION FROM TEST STANDARD.....	20
4.1.6 TEST SETUP.....	21
4.1.7 EUT OPERATING CONDITION.....	22
4.1.8 TEST RESULTS .....	23
4.2 CONDUCTED EMISSION MEASUREMENT .....	32
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	32
4.2.2 TEST INSTRUMENTS.....	32
4.2.3 TEST PROCEDURES .....	33
4.2.4 DEVIATION FROM TEST STANDARD.....	33
4.2.5 TEST SETUP.....	33
4.2.6 EUT OPERATING CONDITIONS .....	33
4.2.7 TEST RESULTS .....	34
4.3 PEAK TRANSMIT POWER MEASUREMENT .....	36
4.3.1 LIMITS OF PEAK TRANSMIT POWER MEASUREMENT .....	36
4.3.2 TEST SETUP.....	36
4.3.3 TEST INSTRUMENTS.....	36
4.3.4 TEST PROCEDURE.....	37
4.3.5 DEVIATION FROM TEST STANDARD.....	37
4.3.6 EUT OPERATING CONDITIONS .....	37



A D T

4.3.7	TEST RESULTS .....	38
4.4	PEAK POWER SPECTRAL DENSITY MEASUREMENT .....	41
4.4.1	LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT .....	41
4.4.2	TEST SETUP .....	41
4.4.3	TEST INSTRUMENTS .....	41
4.4.4	TEST PROCEDURES .....	41
4.4.5	DEVIATION FROM TEST STANDARD .....	41
4.4.6	EUT OPERATING CONDITIONS .....	41
4.4.7	TEST RESULTS .....	42
4.5	PEAK POWER EXCURSION MEASUREMENT .....	44
4.5.1	LIMITS OF PEAK POWER EXCURSION MEASUREMENT .....	44
4.5.2	TEST SETUP .....	44
4.5.3	TEST INSTRUMENTS .....	44
4.5.4	TEST PROCEDURE .....	44
4.5.5	DEVIATION FROM TEST STANDARD .....	45
4.5.6	EUT OPERATING CONDITIONS .....	45
4.5.7	TEST RESULTS .....	46
4.6	FREQUENCY STABILITY .....	47
4.6.1	LIMITS OF FREQUENCY STABILITY MEASUREMENT .....	47
4.6.2	TEST SETUP .....	47
4.6.3	TEST INSTRUMENTS .....	47
4.6.4	TEST PROCEDURE .....	48
4.6.5	DEVIATION FROM TEST STANDARD .....	48
4.6.6	EUT OPERATING CONDITION .....	48
4.6.7	TEST RESULTS .....	49
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	50
6.	INFORMATION ON THE TESTING LABORATORIES .....	51
7.	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	52



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF131210C07-1	Original release	Dec. 24, 2013



# 1. CERTIFICATION

**PRODUCT:** Wireless Dual Band VoIP Router

**MODEL:** EPG600

**BRAND:** EnGenius

**APPLICANT:** EnGenius Technologies

**TESTED:** Dec. 14 ~ Dec. 17, 2013

**TEST SAMPLE:** ENGINEERING SAMPLE

**STANDARDS: FCC Part 15, Subpart E (Section 15.407)**

ANSI C63.10-2009

The above equipment (model: EPG600) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY:** Ivy Lin , **DATE:** Dec. 24, 2013  
Ivy Lin / Specialist

**APPROVED BY:** Ken Liu , **DATE:** Dec. 24, 2013  
Ken Liu / Senior Manager

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART E (SECTION 15.407)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.407(b)(6)	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -14.79dB at 0.15781MHz.
15.407(b/1/2/3)(b)(6)	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -1.1dB at 51.24MHz.
15.407(a/1/2)	Max Average Transmit Power	PASS	Meet the requirement of limit.
15.407(a)(6)	Peak Power Excursion	PASS	Meet the requirement of limit.
15.407(a/1/2)	Peak Power Spectral Density	PASS	Meet the requirement of limit.
15.407(g)	Frequency Stability	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is IPEX not a standard connector.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.34 dB
	200MHz ~1000MHz	3.35 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>EUT</b>	Wireless Dual Band VoIP Router
<b>MODEL NO.</b>	EPG600
<b>POWER SUPPLY</b>	12Vdc (Adapter)
<b>MODULATION TYPE</b>	64QAM, 16QAM, QPSK, BPSK
<b>MODULATION TECHNOLOGY</b>	OFDM
<b>TRANSFER RATE</b>	802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 300.0Mbps
<b>OPERATING FREQUENCY</b>	5180 ~ 5240MHz
<b>NUMBER OF CHANNEL</b>	4 for 802.11a, 802.11n (20MHz) 2 for 802.11n (40MHz)
<b>OUTPUT POWER</b>	48.553mW
<b>ANTENNA TYPE</b>	Refer to Note as below
<b>ANTENNA CONNECTOR</b>	Refer to Note as below
<b>DATA CABLE</b>	N/A
<b>I/O PORTS</b>	Refer to user's manual
<b>ACCESSORY DEVICES</b>	Adapter

**NOTE:**

- The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers.

MODULATION MODE	TX FUNCTION
802.11b	1TX
802.11g	1TX
802.11a	1TX
802.11n (20MHz) (MCS 8 ~ 15)	2TX
802.11n (40MHz) (MCS 8 ~ 15)	2TX

- The following antennas are provided to this EUT.

Antenna	Antenna Type	Gain (dBi)		Antenna Connector
		2.4GHz	5GHz	
Ant. 1	PIFA	1.6	-	IPEX
Ant. 2	PIFA	3.5	-	
Ant. 3	PCB	-	5.7	
Ant. 4	PIFA	-	4.0	

\* 802.11 b/g use Ant. 1, 802.11a uses Ant. 3.

3. The EUT consumes power from the following adapter.

<b>BRAND:</b>	Shenzhen Gongjin Electronics CO., LTD.
<b>MODEL:</b>	S24B12-120A125-04
<b>INPUT:</b>	100-240Vac, 50/60Hz, Max 0.7A LPS
<b>OUTPUT:</b>	12Vdc, 1.25A
<b>POWER LINE:</b>	DC 1.4m non-shielded cable without core

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 DESCRIPTION OF TEST MODES

4 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
36	5180MHz	44	5220MHz
40	5200MHz	48	5240MHz

2 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
38	5190MHz	46	5230MHz



### 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G**: Radiated Emission above 1GHz      **RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission      **APCM**: Antenna Port Conducted Measurement

**NOTE:**

1. For 1TX: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.
2. For 2TX: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane**.

**RADIATED EMISSION TEST (ABOVE 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	36 to 48	36, 40, 48	OFDM	BPSK	6.0
-	802.11n (20MHz)	36 to 48	36, 40, 48	OFDM	BPSK	7.2
-	802.11n (40MHz)	38 to 46	38, 46	OFDM	BPSK	15.0

**RADIATED EMISSION TEST (BELOW 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (20MHz)	36 to 48	36	OFDM	BPSK	7.2

**POWER LINE CONDUCTED EMISSION TEST:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (20MHz)	36 to 48	36	OFDM	BPSK	7.2

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	36 to 48	36, 40, 48	OFDM	BPSK	6.0
-	802.11n (20MHz)	36 to 48	36, 40, 48	OFDM	BPSK	7.2
-	802.11n (40MHz)	38 to 46	38, 46	OFDM	BPSK	15.0

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Chris Lin
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Chris Lin
PLC	24deg. C, 64%RH	120Vac, 60Hz	Match Tsui
APCM	25deg. C, 60%RH	120Vac, 60Hz	Johnny Yu



A D T


### 3.3 DUTY CYCLE OF TEST SIGNAL

#### MODULATION TYPE: BPSK

02.11a: Duty cycle of test signal is > 98 %

802.11n (20MHz): Duty cycle of test signal is > 98 %

802.11n (40MHz): Duty cycle of test signal is > 98 %






A D T

**MODULATION TYPE: QPSK**

**02.11a:** Duty cycle of test signal is > 98 %

**802.11n (20MHz):** Duty cycle of test signal is > 98 %

**802.11n (40MHz):** Duty cycle of test signal is > 98 %






A D T

**MODULATION TYPE: 16QAM**

**02.11a:** Duty cycle of test signal is > 98 %

**802.11n (20MHz):** Duty cycle of test signal is > 98 %

**802.11n (40MHz):** Duty cycle of test signal is > 98 %






A D T

**MODULATION TYPE: 64QAM**

**02.11a:** Duty cycle of test signal is > 98 %

**802.11n (20MHz):** Duty cycle of test signal is > 98 %

**802.11n (40MHz):** Duty cycle of test signal is > 98 %



### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	USB Flash Drive	KINGMAX	PD-09	N/A	FCC DoC Approved
2	Notebook	DELL	E5410	1HC2XM1	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	10m RJ45 UTP cable

**NOTE:**

1. All power cords of the above support units are non-shielded (1.8m).
2. Item 2 acted as a communication partner to transfer data.

### 3.4.1 CONFIGURATION OF SYSTEM UNDER TEST





### 3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart E (15.407)**

**789033 D01 General UNII Test Procedures v01 r03**

**662911 D01 Multiple Transmitter Output v02**

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

## 4. TEST TYPES AND RESULTS

### 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

APPLICABLE TO	LIMIT	
√	FIELD STRENGTH AT 3m (dBμV/m)	
	PK	AV
	74	54
	EIRP LIMIT (dBm)	EQUIVALENT FIELD STRENGTH AT 3m (dBμV/m)
	PK	PK
	-27	68.3

**NOTE:** The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

#### 4.1.3 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESI7	838496/016	Dec. 25, 2012	Dec. 24, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Jan. 31, 2013	Jan. 30, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Mar. 20, 2013	Mar. 19, 2014
HORN Antenna SCHWARZBECK	9120D	209	Sep. 12, 2013	Sep. 11, 2014
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 15, 2013	Jul. 14, 2014
Preamplifier Agilent	8447D	2944A10633	Oct. 07, 2013	Oct. 06, 2014
Preamplifier Agilent	8449B	3008A01964	Aug. 26, 2013	Aug. 25, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	214378/4	Aug. 26, 2013	Aug. 25, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 106	12738/6+309224/4	Aug. 26, 2013	Aug. 25, 2014
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA	NA
Turn Table BV ADT	TT100	TT93021703	NA	NA
Turn Table Controller BV ADT	SC100	SC93021703	NA	NA
26GHz ~ 40GHz Amplifier	EM26400	815221	Oct. 18, 2013	Oct. 17, 2014
High Speed Power Meter	ML2495A	0842014	Apr. 25, 2013	Apr. 24, 2014
Power Sensor	MA2411B	0738404	Apr. 24, 2013	Apr. 23, 2014
WIT Standard Temperature And Humidity Chamber	TH-4S-C	W981030	Jun. 10, 2013	Jun. 09, 2014

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HwaYa Chamber 3.
  3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  4. The FCC Site Registration No. is 988962.
  5. The IC Site Registration No. is IC 7450F-3.

#### 4.1.4 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**NOTE:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.5 DEVIATION FROM TEST STANDARD


No deviation.

#### 4.1.6 TEST SETUP

##### Frequency range 30MHz~1GHz



##### Frequency range above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.7 EUT OPERATING CONDITION

- a. Placed the EUT on the testing table.
- b. Prepared notebooks to act as communication partner and placed it outside of testing area.
- c. The communication partner connected with EUT via a RJ45 cable and run a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- d. The communication partner sent data to EUT by command "PING".
- e. The necessary accessories enabled the system in full functions.

#### 4.1.8 TEST RESULTS

#### ABOVE 1GHz DATA :

#### 802.11a

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 36	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5127.00	56.2 PK	74.0	-17.8	1.80 H	146	51.10	5.10
2	5127.00	44.3 AV	54.0	-9.7	1.80 H	146	39.20	5.10
3	5150.00	56.9 PK	74.0	-17.1	1.80 H	146	51.80	5.10
4	5150.00	43.9 AV	54.0	-10.1	1.80 H	146	38.80	5.10
5	*5180.00	99.8 PK			1.80 H	145	62.10	37.70
6	*5180.00	90.7 AV			1.80 H	145	53.00	37.70
7	#10360.00	59.0 PK	74.0	-15.0	1.01 H	344	41.50	17.50
8	#10360.00	47.6 AV	54.0	-6.4	1.01 H	344	30.10	17.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5127.00	60.5 PK	74.0	-13.5	1.00 V	69	55.40	5.10
2	5127.00	49.5 AV	54.0	-4.5	1.00 V	69	44.40	5.10
3	5150.00	62.0 PK	74.0	-12.0	1.05 V	75	56.90	5.10
4	5150.00	47.5 AV	54.0	-6.5	1.05 V	75	42.40	5.10
5	*5180.00	107.0 PK			1.00 V	69	69.30	37.70
6	*5180.00	98.4 AV			1.00 V	69	60.70	37.70
7	#10360.00	65.3 PK	74.0	-8.7	1.52 V	62	47.80	17.50
8	#10360.00	52.1 AV	54.0	-1.9	1.52 V	62	34.60	17.50

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. “ \* “: Fundamental frequency.
6. “#“:The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 40	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	56.0 PK	74.0	-18.0	1.10 H	174	50.90	5.10
2	5150.00	45.2 AV	54.0	-8.8	1.10 H	174	40.10	5.10
3	*5200.00	100.9 PK			1.01 H	164	63.10	37.80
4	*5200.00	91.6 AV			1.01 H	164	53.80	37.80
5	#10400.00	60.8 PK	74.0	-13.2	1.15 H	236	43.00	17.80
6	#10400.00	48.2 AV	54.0	-5.8	1.15 H	236	30.40	17.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	59.4 PK	74.0	-14.6	1.15 V	45	54.30	5.10
2	5150.00	48.7 AV	54.0	-5.3	1.15 V	45	43.60	5.10
3	*5200.00	108.4 PK			1.10 V	43	70.60	37.80
4	*5200.00	99.3 AV			1.10 V	43	61.50	37.80
5	#10400.00	63.5 PK	74.0	-10.5	1.63 V	262	45.70	17.80
6	#10400.00	51.2 AV	54.0	-2.8	1.63 V	262	33.40	17.80

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. “ \* “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 48	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	101.2 PK			1.00 H	157	63.30	37.90
2	*5240.00	92.8 AV			1.00 H	157	54.90	37.90
3	5350.00	56.3 PK	74.0	-17.7	1.10 H	160	50.90	5.40
4	5350.00	42.9 AV	54.0	-11.1	1.10 H	160	37.50	5.40
5	#10480.00	61.0 PK	74.0	-13.0	1.47 H	258	42.70	18.30
6	#10480.00	48.7 AV	54.0	-5.3	1.47 H	258	30.40	18.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	109.2 PK			1.35 V	42	71.30	37.90
2	*5240.00	99.9 AV			1.35 V	42	62.00	37.90
3	5350.00	57.1 PK	74.0	-16.9	1.40 V	50	51.70	5.40
4	5350.00	43.9 AV	54.0	-10.1	1.40 V	50	38.50	5.40
5	#10480.00	62.8 PK	74.0	-11.2	1.31 V	19	44.50	18.30
6	#10480.00	50.3 AV	54.0	-3.7	1.31 V	19	32.00	18.30

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. “ \* “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 36	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5128.00	55.6 PK	74.0	-18.4	1.10 H	90	50.50	5.10
2	5128.00	43.9 AV	54.0	-10.1	1.10 H	90	38.80	5.10
3	5150.00	57.4 PK	74.0	-16.6	1.10 H	75	52.30	5.10
4	5150.00	43.5 AV	54.0	-10.5	1.10 H	75	38.40	5.10
5	*5180.00	102.1 PK			1.00 H	84	64.40	37.70
6	*5180.00	92.6 AV			1.00 H	84	54.90	37.70
7	#10360.00	61.5 PK	74.0	-12.5	1.00 H	81	44.00	17.50
8	#10360.00	49.0 AV	54.0	-5.0	1.00 H	81	31.50	17.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5128.00	59.3 PK	74.0	-14.7	1.23 V	285	54.20	5.10
2	5128.00	48.5 AV	54.0	-5.5	1.23 V	285	43.40	5.10
3	5150.00	61.9 PK	74.0	-12.1	1.25 V	290	56.80	5.10
4	5150.00	46.8 AV	54.0	-7.2	1.25 V	290	41.70	5.10
5	*5180.00	106.5 PK			1.23 V	286	68.80	37.70
6	*5180.00	96.0 AV			1.23 V	286	58.30	37.70
7	#10360.00	62.8 PK	74.0	-11.2	1.71 V	5	45.30	17.50
8	#10360.00	50.7 AV	54.0	-3.3	1.71 V	5	33.20	17.50

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. “ \* ”: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 40	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	56.5 PK	74.0	-17.5	1.10 H	80	51.40	5.10
2	5150.00	45.7 AV	54.0	-8.3	1.10 H	80	40.60	5.10
3	*5200.00	102.3 PK			1.00 H	76	64.50	37.80
4	*5200.00	91.6 AV			1.00 H	76	53.80	37.80
5	#10400.00	60.8 PK	74.0	-13.2	1.12 H	332	43.00	17.80
6	#10400.00	49.0 AV	54.0	-5.0	1.12 H	332	31.20	17.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	58.4 PK	74.0	-15.6	1.60 V	290	53.30	5.10
2	5150.00	47.1 AV	54.0	-6.9	1.60 V	290	42.00	5.10
3	*5200.00	106.7 PK			1.44 V	283	68.90	37.80
4	*5200.00	96.0 AV			1.44 V	283	58.20	37.80
5	#10400.00	63.5 PK	74.0	-10.5	1.69 V	30	45.70	17.80
6	#10400.00	51.3 AV	54.0	-2.7	1.69 V	30	33.50	17.80

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. “ \* “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 48	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	102.0 PK			1.00 H	56	64.10	37.90
2	*5240.00	92.8 AV			1.00 H	56	54.90	37.90
3	5350.00	56.0 PK	74.0	-18.0	1.10 H	100	50.60	5.40
4	5350.00	44.0 AV	54.0	-10.0	1.10 H	100	38.60	5.40
5	#10480.00	65.5 PK	74.0	-8.5	1.49 H	304	47.20	18.30
6	#10480.00	52.2 AV	54.0	-1.8	1.49 H	304	33.90	18.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	106.6 PK			1.11 V	255	68.70	37.90
2	*5240.00	96.6 AV			1.11 V	255	58.70	37.90
3	5350.00	56.7 PK	74.0	-17.3	1.20 V	260	51.30	5.40
4	5350.00	43.9 AV	54.0	-10.1	1.20 V	260	38.50	5.40
5	#10480.00	64.5 PK	74.0	-9.5	1.75 V	319	46.20	18.30
6	#10480.00	52.0 AV	54.0	-2.0	1.75 V	319	33.70	18.30

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. “ \* “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 38	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	61.7 PK	74.0	-12.3	1.10 H	60	56.60	5.10
2	5150.00	47.0 AV	54.0	-7.0	1.10 H	60	41.90	5.10
3	*5190.00	96.1 PK			1.01 H	54	58.30	37.80
4	*5190.00	85.7 AV			1.01 H	54	47.90	37.80
5	#10380.00	57.8 PK	74.0	-16.2	1.15 H	55	40.20	17.60
6	#10380.00	46.6 AV	54.0	-7.4	1.15 H	55	29.00	17.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	68.0 PK	74.0	-6.0	1.01 V	285	62.90	5.10
2	5150.00	52.6 AV	54.0	-1.4	1.01 V	285	47.50	5.10
3	*5190.00	101.3 PK			1.02 V	286	63.50	37.80
4	*5190.00	90.9 AV			1.02 V	286	53.10	37.80
5	#10380.00	58.4 PK	74.0	-15.6	1.14 V	85	40.80	17.60
6	#10380.00	47.7 AV	54.0	-6.3	1.14 V	85	30.10	17.60

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. “ \* “: Fundamental frequency.
6. "#":The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 46	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5230.00	101.8 PK			1.01 H	49	63.90	37.90
2	*5230.00	90.7 AV			1.01 H	49	52.80	37.90
3	5350.00	57.0 PK	74.0	-17.0	1.19 H	54	51.60	5.40
4	5350.00	44.1 AV	54.0	-9.9	1.19 H	54	38.70	5.40
5	#10460.00	59.4 PK	74.0	-14.6	1.17 H	45	41.30	18.10
6	#10460.00	47.1 AV	54.0	-6.9	1.17 H	45	29.00	18.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5230.00	104.3 PK			1.22 V	285	66.40	37.90
2	*5230.00	93.9 AV			1.22 V	285	56.00	37.90
3	5350.00	56.9 PK	74.0	-17.1	1.13 V	317	51.50	5.40
4	5350.00	44.4 AV	54.0	-9.6	1.13 V	317	39.00	5.40
5	#10460.00	61.8 PK	74.0	-12.2	1.18 V	99	43.70	18.10
6	#10460.00	49.0 AV	54.0	-5.0	1.18 V	99	30.90	18.10

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. “ \* “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.

**BELOW 1GHz WORST-CASE DATA : 802.11n (20MHz)**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 36	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.07	27.3 QP	40.0	-12.7	1.25 H	17	42.20	-14.90
2	177.37	30.5 QP	43.5	-13.0	1.00 H	266	45.40	-14.90
3	375.29	38.9 QP	46.0	-7.1	1.50 H	203	49.80	-10.90
4	499.48	36.4 QP	46.0	-9.6	1.25 H	15	44.70	-8.30
5	625.60	31.9 QP	46.0	-14.1	1.00 H	191	37.40	-5.50
6	875.91	44.0 QP	46.0	-2.0	1.50 H	72	45.00	-1.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	51.24	38.9 QP	40.0	-1.1	1.25 V	13	53.20	-14.30
2	154.09	31.8 QP	43.5	-11.7	1.00 V	2	45.30	-13.50
3	375.29	35.1 QP	46.0	-10.9	1.50 V	163	46.00	-10.90
4	499.48	36.0 QP	46.0	-10.0	1.00 V	185	44.30	-8.30
5	625.60	31.3 QP	46.0	-14.7	1.25 V	319	36.80	-5.50
6	875.91	35.4 QP	46.0	-10.6	1.50 V	133	36.40	-1.00

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 4.2 CONDUCTED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.  
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.  
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Nov. 17, 2013	Nov. 16, 2014
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 28, 2012	Dec. 27, 2013
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 21, 2012	Dec. 20, 2013
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 17, 2013	Jul. 16, 2014
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 2. The test was performed in HwaYa Shielded Room 2.  
 3. The VCCI Site Registration No. is C-2047.



#### 4.2.3 TEST PROCEDURES


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.5 TEST SETUP



- Note:**
- Support units were connected to second LISN.
  - Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.


## 4.2.7 TEST RESULTS

### CONDUCTED WORST-CASE DATA : 802.11n (20MHz)

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	0.17	50.61	38.96	50.78	39.13	65.58	55.58	-14.79	-16.44
2	0.22031	0.17	42.90	33.11	43.07	33.28	62.81	52.81	-19.73	-19.52
3	0.54844	0.22	35.98	29.68	36.20	29.90	56.00	46.00	-19.80	-16.10
4	3.50000	0.35	33.71	28.87	34.06	29.22	56.00	46.00	-21.94	-16.78
5	4.55469	0.38	34.39	28.04	34.77	28.42	56.00	46.00	-21.23	-17.58
6	8.84375	0.42	36.85	30.89	37.27	31.31	60.00	50.00	-22.73	-18.69


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. The emission levels of other frequencies were very low against the limit.
  3. Margin value = Emission level - Limit value
  4. Correction factor = Insertion loss + Cable loss
  5. Emission Level = Correction Factor + Reading Value.



PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16172	0.18	50.13	38.79	50.31	38.97	65.38	55.38	-15.06	-16.40
2	0.22531	0.19	42.87	33.78	43.06	33.97	62.62	52.62	-19.56	-18.65
3	0.54844	0.25	34.70	27.93	34.95	28.18	56.00	46.00	-21.05	-17.82
4	3.48828	0.36	33.81	29.16	34.17	29.52	56.00	46.00	-21.83	-16.48
5	4.64063	0.40	33.85	26.77	34.25	27.17	56.00	46.00	-21.75	-18.83
6	9.07422	0.47	36.94	30.85	37.41	31.32	60.00	50.00	-22.59	-18.68

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. The emission levels of other frequencies were very low against the limit.
  3. Margin value = Emission level - Limit value
  4. Correction factor = Insertion loss + Cable loss
  5. Emission Level = Correction Factor + Reading Value.



### 4.3 PEAK TRANSMIT POWER MEASUREMENT

#### 4.3.1 LIMITS OF PEAK TRANSMIT POWER MEASUREMENT

FREQUENCY BAND	LIMIT
5.15 ~ 5.25GHz	The lesser of 50mW (17dBm) or 4dBm + 10logB

**NOTE:** Where B is the 26dB emission bandwidth in MHz.

Per KDB 662911 D01 Multiple Transmitter Output v02 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4;


Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any NANT;

Array Gain = 5 log(NANT/NSS) dB or 3 dB, whichever is less for 20-MHz channel widths with NANT ≥ 5.

For power measurements on all other devices: Array Gain = 10 log(NANT/NSS) dB.

#### 4.3.2 TEST SETUP

##### FOR POWER OUTPUT MEASUREMENT



##### FOR 26dB BANDWIDTH



#### 4.3.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

#### 4.3.4 TEST PROCEDURE

##### FOR AVERAGE POWER MEASUREMENT

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

##### FOR 26dB BANDWIDTH

- 1) Set RBW = approximately 1% of the emission bandwidth.
- 2) Set the VBW > RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

#### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

### 4.3.7 TEST RESULTS

#### 802.11a

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (mW)	AVERAGE POWER (dBm)	POWER LIMIT (dBm)	PASS/FAIL
36	5180	46.132	16.64	16.99	PASS
40	5200	45.082	16.54	16.89	PASS
48	5240	44.361	16.47	16.93	PASS

**NOTE:**

1.  $4\text{dBm} + 10\log(19.95) = 16.99 \text{ dBm} < 17\text{dBm}$
2.  $4\text{dBm} + 10\log(19.44) = 16.89 \text{ dBm} < 17\text{dBm}$
3.  $4\text{dBm} + 10\log(19.65) = 16.93 \text{ dBm} < 17\text{dBm}$

#### 802.11n (20MHz)

CHAN.	FREQ. (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
36	5180	13.98	13.72	48.553	16.86	16.94	PASS
40	5200	13.84	13.43	46.239	16.65	16.97	PASS
48	5240	13.67	13.95	48.112	16.82	16.94	PASS

**NOTE:**

**CHAIN 0**

1.  $4\text{dBm} + 10\log(19.68) = 16.94 \text{ dBm} < 17\text{dBm}$
2.  $4\text{dBm} + 10\log(19.94) = 16.99 \text{ dBm} < 17\text{dBm}$
3.  $4\text{dBm} + 10\log(19.68) = 16.94 \text{ dBm} < 17\text{dBm}$

**CHAIN 1**

1.  $4\text{dBm} + 10\log(19.99) = 17.01 \text{ dBm} > 17\text{dBm}$
2.  $4\text{dBm} + 10\log(19.82) = 16.97 \text{ dBm} < 17\text{dBm}$
3.  $4\text{dBm} + 10\log(19.83) = 16.97 \text{ dBm} < 17\text{dBm}$

#### 802.11n (40MHz)

CHAN.	FREQ. (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
38	5190	12.01	11.60	30.339	14.82	17	PASS
46	5230	13.50	13.93	47.104	16.73	17	PASS

**NOTE:**

**CHAIN 0**

1.  $4\text{dBm} + 10\log(41.06) = 20.13 \text{ dBm} > 17\text{dBm}$
2.  $4\text{dBm} + 10\log(41.37) = 20.17 \text{ dBm} > 17\text{dBm}$

**CHAIN 1**

1.  $4\text{dBm} + 10\log(41.47) = 20.18 \text{ dBm} > 17\text{dBm}$
2.  $4\text{dBm} + 10\log(53.82) = 21.31 \text{ dBm} > 17\text{dBm}$



**26dB BANDWIDTH:**

**802.11a**

CHANNEL	FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)	PASS / FAIL
36	5180	19.95	PASS
40	5200	19.44	PASS
48	5240	19.65	PASS

**802.11n (20MHz)**

CHANNEL	FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)		PASS / FAIL
		CHAIN 0	CHAIN 1	
36	5180	19.68	19.99	PASS
40	5200	19.94	19.82	PASS
48	5240	19.68	19.83	PASS

**802.11n (40MHz)**


CHANNEL	FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)		PASS / FAIL
		CHAIN 0	CHAIN 1	
38	5190	41.06	41.47	PASS
46	5230	41.37	53.82	PASS




A D T

### SPECTRUM PLOT OF WORST VALUE


#### 802.11a



#### 802.11n (20MHz)



#### 802.11n (40MHz)






#### 4.4 PEAK POWER SPECTRAL DENSITY MEASUREMENT

##### 4.4.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT

FREQUENCY BAND	LIMIT
5.15 ~ 5.25GHz	4dBm

##### 4.4.2 TEST SETUP



##### 4.4.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

##### 4.4.4 TEST PROCEDURES

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 30 KHz, Set VBW  $\geq$  1 MHz, Detector = RMS
- 3) Set Channel power measure = 1MHz
- 4) Sweep time = 0.3 second.
- 5) Perform a single sweep.
- 6) Record the max value

##### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

##### 4.4.6 EUT OPERATING CONDITIONS

Same as 4.3.6.

#### 4.4.7 TEST RESULTS

##### 802.11a

CHANNEL	FREQUENCY (MHz)	PSD (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
36	5180	2.75	4	PASS
40	5200	2.12	4	PASS
48	5240	1.43	4	PASS

##### 802.11n (20MHz)

CHAN.	FREQ. (MHz)	PSD (dBm)		TOTAL POWER DENSITY (dBm)	MAX. LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1			
36	5180	0.42	0.56	3.50	4	PASS
40	5200	0.31	0.18	3.26	4	PASS
48	5240	0.30	1.27	3.82	4	PASS

**NOTE:**

- 802.11n transmit signals are completely uncorrelated.
- Directional gain =  $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10}) / N_{ANT}] = 4.9 < 6\text{dBi}$ , so the limit no need to reduced.
- Refer to section 3.3 for duty cycle spectrum plot.

##### 802.11n (40MHz)

CHAN.	FREQ. (MHz)	PSD (dBm)		TOTAL POWER DENSITY (dBm)	MAX. LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1			
38	5190	-5.93	-5.90	-2.90	4	PASS
46	5230	-2.82	-1.66	0.81	4	PASS

**NOTE:**


- 802.11n transmit signals are completely uncorrelated.
- Directional gain =  $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10}) / N_{ANT}] = 4.9 < 6\text{dBi}$ , so the limit no need to reduced.
- Refer to section 3.3 for duty cycle spectrum plot.




A D T

### SPECTRUM PLOT OF WORST VALUE


#### 802.11a



#### 802.11n (20MHz)



#### 802.11n (40MHz)




## 4.5 PEAK POWER EXCURSION MEASUREMENT

### 4.5.1 LIMITS OF PEAK POWER EXCURSION MEASUREMENT

Shall not exceed 13 dB

### 4.5.2 TEST SETUP



### 4.5.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

### 4.5.4 TEST PROCEDURE

- 1) Set RBW = 1 MHz, VBW  $\geq$  3 MHz, Detector = peak.
- 2) Trace mode = max-hold. Allow the sweeps to continue until the trace stabilizes.
- 3) Use the peak search function to find the peak of the spectrum.
- 4) Measure the PPSD.
- 5) Compute the ratio of the maximum of the peak-max-hold spectrum to the PPSD. Find the worst channel and modulation mode as above test procedure, and follow KDB 789033 D01 General UNII Test Procedures v01r03 and repeat step 1 to 5 for final testing of each modulation mode on a single channel ( all modulation types ) in a single operating band to compliance with the peak excursion requirement.

#### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.5.6 EUT OPERATING CONDITIONS


Same as 4.2.6



**A D T**

### 4.5.7 TEST RESULTS

MODULATION MODE	MODULATION TYPE	FREQUENCY (MHz)	PEAK VALUE (dBm)	PPSD (dBm)	PEAK EXCURSION (dB)	LIMIT (dB)	PASS/ FAIL
802.11a	BPSK	5240	8.43	1.43	1.43	13	PASS
	QPSK		8.23	0.74	0.74	13	PASS
	16QAM		9.27	1.35	1.35	13	PASS
	64QAM		9.46	1.33	1.33	13	PASS
802.11n (20MHz)	BPSK	5240	7.66	0.30	0.30	13	PASS
	QPSK		9.58	1.32	1.32	13	PASS
	16QAM		10.00	2.16	2.16	13	PASS
	64QAM		9.38	1.07	1.07	13	PASS
802.11n (40MHz)	BPSK	5240	4.83	-2.82	-2.82	13	PASS
	QPSK		-0.62	-8.92	-8.92	13	PASS
	16QAM		6.35	-1.87	-1.87	13	PASS
	64QAM		6.75	-1.82	-1.82	13	PASS




## 4.6 FREQUENCY STABILITY

### 4.6.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency of the carrier signal shall be maintained within band of operation

### 4.6.2 TEST SETUP



### 4.6.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

#### 4.6.4 TEST PROCEDURE

- a. The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- b. Turn the EUT on and couple its output to a spectrum analyzer.
- c. Turn the EUT off and set the chamber to the highest temperature specified.
- d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

#### 4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.6.6 EUT OPERATING CONDITION

Set the EUT transmit at un-modulation mode to test frequency stability.



#### 4.6.7 TEST RESULTS

FREQUENCY STABILITY VERSUS TEMP.									
OPERATING FREQUENCY: 5240MHz									
TEMP. (°C)	POWER SUPPLY (Vac)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
50	120	5239.9783	-0.00041	5239.9748	-0.00048	5239.975	-0.00048	5239.9811	-0.00036
40	120	5240.0065	0.00012	5240.0098	0.00019	5240.0064	0.00012	5240	0.00000
30	120	5240.0128	0.00024	5240.015	0.00029	5240.0144	0.00027	5240.011	0.00021
20	120	5240.0069	0.00013	5240.0024	0.00005	5240.0046	0.00009	5240.0068	0.00013
10	120	5239.9954	-0.00009	5239.9906	-0.00018	5239.9905	-0.00018	5239.9923	-0.00015
0	120	5240.0054	0.00010	5239.9991	-0.00002	5239.9973	-0.00005	5239.9981	-0.00004
-10	120	5239.9771	-0.00044	5239.9813	-0.00036	5239.9797	-0.00039	5239.9747	-0.00048
-20	120	5239.9752	-0.00047	5239.9701	-0.00057	5239.9796	-0.00039	5239.9759	-0.00046
-30	120	5240.0214	0.00041	5240.0198	0.00038	5240.0196	0.00037	5240.0216	0.00041

FREQUENCY STABILITY VERSUS VOLTAGE									
OPERATING FREQUENCY: 5240MHz									
TEMP. (°C)	POWER SUPPLY (Vac)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
20	138	5240.0063	0.00012	5240.0019	0.00004	5240.0054	0.00010	5240.0073	0.00014
	120	5240.0069	0.00013	5240.0024	0.00005	5240.0046	0.00009	5240.0068	0.00013
	102	5240.0064	0.00012	5240.0024	0.00005	5240.0047	0.00009	5240.0063	0.00012

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



## 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Telecom Lab:**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

## **7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No modifications were made to the EUT by the lab during the test.

**---END---**